

WebClient Non-Blocking

1- Create controller

```
ProviderWebClient.java WebClientController.java WebClientConfig.java
1 package com.demo.consumer.webclient;
2
3 import org.springframework.web.bind.annotation.GetMapping;
10
11 @RestController
12 @RequestMapping("/api/web-client")
13 @RequiredArgsConstructor
14 public class WebClientController {
15
16     private final ProviderWebClient providerWebClient;
17
18     @GetMapping("/instance")
19     public Mono<String> getInstance(){
20         // WebClient webClient = WebClient.create();
21         //
22         // Mono<String> response = webClient.get()
23         //     .uri("http://localhost:9091/instance-info")
24         //     .retrieve()
25         //     .bodyToMono(String.class);
26         //
27         // return response;
28         return providerWebClient.getInstanceInfo();
29     }
30 }
```

2- Create bean

```
ProviderWebClient.java WebClientController.java WebClientConfig.java
1 package com.demo.consumer.webclient;
2
3 import org.springframework.context.annotation.Bean;
6
7 @Configuration
8 public class WebClientConfig {
9
10     @Bean
11     public WebClient webClient() {
12         return WebClient.create("http://localhost:9091");
13     }
14
15 }
16
```

3- Create Client

```
ProviderWebClient.java WebClientController.java WebClientConfig.java
1 package com.demo.consumer.webclient;
2
3 import org.springframework.stereotype.Service;
8
9 @Service
10 @RequiredArgsConstructor
11 public class ProviderWebClient {
12     private final WebClient webClient;
13     public Mono<String> getInstanceInfo() {
14
15         return webClient.get()
16             .uri("/instance-info")
17             .retrieve()
18             .bodyToMono(String.class);
19     }
20 }
```

```
<dependency>
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-webflux</artifactId>
</dependency>
```