

User manual search (offline, online), forum search

Threaded and non-threaded script code

Callback functions

Dynamics callback functions

Joint callback functions

Contact callback function

Vision callback functions

Trigger callback functions

User config callback functions

Script execution order

Buffers

Lua vs Python scripts

Lua crash course

Plugins

CoppeliaSim's library

Accessing scene objects programmatically

Explicit and non-explicit calls

CoppeliaSim API framework

Regular API reference

Regular API constants

Properties

Properties reference

Simulation

Simulation dialog

Tutorials

BubbleRob tutorial

Building a clean model tutorial

Line following BubbleRob tutorial

Inverse kinematics tutorial

External controller tutorial

Plugin tutorial

Robot language interpreter integration tutorial

ROS tutorials

ROS tutorial

ROS 2 tutorial

Compiling CoppeliaSim



# Callback functions

Callbacks or callback functions are script functions that are triggered by a specific event. They represent the only entrance into script code. They can be categorized into user callbacks, and system callbacks:

- user callback functions are directly triggered by user code, or a plugin. This happens for instance when the user calls a script function in a different script via `sim.callScriptFunction`, or when the user clicks a custom UI button, which triggers a custom event. User callback functions can usually run in any type of script.
- system callback functions on the other hand are triggered by CoppeliaSim when a certain event happens, for instance when a script is initialized, or before switching to another scene. System callback functions have fixed function names, such as `sysCall_init` or `sysCall_beforeInstanceSwitch`. Not all system callback functions are supported by all types of scripts, e.g. some can only run in an `add-on` (e.g. `sysCall_addOnScriptSuspend`).

While most system callback functions operate in a relatively straight-forward manner and are easy to understand (see further down for a complete list of system callback functions), some require a little bit more explanations:

- Dynamics callback functions are called by the physics engine before and after each dynamics simulation step
- The contact callback function is called by the physics engine for each contact pair
- Joint callback functions are called for custom joint control
- Vision callback functions are called whenever a new image is acquires or applied
- Trigger callback functions are called when a certain trigger event is fired
- User config callback functions are called when the user double-clicks a user parameter icon

Following is a list of all supported system callback functions. Most support returning `{cmd='cleanup'}` or `{cmd='restart'}` to end or restart the script. Refer to the comments in the code below for details about individual functions:

Python

Lua

```

#python

def sysCall_init():
    # Do some initialization here.
    pass

def sysCall_thread():
    # Entry point for threaded scripts.
    pass

def sysCall_cleanup():
    # Do some clean-up here.
    pass

def sysCall_nonSimulation():
    # Is executed when simulation is not running.
    # Not for simulation scripts or the main script.
    pass

def sysCall_beforeSimulation():
    # Simulation is about to start.
    # Not for simulation scripts or the main script.
    pass

def sysCall_afterSimulation():
    # Simulation has just ended.
    # Not for simulation scripts or the main script.
    pass

def sysCall_actuation():
    # Put some actuation code here.
    pass

def sysCall_sensing():
    # Put some sensing code here.
    pass

def sysCall_suspend():
    # Simulation is about to be suspended.
    pass

def sysCall_suspended():
    # Simulation is suspended.
    pass

def sysCall_resume():
    # Simulation is about to resume.
    pass

def sysCall_realTimeIdle():
    # Is executed when idle in real-time mode
    pass

def sysCall_beforeInstanceSwitch():
    # About to switch to another scene.
    # Not for simulation scripts or the main script.
    pass

def sysCall_afterInstanceSwitch():
    # Switched to another scene.
    # Not for simulation scripts or the main script.
    pass

def sysCall_beforeSave(inData):
    # About to save the scene, or about to set an undo/redo point
    print(str(inData['regularSave']), inData['file'])

def sysCall_afterSave(inData):
    # After the scene was saved, or after an undo/redo point was set
    print(str(inData['regularSave']), inData['file'])

def sysCall_afterLoad():
    # After the scene was loaded
    pass

def sysCall_selChange(inData):
    # After selection was changed
    for handle in inData['sel']:
        print(f"Object with handle {handle} is selected")

def sysCall_beforeCopy(inData):
    # Before one or several objects will be copied. Can be reentrant
    for handle in inData['objects']:
        print(f"Object with handle {handle} will be copied")

def sysCall_afterCopy(inData):
    # After one or several objects were copied. Can be reentrant
    for handle in inData['objects']:
        print(f"Object with handle {handle} was copied")

```

```

def sysCall_afterCreate(inData):
    # After one or several objects were created. Can be reentrant
    for handle in inData['objects']:
        print(f"Object with handle {handle} was created")

def sysCall_beforeDelete(inData):
    # Before one or several objects will be deleted. Can be reentrant
    for handle in inData['objects']:
        print(f"Object with handle {handle} will be deleted")
    # inData['allObjects'] indicates if all objects in the scene will be deleted

def sysCall_afterDelete(inData):
    # After one or several objects were deleted. Can be reentrant
    for handle in inData['objects']:
        print(f"Object with handle {handle} was deleted")
    # inData['allObjects'] indicates if all objects in the scene were deleted

def sysCall_beforeMainScript():
    # Can be used to step a simulation in a custom manner.
    outData = {"doNotRunMainScript": False} # when true, then the main script won't be executed
    return outData

def sysCall_addOnScriptSuspend():
    # Add-on execution is about to be suspended.
    # Only for add-ons.
    pass

def sysCall_addOnScriptResume():
    # Add-on execution is about to be resumed.
    # Only for add-ons.
    pass

def sysCall_dyn(inData):
    # See the dynamics callback function section for details
    return {...}

def sysCall_joint(inData):
    # See the joint callback function section for details
    return {...}

def sysCall_contact(inData):
    # See the contact callback function section for details
    return {...}

def sysCall_vision(inData):
    # See the vision callback function section for details
    # Only for customization scripts and simulation scripts.
    return {...}

def sysCall_trigger(inData):
    # See the trigger callback function section for details
    # Only for customization scripts and simulation scripts.
    return {...}

def sysCall_userConfig():
    # See the user config callback function section for details.
    # Only for customization scripts.
    pass

def sysCall_moduleEntry(inData):
    # Called when a user module menu entry is selected, e.g.
    print(f"Following module menu entry was selected: {inData['handle']}")
    # See sim.moduleEntry for details.

def sysCall_msg(msg, origin):
    # Synchronously called when sim.broadcastMsg is called, or when sysCall_init, sysCall_cleanup,
    # sysCall_addOnScriptSuspend, sysCall_addOnScriptResume or sysCall_userConfig is called. Can be reentrant
    pass

def sysCall_data(inData):
    # Asynchronously called when custom data properties attached to this script, or this script's parent are modified
    # Only for simulation- and customization scripts
    pass

def sysCall_event(cborBuffer):
    # Asynchronously called when an internal variable or state changes. Can be reentrant
    # Mainly used to synchronize an external GUI/viewer/renderer with CoppeliaSim.
    # See also sim.getGenesisEvents and sim.setEventFilters
    pass

```