InfraDocs — Start Here

Operator runbook: current state, architecture, and reinstall steps

Home-lab documentation cockpit · Hosts: oci (primary) · oci-p · n150 · Prepared 2026-07-30

> **Current state:** InfraDocs has been **cleanly removed** from all three servers (containers, volumes, images, and networks). The nginx vhost, TLS cert, and DNS record for `infra.mdbdemo.in` are **untouched** — so reinstalling on oci brings the public URL straight back with no DNS/cert changes.

1 · How the public URL actually works

`infra.mdbdemo.in` is served by **plain nginx on oci behind Cloudflare's proxy** — *not* a Cloudflare Tunnel and *not* the compose `cloudflare` / `tailscale` profiles (those are empty on every host). The full path:

```
infra.mdbdemo.in   → Cloudflare (proxied / orange-cloud: 104.21.85.122, 172.67.205.180)   →
oci public IP :443   → nginx /etc/nginx/sites-enabled/infra.mdbdemo.in (Let's Encrypt cert)
  → upstream infradocs_primary = 127.0.0.1:8081   → oci's infradocs-web container
```

The upstream is defined in `/etc/nginx/conf.d/infradocs-primary.conf`: `upstream infradocs_primary { server 127.0.0.1:8081; }`

2 · Server roles & DNS records

Host	SERVER_ID	Web port	Role	Public ingress
oci	OCI	:8081	Primary (aggregates the UI)	nginx → `infra.mdbdemo.in`
oci-p	OCI-P	:8081	Secondary	none
n150	N150	:8083 (caddy)	Secondary	none (its cloudflared serves other apps)

DNS record	Status	Notes
`infra.mdbdemo.in`	LIVE	Cloudflare-proxied → oci nginx. Returns **502** while InfraDocs is down; back to 200 on reinstall. Record + cert + vhost all intact.
`infra.ocialwaysfree.site`	UNUSED	nginx vhost exists but is **not enabled**; DNS does not resolve. Points at an old *native* (non-Docker) deploy. Ignore it.

> **Why 502 and not "tunnel error 1033"?** Because there is no tunnel. nginx stays up and just has no origin on `:8081` until the stack is running again. Nothing to delete or repoint — the URL self-heals on reinstall.

3 · Reinstall — do oci first

The repo already lives at `~/infradocs` on each host, so reinstall = re-run the deployer. Start with **oci**, the primary that `infra.mdbdemo.in` fronts:

```
# On your Mac
ssh oci
cd ~/infradocs
git pull                          # optional: pull the hardening branch if merged
bash deploy/docker/deploy.sh
```

When `deploy.sh` asks how to expose the browser wizard, choose **3) Skip** — nginx already fronts oci. Once `:8081` is healthy, `infra.mdbdemo.in` returns 200 automatically.

Then the secondaries

```
ssh oci-p 'cd ~/infradocs && bash deploy/docker/deploy.sh'

# n150: direct ssh times out on :22 — hop through oci
ssh oci 'ssh n150 "cd ~/infradocs && bash deploy/docker/deploy.sh"'
```

For the secondaries, either **Skip** exposure too, or pick **1) Tailscale** if you want a private URL to reach them directly.

First login

`admin` / `Changeme001` → change the password immediately → complete the wizard.

4 · Two heads-ups before you run it

① **The saved `.env` is reused by default.** Each host's `deploy/docker/.env` was kept during removal, so `deploy.sh` reuses it. oci's `.env` was *missing* `MONGO_PASSWORD` — the script auto-backfills it. Because removal wiped the old `mongo_data` volume (`down -v`), this is a clean first-run and auth won't lock you out; the catalog repopulates on the first scan.

Want a **fully fresh** config instead? Delete the env first, then deploy:
`rm ~/infradocs/deploy/docker/.env` — it'll re-prompt for SERVER_ID and projects-root.

② **`remove.sh` can fail silently.** It swallows errors (`2>/dev/null || true`). On oci the bundled `down` couldn't parse the compose file (missing required `MONGO_PASSWORD`), so it looked done but wasn't. If you ever remove again and containers linger, tear down explicitly with a throwaway value (the value is irrelevant for a down):
`cd ~/infradocs/deploy/docker && MONGO_PASSWORD=teardown docker compose --env-file .env down -v --remove-orphans`

5 · Handy verification & management commands

```
# Is the stack up on a host?
docker ps --filter name=infradocs --format '{{.Names}}  {{.Status}}'

# Follow logs / check health (from the deploy dir)
cd ~/infradocs/deploy/docker
docker compose --env-file .env ps
docker compose --env-file .env logs -f api
```

```
# Is the public URL healthy? (run from your Mac)
curl -s -o /dev/null -w 'infra.mdbdemo.in -> HTTP %{http_code}\n' https://infra.mdbdemo.in/

# nginx / cert on oci (should already exist — do not recreate)
ls -l /etc/nginx/sites-enabled/infra.mdbdemo.in
sudo nginx -t && sudo systemctl reload nginx
```

6 · Full decommission (only if NOT reinstalling)

Skip this if you're reinstalling — leave nginx/cert/DNS as-is. To permanently retire the public URL on oci:

```
sudo rm /etc/nginx/sites-enabled/infra.mdbdemo.in && sudo nginx -s reload
sudo certbot delete --cert-name infra.mdbdemo.in
# then delete the infra.mdbdemo.in record in the Cloudflare dashboard
```

InfraDocs V6 · pipeline: scanners → correlator → MongoDB → FastAPI → React · Two-tier RBAC (viewer/operator), self-protected units prefixed `infradocs`. This is a home-lab deployment, not production.