Sistemas e Multimédia

TPW-IITecnologia e Prática da Web II





- □ jQuery
 - Visão geral
 - Instalação
 - Sintaxe
 - Ready function
 - Exemplos

jQuery


☐ jQuery é uma biblioteca de funções em JavaScript criada por John Resig e disponibilizada como software livre e aberto.

Objetivos:

- Adicionar efeitos visuais e animações;
- Buscar informações no servidor sem necessidade de recarregar a página;
- Prover interatividade;
- Alterar conteúdos;
- Modificar apresentação e estilização;
- Simplificar tarefas específicas de JavaScript;
- Realizar outras tarefas relacionadas às descritas.

□ 5 funcionalidades jQuery

- Select DOM (Document Object Model) elements on a page – one element or a group of them
- Set properties of DOM elements, in groups ("Find something, do something with it")
- Creates, deletes, shows, hides DOM elements
- Defines event behavior on a page (click, mouse movement, dynamic styles, animations, dynamic content)
- AJAX calls



- □ Recursos de aprendizagem:
 - www.jquery.com
 - http://docs.jquery.com
 - www.visualjquery.com
 - www.Jqueryfordesigners.com
 - www.gscottolson.com/weblog/ cheat sheet
 - www.javascripttoolbox.com/jquery
 - www.w3schools.com/jquery

M

jQuery instalação

□ Instalação

- Fazer download
 - □ http://jquery.com/

Ou referenciar um CDN – Content Delivery Network via URL

Google

Micrososft

jQuery sintaxe

□ The jQuery Function

```
■ jQuery() = $()
```

- \$(function)
 The "Ready" handler
- \$('selector')
 Element selector expression
- \$(element)
 Specify element(s) directly
- \$('HTML')
 HTML creation
- \$.function()
 Execute a jQuery function
- \$.fn.myfunc(){} Create jQuery function

- ☐ The jQuery syntax is tailor made for **selecting** HTML elements and performing some **action** on the element(s).
- □ Basic syntax is: \$(selector).action()
 - A \$ sign to define/access jQuery
 - A (selector) to "query (or find)" HTML elements
 - A jQuery action() to be performed on the element(s)
- Examples:
 - \$(this).hide() hides the current element
 - \$("p").hide() hides all elements
 - \$(".test").hide() hides all elements with class="test"
 - \$("#test").hide() hides the element with id="test"

☐ JavaScript versus jQuery

Sintaxe JavaScript	Sintaxe jQuery
document.getElementsByTagName("p")	\$("p")
document.getElementById("um").setAttribute("class", "cor")	\$("#um").attr("class", "cor")

- □ ready() function
 - Esta função evita que qualquer código jQuery seja executado antes que o documento esteja completamente carregado (está pronto).
- □ 5 formas de especificar a ready() function
 - iquery(document).ready(function(){...});
 Ou.. \$(document).ready(function(){...});
 - jquery().ready(function(){...});
 Ou.. \$().ready(function(){...});
 - jquery(function(){...});
 Ou.. \$(function(){...});
 - jquery(dofunc);
 Ou.. \$(dofunc);

Exemplos: ready function

```
<script type="text/javascript">
     $().ready(function(){
         // jQuery methods go here...
     });
     jquery(document).ready(function () {
        // jQuery methods go here...
     });
     $(function () {
         // jQuery methods go here...
     });
 </script>
```

16

Exemplos: jQuery User Interface

http://jqueryui.com/

Interactions

- Draggable
- Droppable
- Resizable
- Selectable
- Sortable

Widgets

- Accordion
- Autocomplete
- Button
- Datepicker
- Dialog
- Menu
- Progressbar
- Slider
- Spinner
- Tabs
- Tooltip

Effects


- Add Class
- Color Animation
- Effect
- Hide
- Remove Class
- Show
- Switch Class
- Toggle
- Toggle Class

Utilities

- Position
- Widget Factory

JJM

Exemplo:



Exemplo:

```
displaying information. The dialog window can
<!doctype html>
                                                                be moved, resized and closed with the 'x' icon.
<html>
     <head>
     <meta charset="utf-8" />
     <title>jQuery UI Dialog - Default functionality</title>
     <link rel="stylesheet"</pre>
     href="http://code.jquery.com/ui/1.10.3/themes/smoothness/jquery-ui.css" />
     <script src="http://code.jquery.com/jquery-1.9.1.js"></script>
     <script src="http://code.jquery.com/ui/1.10.3/jquery-ui.js"></script>
     <link rel="stylesheet" href="/resources/demos/style.css" />
     <script>
     $ (function() {
          $( "#dialog" ).dialog();
     });
     </script>
     </head>
<body>
<div id="dialog" title="Basic dialog">
   This is the default dialog which is useful for displaying
          information. The dialog window can be moved, resized and closed with the 'x'
icon.
</div>
</body>
</html>
```

Basic dialog

This is the default dialog which is useful for

jQuery Mobile


20



http://jquerymobile.com/

http://jquerymobile.com/demos/





http://themeroller.jquerymobile.com/