

Parcel Perfect Ecommerce Service v27

Overview

ecomService is a web services interface between an ecommerce site and a Parcel Perfect environment. It facilitates requesting quotes for transport charges from the courier and submitting collection requests. All methods to achieve this are outlined below.

Environment

Methods are exposed via both REST-based Json and SOAP end points. Documentation and examples are provided for both.

Testing environment

You will need to obtain a test account from Parcel Perfect. Email support@parcelperfect.com with the subject: Request for ecom test account. Please provide your contact details and which courier / transport provider you are working with.

On approval, you will be provided a username, password and account number.

Documentation and examples

You can find all supporting documentation and examples to run in the test environment at <http://adpdemo.pperfect.com/ecomService/v17/downloads/>

End Point URLs

Type	URL
Json end point	http://adpdemo.pperfect.com/ecomService/v27/Json/
SOAP end point	http://adpdemo.pperfect.com/ecomService/v27/Soap/
SOAP WSDL	http://adpdemo.pperfect.com/ecomService/v27/Soap/index.php?wsdl

Authentication

Methods – Full API Specification at end of document


Method	Function
getSalt	On submitting the user name the method returns a salt value
getToken	On submitting the user name and encrypted password using the salt value and the user password, this method passes back a token
expireToken	Calling this method invalidates the existing token

In order to use the web-services, one must first authenticate by getting a security token. All methods within the Ecommerce Webservice other than the Auth class require the token to be submitted with the request.

With your username and password, first get a salt from the end point URL. Encrypt the salt with MD5 and use your username and encrypted password to get a token.

The token is valid until you call the expireToken or getSalt methods.

Authentication method flow



- 1) Make a call to getSalt with your username (email address)
- 2) The response will include a salt
- 3) Concatenate the password and the salt and create an md5 hash: md5(password+salt)
- 4) Call getSecureToken using the md5 hash create in 3) above as your password
- 5) The response will include the token to be used with subsequent requests

Tokens do not expire and will remain active as long as required. Should your token expire and a new one is requested we will simply re-enable the original token.

SSS

Getting a quote from ecomService

Class – Waybill

Method	Function
getSingleWaybill	Returns full waybills details for the submitted waybill number.

Class – Quote

Method	Function
requestQuote	Requests a quote using submitted details. Returns costs based on a service level.
updateService	Sets the service of an existing quote, preparing it for conversion.
quoteToWaybill	Converts a quote into a waybill.
getPlacesByName	Returns a list of places based on a partial name lookup.
getPlacesByPostcode	Returns a list of places based on a postal code lookup.
getDeflItems	Returns a list of default content items.

Class – Collection

Method	Function
submitCollection	Submits through a collection request to the courier.
quoteToCollection	Converts a quote to a collection with associated waybill number.
submitCompoundCollection	Submits through a bulk collection with multiple waybills and destinations attached.

An excel document accompanies this document that includes a breakdown for each method and its fields.

Before submitting a requestQuote, you will need to obtain the originating and destination place value via getPlacesByName or getPlacesByPostcode. The place value selected from either of these two functions will be used in the requestQuote method. In the case where the originating place is constant, the place value can be pre-determined and is not necessary to call these methods.

Along with the places, at least one entry in the requestQuote.contents array must be submitted. This is the minimum amount of freight that can be transported. The requestQuote method returns an array of possible transport costs against each service available. If only one service is available, then it is unnecessary to call the updateService method. If there is more than one service available, call the updateService method to update the quote with the user selected service.

Request quote method flow

