

The Legend of Python, Modular Interface Specification

Revision 1.8 11/9/2018

Generated by Doxygen 1.8.13

Contents

1	Hierarchical Index	1
1.1	Class Hierarchy	1
2	Class Index	3
2.1	Class List	3
3	File Index	5
3.1	File List	5
4	Class Documentation	7
4.1	actor.aquamentus.Aquamentus Class Reference	7
4.1.1	Detailed Description	8
4.1.2	Constructor & Destructor Documentation	8
4.1.2.1	__init__()	8
4.1.3	Member Function Documentation	9
4.1.3.1	attack()	9
4.1.3.2	bossLogic()	9
4.1.3.3	checkState()	9
4.1.3.4	swapDirection()	9
4.1.4	Member Data Documentation	10
4.1.4.1	hitCount	10
4.1.4.2	isHit	10
4.1.4.3	oldx	10
4.1.4.4	oldy	10
4.2	actor.boomerang.Boomerang Class Reference	10

4.2.1	Detailed Description	11
4.2.2	Constructor & Destructor Documentation	11
4.2.2.1	__init__()	12
4.3	actor.boss.Boss Class Reference	12
4.3.1	Detailed Description	13
4.3.2	Constructor & Destructor Documentation	13
4.3.2.1	__init__()	13
4.3.3	Member Function Documentation	14
4.3.3.1	hit()	14
4.3.3.2	move()	14
4.3.3.3	update()	14
4.3.4	Member Data Documentation	14
4.3.4.1	id	14
4.4	collision.door.Door Class Reference	15
4.4.1	Detailed Description	15
4.4.2	Constructor & Destructor Documentation	15
4.4.2.1	__init__()	15
4.4.3	Member Function Documentation	16
4.4.3.1	collision()	16
4.4.4	Member Data Documentation	16
4.4.4.1	state	16
4.5	actor.enemy.Enemy Class Reference	17
4.5.1	Detailed Description	18
4.5.2	Constructor & Destructor Documentation	18
4.5.2.1	__init__()	18
4.5.3	Member Function Documentation	18
4.5.3.1	hit()	18
4.5.3.2	move()	19
4.5.3.3	update()	19
4.5.4	Member Data Documentation	19

4.5.4.1	hitCount	19
4.5.4.2	hitdir	19
4.5.4.3	id	20
4.6	actor.fireball.Fireball Class Reference	20
4.6.1	Detailed Description	21
4.6.2	Constructor & Destructor Documentation	21
4.6.2.1	__init__()	21
4.6.3	Member Function Documentation	22
4.6.3.1	checkState()	22
4.6.3.2	end()	22
4.6.3.3	hit()	22
4.6.3.4	logic()	22
4.6.3.5	move()	23
4.6.3.6	start()	23
4.6.3.7	update()	23
4.6.4	Member Data Documentation	23
4.6.4.1	id	23
4.6.4.2	image	24
4.7	actor.healthbar.Health_Bar Class Reference	24
4.7.1	Detailed Description	24
4.7.2	Constructor & Destructor Documentation	25
4.7.2.1	__init__()	25
4.7.3	Member Function Documentation	25
4.7.3.1	health()	25
4.7.4	Member Data Documentation	25
4.7.4.1	h_sprite_sheet	25
4.7.4.2	image	26
4.7.4.3	rect	26
4.8	actor.item.Item Class Reference	26
4.8.1	Detailed Description	27

4.8.2	Constructor & Destructor Documentation	27
4.8.2.1	__init__()	27
4.8.3	Member Function Documentation	27
4.8.3.1	collision()	27
4.9	actor.keese.Keese Class Reference	28
4.9.1	Detailed Description	29
4.9.2	Constructor & Destructor Documentation	29
4.9.2.1	__init__()	29
4.9.3	Member Function Documentation	30
4.9.3.1	checkState()	30
4.9.3.2	enemyLogic()	30
4.9.3.3	genRestLength()	30
4.9.3.4	genTravelPoint()	30
4.9.3.5	setMoveSpeed()	31
4.9.3.6	stop()	31
4.9.3.7	switchSprite()	31
4.9.4	Member Data Documentation	31
4.9.4.1	hitCount	31
4.9.4.2	image	31
4.9.4.3	isHit	32
4.9.4.4	xSpeed	32
4.9.4.5	ySpeed	32
4.10	collision.level.Level Class Reference	32
4.10.1	Detailed Description	33
4.11	collision.levelmanager.LevelManager Class Reference	33
4.11.1	Detailed Description	34
4.11.2	Constructor & Destructor Documentation	34
4.11.2.1	__init__()	34
4.11.3	Member Function Documentation	35
4.11.3.1	make()	35

4.11.3.2	transition()	35
4.12	actor.player.Player Class Reference	35
4.12.1	Detailed Description	38
4.12.2	Constructor & Destructor Documentation	38
4.12.2.1	__init__()	38
4.12.3	Member Function Documentation	38
4.12.3.1	attackupdate()	38
4.12.3.2	move()	38
4.12.3.3	moveupdate()	39
4.12.4	Member Data Documentation	39
4.12.4.1	attacksword	39
4.12.4.2	dir	39
4.13	actor.rupee.Rupee_Bar Class Reference	39
4.13.1	Detailed Description	40
4.13.2	Constructor & Destructor Documentation	40
4.13.2.1	__init__()	40
4.13.3	Member Data Documentation	40
4.13.3.1	image	40
4.13.3.2	rect	41
4.14	actor.spritesheet.SpriteSheet Class Reference	41
4.14.1	Detailed Description	41
4.14.2	Constructor & Destructor Documentation	42
4.14.2.1	__init__()	42
4.14.3	Member Function Documentation	42
4.14.3.1	get_image()	42
4.14.3.2	get_imageNT()	43
4.14.4	Member Data Documentation	43
4.14.4.1	sprite_sheet	43
4.15	actor.stalfos.Stalfos Class Reference	43
4.15.1	Detailed Description	45

4.15.2	Constructor & Destructor Documentation	45
4.15.2.1	__init__()	45
4.15.3	Member Function Documentation	45
4.15.3.1	checkState()	45
4.15.3.2	enemyLogic()	46
4.15.3.3	genTravelPath()	46
4.15.3.4	setWalkSpeed()	46
4.15.3.5	stop()	46
4.15.4	Member Data Documentation	46
4.15.4.1	direction	46
4.15.4.2	dmg	47
4.15.4.3	hitCount	47
4.15.4.4	hitdir	47
4.15.4.5	HP	47
4.15.4.6	image	47
4.15.4.7	isHit	47
4.15.4.8	isMoving	48
4.15.4.9	maxHP	48
4.15.4.10	obj	48
4.15.4.11	oldx	48
4.15.4.12	oldy	48
4.15.4.13	previousDirection	48
4.15.4.14	spriteIndex	49
4.15.4.15	sprites	49
4.15.4.16	walkFrames	49
4.15.4.17	walkStartFrame	49
4.15.4.18	xSpeed	49
4.15.4.19	ySpeed	49
4.16	actor.sword.Sword Class Reference	50
4.16.1	Detailed Description	50

4.16.2	Constructor & Destructor Documentation	50
4.16.2.1	__init__()	50
4.16.3	Member Data Documentation	51
4.16.3.1	image	51
4.17	collision.wall.Wall Class Reference	51
4.17.1	Detailed Description	52
4.17.2	Constructor & Destructor Documentation	52
4.17.2.1	__init__()	52
4.17.3	Member Function Documentation	52
4.17.3.1	collision()	52
4.17.4	Member Data Documentation	53
4.17.4.1	id	53
4.17.4.2	image	53
4.17.4.3	rect	53
5	File Documentation	55
5.1	src/actor/aquamentus.py File Reference	55
5.1.1	Detailed Description	55
5.1.2	Function Documentation	56
5.1.2.1	populateSprites()	56
5.2	src/actor/boomerang.py File Reference	56
5.2.1	Detailed Description	56
5.2.2	Function Documentation	57
5.2.2.1	populateSprites()	57
5.2.2.2	stuncoefficient()	57
5.3	src/actor/boss.py File Reference	57
5.3.1	Detailed Description	58
5.4	src/actor/constants.py File Reference	58
5.4.1	Detailed Description	59
5.5	src/actor/enemy.py File Reference	60
5.5.1	Detailed Description	60

5.6	src/actor/fireball.py File Reference	60
5.6.1	Detailed Description	61
5.6.2	Function Documentation	61
5.6.2.1	populateSprites()	61
5.7	src/actor/healthbar.py File Reference	61
5.7.1	Detailed Description	62
5.8	src/actor/item.py File Reference	62
5.8.1	Detailed Description	62
5.9	src/actor/keese.py File Reference	62
5.9.1	Detailed Description	63
5.9.2	Function Documentation	63
5.9.2.1	populateSprites()	63
5.10	src/actor/player.py File Reference	63
5.10.1	Detailed Description	64
5.11	src/actor/rupee.py File Reference	64
5.11.1	Detailed Description	64
5.12	src/actor/spritesheet.py File Reference	64
5.12.1	Detailed Description	65
5.13	src/actor/stalfos.py File Reference	65
5.13.1	Detailed Description	65
5.13.2	Function Documentation	65
5.13.2.1	populateSprites()	66
5.14	src/actor/sword.py File Reference	66
5.14.1	Detailed Description	66
5.15	src/collision/door.py File Reference	66
5.15.1	Detailed Description	67
5.16	src/collision/level.py File Reference	67
5.16.1	Detailed Description	67
5.17	src/collision/levelmanager.py File Reference	67
5.17.1	Detailed Description	68
5.18	src/collision/wall.py File Reference	68
5.18.1	Detailed Description	68
5.19	src/config/colour.py File Reference	68
5.19.1	Detailed Description	69
5.20	src/config/window.py File Reference	69
5.20.1	Detailed Description	69

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

collision.levelmanager.LevelManager	33
object	
actor.spritesheet.SpriteSheet	41
Sprite	
actor.boomerang.Boomerang	10
actor.boss.Boss	12
actor.aquamentus.Aquamentus	7
actor.enemy.Enemy	17
actor.keese.Keese	28
actor.stalfos.Stalfos	43
actor.fireball.Fireball	20
actor.healthbar.Health_Bar	24
actor.item.Item	26
actor.player.Player	35
actor.rupee.Rupee_Bar	39
actor.sword.Sword	50
collision.door.Door	15
collision.level.Level	32
collision.wall.Wall	51

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

actor.aquamentus.Aquamentus		
	This class represents the Aquamentus Boss	7
actor.boomerang.Boomerang		
	Boomerang Weapon Class The class holding the creation, behaviour, and collision effects of the player's boomerang weapon	10
actor.boss.Boss		
	Superclass for representing a Boss	12
collision.door.Door		
	Dungeon Door Class This class is used to place a door on one of four places of a dungeon room, to allow the player to walk through and traverse to other rooms within the dungeon	15
actor.enemy.Enemy		
	Superclass for representing an Enemy	17
actor.fireball.Fireball		
	This class represents the Fireball object	20
actor.healthbar.Health_Bar		
	This class represents the HealthBar for the user controlled player character	24
actor.item.Item		
	Consumable Item Class This class is used for the creation of a random consumable item, spawned once an enemy has been defeated on their last position before despawn	26
actor.keese.Keese		
	This class represents the Keese enemy	28
collision.level.Level		
	Dungeon level background class Creates the background of a dungeon, can be modified in the future to change colour based on sprite sheet and new arg	32
collision.levelmanager.LevelManager		
	Dungeon Level Creation Class Class used as a master constructor for every dungeon levels, getting pre-written data and loading it when the game starts and when a transition occurs . . .	33
actor.player.Player		
	Player Class A pygame sprite subclass for defining the creation of the game's playable character, as well as its interactions with both the user and other entities within the game	35
actor.rupee.Rupee_Bar		
	This class represents the RupeeBar object	39
actor.spritesheet.SpriteSheet		
	This class represents the SpriteSheet object, allowing sprites to be loaded and processed . . .	41
actor.stalfos.Stalfos		
	This class represents the Stalfos enemy	43

[actor.sword.Sword](#)

Player [Sword](#) Class Class for the creation and deletion of the sword sprite object, made when the player attacks 50

[collision.wall.Wall](#)

This class represents the [Wall](#) class for collision for objects in the environment 51

Chapter 3

File Index

3.1 File List

Here is a list of all documented files with brief descriptions:

src/actor/ aquamentus.py	
Aquamentus Boss	55
src/actor/ boomerang.py	
Boomerang Weapon	56
src/actor/ boss.py	
Boss Template	57
src/actor/ constants.py	
Actor Constants	58
src/actor/ enemy.py	
Enemy Template	60
src/actor/ fireball.py	
Fireball object	60
src/actor/ healthbar.py	
HealthBar Class	61
src/actor/ item.py	
Consumable Items	62
src/actor/ keese.py	
Keese Enemy	62
src/actor/ player.py	
Playable Characer	63
src/actor/ rupee.py	
Rupee_Bar Class	64
src/actor/ spritesheet.py	
SpriteSheet Class	64
src/actor/ stalfos.py	
Stalfos Enemy	65
src/actor/ sword.py	
Player Sword	66
src/collision/ door.py	
Dungeon Door	66
src/collision/ level.py	
Dungeon Background	67
src/collision/ levelmanager.py	
Dungeon Level Master Creator	67
src/collision/ wall.py	
Wall Class	68

src/config/ colour.py	
Colour Constants	68
src/config/ window.py	
Window Constants	69


Chapter 4

Class Documentation

4.1 actor.aquamentus.Aquamentus Class Reference

This class represents the [Aquamentus](#) Boss.

Inheritance diagram for actor.aquamentus.Aquamentus:



Public Member Functions

- `def __init__ (self, x, y)`
Constructor for [Aquamentus](#).
- `def checkState (self)`
Evaluates the state of the [Aquamentus](#).
- `def swapDirection (self)`
Swaps [Aquamentus](#)' direction.
- `def attack (self)`
Allows for [Aquamentus](#) to attack.
- `def bossLogic (self)`
Controls [Aquamentus](#) logic.

Public Attributes

- [isAttacking](#)
Represents wether or not the boss is attacking.
- [attackStartFrame](#)
Represents the frame that the boss starts an attack.
- [fireballs](#)
Represents the boss' fireballs.
- [xSpeed](#)
[Aquamentus](#)' set x speed.
- [maxHP](#)
[Aquamentus](#)' max health.
- [HP](#)
[Aquamentus](#)' current health.
- [dmg](#)
[Aquamentus](#)' damage.
- [image](#)
Sprite image.
- [sprites](#)
Array of sprites.
- [obj](#)
Collision list.
- [spriteIndex](#)
Index for the array of sprites.
- [hitCount](#)
Integer value representing the buffer for the number of hits for [Aquamentus](#) after being hit by player character.
- [isHit](#)
Represents the current state if [Aquamentus](#) has collided with player character attack.
- [oldx](#)
This represents the previous x-location of [Aquamentus](#) in movement/stationary state.
- [oldy](#)
This represents the previous y-location of [Aquamentus](#) in movement/stationary state.

4.1.1 Detailed Description

This class represents the [Aquamentus](#) Boss.

4.1.2 Constructor & Destructor Documentation

4.1.2.1 `__init__()`

```
def actor.aquamentus.Aquamentus.__init__ (
    self,
    x,
    y )
```

Constructor for [Aquamentus](#).

Constructor takes two parameters, the x and y coordinates

Parameters

<i>x</i>	X coordinate of the starting postion of the Aquamentus
<i>y</i>	Y coordinate of the starting postion of the Aquamentus

4.1.3 Member Function Documentation

4.1.3.1 attack()

```
def actor.aquamentus.Aquamentus.attack (
    self )
```

Allows for [Aquamentus](#) to attack.

Spawns fireballs at Aquamenuts' mouth and sets their move speed

4.1.3.2 bossLogic()

```
def actor.aquamentus.Aquamentus.bossLogic (
    self )
```

Controls [Aquamentus](#) logic.

Uses the states to control the [Aquamentus](#)

4.1.3.3 checkState()

```
def actor.aquamentus.Aquamentus.checkState (
    self )
```

Evaluates the state of the [Aquamentus](#).

Evalautes if [Aquamentus](#) can stop, if it is in iframes, if it collides with something, and if it has died

4.1.3.4 swapDirection()

```
def actor.aquamentus.Aquamentus.swapDirection (
    self )
```

Swaps [Aquamentus](#)' direction.

Multiplies the speed in the x direction by -1

4.1.4 Member Data Documentation

4.1.4.1 hitCount

```
actor.aquamentus.Aquamentus.hitCount
```

Integer value representing the buffer for the number of hits for [Aquamentus](#) after being hit by player character.

4.1.4.2 isHit

```
actor.aquamentus.Aquamentus.isHit
```

Represents the current state if [Aquamentus](#) has collided with player character attack.

4.1.4.3 oldx

```
actor.aquamentus.Aquamentus.oldx
```

This represents the previous x-location of [Aquamentus](#) in movement/stationary state.

4.1.4.4 oldy

```
actor.aquamentus.Aquamentus.oldy
```

This represents the previous y-location of [Aquamentus](#) in movement/stationary state.


The documentation for this class was generated from the following file:

- [src/actor/aquamentus.py](#)

4.2 actor.boomerang.Boomerang Class Reference

[Boomerang](#) Weapon Class The class holding the creation, behaviour, and collision effects of the player's boomerang weapon.

Inheritance diagram for actor.boomerang.Boomerang:



Public Member Functions

- `def __init__ (self, x, y, direction, obj, player)`
Boomerang constructor A sprite subclass constructor that takes an x and y position (the players), a direction for the boomerang's trajectory, a list of collidable objects, as well as the player object (to add to the collision list)
- `def moveupdate (self)`
Boomerang position updating function, updating position based on changing trajectory speed.
- `def collisionupdate (self)`
Boomerang collision updating function, constantly checking for collisions and acting accordingly.
- `def spriteupdate (self)`
Updates the boomerang sprite every 10 frames.
- `def update (self)`
Boomerang updating function, repeatedly running `moveupdate` and `collisionupdate`.
- `def collision (self)`
Default collision function to satisfy other class collision calls to this object.

Public Attributes

- [image](#)
Boomerang sprite image.
- [rect](#)
Position of boomerang.
- [dir](#)
Initial travel direction of boomerang.
- [speed](#)
Boomerang initial update speed.
- [obj](#)
List of objects the boomerang could collide with.
- [killable](#)
Boolean to tell when the boomerang should be deleted.
- [sprites](#)
List of sprites for boomerang.
- [spriteIndex](#)
Index of the current sprite.
- [frameCounter](#)
Total number of frames boomerang is onscreen.

4.2.1 Detailed Description

[Boomerang](#) Weapon Class The class holding the creation, behaviour, and collision effects of the player's boomerang weapon.

4.2.2 Constructor & Destructor Documentation

4.2.2.1 `__init__()`

```
def actor.boomerang.Boomerang.__init__ (
    self,
    x,
    y,
    direction,
    obj,
    player )
```

Boomerang constructor A sprite subclass constructor that takes an x and y position (the players), a direction for the boomerang's trajectory, a list of collidable objects, as well as the player object (to add to the collision list)

Parameters

<i>x</i>	X coordinate of boomerang spawn
<i>y</i>	Y coordinate of boomerang spawn
<i>direction</i>	Direction of boomerang path
<i>obj</i>	List of objects to check for collision with the boomerang
<i>player</i>	Player object to also check collision for


The documentation for this class was generated from the following file:

- `src/actor/boomerang.py`

4.3 actor.boss.Boss Class Reference

Superclass for representing a **Boss**.

Inheritance diagram for actor.boss.Boss:



Public Member Functions

- `def __init__ (self, x, y)`
*Constructor for **Boss**.*
- `def checkState (self)`
*Empty function for evaluating **Boss** state.*
- `def move (self)`
*Moves the **Boss**.*
- `def bossLogic (self)`
*Empty function for logic of **Boss**.*
- `def update (self)`
*Update loop for a **Boss**.*
- `def hit (self, dir)`
*Hit detection for **Boss**.*

Public Attributes

- [image](#)
Boss Pygame surface.
- [rect](#)
Rectangle that represents boss.
- [id](#)
X position of the boss.
- [isHit](#)
Whether the boss is hit or not.
- [stuncount](#)
The amount of stun frames the boss has remaining.
- [maxHP](#)
Boss' max health.
- [HP](#)
Boss' current health.
- [dmg](#)
Boss' damage.
- [hitCount](#)
Boss' hit count.
- [xSpeed](#)
Boss' speed in the x direction.
- [ySpeed](#)
Boss' speed in the y direction.
- [frameCounter](#)
Total number of frames the boss has been alive for.

4.3.1 Detailed Description

Superclass for representing a [Boss](#).

4.3.2 Constructor & Destructor Documentation

4.3.2.1 `__init__()`

```
def actor.boss.Boss.__init__ (
    self,
    x,
    y )
```

Constructor for [Boss](#).

Constructor takes two parameters, the x and y coordinates

Parameters

x	X coordinate of the starting position of the Boss
y	Y coordinate of the starting position of the Boss

4.3.3 Member Function Documentation

4.3.3.1 hit()

```
def actor.boss.Boss.hit (
    self,
    dir )
```

Hit detection for [Boss](#).

Handles health and iframes

4.3.3.2 move()

```
def actor.boss.Boss.move (
    self )
```

Moves the [Boss](#).

Adds the x speed and y speed to the x and y position of the [Boss](#)

4.3.3.3 update()

```
def actor.boss.Boss.update (
    self )
```

Update loop for a [Boss](#).

Checks state, does the logic, and then moves [Boss](#)

4.3.4 Member Data Documentation

4.3.4.1 id

```
actor.boss.Boss.id
```

X position of the boss.

Y position of the boss [Boss](#) ID


The documentation for this class was generated from the following file:

- [src/actor/boss.py](#)

4.4 collision.door.Door Class Reference

Dungeon [Door](#) Class This class is used to place a door on one of four places of a dungeon room, to allow the player to walk through and traverse to other rooms within the dungeon.

Inheritance diagram for collision.door.Door:



Public Member Functions

- `def __init__ (self, direction, state)`
[Door](#) constructor, making a door on the specified side of the dungeon.
- `def collision (self, i)`
This method checks for collision with the [Door](#) object and other sprite object.
- `def openDoor (self)`
Function to set a door state and sprite to open Changes a blocked door (state 1/2) to an open door (state 0), changing collision attributes and sprites respectively.

Public Attributes

- **dungeon_sheet**
- [state](#)
DOOR STATE 0 = open 1 = blocked (objective door) 2 = locked (key door) State of the door, integer value on whether the door is open(0), blocked by an objective(1), or locked(2) (blocked = eg.
- **dir**
- [image](#)
Sprite image of the door.
- [rect](#)
X and y coordinates of the image.
- [id](#)
Collision ID (to help other objects identify what they are colliding with and how to react)

4.4.1 Detailed Description

Dungeon [Door](#) Class This class is used to place a door on one of four places of a dungeon room, to allow the player to walk through and traverse to other rooms within the dungeon.

4.4.2 Constructor & Destructor Documentation

4.4.2.1 __init__()

```
def collision.door.Door.__init__ (
    self,
    direction,
    state )
```

[Door](#) constructor, making a door on the specified side of the dungeon.

Parameters

<i>direction</i>	Integer value of the wall the door will be on (direction from centre of room)
------------------	---

4.4.3 Member Function Documentation**4.4.3.1 collision()**

```
def collision.door.Door.collision (
    self,
    i )
```

This method checks for collision with the [Door](#) object and other sprite object.

The collision will be checked with the [Door](#) and other sprite object as the object collides with the wall.

Parameters

<i>i</i>	This is the sprite object that is passed into the method, and checks if the object is colliding with the Door object, resetting the sprite objects location accordingly.
----------	--

4.4.4 Member Data Documentation**4.4.4.1 state**

```
collision.door.Door.state
```

DOOR STATE 0 = open 1 = blocked (objective door) 2 = locked (key door) State of the door, integer value on whether the door is open(0), blocked by an objective(1), or locked(2) (blocked = eg.

kill all enemies in room to open)


The documentation for this class was generated from the following file:

- [src/collision/door.py](#)

4.5 actor.enemy.Enemy Class Reference

Superclass for representing an [Enemy](#).

Inheritance diagram for actor.enemy.Enemy:



Public Member Functions

- `def __init__ (self, x, y)`
Constructor for [Enemy](#).
- `def checkState (self)`
Empty function for evaluating [Enemy](#) state.
- `def move (self)`
Moves the [Enemy](#).
- `def enemyLogic (self)`
Empty function for logic of [Enemy](#).
- `def update (self)`
Update loop for a [Enemy](#).
- `def hit (self, direc)`
Hit detection for [Enemy](#).

Public Attributes

- `image`
[Enemy](#) Pygame surface.
- `rect`
Rectangle that represents enemy.
- `id`
[Enemy](#) x position.
- `isHit`
Whether the enemy is hit.
- `stuncount`
Remaining stun frames.
- `maxHP`
[Enemy](#) max health.
- `HP`
[Enemy](#) current health.
- `dmg`
[Enemy](#) damage.
- `hitCount`
This represents the buffer for the number of hits for the [Enemy](#) after being hit by player character.

- [hitdir](#)
Represents the direction [Enemy](#) is hit in by player character attack.
- [xSpeed](#)
[Enemy](#) speed in the x direction.
- [ySpeed](#)
[Enemy](#) speed in the y direction.
- [frameCounter](#)
Total number of frames the enemy has been alive.

4.5.1 Detailed Description

Superclass for representing an [Enemy](#).

4.5.2 Constructor & Destructor Documentation

4.5.2.1 `__init__()`

```
def actor.enemy.Enemy.__init__ (
    self,
    x,
    y )
```

Constructor for [Enemy](#).

Constructor takes two parameters, the x and y coordinates

Parameters

x	X coordinate of the starting postion of the Enemy
y	Y coordinate of the starting postion of the Enemy

4.5.3 Member Function Documentation

4.5.3.1 `hit()`

```
def actor.enemy.Enemy.hit (
    self,
    direc )
```

Hit dectetion for [Enemy](#).

Handles health, iframes and knockback direction

Parameters

<i>direc</i>	Direction of the knockback
--------------	----------------------------

4.5.3.2 move()

```
def actor.enemy.Enemy.move (
    self )
```

Moves the [Enemy](#).

Adds the x speed and y speed to the x and y postion of the [Enemy](#)

4.5.3.3 update()

```
def actor.enemy.Enemy.update (
    self )
```

Update loop for a [Enemy](#).

Checks state, does the logic, and then moves [Enemy](#)

4.5.4 Member Data Documentation

4.5.4.1 hitCount

```
actor.enemy.Enemy.hitCount
```

This represents the buffer for the number of hits for the [Enemy](#) after being hit by player character.

4.5.4.2 hitdir

```
actor.enemy.Enemy.hitdir
```

Represents the direction [Enemy](#) is hit in by player character attack.

4.5.4.3 id

`actor.enemy.Enemy.id`

[Enemy](#) x position.

[Enemy](#) y position [Enemy](#) Id type


The documentation for this class was generated from the following file:

- `src/actor/enemy.py`

4.6 actor.fireball.Fireball Class Reference

This class represents the [Fireball](#) object.

Inheritance diagram for `actor.fireball.Fireball`:



Public Member Functions

- `def __init__ (self, x, y, xSpeed, ySpeed)`
Constructor for [Fireball](#).
- `def start (self, x, y, xs, ys)`
Starts the [Fireball](#)'s movement.
- `def end (self)`
Ends the [Fireball](#)'s movement.
- `def hit (self, dir)`
Empty function for being hit by player.
- `def checkState (self)`
Evaluates the state of the [Fireball](#).
- `def move (self)`
Moves the [Fireball](#).
- `def logic (self)`
Updates the [Fireball](#) sprite.
- `def update (self)`
Updates the [Fireball](#) every frame

Public Attributes

- [image](#)
Fireball surface.
- [rect](#)
Rectangle that represents the fireball.
- [id](#)
Fireball x postion.
- [isHit](#)
Wether the fireball is hit.
- [dmg](#)
Fireball damage.
- [hitCount](#)
Fireball hit frames.
- [xSpeed](#)
Fireball speed in the x direction.
- [ySpeed](#)
Fireball speed in the y direction.
- [frameCounter](#)
Total number of frames fireball is alive.
- **sprites**
- [obj](#)
Fireball collision list.
- [spriteIndex](#)
Sprite list index.

4.6.1 Detailed Description

This class represents the [Fireball](#) object.

4.6.2 Constructor & Destructor Documentation

4.6.2.1 `__init__()`

```
def actor.fireball.Fireball.__init__ (
    self,
    x,
    y,
    xSpeed,
    ySpeed )
```

Constructor for [Fireball](#).

Constructor takes four parameters, the x and y coordinates and the x and y speeds

Parameters

<i>x</i>	X coordinate of the starting postion of the Fireball
<i>y</i>	Y coordinate of the starting postion of the Fireball
<i>xSpeed</i>	The speed in the x direction of the Fireball
<i>ySpeed</i>	The speed in the y direction of the Fireball

4.6.3 Member Function Documentation

4.6.3.1 `checkState()`

```
def actor.fireball.Fireball.checkState (
    self )
```

Evaluates the state of the [Fireball](#).

Checks for collision with walls, doors, and players

4.6.3.2 `end()`

```
def actor.fireball.Fireball.end (
    self )
```

Ends the [Fireball](#)'s movement.

Sets the x and y speed to 0 and places the [Fireball](#) of screen

4.6.3.3 `hit()`

```
def actor.fireball.Fireball.hit (
    self,
    dir )
```

Empty function for being hit by player.

Needs to exist for when player sword collides with [Fireball](#)

4.6.3.4 `logic()`

```
def actor.fireball.Fireball.logic (
    self )
```

Updates the [Fireball](#) sprite.

Swaps between the 2 sprites every 15 frames

4.6.3.5 move()

```
def actor.fireball.Fireball.move (
    self )
```

Moves the [Fireball](#).

Adds the x speed and y speed to the x and y postion of the [Fireball](#)

4.6.3.6 start()

```
def actor.fireball.Fireball.start (
    self,
    x,
    y,
    xs,
    ys )
```

Starts the [Fireball](#)'s movement.

Sets the x and y postions and x and y speeds for [Fireball](#)

Parameters

x	X coordinate of where the Fireball is placed
y	Y coordinate of where the Fireball is placed
xs	The speed in the x direction of the Fireball
ys	The speed in the y direction of the Fireball

4.6.3.7 update()

```
def actor.fireball.Fireball.update (
    self )
```

Updates the [Fireball](#) every frame

Checks the state, applies the logic, and then moves the [Fireball](#)

4.6.4 Member Data Documentation

4.6.4.1 id

```
actor.fireball.Fireball.id
```

[Fireball](#) x postion.

[Fireball](#) y positon [Fireball](#) ID type

4.6.4.2 image

`actor.fireball.Fireball.image`

[Fireball](#) surface.

[Fireball](#) current sprite.


The documentation for this class was generated from the following file:

- `src/actor/fireball.py`

4.7 actor.healthbar.Health_Bar Class Reference

This class represents the HealthBar for the user controlled player character.

Inheritance diagram for `actor.healthbar.Health_Bar`:



Public Member Functions

- `def __init__ (self, x, y)`
Constructor HealthBar class.
- `def health (self, i)`
Method to update the current sprite image for the healthbar.

Public Attributes

- `image`
This represents the sprite image for the [Health_Bar](#) object.
- `h_sprite_sheet`
This represents the spritesheet for the image for the [Health_Bar](#) object, containing all sprites associated with the health bar.
- `rect`
This represents rectangle for position for the sprite image of the [Health_Bar](#) object.

4.7.1 Detailed Description

This class represents the HealthBar for the user controlled player character.

The HealthBar class uses the base class for visible game objects from Pygame library.

4.7.2 Constructor & Destructor Documentation

4.7.2.1 __init__()

```
def actor.healthbar.Health_Bar.__init__ (
    self,
    x,
    y )
```

Constructor HealthBar class.

Constructor for class initializes the x and y location of the HealthBar object.

Parameters

<i>x</i>	this represents the x-coordinate at which the HealthBar object will be drawn.
<i>y</i>	this represents the y-coordinate at which the HealthBar object will be drawn.

4.7.3 Member Function Documentation

4.7.3.1 health()

```
def actor.healthbar.Health_Bar.health (
    self,
    i )
```

Method to update the current sprite image for the healthbar.

This method will allow the HealthBar to update as soon as the player character is damaged/receives health.

Parameters

<i>i</i>	value represening the number of heart sprites to render to screen.
----------	--

4.7.4 Member Data Documentation

4.7.4.1 h_sprite_sheet

```
actor.healthbar.Health_Bar.h_sprite_sheet
```

This represents the spritesheet for the image for the [Health_Bar](#) object, containing all sprites associated with the health bar.

4.7.4.2 image

```
actor.healthbar.Health_Bar.image
```

This represents the sprite image for the [Health_Bar](#) object.

4.7.4.3 rect

```
actor.healthbar.Health_Bar.rect
```

This represents rectangle for position for the sprite image of the [Health_Bar](#) object.


The documentation for this class was generated from the following file:

- [src/actor/healthbar.py](#)

4.8 actor.item.Item Class Reference

Consumable [Item](#) Class This class is used for the creation of a random consumable item, spawned once an enemy has been defeated on their last position before despawn.

Inheritance diagram for actor.item.Item:



Public Member Functions

- `def __init__ (self, x, y, typ)`
[Item](#) constructor A sprite subclass constructor which takes a pair of x-y coordinates, commonly those of the killed enemy, and an item type, in the form of a randomly generated integer from 0 to the # of possible items.
- `def collision (self, p)`
Collision handler for the player and the consumable item, depending on the item's type.

Public Attributes

- [image](#)
Item sprite image.
- [itemsprite](#)
List of possible item sprite images.
- [rect](#)
Item x and y position.
- [id](#)
Collision ID (how other items tell what this item is)
- [type](#)
Integer value to determine what kind of item this is (rupee, heart, etc)

4.8.1 Detailed Description

Consumable [Item](#) Class This class is used for the creation of a random consumable item, spawned once an enemy has been defeated on their last position before despawn.

4.8.2 Constructor & Destructor Documentation

4.8.2.1 `__init__()`

```
def actor.item.Item.__init__ (
    self,
    x,
    y,
    typ )
```

[Item](#) constructor A sprite subclass constructor which takes a pair of x-y coordinates, commonly those of the killed enemy, and an item type, in the form of a randomly generated integer from 0 to the # of possible items.

Parameters

<i>x</i>	X coordinate of the spawned item
<i>y</i>	Y coordinate of the spawned item
<i>typ</i>	Integer value to specify the type of consumable item

4.8.3 Member Function Documentation

4.8.3.1 `collision()`

```
def actor.item.Item.collision (
    self,
```

p)

Collision handler for the player and the consumable item, depending on the item's type.

Parameters

<i>p</i>	Player object
----------	---------------


The documentation for this class was generated from the following file:

- [src/actor/item.py](#)

4.9 actor.keese.Keese Class Reference

This class represents the [Keese](#) enemy.

Inheritance diagram for actor.keese.Keese:



Public Member Functions

- `def __init__ (self, x, y)`
Constructor for [Keese](#).
- `def genRestLength (self)`
Sets the [Keese](#) rest length.
- `def genTravelPoint (self)`
Creates a new travel point for [Keese](#).
- `def switchSprite (self)`
Iterates through the sprite list.
- `def stop (self)`
Stops the [Keese](#).
- `def setMoveSpeed (self)`
Sets the [Keese](#) x and y movement speed.
- `def checkState (self)`
Evaluates the state of the [Keese](#).
- `def enemyLogic (self)`
Controls [Keese](#) logic.

Public Attributes

- [isMoving](#)
Whether the [Keese](#) is moving.
- [canStop](#)
Whether the [Keese](#) can stop.
- [isResting](#)
Whether the [Keese](#) is resting.
- [travelPoint](#)
Point the [Keese](#) is traveling to.
- [restTime](#)
The amount of frames the [Keese](#) will rest for.
- [restStartFrame](#)
The frame the [Keese](#) starts resting.
- [flyStartFrame](#)
The frame the [Keese](#) starts flying on.
- [spriteIndex](#)
The sprite list index.
- [maxHP](#)
[Keese](#) max health.
- [HP](#)
[Keese](#) current health.
- [dmg](#)
[Keese](#) damage.
- [image](#)
[Keese](#) current sprite.
- [sprites](#)
[Keese](#) sprite list.
- [xSpeed](#)
The current x-directional speed for [Keese](#) in movement/stationary state.
- [ySpeed](#)
The current y-directional speed for [Keese](#) in movement/stationary state.
- [hitCount](#)
Integer value representing the buffer for the number of hits for [Keese](#) after being hit by player character.
- [isHit](#)
Represents the current state if [Keese](#) has collided with player character attack.

4.9.1 Detailed Description

This class represents the [Keese](#) enemy.

4.9.2 Constructor & Destructor Documentation

4.9.2.1 `__init__()`

```
def actor.keese.Keese.__init__ (
    self,
    x,
    y )
```

Constructor for [Keese](#).

Constructor takes two parameters, the x and y coordinates

Parameters

<i>x</i>	X coordinate of the starting postion of the Keese
<i>y</i>	Y coordinate of the starting postion of the Keese

4.9.3 Member Function Documentation

4.9.3.1 checkState()

```
def actor.keese.Keese.checkState (
    self )
```

Evaluates the state of the [Keese](#).

Evalautes if the [Keese](#) if moving, if it can stop, if it is in iframes, and if it has died

4.9.3.2 enemyLogic()

```
def actor.keese.Keese.enemyLogic (
    self )
```

Controls [Keese](#) logic.

Uses the states to control the [Keese](#)

4.9.3.3 genRestLength()

```
def actor.keese.Keese.genRestLength (
    self )
```

Sets the [Keese](#) rest length.

Generates a random number between [1,2] inclusive as the rest time between movements and sets the rest start frame to the current frame

4.9.3.4 genTravelPoint()

```
def actor.keese.Keese.genTravelPoint (
    self )
```

Creates a new travel point for [Keese](#).

Generate a random point to move to between 0 an the width - 30 of the screen for the x coordinate and between 0 and the height - 30 of the screen for the y coordinate

4.9.3.5 setMoveSpeed()

```
def actor.keese.Keese.setMoveSpeed (
    self )
```

Sets the [Keese](#) x and y movement speed.

Compares the two lengths of travel (x and y) and sets the speed in which ever direction is longer to the max speed and the other to a scalar multiple of the max speed based on the ratio of the two lengths

4.9.3.6 stop()

```
def actor.keese.Keese.stop (
    self )
```

Stops the [Keese](#).

Sets the [Keese](#) speed in the x direction and the y direction to zero

4.9.3.7 switchSprite()

```
def actor.keese.Keese.switchSprite (
    self )
```

Iterates through the sprite list.

Swaps between the two sprites that are available for the keese

4.9.4 Member Data Documentation

4.9.4.1 hitCount

```
actor.keese.Keese.hitCount
```

Integer value representing the buffer for the number of hits for [Keese](#) after being hit by player character.

4.9.4.2 image

```
actor.keese.Keese.image
```

[Keese](#) current sprite.

Set [Keese](#) starting sprite.

4.9.4.3 isHit

```
actor.keese.Keese.isHit
```

Represents the current state if [Keese](#) has collided with player character attack.

4.9.4.4 xSpeed

```
actor.keese.Keese.xSpeed
```

The current x-directional speed for [Keese](#) in movement/stationary state.

4.9.4.5 ySpeed

```
actor.keese.Keese.ySpeed
```

The current y-directional speed for [Keese](#) in movement/stationary state.


The documentation for this class was generated from the following file:

- [src/actor/keese.py](#)

4.10 collision.level.Level Class Reference

Dungeon level background class Creates the background of a dungeon, can be modified in the future to change colour based on sprite sheet and new arg.

Inheritance diagram for `collision.level.Level`:



Public Member Functions

- `def __init__(self)`
Background initializer Initialize a background to constantly be printed as game background.

Public Attributes

- [image](#)
Level background sprite image.
- [rect](#)
Background x and y coordinates (adjusted for the HUD display)

4.10.1 Detailed Description

Dungeon level background class Creates the background of a dungeon, can be modified in the future to change colour based on sprite sheet and new arg.

The documentation for this class was generated from the following file:

- [src/collision/level.py](#)

4.11 collision.levelmanager.LevelManager Class Reference

Dungeon Level Creation Class Class used as a master constructor for every dungeon levels, getting pre-written data and loading it when the game starts and when a transition occurs.

Public Member Functions

- `def __init__ (self, spritelist, collidlist, updatelist)`
Dungeon Level Master Initializer The class initializer, taking empty lists, each for letting the [make\(\)](#) function define what objects need to be drawn/collidable/updatable.
- `def make (self, x, y)`
Dungeon Level Constructor The main function to load a given index of data from leveledata.py, and load it into the game environment.
- `def transition (self, xchange, ychange)`
Dungeon level transition function, used to go to an adjacent level, clear all current data, and load new room data.
- `def open (self)`
Function to open all blocked doors in the current dungeon room (usually used when all enemies defeated, locked doors stay locked)
- `def endroom (self)`
Function to store current data, open all blocked doors, and possibly spawn a key/prize when all enemies defeated When all enemies in a room are killed, this function is called, changing the enemy array in leveledata.py for the current level to an empty array (so enemies don't reload once you enter again), running the self.open() function to open all blocked doors, and if the roomID is a predetermined key/rupy room, spawn a key/rupy in the middle of the room.
- `def clear (self)`
Clears the levelmanager's update lists Empty all sprite lists for the game (spritelist, collisionlist, and updatelist), usually used in transition from one room to another.

Public Attributes

- [sl](#)
List of objects to be printed (ie player, not invisible walls)
- [cl](#)
List of objects that can be collided with (ie keese, not level background)
- [ul](#)
List of objects that need to be constantly updated (ie player, not walls/static objects)
- [x](#)
X-Coordinate of the level in leveledata's Room ID array (RID[y][x])
- [y](#)
Y-Coordinate of the level in leveledata's Room ID array (RID[y][x])
- [level](#)
Level background.
- [RID](#)
Misc room spawnings (ie shop room)
- **enarray**
- **boss**
- **doors**
- **killed**

Static Public Attributes

- list **keyset** = [3, 7, 17]
- list **rupeset** = [1, 16, 12]
- [LD](#) = None
List of all rooms to load (to be altered)

4.11.1 Detailed Description

Dungeon Level Creation Class Class used as a master constructor for every dungeon levels, getting pre-written data and loading it when the game starts and when a transition occurs.

4.11.2 Constructor & Destructor Documentation

4.11.2.1 `__init__()`

```
def collision.levelmanager.LevelManager.__init__ (
    self,
    spritelist,
    collidlist,
    updatelist )
```

Dungeon Level Master Initializer The class initializer, taking empty lists, each for letting the [make\(\)](#) function define what objects need to be drawn/collidable/updatable.

Parameters

<i>spritelist</i>	List of objects for the game to print (usually empty pygame.sprite.Group)
<i>collidlist</i>	List of objects which have a collision interaction with the player (usually empty pygame.sprite.Group)
<i>updatelist</i>	List of objects which need to be regularly updated (usually empty pygame.sprite.Group)

4.11.3 Member Function Documentation

4.11.3.1 make()

```
def collision.levelmanager.LevelManager.make (
    self,
    x,
    y )
```

Dungeon Level Constructor The main function to load a given index of data from leveledata.py, and load it into the game environment.

Parameters

<i>i</i>	Index of the room to be created
----------	---------------------------------

4.11.3.2 transition()

```
def collision.levelmanager.LevelManager.transition (
    self,
    xchange,
    ychange )
```

Dungeon level transition function, used to go to an adjacent level, clear all current data, and load new room data.

Parameters

<i>j</i>	Value to add to the current index to get to new room
----------	--


The documentation for this class was generated from the following file:

- src/collision/[levelmanager.py](#)

4.12 actor.player.Player Class Reference

Player Class A pygame sprite subclass for defining the creation of the game's playable character, as well as its interactions with both the user and other entities within the game.

Inheritance diagram for actor.player.Player:



Public Member Functions

- `def __init__ (self, x, y, hud)`
Player constructor The constructor for the player object, used within the initialization of the game.
- `def movechar (self)`
Function to move the player in a specified direction.
- `def move (self, d, b)`
Function to store which movement buttons are being pressed and let go of by the user.
- `def attack (self)`
Function to react to the user pressing the attack button, putting the player into an attack animation and spawning a sword for the duration.
- `def useitem (self)`
Function to react to the user pressing the use item button, putting the player into an attack animation and spawning a boomerang for the duration.
- `def moveupdate (self)`
UPDATE LOOP FUNCTIONS.
- `def attackupdate (self)`
Update function for attack and boomerang conditions, as well as handing user collision with enemies (damage taken) Checks sword collision on enemies, and checks the timeout on both the sword and boomerang attack animations, telling the player when they can move again.
- `def collisionupdate (self)`
Update function to check collisions between the player and any specified collidable objects, and call their respective collision events.
- `def update (self)`
Player master update function, running all update functions, repeated in main file loop.

Public Attributes

- `image`
Player sprite image.
- `id`
Collision ID (To tell other objects what this object is)
- `leveltrans`
Boolean value to tell the game when the player has left the room, and a room transition is needed.
- `rect`
Player x and y position.
- `walkLeft`
Animation sprites for player walking left.
- `walkRight`
Animation sprites for player walking right.
- `walkUp`
Animation sprites for player walking up.

- [walkDown](#)
Animation sprites for player walking down.
- [attacksprite](#)
Animation sprites for player attacking.
- [obj](#)
List of objects that the player can collide with.
- [hbar](#)
Health bar corresponding to the player's health.
- **rbar**
- **kbar**
- [totalhp](#)
Player's maximum HP amount.
- [hp](#)
Player's current HP amount (starts at max)
- [rupees](#)
Player's rupee counter.
- [keys](#)
Player's key counter.
- **collision**
- **collidbuy**
- **doorcount**
- **spawning**
- **spawncount**
- [moveable](#)
Boolean allowing and stoping the player from moving.
- [attackbool](#)
Boolean to tell whether the player is attacking or not.
- [attackcount](#)
Attack counter, to control how long the attack lasts.
- [attacksword](#)
Holder for a sword object when attacking.
- [item](#)
Holder for a boomerang object when using item.
- [itembool](#)
Boolean to tell whether the player is using their boomerang or not.
- [oldx](#)
Player's x value one frame ago.
- [oldy](#)
Player's y value one frame ago.
- [dirbool](#)
Boolean array to tell which directional buttons are pressed or not (starting left going clockwise, dirbool[0] is left, dirbool[1] is up, etc)
- [dir](#)
Current direction the player is facing.
- [hit](#)
Boolean on whether the player was recently hit.
- [hitcount](#)
How long a hit counts for on the player (how long until self.hit turns off)
- **speed**
- **debug**
- [hasWon](#)
Has the player won or not.

4.12.1 Detailed Description

Player Class A pygame sprite subclass for defining the creation of the game's playable character, as well as its interactions with both the user and other entities within the game.

4.12.2 Constructor & Destructor Documentation

4.12.2.1 `__init__()`

```
def actor.player.Player.__init__ (
    self,
    x,
    y,
    hud )
```

Player constructor The constructor for the player object, used within the initialization of the game.

The only arguments passed are an initial x and y position, as well as heads-up-display (HUD) elements.

Parameters

<i>x</i>	Initial player x coordinate
<i>y</i>	Initial player y coordinate
<i>hud</i>	Array of HUD elements which act directly with the user's tracked values (health bar, rupy/key count)

4.12.3 Member Function Documentation

4.12.3.1 `attackupdate()`

```
def actor.player.Player.attackupdate (
    self )
```

Update function for attack and boomerang conditions, as well as handing user collision with enemies (damage taken) Checks sword collision on enemies, and checks the timeout on both the sword and boomerang attack animations, telling the player when they can move again.

Also updates the player and reacts accordingly to receiving damage.

4.12.3.2 `move()`

```
def actor.player.Player.move (
    self,
    d,
    b )
```

Function to store which movement buttons are being pressed and let go of by the user.

Parameters

<i>d</i>	Direction related to the button pressed (integer value from 0 to 3, starting from the left and going clockwise)
<i>b</i>	Boolean value on whether the button is pressed or not

4.12.3.3 moveupdate()

```
def actor.player.Player.moveupdate (
    self )
```

UPDATE LOOP FUNCTIONS.

Update function for player movement and according sprite animation

4.12.4 Member Data Documentation

4.12.4.1 attacksword

```
actor.player.Player.attacksword
```

Holder for a sword object when attacking.

Sprite function to delete a sprite object and all relations of the object in the project.

4.12.4.2 dir

```
actor.player.Player.dir
```

Current direction the player is facing.

Render Appropriate Sprites According to movement.


The documentation for this class was generated from the following file:

- [src/actor/player.py](#)

4.13 actor.rupee.Rupee_Bar Class Reference

This class represents the RupeeBar object.

Inheritance diagram for actor.rupee.Rupee_Bar:



Public Member Functions

- `def __init__(self, x, y)`
Constructor for the RupeeBar object.

Public Attributes

- `image`
This represents the sprite image of the [Rupee_Bar](#) object.
- `rect`
This represents rectangle for collision and position for the sprite image of the [Rupee_Bar](#) object.

4.13.1 Detailed Description

This class represents the RupeeBar object.

The Rupee class uses the Pygame library and SpriteSheet module to create an image for the

4.13.2 Constructor & Destructor Documentation

4.13.2.1 __init__()

```
def actor.rupee.Rupee_Bar.__init__ (
    self,
    x,
    y )
```

Constructor for the RupeeBar object.

Constructor for class initializes the x and y location of the RupeeBar object.

Parameters

<code>x</code>	this represents the x-coordinate at which the RupeeBar object will be drawn.
<code>y</code>	this represents the y-coordinate at which the RupeeBar object will be drawn.

4.13.3 Member Data Documentation

4.13.3.1 image

```
actor.rupee.Rupee_Bar.image
```

This represents the sprite image of the [Rupee_Bar](#) object.

4.13.3.2 rect

```
actor.rupee.Rupee_Bar.rect
```

This represents rectangle for collision and position for the sprite image of the [Rupee_Bar](#) object.


The documentation for this class was generated from the following file:

- [src/actor/rupee.py](#)

4.14 actor.spritesheet.SpriteSheet Class Reference

This class represents the [SpriteSheet](#) object, allowing sprites to be loaded and processed.

Inheritance diagram for actor.spritesheet.SpriteSheet:



Public Member Functions

- `def __init__(self, file_name)`
Constructor for the [SpriteSheet](#) class.
- `def get_image(self, x, y, width, height)`
Accessor to return an image splice from the loaded [SpriteSheet](#).
- `def get_imageNT(self, x, y, width, height)`
Accessor to return an image splice from the loaded [SpriteSheet](#), WITHOUT removing the image background.

Public Attributes

- [sprite_sheet](#)
This represents the current spritesheet loaded from the specific file_name path.

4.14.1 Detailed Description

This class represents the [SpriteSheet](#) object, allowing sprites to be loaded and processed.

The [SpriteSheet](#) class uses the Pygame library to load images and change the transparency on those images.

4.14.2 Constructor & Destructor Documentation

4.14.2.1 `__init__()`

```
def actor.spritesheet.SpriteSheet.__init__ (
    self,
    file_name )
```

Constructor for the [SpriteSheet](#) class.

This constructor initializes an image file using the Pygame library.

Parameters

<i>file_name</i>	This is the string representing the path to the image file.
------------------	---

4.14.3 Member Function Documentation

4.14.3.1 `get_image()`

```
def actor.spritesheet.SpriteSheet.get_image (
    self,
    x,
    y,
    width,
    height )
```

Accessor to return an image splice from the loaded [SpriteSheet](#).

This accessor returns an image splice based on the x,y location and the height and width of the image.

Parameters

<i>x</i>	The x-coordinate for starting point of the splice on the SpriteSheet .
<i>y</i>	The y-coordinate for starting point of the splice on the SpriteSheet .
<i>width</i>	The width of the splice on the SpriteSheet .
<i>height</i>	The height of the splice on the SpriteSheet .

Returns

image This returns the newly spliced image after removing the image background transparency.

4.14.3.2 get_imageNT()

```
def actor.spritesheet.SpriteSheet.get_imageNT (
    self,
    x,
    y,
    width,
    height )
```

Accessor to return an image splice from the loaded [SpriteSheet](#), WITHOUT removing the image background.

This accessor returns an image splice based on the x,y location and the height and width of the image.

Parameters

<i>x</i>	The x-coordinate for starting point of the splice on the SpriteSheet .
<i>y</i>	The y-coordinate for starting point of the splice on the SpriteSheet .
<i>width</i>	The width of the splice on the SpriteSheet .
<i>height</i>	The height of the splice on the SpriteSheet .

Returns

image This returns the newly spliced image WITHOUT removing the image background transparency.

4.14.4 Member Data Documentation

4.14.4.1 sprite_sheet

```
actor.spritesheet.SpriteSheet.sprite_sheet
```

This represents the current spritesheet loaded from the specific file_name path.


The documentation for this class was generated from the following file:

- src/actor/[spritesheet.py](#)

4.15 actor.stalfos.Stalfos Class Reference

This class represents the [Stalfos](#) enemy.

Inheritance diagram for actor.stalfos.Stalfos:



Public Member Functions

- `def __init__ (self, x, y)`
Constructor for [Stalfos](#).
- `def checkState (self)`
Evaluates the state of the [Stalfos](#).
- `def enemyLogic (self)`
Controls [Stalfos](#) logic.
- `def genTravelPath (self)`
Creates a new travel point for [Stalfos](#).
- `def setWalkSpeed (self)`
Sets the walk speed of the [Stalfos](#).
- `def stop (self)`
Stops the [Stalfos](#).

Public Attributes

- `isMoving`
Call superclass constructor.
- `previousDirection`
Movement integer value for previous direction of movement for [Stalfos](#) state.
- `direction`
Movement integer value for current direction of movement for [Stalfos](#) state.
- `walkFrames`
Integer representing the frames walked by [Stalfos](#) in movement state.
- `walkStartFrame`
Integer value for movement frame for [Stalfos](#) during movement state.
- `oldx`
This represents the previous x-location of [Stalfos](#) in movement/stationary state.
- `oldy`
This represents the previous y-location of [Stalfos](#) in movement/stationary state.
- `obj`
This represents the list of objects [Stalfos](#) can collide with, in movement/stationary state.
- `maxHP`
The integer value setting the [Stalfos](#) health to maximum health.
- `HP`
The integer value representing Current [Stalfos](#) health.
- `dmg`
The integer value representing the current damage value that the [Stalfos](#) object has received from player character.
- `image`
Spritesheet for the accessing of the [Stalfos](#) sprite image.
- `sprites`
Creates a list of sprites list for [Stalfos](#).
- `spriteIndex`
Represents the integer value for the current index in the sprite list for [Stalfos](#).
- `hitdir`
Represents the integer value (0,1,2,3) direction [Stalfos](#) is hit in by player character attack.
- `hitCount`
Integer value representing the buffer for the number of hits for the Enemy after being hit by player character.
- `isHit`

Represents the current state if [Stalfos](#) has collided with player character attack.

- [xSpeed](#)

The current x-directional speed for [Stalfos](#) in movement/stationary state.

- [ySpeed](#)

The current y-directional speed for [Stalfos](#) in movement/stationary state.

4.15.1 Detailed Description

This class represents the [Stalfos](#) enemy.

4.15.2 Constructor & Destructor Documentation

4.15.2.1 `__init__()`

```
def actor.stalfos.Stalfos.__init__ (
    self,
    x,
    y )
```

Constructor for [Stalfos](#).

Constructor takes two parameters, the x and y coordinates

Parameters

<i>x</i>	X coordinate of the starting postion of the Keese
<i>y</i>	Y coordinate of the starting postion of the Keese

4.15.3 Member Function Documentation

4.15.3.1 `checkState()`

```
def actor.stalfos.Stalfos.checkState (
    self )
```

Evaluates the state of the [Stalfos](#).

Evalautes if the [Stalfos](#) if moving, if it can stop, if it is in iframes, if it collides with something, and if it has died

4.15.3.2 enemyLogic()

```
def actor.stalfos.Stalfos.enemyLogic (
    self )
```

Controls [Stalfos](#) logic.

Uses the states to control the [Stalfos](#)

4.15.3.3 genTravelPath()

```
def actor.stalfos.Stalfos.genTravelPath (
    self )
```

Creates a new travel point for [Stalfos](#).

Generates a direction to walk and the distance to move

4.15.3.4 setWalkSpeed()

```
def actor.stalfos.Stalfos.setWalkSpeed (
    self )
```

Sets the walk speed of the [Stalfos](#).

Sets speed based on the direction

4.15.3.5 stop()

```
def actor.stalfos.Stalfos.stop (
    self )
```

Stops the [Stalfos](#).

Sets the [Stalfos](#) speed in the x direction and the y direction to zero

4.15.4 Member Data Documentation

4.15.4.1 direction

```
actor.stalfos.Stalfos.direction
```

Movement integer value for current direction of movement for [Stalfos](#) state.

4.15.4.2 dmg

```
actor.stalfos.Stalfos.dmg
```

The integer value representing the current damage value that the [Stalfos](#) object has received from player character.

4.15.4.3 hitCount

```
actor.stalfos.Stalfos.hitCount
```

Integer value representing the buffer for the number of hits for the Enemy after being hit by player character.

4.15.4.4 hitdir

```
actor.stalfos.Stalfos.hitdir
```

Represents the integer value (0,1,2,3) direction [Stalfos](#) is hit in by player character attack.

4.15.4.5 HP

```
actor.stalfos.Stalfos.HP
```

The integer value representing Current [Stalfos](#) health.

4.15.4.6 image

```
actor.stalfos.Stalfos.image
```

Spritesheet for the accessing of the [Stalfos](#) sprite image.

Set [Stalfos](#) starting sprite.

Sprite image for the [Stalfos](#) object.

4.15.4.7 isHit

```
actor.stalfos.Stalfos.isHit
```

Represents the current state if [Stalfos](#) has collided with player character attack.

4.15.4.8 isMoving

```
actor.stalfos.Stalfos.isMoving
```

Call superclass constructor.

Check for movement.

Boolean values for keeping track of the [Stalfos](#) state.

4.15.4.9 maxHP

```
actor.stalfos.Stalfos.maxHP
```

The integer value setting the [Stalfos](#) health to maximum health.

4.15.4.10 obj

```
actor.stalfos.Stalfos.obj
```

This represents the list of objects [Stalfos](#) can collide with, in movement/stationary state.

4.15.4.11 oldx

```
actor.stalfos.Stalfos.oldx
```

This represents the previous x-location of [Stalfos](#) in movement/stationary state.

4.15.4.12 oldy

```
actor.stalfos.Stalfos.oldy
```

This represents the previous y-location of [Stalfos](#) in movement/stationary state.

4.15.4.13 previousDirection

```
actor.stalfos.Stalfos.previousDirection
```

Movement integer value for previous direction of movement for [Stalfos](#) state.

4.15.4.14 spriteIndex

```
actor.stalfos.Stalfos.spriteIndex
```

Represents the integer value for the current index in the sprite list for [Stalfos](#).

4.15.4.15 sprites

```
actor.stalfos.Stalfos.sprites
```

Creates a list of sprites list for [Stalfos](#).

4.15.4.16 walkFrames

```
actor.stalfos.Stalfos.walkFrames
```

Integer representing the frames walked by Stalfos in movement state.

4.15.4.17 walkStartFrame

```
actor.stalfos.Stalfos.walkStartFrame
```

Integer value for movement frame for [Stalfos](#) during movement state.

4.15.4.18 xSpeed

```
actor.stalfos.Stalfos.xSpeed
```

The current x-directional speed for [Stalfos](#) in movement/stationary state.

4.15.4.19 ySpeed

```
actor.stalfos.Stalfos.ySpeed
```

The current y-directional speed for [Stalfos](#) in movement/stationary state.


The documentation for this class was generated from the following file:

- src/actor/[stalfos.py](#)

4.16 actor.sword.Sword Class Reference

Player [Sword](#) Class Class for the creation and deletion of the sword sprite object, made when the player attacks.

Inheritance diagram for actor.sword.Sword:



Public Member Functions

- `def __init__ (self, x, y, direction)`
[Sword](#) constructor, taking an x and y coordinate, and the direction for the sword to be pointing (player direction)

Public Attributes

- [sprite](#)
Array of all possible sword directions (following usual directional standards, 0-3, starting at left going clockwise)
- [image](#)
Sprite image of the sword.
- [rect](#)
X and Y position of the sword.

4.16.1 Detailed Description

Player [Sword](#) Class Class for the creation and deletion of the sword sprite object, made when the player attacks.

4.16.2 Constructor & Destructor Documentation

4.16.2.1 __init__()

```

def actor.sword.Sword.__init__ (
    self,
    x,
    y,
    direction )
  
```

[Sword](#) constructor, taking an x and y coordinate, and the direction for the sword to be pointing (player direction)

Parameters

<i>x</i>	Sword 's x coordinate
<i>y</i>	Sword 's y coordinate
<i>direction</i>	Sword 's direction (integer from 0 to 3, starting left, going clockwise)

4.16.3 Member Data Documentation

4.16.3.1 image

```
actor.sword.Sword.image
```

Sprite image of the sword.

Below is for testing `self.image = pygame.Surface([26, 14]) self.image.fill((200, 0, 0))`


The documentation for this class was generated from the following file:

- [src/actor/sword.py](#)

4.17 collision.wall.Wall Class Reference

This class represents the [Wall](#) class for collision for objects in the environment.

Inheritance diagram for collision.wall.Wall:



Public Member Functions

- `def __init__ (self, x, y, w, h, sprite)`
Constructor for the [Wall](#) class.
- `def collision (self, i)`
This method checks for collision with the [Wall](#) object and other sprite object.

Public Attributes

- [image](#)
This represents the sprite image for [Wall](#) object.
- [rect](#)
This represents rectangle for position for the sprite image of the [Wall](#) object.
- [id](#)
This represents the ID for the [Wall](#) object, ised for collision in [main.py](#).

4.17.1 Detailed Description

This class represents the [Wall](#) class for collision for objects in the environment.

The [Wall](#) class uses the base class for visible game objects from Pygame library.

4.17.2 Constructor & Destructor Documentation

4.17.2.1 `__init__()`

```
def collision.wall.Wall.__init__ (
    self,
    x,
    y,
    w,
    h,
    sprite )
```

Constructor for the [Wall](#) class.

Constructor for [Wall](#) class initializes a [Wall](#) object based on the x/y location and the width/height of the wall, and the sprite the collision for the wall will be created upon.

Parameters

<i>x</i>	This represents the integer value for the x-location for the Wall object to be created.
<i>y</i>	This represents the integer value for the y-location for the Wall object to be created.
<i>w</i>	This represents the integer value for the width of the Wall object when created.
<i>h</i>	This represents the integer value for the height of the Wall object when created.
<i>sprite</i>	This represents the sprite that the collision for a Wall will be present upon at all times.

4.17.3 Member Function Documentation

4.17.3.1 `collision()`

```
def collision.wall.Wall.collision (
    self,
    i )
```

This method checks for collision with the [Wall](#) object and other sprite object.

The collision will be checked with the [Wall](#) and other sprite object as the object collides with the wall.

Parameters

<i>i</i>	This is the sprite object that is passed into the method, and checks if the object is colliding with the Wall object, resetting the sprite objects location accordingly.
----------	--

4.17.4 Member Data Documentation

4.17.4.1 id

```
collision.wall.Wall.id
```

This represents the ID for the [Wall](#) object, ised for collision in **main.py**.

4.17.4.2 image

```
collision.wall.Wall.image
```

This represents the sprite image for [Wall](#) object.

4.17.4.3 rect

```
collision.wall.Wall.rect
```

This represents rectangle for position for the sprite image of the [Wall](#) object.

The documentation for this class was generated from the following file:

- [src/collision/wall.py](#)

Chapter 5

File Documentation

5.1 src/actor/aquamentus.py File Reference

Aquamentus Boss

Classes

- class `actor.aquamentus.Aquamentus`
This class represents the [Aquamentus](#) Boss.

Functions

- def `actor.aquamentus.populateSprites ()`
Creates the sprite list for [Aquamentus](#).

Variables

- string `actor.aquamentus.SPRITE_MAP` = 'src/actor/sprites/aquamentus.png'

5.1.1 Detailed Description

Aquamentus Boss

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 8 2018

5.1.2 Function Documentation

5.1.2.1 populateSprites()

```
def actor.aquamentus.populateSprites ( )
```

Creates the sprite list for Aquamentus.

Iterates through a sprite sheet to pull images for the sprite array

Returns

sprites Array if the sprites that represent the Aquamentus

5.2 src/actor/boomerang.py File Reference

Boomerang Weapon

Classes

- class [actor.boomerang.Boomerang](#)
Boomerang Weapon Class The class holding the creation, behaviour, and collision effects of the player's boomerang weapon.

Functions

- def [actor.boomerang.populateSprites](#) ()
Creates the sprite list for Boomerang.
- def [actor.boomerang.stuncoefficient](#) (x)
Finds the coefficient for the stun value Uses a quadratic equation with the frame counter to find the coefficient.

Variables

- string **actor.boomerang.SPRITE_MAP** = 'src/actor/sprites/boomerang.png'

5.2.1 Detailed Description

Boomerang Weapon

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 6 2018

5.2.2 Function Documentation

5.2.2.1 populateSprites()

```
def actor.boomerang.populateSprites ( )
```

Creates the sprite list for Boomerang.

Iterates through a sprite sheet to pull images for the sprite array

Returns

sprites Array if the sprites that represent the Boomerang

5.2.2.2 stuncoefficient()

```
def actor.boomerang.stuncoefficient (
    x )
```

Finds the coefficient for the stun value Uses a quadratic equation with the frame counter to find the coefficient.

Parameters

x	The current frame of the boomerang
---	------------------------------------

Returns

c The coefficient for the boomerang stun

5.3 src/actor/boss.py File Reference

Boss Template

Classes

- class [actor.boss.Boss](#)

Superclass for representing a [Boss](#).

5.3.1 Detailed Description

Boss Template

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.4 src/actor/constants.py File Reference

Actor Constants

Variables

- tuple `actor.constants.BLACK` = (0,0,0)
Defines the colour black.
- tuple `actor.constants.WHITE` = (255, 255, 255)
Defines the colour white.
- tuple `actor.constants.PURPLE` = (255, 50, 255)
Defines the colour purple.
- tuple `actor.constants.RED` = (255, 50, 50)
Defines the colour red.
- tuple `actor.constants.BLUE` = (0,0,255)
Defines the color blue.
- int `actor.constants.PLAYER_WIDTH` = 15
Defines the player's width.
- int `actor.constants.PLAYER_HEIGHT` = 15
Defines the player's height.
- int `actor.constants.PLAYER_SPEED` = 2
Defines the player's speed.
- int `actor.constants.PLAYER_MAX_HP` = 3
Defines the player's max hp.
- int `actor.constants.PLAYER_DOORCOUNT` = 20
Defines how many frames the player collides with a locked door before a key is used.
- int `actor.constants.PLAYER_SPAWNCOUNT` = 8
Defines how long the player is uncontrollable for when entering a new room (movement to walk out of door)
- int `actor.constants.HIT_SPEED` = 12
Defines the speed of the knock back applied per frame.
- int `actor.constants.HIT_TIME` = 5
Defines the number of frames hit speed is applied for.
- int `actor.constants.HIT_IFRAME` = 30
Defines the number of iframes.
- int `actor.constants.ATK_WIDTH` = 15
Defines the width of the attack hitbox.

- int `actor.constants.ATK_HEIGHT` = 15
Defines the height of the attack hitbox.
- int `actor.constants.ATK_LENGTH` = 10
Defines the number of frames the hit stays out for.
- int `actor.constants.ATK_BUFFER` = 20
Defines the number of frames before the next attack can start.
- int `actor.constants.BOOM_SPEED` = 9
Defines the bommerang speed.
- float `actor.constants.BOOM_RETURN` = 0.3
Defines the acceleration in the opposite direction of the bommerang's travel path.
- int `actor.constants.GLOBAL_FRAME_BUFFER` = 12
Coordinate Divisor that determines range in which next sprite should render.
- int `actor.constants.KEESE_MAX_HP` = 1
Defines the keese's max hp.
- float `actor.constants.KEESE_DMG` = 0.5
Defines the keese's damage.
- int `actor.constants.KEESE_MAX_SPEED` = 2
Defines the keese's max speed.
- int `actor.constants.KEESE_MIN_SPEED` = 1
Defines the keese's min speed.
- int `actor.constants.ACCEPTABLE_RADIUS` = 20
Defines the keese's minimum magnitude from its determined travel point before stopping.
- int `actor.constants.KEESE_MAGNITUDE_MIN` = 200
Defines the keese's minimum magnitude for selecting its next travel point.
- int `actor.constants.STALFOS_MAX_HP` = 2
Defines the stalfos' max hp.
- int `actor.constants.STALFOS_DMG` = 1
Defines the stalfos' damage.
- int `actor.constants.STALFOS_SPEED` = 1
Defines the stalfos' speed.
- int `actor.constants.STALFOS_HIT_SPEED` = 10
Defines the stalfos' speed during knockback.
- int `actor.constants.ENEMY_STUNCOUNT` = 35
Length of frames an enemy will be stunned for when hit by a boomerang.
- int `actor.constants.AQUAMENTUS_MAX_HP` = 5
Defines the aquamentus' max hp.
- int `actor.constants.AQUAMENTUS_DMG` = 2
Defines the aquamentus' damage.
- int `actor.constants.AQUAMENTUS_SPEED` = 1
Defines the aquamentus' speed.
- int `actor.constants.FIREBALL_DMG` = 1
Defines the fireballs damage.

5.4.1 Detailed Description

Actor Constants

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 9 2018

5.5 `src/actor/enemy.py` File Reference

Enemy Template

Classes

- class `actor.enemy.Enemy`
Superclass for representing an `Enemy`.

5.5.1 Detailed Description

Enemy Template

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.6 `src/actor/fireball.py` File Reference

Fireball object

Classes

- class `actor.fireball.Fireball`
This class represents the `Fireball` object.

Functions

- def `actor.fireball.populateSprites ()`
Creates the sprite list for `Fireball`.

Variables

- string **actor.fireball.SPRITE_MAP** = 'src/actor/sprites/fireball.png'

5.6.1 Detailed Description

Fireball object

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.6.2 Function Documentation

5.6.2.1 populateSprites()

```
def actor.fireball.populateSprites ( )
```

Creates the sprite list for Fireball.

Iterates through a sprite sheet to pull images for the sprite array

Returns

sprites Array if the sprites that represent the Fireball

5.7 src/actor/healthbar.py File Reference

HealthBar Class

Classes

- class [actor.healthbar.Health_Bar](#)

This class represents the HealthBar for the user controlled player character.

5.7.1 Detailed Description

HealthBar Class

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.8 src/actor/item.py File Reference

Consumable Items

Classes

- class [actor.item.Item](#)

Consumable [Item](#) Class This class is used for the creation of a random consumable item, spawned once an enemy has been defeated on their last position before despawn.

5.8.1 Detailed Description

Consumable Items

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 6 2018

5.9 src/actor/keese.py File Reference

Keese Enemy

Classes

- class [actor.keese.Keese](#)

This class represents the [Keese](#) enemy.

Functions

- def [actor.keese.populateSprites](#) ()
Creates the sprite list for [Keese](#).

Variables

- string **actor.keese.SPRITE_MAP** = 'src/actor/sprites/keese.png'

5.9.1 Detailed Description

Keese Enemy

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.9.2 Function Documentation

5.9.2.1 populateSprites()

```
def actor.keese.populateSprites ( )
```

Creates the sprite list for Keese.

Iterates through a sprite sheet to pull images for the sprite array

Returns

sprites Array if the sprites that represent the Keese

5.10 src/actor/player.py File Reference

Playable Characer

Classes

- class [actor.player.Player](#)
[Player](#) Class A pygame sprite subclass for defining the creation of the game's playable character, as well as its interactions with both the user and other entities within the game.

5.10.1 Detailed Description

Playable Characer

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 6 2018

5.11 `src/actor/rupee.py` File Reference

Rupee_Bar Class

Classes

- class [actor.rupee.Rupee_Bar](#)
This class represents the RupeeBar object.

5.11.1 Detailed Description

Rupee_Bar Class

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.12 `src/actor/spritesheet.py` File Reference

SpriteSheet Class

Classes

- class [actor.spritesheet.SpriteSheet](#)
This class represents the [SpriteSheet](#) object, allowing sprites to be loaded and processed.

5.12.1 Detailed Description

SpriteSheet Class

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.13 src/actor/stalfos.py File Reference

Stalfos Enemy

Classes

- class [actor.stalfos.Stalfos](#)
This class represents the [Stalfos](#) enemy.

Functions

- def [actor.stalfos.populateSprites](#) ()
Creates the sprite list for [Stalfos](#).

Variables

- string **actor.stalfos.SPRITE_MAP** = 'src/actor/sprites/stalfos.png'

5.13.1 Detailed Description

Stalfos Enemy

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.13.2 Function Documentation

5.13.2.1 populateSprites()

```
def actor.stalfos.populateSprites ( )
```

Creates the sprite list for Stalfos.

Iterates through a sprite sheet to pull images for the sprite array

Returns

sprites Array if the sprites that represent the Stalfos

5.14 src/actor/sword.py File Reference

Player Sword

Classes

- class [actor.sword.Sword](#)

Player [Sword](#) Class Class for the creation and deletion of the sword sprite object, made when the player attacks.

5.14.1 Detailed Description

Player Sword

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 8 2018

5.15 src/collision/door.py File Reference

Dungeon Door

Classes

- class [collision.door.Door](#)

Dungeon [Door](#) Class This class is used to place a door on one of four places of a dungeon room, to allow the player to walk through and traverse to other rooms within the dungeon.

5.15.1 Detailed Description

Dungeon Door

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.16 src/collision/level.py File Reference

Dungeon Background

Classes

- class [collision.level.Level](#)

Dungeon level background class Creates the background of a dungeon, can be modified in the future to change colour based on sprite sheet and new arg.

5.16.1 Detailed Description

Dungeon Background

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.17 src/collision/levelmanager.py File Reference

Dungeon Level Master Creator

Classes

- class [collision.levelmanager.LevelManager](#)

Dungeon Level Creation Class Class used as a master constructor for every dungeon levels, getting pre-written data and loading it when the game starts and when a transition occurs.

5.17.1 Detailed Description

Dungeon Level Master Creator

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.18 src/collision/wall.py File Reference

Wall Class

Classes

- class [collision.wall.Wall](#)

This class represents the [Wall](#) class for collision for objects in the environment.

5.18.1 Detailed Description

Wall Class

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.19 src/config/colour.py File Reference

Colour Constants

Variables

- tuple [config.colour.WHITE](#) = (255, 255, 255)

Defines the colour white.

5.19.1 Detailed Description

Colour Constants

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

5.20 src/config/window.py File Reference

Window Constants

Variables

- int `config.window.Y_OFFSET` = 56
Y offset for HUD.
- int `config.window.Wwidth` = 480
Width of the window.
- int `config.window.Wheight` = 320 + Y_OFFSET
Height of the window.

5.20.1 Detailed Description

Window Constants

Author

Giacomo Loparco, Bilal Jaffry, Lucas Zacharewicz

Date

November 7 2018

Index

- `__init__`
 - `actor::aquamentus::Aquamentus`, 8
 - `actor::boomerang::Boomerang`, 11
 - `actor::boss::Boss`, 13
 - `actor::enemy::Enemy`, 18
 - `actor::fireball::Fireball`, 21
 - `actor::healthbar::Health_Bar`, 25
 - `actor::item::Item`, 27
 - `actor::keese::Keese`, 29
 - `actor::player::Player`, 38
 - `actor::rupee::Rupee_Bar`, 40
 - `actor::spritesheet::SpriteSheet`, 42
 - `actor::stalfos::Stalfos`, 45
 - `actor::sword::Sword`, 50
 - `collision::door::Door`, 15
 - `collision::levelmanager::LevelManager`, 34
 - `collision::wall::Wall`, 52
- `actor.aquamentus.Aquamentus`, 7
- `actor.boomerang.Boomerang`, 10
- `actor.boss.Boss`, 12
- `actor.enemy.Enemy`, 17
- `actor.fireball.Fireball`, 20
- `actor.healthbar.Health_Bar`, 24
- `actor.item.Item`, 26
- `actor.keese.Keese`, 28
- `actor.player.Player`, 35
- `actor.rupee.Rupee_Bar`, 39
- `actor.spritesheet.SpriteSheet`, 41
- `actor.stalfos.Stalfos`, 43
- `actor.sword.Sword`, 50
- `actor::aquamentus::Aquamentus`
 - `__init__`, 8
 - `attack`, 9
 - `bossLogic`, 9
 - `checkState`, 9
 - `hitCount`, 10
 - `isHit`, 10
 - `oldx`, 10
 - `oldy`, 10
 - `swapDirection`, 9
- `actor::boomerang::Boomerang`
 - `__init__`, 11
- `actor::boss::Boss`
 - `__init__`, 13
 - `hit`, 14
 - `id`, 14
 - `move`, 14
 - `update`, 14
- `actor::enemy::Enemy`
 - `__init__`, 18
 - `hit`, 18
 - `hitCount`, 19
 - `hitdir`, 19
 - `id`, 19
 - `move`, 19
 - `update`, 19
- `actor::fireball::Fireball`
 - `__init__`, 21
 - `checkState`, 22
 - `end`, 22
 - `hit`, 22
 - `id`, 23
 - `image`, 23
 - `logic`, 22
 - `move`, 22
 - `start`, 23
 - `update`, 23
- `actor::healthbar::Health_Bar`
 - `__init__`, 25
 - `h_sprite_sheet`, 25
 - `health`, 25
 - `image`, 26
 - `rect`, 26
- `actor::item::Item`
 - `__init__`, 27
 - `collision`, 27
- `actor::keese::Keese`
 - `__init__`, 29
 - `checkState`, 30
 - `enemyLogic`, 30
 - `genRestLength`, 30
 - `genTravelPoint`, 30
 - `hitCount`, 31
 - `image`, 31
 - `isHit`, 31
 - `setMoveSpeed`, 30
 - `stop`, 31
 - `switchSprite`, 31
 - `xSpeed`, 32
 - `ySpeed`, 32
- `actor::player::Player`
 - `__init__`, 38
 - `attacksword`, 39
 - `attackupdate`, 38
 - `dir`, 39
 - `move`, 38
 - `moveupdate`, 39
- `actor::rupee::Rupee_Bar`

- `__init__`, 40
 - `image`, 40
 - `rect`, 41
- `actor::spritesheet::SpriteSheet`
 - `__init__`, 42
 - `get_image`, 42
 - `get_imageNT`, 42
 - `sprite_sheet`, 43
- `actor::stalfos::Stalfos`
 - `__init__`, 45
 - `checkState`, 45
 - `direction`, 46
 - `dmg`, 46
 - `enemyLogic`, 45
 - `genTravelPath`, 46
 - `hitCount`, 47
 - `hitdir`, 47
 - `HP`, 47
 - `image`, 47
 - `isHit`, 47
 - `isMoving`, 47
 - `maxHP`, 48
 - `obj`, 48
 - `oldx`, 48
 - `oldy`, 48
 - `previousDirection`, 48
 - `setWalkSpeed`, 46
 - `spriteIndex`, 48
 - `sprites`, 49
 - `stop`, 46
 - `walkFrames`, 49
 - `walkStartFrame`, 49
 - `xSpeed`, 49
 - `ySpeed`, 49
- `actor::sword::Sword`
 - `__init__`, 50
 - `image`, 51
- `aquamentus.py`
 - `populateSprites`, 56
- `attack`
 - `actor::aquamentus::Aquamentus`, 9
- `attacksword`
 - `actor::player::Player`, 39
- `attackupdate`
 - `actor::player::Player`, 38
- `boomerang.py`
 - `populateSprites`, 57
 - `stuncoefficient`, 57
- `bossLogic`
 - `actor::aquamentus::Aquamentus`, 9
- `checkState`
 - `actor::aquamentus::Aquamentus`, 9
 - `actor::fireball::Fireball`, 22
 - `actor::keese::Keese`, 30
 - `actor::stalfos::Stalfos`, 45
- `collision`
 - `actor::item::Item`, 27
 - `collision::door::Door`, 16
 - `collision::wall::Wall`, 52
 - `collision.door.Door`, 15
 - `collision.level.Level`, 32
 - `collision.levelmanager.LevelManager`, 33
 - `collision.wall.Wall`, 51
 - `collision::door::Door`
 - `__init__`, 15
 - `collision`, 16
 - `state`, 16
 - `collision::levelmanager::LevelManager`
 - `__init__`, 34
 - `make`, 35
 - `transition`, 35
 - `collision::wall::Wall`
 - `__init__`, 52
 - `collision`, 52
 - `id`, 53
 - `image`, 53
 - `rect`, 53
- `dir`
 - `actor::player::Player`, 39
- `direction`
 - `actor::stalfos::Stalfos`, 46
- `dmg`
 - `actor::stalfos::Stalfos`, 46
- `end`
 - `actor::fireball::Fireball`, 22
- `enemyLogic`
 - `actor::keese::Keese`, 30
 - `actor::stalfos::Stalfos`, 45
- `fireball.py`
 - `populateSprites`, 61
- `genRestLength`
 - `actor::keese::Keese`, 30
- `genTravelPath`
 - `actor::stalfos::Stalfos`, 46
- `genTravelPoint`
 - `actor::keese::Keese`, 30
- `get_image`
 - `actor::spritesheet::SpriteSheet`, 42
- `get_imageNT`
 - `actor::spritesheet::SpriteSheet`, 42
- `h_sprite_sheet`
 - `actor::healthbar::Health_Bar`, 25
- `health`
 - `actor::healthbar::Health_Bar`, 25
- `hit`
 - `actor::boss::Boss`, 14
 - `actor::enemy::Enemy`, 18
 - `actor::fireball::Fireball`, 22
- `hitCount`
 - `actor::aquamentus::Aquamentus`, 10
 - `actor::enemy::Enemy`, 19

- actor::keese::Keese, 31
- actor::stalfos::Stalfos, 47
- hitdir
 - actor::enemy::Enemy, 19
 - actor::stalfos::Stalfos, 47
- HP
 - actor::stalfos::Stalfos, 47
- id
 - actor::boss::Boss, 14
 - actor::enemy::Enemy, 19
 - actor::fireball::Fireball, 23
 - collision::wall::Wall, 53
- image
 - actor::fireball::Fireball, 23
 - actor::healthbar::Health_Bar, 26
 - actor::keese::Keese, 31
 - actor::rupee::Rupee_Bar, 40
 - actor::stalfos::Stalfos, 47
 - actor::sword::Sword, 51
 - collision::wall::Wall, 53
- isHit
 - actor::aquamentus::Aquamentus, 10
 - actor::keese::Keese, 31
 - actor::stalfos::Stalfos, 47
- isMoving
 - actor::stalfos::Stalfos, 47
- keese.py
 - populateSprites, 63
- logic
 - actor::fireball::Fireball, 22
- make
 - collision::levelmanager::LevelManager, 35
- maxHP
 - actor::stalfos::Stalfos, 48
- move
 - actor::boss::Boss, 14
 - actor::enemy::Enemy, 19
 - actor::fireball::Fireball, 22
 - actor::player::Player, 38
- moveupdate
 - actor::player::Player, 39
- obj
 - actor::stalfos::Stalfos, 48
- oldx
 - actor::aquamentus::Aquamentus, 10
 - actor::stalfos::Stalfos, 48
- oldy
 - actor::aquamentus::Aquamentus, 10
 - actor::stalfos::Stalfos, 48
- populateSprites
 - aquamentus.py, 56
 - boomerang.py, 57
 - fireball.py, 61
 - keese.py, 63
 - stalfos.py, 65
- previousDirection
 - actor::stalfos::Stalfos, 48
- rect
 - actor::healthbar::Health_Bar, 26
 - actor::rupee::Rupee_Bar, 41
 - collision::wall::Wall, 53
- setMoveSpeed
 - actor::keese::Keese, 30
- setWalkSpeed
 - actor::stalfos::Stalfos, 46
- sprite_sheet
 - actor::spritesheet::SpriteSheet, 43
- spriteIndex
 - actor::stalfos::Stalfos, 48
- sprites
 - actor::stalfos::Stalfos, 49
- src/actor/aquamentus.py, 55
- src/actor/boomerang.py, 56
- src/actor/boss.py, 57
- src/actor/constants.py, 58
- src/actor/enemy.py, 60
- src/actor/fireball.py, 60
- src/actor/healthbar.py, 61
- src/actor/item.py, 62
- src/actor/keese.py, 62
- src/actor/player.py, 63
- src/actor/rupee.py, 64
- src/actor/spritesheet.py, 64
- src/actor/stalfos.py, 65
- src/actor/sword.py, 66
- src/collision/door.py, 66
- src/collision/level.py, 67
- src/collision/levelmanager.py, 67
- src/collision/wall.py, 68
- src/config/colour.py, 68
- src/config/window.py, 69
- stalfos.py
 - populateSprites, 65
- start
 - actor::fireball::Fireball, 23
- state
 - collision::door::Door, 16
- stop
 - actor::keese::Keese, 31
 - actor::stalfos::Stalfos, 46
- stuncoefficient
 - boomerang.py, 57
- swapDirection
 - actor::aquamentus::Aquamentus, 9
- switchSprite
 - actor::keese::Keese, 31
- transition
 - collision::levelmanager::LevelManager, 35
- update

actor::boss::Boss, [14](#)
actor::enemy::Enemy, [19](#)
actor::fireball::Fireball, [23](#)

walkFrames

actor::stalfos::Stalfos, [49](#)

walkStartFrame

actor::stalfos::Stalfos, [49](#)

xSpeed

actor::keese::Keese, [32](#)

actor::stalfos::Stalfos, [49](#)

ySpeed

actor::keese::Keese, [32](#)

actor::stalfos::Stalfos, [49](#)