

Ascii1000D Test : PNR 999-9999999-999

John Mogilewsky

Table of Contents

Ascii1000D - Description 1

Description 1

System definitions 1

System 2 Definitions 2

Description part two 2

Ascii1000D - Inspect 2

.1. Prerequisites 2

.1.1. Support equipment 2

.1.2. Supplies 2

.1.3. Spares 2

.2. Procedure 2

.3. Closing Requirements 3

1. Ascii1000D - Remove 3

1.1. Prerequisites 3

1.1.1. Support equipment 3

1.1.2. Supplies 3

1.1.3. Spares 3

1.2. Procedure 3

1.3. Closing Requirements 3

2. Ascii1000D - Install:DMC 4

2.1. Prerequisites 4

2.1.1. Support equipment 4

2.1.2. Supplies 4

2.1.3. Spares 4

2.2. Procedure 4

2.3. Closing Requirements 4

Ascii1000D - Description

Description

System definitions

Bold, *underline*, **highlight**, subscript, superscript, other text styles available.

Special characters invoked by character substitution such as ©, ®, →, and more.

Keyboard sequences are supported by the kbd macro, for example CTRL+ALT+DEL

NoteThe KBD macro is only active when the EXPERIMENTAL document attribute is declared. Otherwise, it appears as monospaced verbatim text.

Unordered List

- Item
- Item
- Item

Ordered list

1. Item
2. Item
- 2.1

Item

1 Item

1.1 Item

1. Item

System 2 Definitions

Demo for change process

Description part two

Descriptive data modules are relatively unconstrained.

This content is specific to CONFIG1.

Ascii1000D - Inspect

.1. Prerequisites

.1.1. Support equipment

NA

.1.2. Supplies

NA

.1.3. Spares

NA

.2. Procedure

Warning Material may cause burning to death

1. **Warning** High voltage kills! ZAP

Turn on the system if the temperature is under 80°

2. Use the `source` switch to ensure that the electrical system is not AC (Alternating Current) during maintenance.

3. Ensure electrical safety procedures are followed.

1. If the system is CONFIG1, check yellow warning light
2. Confirm green light
3. Reserve spare units in accordance with OEM (Original Equipment Manufacturer) published storage procedures.

.3. Closing Requirements

NA

1. Ascii1000D - Remove

1.1. Prerequisites

1.1.1. Support equipment

NA

1.1.2. Supplies

NA

1.1.3. Spares

NA

1.2. Procedure

1. **Warning** Do not remove the wrong part

Remove the part.

- 1.1 **Caution** Skydrol is a surface irritant and inhalation hazard

Drain fluids from part.

- 1.2 Perform other cleaning operations.

2. Reserve the removed part for bench testing according to OEM (Original Equipment Manufacturer) storage procedures.

1.3. Closing Requirements

NA

2. Ascii1000D - Install:DMC

2.1. Prerequisites

2.1.1. Support equipment

NA

2.1.2. Supplies

NA

2.1.3. Spares

| PNR | NOMEN | QTY |
|----------------|--------------|-----|
| 999-999999-99 | SparePart | 1 |
| 999-888888-991 | SpareConfig1 | 1 |

2.2. Procedure

1. Install the part
2. For CONFIG1, perform the following steps
 - 2.1 Remove the yellow light]

2.3. Closing Requirements

Perform inspection [Ascii1000D - Inspect](#)