

User Manual for Financial Scores and Ratios API (Windows VM Server)

This API, built using Flask, provides access to financial scores and ratio data stored in a PostgreSQL database (ohcldata). It runs on a Windows VM server with IP 192.168.50.54 and offers endpoints for retrieving specific scores, aggregated summaries, top/bottom scores, and ratio data, with options for JSON, CSV, or Excel output. The port is set to 5000.

Base URL

- **Base URL:** http://192.168.50.54:5000
- **Port:** 5000 (configured via FLASK_PORT environment variable)

General Notes

- **Authentication:** No authentication is implemented.
 - **Date Format:** Use YYYY-MM-DD (e.g., 2018-04-01).
 - **Aggregation Methods:** Supports max, min, or both.
 - **Export Formats:** json (default), csv, excel. Use export_format or file_format to specify.
 - **Error Handling:** Errors return JSON with an error key (e.g., 400 for bad requests, 404 for no data, 500 for server errors).
 - **Network Access:** Ensure your device is on the same network as the VM (e.g., 192.168.50.x) and the firewall allows port 5000.
-

Endpoints

1. /api/get_score

Purpose: Retrieve a specific score for a stock on a single date (aggregated over a month).

Method: GET

Parameters:

- stock (string, required): Stock symbol (e.g., AAPL).
- score_type (string, required): Type of score (s, i, p for n_ratios; others for b_ratios).
- score_subtype (string, required): Score column (e.g., n1, b1).
- date (string, optional): Date (default: 2018-04-01).
- aggregation_method (string, optional): max, min, both (default: max).
- export_format (string, optional): json, csv, excel.

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_score?stock=AAPL&score_type=s&score_subtype=n1&date=2018-04-01&aggregation_method=max`
 - **Request:** GET
`http://192.168.50.54:5000/api/get_score?stock=AAPL&score_type=s&score_subtype=n1&date=2018-04-01&aggregation_method=both&export_format=csv`
-

2. /api/get_score_range

Purpose: Retrieve scores for a stock over a date range.

Method: GET

Parameters:

- Same as /api/get_score, but with start_date and end_date instead of date.

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_score_range?stock=AAPL&score_type=s&score_subtype=n1&start_date=2018-04-01&end_date=2018-06-30`
-

3. /api/get_all_scores

Purpose: Retrieve all scores for a stock on a single date.

Method: GET

Parameters:

- stock (string, required).
- date (string, required).
- aggregation_method (string, optional): max, min, both.

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_all_scores?stock=AAPL&date=2018-04-01&aggregation_method=both`
-

4. /api/get_all_scores_range

Purpose: Retrieve all scores for a stock over a date range.

Method: GET

Parameters:

- stock (string, required).
- start_date (string, optional): Default 2018-04-01.
- end_date (string, required).
- aggregation_method (string, optional).

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_all_scores_range?stock=AAPL&start_date=2018-04-01&end_date=2018-05-31`
-

5. /api/get_scores_by_subtype

Purpose: Retrieve scores for a subtype across stocks on a single date.

Method: GET

Parameters:

- score_subtype (string, required).
- date (string, required).
- stocks (list, optional).
- aggregation_method (string, optional).

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_scores_by_subtype?score_subtype=n1&date=2018-04-01&stocks=AAPL&stocks=GOOGL`
-

6. /api/get_scores_by_subtype_range

Purpose: Retrieve scores for a subtype across stocks over a range.

Method: GET

Parameters:

- score_subtype (string, required).
- start_date (string, optional): Default 2018-04-01.

- end_date (string, optional): Default 2018-04-30.
- stocks (list, optional).
- aggregation_method (string, optional).

Example:

- **Request:** GET
http://192.168.50.54:5000/api/get_scores_by_subtype_range?score_subtype=n1&start_date=2018-04-01&end_date=2018-05-31&stocks=AAPL
-

7. /api/get_scores_for_type_date

Purpose: Retrieve aggregated scores for a score type on a single date.

Method: GET

Parameters:

- score_type (string, required).
- date (string, optional): Default 2018-04-01.
- stocks (list, optional).
- aggregation_method (string, optional).
- export_format (string, optional).

Example:

- **Request:** GET
http://192.168.50.54:5000/api/get_scores_for_type_date?score_type=s&date=2018-04-01&stocks=AAPL
-

8. /api/get_scores_for_type_range

Purpose: Retrieve aggregated scores for a score type over a range.

Method: GET

Parameters:

- score_type (string, required).
- start_date (string, optional): Default 2018-04-01.
- end_date (string, optional): Default 2018-04-30.
- stocks (list, optional).
- aggregation_method (string, optional).
- export_format (string, optional).

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_scores_for_type_range?score_type=s&start_date=2018-04-01&end_date=2018-05-31`
-

9. /api/get_score_summary

Purpose: Summarize scores for a single date.

Method: GET

Parameters:

- date (string, required).
- score_type (string, optional).
- score_subtype (string, optional).
- entity (string, optional): stock, sector_index, or both.
- export_format (string, optional).

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_score_summary?date=2018-04-01&score_subtype=n1&entity=stock`
-

10. /api/get_score_summary_range

Purpose: Summarize scores over a date range.

Method: GET

Parameters:

- start_date (string, optional): Default 2018-04-01.
- end_date (string, optional): Default 2018-04-30.
- Other parameters same as /api/get_score_summary.

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_score_summary_range?start_date=2018-04-01&end_date=2018-05-31&score_subtype=n1`
-

11. /api/get_score_summary_by_conditions

Purpose: Summarize scores based on custom conditions.

Method: GET

Parameters:

- conditions (string, required): JSON-encoded (e.g., {"AND": [{"score_subtype": "n1"}, {"score_value": {">": 80}}]}).
- entity (string, optional): stock, sector_index, both (default: both).
- date (string, optional).
- export_format (string, optional).

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/get_score_summary_by_conditions?conditions={"AND": [{"score_subtype": "n1"}, {"score_value": {">": 80}}]}&entity=stock`
-

12. /api/topbottom_scores

Purpose: Retrieve top or bottom scores for a month.

Method: GET

Parameters:

- month (int, required): 1-12.
- year (int, required): 1900-9999.
- direction (string, required): top or bottom.
- direction_n (int, required): 1, 2, or 3.
- subtype (string, optional): e.g., n1.
- file_format (string, optional).

Example:

- **Request:** GET
`http://192.168.50.54:5000/api/topbottom_scores?month=4&year=2018&direction=top&direction_n=2&subtype=n1`
-

13. /api/topbottom_scores_by_range

Purpose: Retrieve top/bottom scores over a date range.

Method: GET

Parameters:

- start_date (string, required).
- end_date (string, required).
- Other parameters same as /api/topbottom_scores.

Example:

- **Request:** GET
http://192.168.50.54:5000/api/topbottom_scores_by_range?start_date=2018-04-01&end_date=2018-05-31&direction=top&direction_n=1
-

14. /api/ratio_data

Purpose: Retrieve historical ratio data.

Method: GET

Parameters:

- ratio_choice (string, optional): e.g., n1 (default: n1).
- file_format (string, optional).

Example:

- **Request:** GET http://192.168.50.54:5000/api/ratio_data?ratio_choice=n1
-

15. /api/ratio_data_by_range

Purpose: Retrieve ratio data for a specific range.

Method: GET

Parameters:

- start_date (string, required).
- end_date (string, required).
- ratio_choice (string, optional).
- file_format (string, optional).

Example:

- **Request:** GET
http://192.168.50.54:5000/api/ratio_data_by_range?start_date=2018-04-01&end_date=2018-05-31&ratio_choice=n1