



MAGNETIC EXPLOSION PROOF LED WORKING LIGHT

Technical Specification

Housing : ABS + PC

Reflector : Aluminium Alloy

Lens : Super Clear Glass

Size : 195mm x 126mm x 215mm

Weight : 1450g including battery

Wattage Output : 3 x 3W

Lumen Output : 765LM

Working Voltage : 11.1V

Light Modes : 3 Modes (high-low-strobe)

6 X 2200mAh Lithium Batteries

Charging time : 8 Hours

Working time : 8-16 hours

IP Rating IP65

Explosion-proof Mark Ex d IIC T6 Gb Function

Magnetic, Adjustable & Heavy Duty

Function as USB Charger as well

ISO9001:2008 & ISO14001:2004

ARCUTRA GLOBAL SERVICES SDN BHD

34-2, JALAN 9/23A, MEDAN MAKMUR, OFF JALAN USAHAWAN, 53200 SETAPAK, KUALA LUMPUR.

Tel: +60341443256 – Email: sales@arcutra.com website: www.arcutra.com

Dimensions





Item No.: DSFB-6203

Range: 300m

Brightness: 1080 lumen

Battery: 18650 battery

Light Source: CREE XP-E LED

Dimming: 2 files (Strong-Medium)

Weight: 1.45kg

Size: 160*130*270mm

Details Show



Data Plate

(Logo, SPEC, MFG,
Warning...)

- Using microcontroller programming control technology.
- Long life: light continuous working time of up to 8 hours, low light can be illuminated more than 16 hours.

Details Show



Note: Ex International Electrotechnical Commission IEC Explosion public signs indicate that the product is explosion-proof.

- 🔧 Flameproof (ic): ic can be applied to an area two zones intrinsically safe electrical products.
- 🔧 II C: Explosive mixture was allowed and the environment II Class B formed in the gas and air.
- 🔧 T6: Device surface temperature does not exceed 135°C.

Details Show

The magnet is using for absorbing the pole, plate, or platform which made of iron or steel materials when there is no spare hand for holding the working light.



Magnet



Package Details

Inner Packing Box

(248*228*155mm)



Portable LED
Working Light



DC Adaptor

USB Cable

(For iPhone & Android Phones)