



What is Quarkus?

Quarkus is a Kubernetes Native Java stack tailored for GraalVM & OpenJDK HotSpot, crafted from the best of breed Java libraries and standards. Also focused on developer experience, making things just work with little to no configuration and allowing to do live coding.

Cheat-sheet tested with **Quarkus 0.21.1**.

Getting Started

Quarkus comes with a Maven archetype to scaffold a very simple starting project.

```
mvn io.quarkus:quarkus-maven-plugin:0.21.1:create \
  -DprojectId=org.acme \
  -DprojectArtifactId=getting-started \
  -DclassName="org.acme.quickstart.GreetingResource" \
  -Dpath="/hello"
```

This creates a simple JAX-RS resource called `GreetingResource`.

```
@Path("/hello")
public class GreetingResource {

    @GET
    @Produces(MediaType.TEXT_PLAIN)
    public String hello() {
        return "hello";
    }
}
```

Extensions

Quarkus comes with extensions to integrate with some libraries such as JSON-B, Camel or MicroProfile spec. To list all available extensions just run:

```
./mvnw quarkus:list-extensions
```

Tip You can use `-DsearchPattern=panache` to filter out all extensions except the ones matching the expression.

And to register the extensions into build tool:

```
./mvnw quarkus:add-extension -Dextensions=""
```

Tip `extensions` property supports CSV format to register more than one extension at once.

Application Lifecycle

You can be notified when the application starts/stops by observing `StartupEvent` and `ShutdownEvent` events.

```
@ApplicationScoped
public class ApplicationLifecycle {
    void onStart(@Observes StartupEvent event) {}
    void onStop(@Observes ShutdownEvent event) {}
}
```

Adding Configuration Parameters

To add configuration to your application, Quarkus relies on **MicroProfile Config spec**.

```
@ConfigProperty(name = "greetings.message")
String message;

@ConfigProperty(name = "greetings.message",
    defaultValue = "Hello")
String messageWithDefault;

@ConfigProperty(name = "greetings.message")
Optional<String> optionalMessage;
```

Properties can be set as:

- **Environment variables** (`GREETINGS_MESSAGE`).
- **System properties** (`-Dgreetings.message`).
- **Resources**
`src/main/resources/application.properties`.
- **External config directory** under the current working directory:
`config/application.properties`.

```
greetings.message = Hello World
```

Tip `Array`, `List` and `Set` are supported. The delimiter is comma `(,)` char and `\` is the escape char.

Configuration Profiles

Quarkus allow you to have multiple configuration in the same file (`application.properties`).

The syntax for this is `%{profile}.config.key=value`.

```
quarkus.http.port=9090
%dev.quarkus.http.port=8181
```

HTTP port will be 9090, unless the 'dev' profile is active.

Default profiles are:

- **dev**: Activated when in development mode (`quarkus:dev`).
- **test**: Activated when running tests.
- **prod**: The default profile when not running in development or test mode

You can create custom profile names by enabling the profile either setting `quarkus.profile` system property or `QUARKUS_PROFILE` environment variable.

```
quarkus.http.port=9090
%staging.quarkus.http.port=9999
```

And enable it `quarkus.profile=staging`.

You can also set it in the build tool:

```
<groupId>org.apache.maven.plugins</groupId>
<artifactId>maven-surefire-plugin</artifactId>
<version>${surefire-plugin.version}</version>
<configuration>
    <systemPropertyVariables>
        <quarkus.test.profile>foo</quarkus.test.profile>
        <buildDirectory>${project.build.directory}</buildDirectory>
    </systemPropertyVariables>
</configuration>
```

Tip Same for `maven-failsafe-plugin`.

```
test {
    useJUnitPlatform()
    systemProperty "quarkus.test.profile", "foo"
}
```

Custom Loader

You can implement your own `ConfigSource` to load configuration from different places than the default ones provided by Quarkus. For example, database, custom XML, REST Endpoints, ...

You need to create a new class and implement `ConfigSource` interface:

```
package com.acme.config;

public class InMemoryConfig implements ConfigSource {

    private Map<String, String> prop = new HashMap<>();

    public InMemoryConfig() {
        // Init properties
    }

    @Override
    public int getOrdinal() {
        // The highest ordinal takes precedence
        return 900;
    }

    @Override
    public Map<String, String> getProperties() {
        return prop;
    }

    @Override
    public String getValue(String propertyName) {
        return prop.get(propertyName);
    }

    @Override
    public String getName() {
        return "MemoryConfigSource";
    }

}
```

Then you need to register the `ConfigSource` as Java service. Create a file `/META-INF/services/org.eclipse.microprofile.config.spi.ConfigSource` with next content:

```
com.acme.config.InMemoryConfig
```

Custom Converters

You can implement your own conversion types from String. Implement `org.eclipse.microprofile.config.spi.Converter` interface:

```
@Priority(DEFAULT_QUARKUS_CONVERTER_PRIORITY + 100)
public class CustomInstantConverter
    implements Converter<Instant> {

    @Override
    public Instant convert(String value) {
        if ("now".equals(value.trim())) {
            return Instant.now();
        }
        return Instant.parse(value);
    }

}
```

`@Priority` annotation is used to override the default `InstantConverter`.

Then you need to register the `Converter` as Java service. Create a file `/META-INF/services/org.eclipse.microprofile.config.spi.Converter` with next content:

```
com.acme.config.CustomInstantConverter
```

Custom Context Path

By default Undertow will serve content from under the root context. If you want to change this you can use the `quarkus.servlet.context-path` config key to set the context path.

Injection

Quarkus is based on CDI 2.0 to implement injection of code. It is not fully supported and only a subset of the specification is implemented.

```
@ApplicationScoped
public class GreetingService {

    public String message(String message) {
        return message.toUpperCase();
    }

}
```

`Scope` annotation is mandatory to make the bean discoverable.

```
@Inject
GreetingService greetingService;
```

Quarkus is designed with Substrate VM in mind. For **Important** this reason, we encourage you to use *package-private* scope instead of *private*.

Produces You can also create a factory of an object by using `@javax.enterprise.inject.Produces` annotation.

```
@Produces
@ApplicationScoped
Message message() {
    Message m = new Message();
    m.setMsn("Hello");
    return m;
}

@Inject
Message msg;
```

You can use qualifiers to return different implementations of the same interface or to customize the configuration of the bean.

```
@Qualifier
@Retention(RUNTIME)
@Target({TYPE, METHOD, FIELD, PARAMETER})
public @interface Quote {
    @Nonbinding String value();
}

@Produces
@Quote("")
Message message(InjectionPoint msg) {
    Message m = new Message();
    m.setMsn(
        msg.getAnnotated()
            .getAnnotation(Quote.class)
            .value()
    );

    return m;
}

@Inject
@Quote("Aloha Beach")
Message message;
```

TIP

Quarkus breaks the CDI spec by allowing you to inject qualified beans without using `@Inject` annotation.

```
@Quote("Aloha Beach")
Message message;
```

JSON Marshalling/Unmarshalling

To work with `JSON-B` you need to add a dependency:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-resteasy-jsonb"
```

Any POJO is marshaled/unmarshalled automatically.

```
public class Sauce {
    private String name;
    private long scovilleHeatUnits;

    // getter/setters
}
```

JSON equivalent:

```
{
    "name":"Blair's Ultra Death",
    "scovilleHeatUnits": 1100000
}
```

In a POST endpoint example:

```
@POST
@Consumes(MediaType.APPLICATION_JSON)
public Response create(Sauce sauce) {
    // Create Sauce
    return Response.created(URI.create(sauce.getId()))
        .build();
}
```

To work with Jackson you need to add:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-resteasy-jackson"
```

If you don't want to use the default ObjectMapper you can customize it by:

```
@ApplicationScoped
public class CustomObjectMapperConfig {
    @Singleton
    @Produces
    public ObjectMapper objectMapper() {
        ObjectMapper objectMapper = new ObjectMapper();
        // perform configuration
        return objectMapper;
    }
}
```

Validator

Quarkus uses **Hibernate Validator** to validate input/output of REST services and business services using Bean validation spec.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-hibernate-validator"
```

Annotate POJO objects with validator annotations such as: @NotNull, @Digits, @NotBlank, @Min, @Max, ...

```
public class Sauce {

    @NotBlank(message = "Name may not be blank")
    private String name;
    @Min(0)
    private long scovilleHeatUnits;

    // getter/setters
}
```

To validate an object use @Valid annotation:

```
public Response create(@Valid Sauce sauce) {}
```

Tip If a validation error is triggered, a violation report is generated and serialized as JSON. If you want to manipulate the output, you need to catch in the code the `ConstraintViolationException` exception.

Create Your Custom Constraints

First you need to create the custom annotation:

```
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR,
          PARAMETER, TYPE_USE })
@Retention(RUNTIME)
@Documented
@Constraint(validatedBy = { NotExpiredValidator.class})
public @interface NotExpired {

    String message() default "Sauce must not be expired";
    Class<?>[] groups() default { };
    Class<? extends Payload>[] payload() default { };

}
```

You need to implement the validator logic in a class that implements `ConstraintValidator`.

```
public class NotExpiredValidator
    implements ConstraintValidator<NotExpired, LocalDate>
{

    @Override
    public boolean isValid(LocalDate value,
                          ConstraintValidatorContext ctx) {

        if ( value == null ) return true;
        LocalDate today = LocalDate.now();
        return ChronoUnit.YEARS.between(today, value) > 0;
    }
}
```

And use it normally:

```
@NotExpired
@JsonbDateFormat(value = "yyyy-MM-dd")
private LocalDate expired;
```

Manual Validation

You can call the validation process manually instead of relaying to @Valid by injecting `Validator` class.

```
@Inject
Validator validator;
```

And use it:

```
Set<ConstraintViolation<Sauce>> violations =
    validator.validate(sauce);
```

Logging

You can configure how Quarkus logs:

```
quarkus.log.console.enable=true
quarkus.log.console.level=DEBUG
quarkus.log.console.color=false
quarkus.log.category."com.lordofthejars".level=DEBUG
```

Prefix is `quarkus.log`.

Property	Default	Description
console.enable	true	Console logging enabled.
console.format	%d{yyyy-MM-dd HH:mm:ss,SSS} %-5p [%c{3.}] (%t) %s%n	Format pattern to use for logging.
console.level	INFO	Minimum log level.
console.color	INFO	Allow color rendering.
file.enable	false	File logging enabled.

Property	Default	Description
file.format	%d{yyyy-MM-dd HH:mm:ss,SSS} %h %N[%i] %-5p [%c{3.}] (%t) %s%n	Format pattern to use for logging.
file.level	ALL	Minimum log level.
file.path	quarkus.log	The path to log file.
file.rotation.max-file-size		The maximum file size of the log file.
file.rotation.max-backup-index	1	The maximum number of backups to keep.
file.rotation.file-suffix		Rotating log file suffix.
file.rotation.rotate-on-boot	true	Indicates rotate logs at bootup.
file.async	false	Log asynchronously.
file.async.queue-length	512	The queue length to use before flushing writing.
file.async.overflow	BLOCK	Action when queue is full.
syslog.enable	false	syslog logging is enabled.
syslog.format	%d{yyyy-MM-dd HH:mm:ss,SSS} %h %N[%i] %-5p [%c{3.}] (%t) %s%n	The format pattern to use for logging to syslog.
syslog.level	ALL	The minimum log level to write to syslog.

Property	Default	Description
syslog.endpoint	localhost:514	The IP address and port of the syslog server.
syslog.app-name	Current process name.	The app name used when formatting the message in RFC5424 format.
syslog.hostname	Current hostname.	The name of the host the messages are being sent from.
syslog.facility	USER_LEVEL	Priority of the message as defined by RFC-5424 and RFC-3164.
syslog.syslog-type	RFC5424	The syslog type of format message.
syslog.protocol	TCP	Protocol used.
syslog.use-counting-framing	false	Message prefixed with the size of the message.
syslog.truncate	true	Message should be truncated.
syslog.block-on-reconnect	true	Block when attempting to reconnect.
syslog.async	false	Log asynchronously.
syslog.async.queue-length	512	The queue length to use before flushing writing.
syslog.async.overflow	BLOCK	Action when queue is full.

Property	Default	Description
category.<category-name>.level	INFO	Minimum level category.
level	INFO	Default minimum level.

Rest Client

Quarkus implements MicroProfile Rest Client spec:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-rest-client"
```

To get content from <http://worldclockapi.com/api/json/cet/now> you need to create a service interface:

```
@Path("/api")
@RegisterRestClient
public interface WorldClockService {

    @GET @Path("/json/cet/now")
    @Produces(MediaType.APPLICATION_JSON)
    WorldClock getNow();

    @GET
    @Path("/json/{where}/now")
    @Produces(MediaType.APPLICATION_JSON)
    WorldClock getSauce(@BeanParam
                        WorldClockOptions worldClockOptions);

}
```

```
public class WorldClockOptions {
    @HeaderParam("Authorization")
    String auth;

    @PathParam("where")
    String where;
}
```

And configure the hostname at application.properties:

```
org.acme.quickstart.WorldClockService/mp-rest/url=
http://worldclockapi.com
```

Injecting the client:

```
@Inject
@RestClient
WorldClockService worldClockService;
```


If invocation happens within JAX-RS, you can propagate headers from incoming to outgoing by using next property.

```
org.eclipse.microprofile.rest.client.propagateHeaders=
    Authorization,MyCustomHeader
```

Tip You can still use the JAX-RS client without any problem `ClientBuilder.newClient().target(...)`

Adding headers

You can customize the headers passed by implementing `MicroProfile ClientHeadersFactory` annotation:

```
@RegisterForReflection
public class BaggageHeadersFactory
    implements ClientHeadersFactory {

    @Override
    public MultivaluedMap<String, String> update(
        MultivaluedMap<String, String> incomingHeaders,
        MultivaluedMap<String, String> outgoingHeaders) {}

}
```

And registering it in the client using `RegisterClientHeaders` annotation.

```
@RegisterClientHeaders (BaggageHeadersFactory.class)
@RegisterRestClient
public interface WorldClockService {}
```

Or statically set:

```
@GET
@ClientHeaderParam(name="X-Log-Level", value="ERROR")
Response getNow();
```

Asynchronous

A method on client interface can return a `CompletionStage` class to be executed asynchronously.

```
@GET @Path("/json/cet/now")
@Produces(MediaType.APPLICATION_JSON)
CompletionStage<WorldClock> getNow();
```

Testing

Quarkus archetype adds test dependencies with JUnit 5 and Rest-Assured library to test REST endpoints.

```
@QuarkusTest
public class GreetingResourceTest {

    @Test
    public void testHelloEndpoint() {
        given()
            .when().get("/hello")
            .then()
                .statusCode(200)
                .body(is("hello"));
    }

}
```

Test port can be set in `quarkus.http.test-port` property.

You can also inject the URL where Quarkus is started:

```
@TestHTTPResource("index.html")
URL url;
```

Quarkus Test Resource

You can execute some logic before the first test run (`start`) and execute some logic at the end of the test suite (`stop`).

You need to create a class implementing `QuarkusTestResourceLifecycleManager` interface and register it in the test via `@QuarkusTestResource` annotation.

```
public class MyCustomTestResource
    implements QuarkusTestResourceLifecycleManager {

    @Override
    public Map<String, String> start() {
        // return system properties that
        // should be set for the running test
        return Collections.emptyMap();
    }

    @Override
    public void stop() {
    }

    // optional
    @Override
    public void inject(Object testInstance) {
    }

    // optional
    @Override
    public int order() {
        return 0;
    }

}
```

And the usage:

```
@QuarkusTestResource (MyCustomTestResource.class)
public class MyTest {
}
```

Mocking

If you need to provide an alternative implementation of a service (for testing purposes) you can do it by using CDI `@Alternative` annotation using it in the test service placed at `src/test/java`:

Important Returning new system properties implies running parallel tests in different JVMs.

```
@Alternative
@Priority(1)
@ApplicationScoped
public class MockExternalService extends ExternalService {}
```

Important This does not work when using native image testing.

A stereotype annotation `io.quarkus.test.Mock` is provided declaring `@Alternative`, `@Priority(1)` and `@Dependent`.

Interceptors

Tests are actually full CDI beans, so you can apply CDI interceptors:

```
@QuarkusTest
@Stereotype
@Transactional
@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.TYPE)
public @interface TransactionalQuarkusTest {

}

@TransactionalQuarkusTest
public class TestStereotypeTestCase {}
```

Test Coverage Due the nature of Quarkus to calculate correctly the coverage information with JaCoCo, you might need offline instrumentation. I recommend reading this document to understand how JaCoCo and Quarkus works and how you can configure JaCoCo to get correct data.

Native Testing

To test native executables annotate the test with `@SubstrateTest`.

Persistence

Quarkus works with JPA(Hibernate) as persistence solution. But also provides an Active Record pattern implementation under Panache project.

To use database access you need to add Quarkus JDBC drivers instead of the original ones. At this time H2, MariaDB, MSSQL and PostgreSQL drivers are supported.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-hibernate-orm-panache,
io.quarkus:quarkus-jdbc-mariadb"
```

```
@Entity
public class Developer extends PanacheEntity {

    // id field is implicit

    public String name;
}
```

And configuration in `src/main/resources/application.properties`:

```
quarkus.datasource.url=jdbc:mariadb://localhost:3306/mydb
quarkus.datasource.driver=org.mariadb.jdbc.Driver
quarkus.datasource.username=developer
quarkus.datasource.password=developer
quarkus.hibernate-orm.database.generation=update
```

List of datasource parameters.

`quarkus.datasource` as prefix is skipped in the next table.

Parameter	Type
driver	String
url	String
username	String
password	String
min-size	Integer
max-size	Integer
initial-size	Integer

Parameter	Type
background-validation-interval	java.time.Duration
acquisition-timeout	java.time.Duration
leak-detection-interval	java.time.Duration
idle-removal-interval	java.time.Duration
transaction-isolation-level	io.quarkus.agroal.runtime.TransactionIsolationLevel
enable-metrics	Boolean
xa	Boolean

Hibernate configuration properties. Prefix `quarkus.hibernate-orm` is skipped.

Parameter	Description	Values[Default]
dialect	Class name of the Hibernate ORM dialect.	Not necessary to set.
dialect.storage-engine	The storage engine when the dialect supports multiple storage engines.	Not necessary to set.

Parameter	Description	Values[Default]	Parameter	Description	Values[Default]	Static Methods		
sql-load-script	Name of the file containing the SQL statements to execute when starts. no-file force Hibernate to skip SQL import.	import.sql	jdbc.statement-fetch-size	Number of rows fetched at a time.		Field		
			jdbc.statement-batch-size	Number of updates sent at a time.		findById	Object	Returns object or null if not found.
			log.sql	Show SQL logs	[false], true	find	String, [Object..., Map<String, Object>, Parameters]	Lists of entities meeting given query with parameters set.
batch-fetch-size	The size of the batches.	-1 disabled.	log.jdbc-warnings	Collect and show JDBC warnings.	[false], true	find	String, Sort, [Object..., Map<String, Object>, Parameters]	Lists of entities meeting given query with parameters set sorted by Sort attribute/s.
query.query-plan-cache-max-size	The maximum size of the query plan cache.		statistics	Enable statiscs collection.	[false], true	findAll		Finds all entities.
query.default-null-ordering	Default precedence of null values in ORDER BY. none, first, last.	[none], first, last.	Database operations:			findAll	Sort	Finds all entities sorted by Sort attribute/s.
			<pre>// Insert Developer developer = new Developer(); developer.name = "Alex"; developer.persist(); // Find All Developer.findAll().list(); // Find By Query Developer.find("name", "Alex").firstResult(); // Delete Developer developer = new Developer(); developer.id = 1; developer.delete(); // Delete By Query long numberOfDeleted = Developer.delete("name", "Alex");</pre>			stream	String, [Object..., Map<String, Object>, Parameters]	java.util.stream.Stream of entities meeting given query with parameters set.
database.generation	Database schema is generation.	[none], create, drop-and-create, drop, update.				stream	String, Sort, [Object..., Map<String, Object>, Parameters]	java.util.stream.Stream of entities meeting given query with parameters set sorted by Sort attribute/s.
database.generation.halt-on-error	Stop on the first error when applying the schema.	[flase], true				streamAll		java.util.stream.Stream of all entities.
database.default-catalog	Default catalog.		Remember to annotate methods with @Transactional annotation to make changes persisted in the database.			streamAll	Sort	java.util.stream.Stream of all entities sorted by Sort attribute/s.
database.default-schema	Default Schema.		If queries start with the keyword from then they are treated as <i>HQL</i> query, if not then next short form is supported:			count		`Number of entities.
database.charset	Charset.		• order by which expands to from EntityName order by ...			count	String, [Object..., Map<String, Object>, Parameters]	Number of entities meeting given query with parameters set.
			• <columnName> which expands to from EntityName where <columnName>=?					
jdbc.timezone	Time Zone JDBC driver.		• <query> which is expanded to from EntityName where <query>					

Field	Parameters	Return
deleteAll		Number of deleted entities.
delete	String, [Object..., Map<String, Object>, Parameters]	Number of deleted entities meeting given query with parameters set.
persist	[Iterable, Steram, Object...]	

If entities are defined in external JAR, you need to enable in these projects the Jandex plugin in project.

```
<plugin>
  <groupId>org.jboss.jandex</groupId>
  <artifactId>jandex-maven-plugin</artifactId>
  <version>1.0.3</version>
  <executions>
    <execution>
      <id>make-index</id>
      <goals>
        <goal>jandex</goal>
      </goals>
    </execution>
  </executions>
  <dependencies>
    <dependency>
      <groupId>org.jboss</groupId>
      <artifactId>jandex</artifactId>
      <version>2.1.1.Final</version>
    </dependency>
  </dependencies>
</plugin>
```

DAO pattern

Also supports *DAO* pattern with PanacheRepository<TYPE>.

```
@ApplicationScoped
public class DeveloperRepository
    implements PanacheRepository<Person> {
    public Person findByName(String name){
        return find("name", name).firstResult();
    }
}
```

EntityManager You can inject EntityManager in your classes:

```
@Inject
EntityManager em;
```

Flushing

You can force flush operation by calling .flush() or .persistAndFlush() to make it in a single call.

Important This flush is less efficient and you still need to commit transaction.

Testing

There is a Quarkus Test Resource that starts and stops H2 server before and after test suite.

Register next dependency io.quarkus:quarkus-test-h2:test.

And annotate the test:

```
@QuarkusTestResource(H2DatabaseTestResource.class)
public class FlywayTestResources {
}
```

Transactions The easiest way to define your transaction boundaries is to use the @Transactional annotation.

Transactions are mandatory in case of none idempotent operations.

```
@Transactional
public void createDeveloper() {}
```

You can control the transaction scope:

- @Transactional(REQUIRED) (default): starts a transaction if none was started, stays with the existing one otherwise.
- @Transactional(REQUIRES_NEW): starts a transaction if none was started; if an existing one was started, suspends it and starts a new one for the boundary of that method.
- @Transactional(MANDATORY): fails if no transaction was started ; works within the existing transaction otherwise.
- @Transactional(SUPPORTS): if a transaction was started, joins it ; otherwise works with no transaction.
- @Transactional(NOT_SUPPORTED): if a transaction was started, suspends it and works with no transaction for the boundary of the method; otherwise works with no transaction.
- @Transactional(NEVER): if a transaction was started, raises an exception; otherwise works with no transaction.

You can configure the default transaction timeout using quarkus.transaction-manager.default-transaction-timeout configuration property. By default it is set to 60 seconds.

You can set a timeout property, in seconds, that applies to transactions created within the annotated method by using @TransactionConfiguration annotation.

```
@Transactional
@TransactionConfiguration(timeout=40)
public void createDeveloper() {}
```

If you want more control over transactions you can inject UserTransaction and use a programmatic way.

```
@Inject UserTransaction transaction

transaction.begin();
transaction.commit();
transaction.rollback();
```

Flyway

Quarkus integrates with Flyway to help you on database schema migrations.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-flyway"
```

Then place migration files to the migrations folder (classpath:db/migration).

You can inject org.flywaydb.core.Flyway to programmatically execute the migration.

```
@Inject
Flyway flyway;

flyway.migrate();
```

Or can be automatically executed by setting migrate-at-start property to true.

```
quarkus.flyway.migrate-at-start=true
```

List of Flyway parameters.

quarkus. as prefix is skipped in the next table.

Parameter	Default	Description
flyway.migrate-at-start	false	Flyway migration automatically.

Parameter	Default	Description
flyway.locations	classpath:db/migration	CSV locations to scan recursively for migrations. Supported prefixes classpath and filesystem.
flyway.connect-retries	0	The maximum number of retries when attempting to connect.
flyway.schemas	none	CSV case-sensitive list of schemas managed.
flyway.table	flyway_schema_history	The name of Flyway's schema history table.
flyway.sql-migration-prefix	V	Prefix for versioned SQL migrations.
flyway.repeatable-sql-migration-prefix	R	Prefix for repeatable SQL migrations.
flyway.baseline-on-migrate		Only migrations above baseline-version will then be applied.
flyway.baseline-version		Version to tag an existing schema with when executing 1 baseline.

Parameter	Default	Description
flyway.baseline-description	Flyway Baseline	Description to tag an existing schema with when executing baseline

Hibernate Search

Quarkus integrates with Elasticsearch to provide a full-featured full-text search using Hibernate Search API.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-hibernate-search-elasticsearch"
```

You need to annotate your model with Hibernate Search API to index it:

```
@Entity
@Indexed
public class Author extends PanacheEntity {

    @FullTextField(analyzer = "english")
    public String bio;

    @FullTextField(analyzer = "name")
    @KeywordField(name = "firstName_sort",
        sortable = Sortable.YES,
        normalizer = "sort")
    public String firstName;

    @OneToMany
    @IndexedEmbedded
    public List<Book> books;

}
```

Important It is not mandatory to use Panache.

You need to define the analyzers and normalizers defined in annotations. You only need to implement ElasticsearchAnalysisConfigurer interface and configure it.

```
public class MyQuarkusAnalysisConfigurer
    implements ElasticsearchAnalysisConfigurer {

    @Override
    public void configure(
        ElasticsearchAnalysisDefinitionContainerContext ctx)
    {

        ctx.analyzer("english").custom()
            .withTokenizer("standard")
            .withTokenFilters("asciifolding",
                "lowercase", "porter_stem");

        ctx.normalizer("sort").custom()
            .withTokenFilters("asciifolding", "lowercase");

    }
}
```

Use Hibernate Search in REST service:

```
public class LibraryResource {

    @Inject
    EntityManager em;

    @Transactional
    public List<Author> searchAuthors(
        @QueryParam("pattern") String pattern) {
        return Search.getSearchSession(em)
            .search(Author.class)
            .predicate(f ->
                pattern == null || pattern.isEmpty() ?
                    f.matchAll() :
                    f.simpleQueryString()
                        .onFields("firstName",
                            "lastName", "books.title")
                        .matching(pattern)
                    )
            .sort(f -> f.byField("lastName_sort"))
            .then().byField("firstName_sort"))
            .fetchHits();

    }

}
```

IMPORTANT When not using Hibernate ORM, index data using Search.getSearchSession(em).createIndexer().startAndWait() at startup time.

Configure the extension in application.properties:

```
quarkus.hibernate-search.elasticsearch.version=7
quarkus.hibernate-search.elasticsearch.
    analysis-configurer=MyQuarkusAnalysisConfigurer
quarkus.hibernate-search.elasticsearch.
    automatic-indexing.synchronization-strategy=searchable
quarkus.hibernate-search.elasticsearch.
    index-defaults.lifecycle.strategy=drop-and-create
quarkus.hibernate-search.elasticsearch.
    index-defaults.lifecycle.required-status=yellow
```

List of Hibernate-Elasticsearch properties prefixed with `quarkus.hibernate-search.elasticsearch:`

Parameter	Description
<code>backends</code>	Map of configuration of additional backends.
<code>version</code>	Version of Elasticsearch
<code>analysis-configurer</code>	Class or name of the neab used to configure.
<code>hosts</code>	List of Elasticsearch servers hosts.
<code>username</code>	Username for auth.
<code>password</code>	Password for auth.
<code>connection-timeout</code>	Duration of connection timeout.
<code>max-connections</code>	Max number of connections to servers.
<code>max-connections-per-route</code>	Max number of connections to server.
<code>indexes</code>	Per-index specific configuration.
<code>discovery.enabled</code>	Enables automatic discovery.
<code>discovery.refresh-interval</code>	Refresh interval of node list.
<code>discovery.default-scheme</code>	Scheme to be used for the new nodes.
<code>automatic-indexing.synchronization-strategy</code>	Status for which you wait before considering the operation completed (queued,committed or searchable).

Parameter **Description**

<code>automatic-indexing.enable-dirty-check</code>	When enabled, re-indexing of is skipped if the changes are on properties that are not used when indexing.
<code>index-defaults.lifecycle.strategy</code>	Index lifecycle (none, validate, update, create, drop-and-create, drop-abd-create-drop)
<code>index-defaults.lifecycle.required-status</code>	Minimal cluster status (green, yellow, red)
<code>index-defaults.lifecycle.required-status-wait-timeout</code>	Waiting time before failing the bootstrap.
<code>index-defaults.refresh-after-write</code>	Set if index should be refreshed after writes.
Possible annotations:	
Parameter	Description
<code>@Indexed</code>	Register entity as full text index
<code>@FullTextField</code>	Full text search. Need to set an analyzer to split tokens.
<code>@KeywordField</code>	The string is kept as one single token but can be normalized.
<code>IndexedEmbedded</code>	Include the Book fields into the Author index.
<code>@ContainerExtraction</code>	Sets how to extract a value from container, e.g from a Map.
<code>@DocumentId</code>	Map an unusual entity identifier to a document identifier.
<code>@GenericField</code>	Full text index for any supported type.
<code>@IdentifierBridgeRef</code>	Reference to the identifier bridge to use for a <code>@DocumentId</code>

Parameter **Description**

<code>@IndexingDependency</code>	How a dependency of the indexing process to a property should affect automatic reindexing.
<code>@ObjectPath</code>	
<code>@ScaledNumberField</code>	For <code>java.math.BigDecimal</code> or <code>java.math.BigInteger</code> that you need higher precision.

Amazon DynamoDB

Quarkus integrates with Amazon DynamoDB:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-amazon-dynamodb"

void onStart(@Observes StartupEvent ev) {
    DynamoDbAsyncClient asyncClient = DynamoDbAsyncClient.create();
    DynamoDbClient client = DynamoDbClient.create();
}
```

Neo4j

Quarkus integrates with Neo4j:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-neo4j"

@Inject
org.neo4j.driver.Driver driver;
```

Configuration properties:

quarkus.neo4j as prefix is skipped in the next table.

Parameter	Default	Description
uri	bolt://localhost:7687	URI of Neo4j.
authentication.username	neo4j	Username.
authentication.password	neo4j	Password.
authentication.disabled	false	Disable authentication.
pool.metrics-enabled	false	Enable metrics.
pool.log-leaked-sessions	false	Enable leaked sessions logging.
pool.max-connection-pool-size	100	Max amount of connections.
pool.max-connection-lifetime	1H	Pooled connections older will be closed and removed from the pool.
pool.connection-acquisition-timeout	1M	Timeout for connection adquisition.
pool.idle-time-before-connection-test	-1	Pooled connections idled in the pool for longer than this timeout will be tested before they are used.

As Neo4j uses SSL communication by default, to create a native executable you need to compile with next options GraalVM options:

`-H:EnableURLProtocols=http,https` `--enable-all-security-services` `-H:+JNI`

And Quarkus Maven Plugin with next configuration:

```
<artifactId>quarkus-maven-plugin</artifactId>
<executions>
  <execution>
    <id>native-image</id>
    <goals>
      <goal>native-image</goal>
    </goals>
    <configuration>
      <enableHttpUrlHandler>true</enableHttpUrlHandler>
      <enableHttpsUrlHandler>true</enableHttpsUrlHandler>
      <enableAllSecurityServices>true</enableAllSecurityServices>
      <enableJni>true</enableJni>
    </configuration>
  </execution>
</executions>
```

Alternatively, and as a not recommended way in production, you can disable SSL and Quarkus will disable Bolt SSL as well. `quarkus.ssl.native=false`.

If you are using Neo4j 4.0, you can use fully reactive. Add next depenency management `io.projectreactor:reactor-bom:Californium-SR4:pom:import` and dependency: `io.projectreactor:reactor-core`.

```
public Publisher<String> get() {
    return Flux.using(driver::rxSession, ...);
}
```

MongoDB Client

Quarkus integrates with MongoDB:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-mongodb-client"
```

```
@Inject
com.mongodb.client.MongoClient client;

@Inject
io.quarkus.mongodb.ReactiveMongoClient client;
```

```
quarkus.mongodb.connection-string=mongodb://localhost:27018
quarkus.mongodb.write-concern.journal=false
```

quarkus.mongodb as prefix is skipped in the next table.

Parameter	Type	Description
connection-string	String	MongoDB connection URI.

Parameter	Type	Description
hosts	List<String>	Addresses passed as <code>host:port</code> .
application-name	String	Application name.
max-pool-size	Int	Maximum number of connections.
min-pool-size	Int	Minimum number of connections.
max-connection-idle-time	Duration	Idle time of a pooled connection.
max-connection-life-time	Duration	Life time of pooled connection.
wait-queue-timeout	Duration	Maximum wait time for new connection.
maintenance-frequency	Duration	Time period between runs of maintenance job.
maintenance-initial-delay	Duration	Time to wait before running the first maintenance job.
wait-queue-multiple	Int	Multiplied with <code>max-pool-size</code> gives max numer of threads waiting.
connection-timeout	Duration	
socket-timeout	Duration	

Parameter	Type	Description	Parameter	Type	Description
tls-insecure	boolean [false]	Insecure TLS.	write-concern.w-timeout	Duration	Timeout to all write commands.
tls	boolean [false]	Enable TLS	credentials.username	String	Username.
replica-set-name	String	Implies hosts given are a seed list.	credentials.password	String	Password.
server-selection-timeout	Duration	Time to wait for server selection.	credentials.auth-mechanism	MONGO-CR, GSSAPI, PLAIN, MONGODB-X509	
local-threshold	Duration	Minimum ping time to make a server eligible.	credentials.auth-source	String	Source of the authentication credentials.
heartbeat-frequency	Duration	Frequency to determine the state of servers.	credentials.auth-mechanism-properties	Map<String, String>	Authentication mechanism properties.
read-preference	primary, primaryPreferred, secondary, secondaryPreferred, nearest	Read preferences.			
max-wait-queue-size	Int	Max number of concurrent operations allowed to wait.			
write-concern.safe	boolean [true]	Ensures are writes are ack.			
write-concern.journal	boolean [true]	Journal writing aspect.			
write-concern.w	String	Value to all write commands.			
write-concern.retry-writes	boolean [false]	Retry writes if network fails.			

Reactive Programming

Quarkus implements **MicroProfile Reactive spec** and uses **RXJava2** to provide reactive programming model.

```
./mvnw quarkus:add-extension
-Dextensions="
    io.quarkus:quarkus-smallrye-reactive-streams-operators"
```

Asynchronous HTTP endpoint is implemented by returning **Java CompletionStage**. You can create this class either manually or using **MicroProfile Reactive Streams spec**:

```
@GET
@Path("/reactive")
@Produces(MediaType.TEXT_PLAIN)
public CompletionStage<String> getHello() {
    return ReactiveStreams.of("h", "e", "l", "l", "o")
        .map(String::toUpperCase)
        .toList()
        .run()
        .thenApply(list -> list.toString());
}
```

Creating streams is also easy, you just need to return **Publisher** object.

```
@GET
@Path("/stream")
@Produces(MediaType.SERVER_SENT_EVENTS)
public Publisher<String> publishers() {
    return Flowable
        .interval(500, TimeUnit.MILLISECONDS)
        .map(s -> atomicInteger.getAndIncrement())
        .map(i -> Integer.toString(i));
}
```

Reactive Messaging

Quarkus relies on **MicroProfile Reactive Messaging spec** to implement reactive messaging streams.

```
mvn quarkus:add-extension
-Dextensions="
    io.quarkus:quarkus-smallrye-reactive-messaging"
```

You can just start using in-memory streams by using **@Incoming** to produce data and **@Outgoing** to consume data.

Produce every 5 seconds one piece of data.


```
@ApplicationScoped
public class ProducerData {

    @Outgoing("my-in-memory")
    public Flowable<Integer> generate() {
        return Flowable.interval(5, TimeUnit.SECONDS)
            .map(tick -> random.nextInt(100));
    }
}
```

If you want to dispatch to all subscribers you can annotate the method with `@Broadcast`.

Consumes generated data from my-in-memory stream.

```
@ApplicationScoped
public class ConsumerData {
    @Incoming("my-in-memory")
    public void randomNumber(int randomNumber) {
        System.out.println("Received " + randomNumber);
    }
}
```

You can also inject an stream as a field:

```
@Inject
@Stream("my-in-memory") Publisher<Integer> randomNumbers;
```

```
@Inject @Stream("generated-price")
Emitter<String> emitter;
```

Patterns

REST API → Message

```
@Inject @Stream("in")
Emitter<String> emitter;

emitter.send(message);
```

Message → Message

```
@Incoming("in")
@Outgoing("out")
public String process(String in) {
}
```

Message → SSE

```
@Inject @Stream("out")
Publisher<String> result;

@GET
@Produces(SERVER_SENT_EVENTS)
public Publisher<String> stream() {
    return result;
}
```

Message → Business Logic

```
@ApplicationScoped
public class ReceiverMessages {
    @Incoming("prices")
    public void print(String price) {
    }
}
```

Possible implementations are:

In-Memory

If the stream is not configured then it is assumed to be an in-memory stream, if not then stream type is defined by connector field.

Kafka

To integrate with Kafka you need to add next extensions:

```
mvn quarkus:add-extension
-Dextensions="
io.quarkus:quarkus-smallrye-reactive-messaging-kafka"
```

Then `@Outgoing`, `@Incoming` or `@Stream` can be used.

Kafka configuration schema: `mp.messaging.[outgoing|incoming].{stream-name}.<property>=<value>`.

The connector type is `smallrye-kafka`.

```
mp.messaging.outgoing.generated-price.connector=
smallrye-kafka
mp.messaging.outgoing.generated-price.topic=
prices
mp.messaging.outgoing.generated-price.bootstrap.servers=
localhost:9092
mp.messaging.outgoing.generated-price.value.serializer=
org.apache.kafka.common.serialization.IntegerSerializer

mp.messaging.incoming.prices.connector=
smallrye-kafka
mp.messaging.incoming.prices.value.deserializer=
org.apache.kafka.common.serialization.IntegerDeserializer
```

A complete list of supported properties are in Kafka site. For the producer and for consumer

JSON-B Serializer/Deserializer

You can use JSON-B to serialize/deserialize objects.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-kafka-client"
```

To serialize you can use `io.quarkus.kafka.client.serialization.JsonbSerializer`.

To deserialize you need to extend `io.quarkus.kafka.client.serialization.JsonbDeserializer` and provide a type.

```
public class BeerDeserializer
    extends JsonbDeserializer<Beer> {

    public BeerDeserializer() {
        super(Beer.class);
    }

}
```

AMQP

To integrate with AMQP you need to add next extensions:

```
./mvnw quarkus:add-extension
-Dextensions="reactive-messaging-amqp"
```

Then `@Outgoing`, `@Incoming` or `@Stream` can be used.

AMQP configuration schema: `mp.messaging.[outgoing|incoming].{stream-name}.<property>=<value>`. Special properties `amqp-username` and `amqp-password` are used to configure AMQP broker credentials.

The connector type is `smallrye-amqp`.

```
amqp-username=quarkus
amqp-password=quarkus
# write
mp.messaging.outgoing.generated-price.connector=
smallrye-amqp
mp.messaging.outgoing.generated-price.address=
prices
mp.messaging.outgoing.generated-price.durable=
true
# read
mp.messaging.incoming.prices.connector=
smallrye-amqp
mp.messaging.incoming.prices.durable=
true
```

A complete list of supported properties for AMQP.

MQTT

To integrate with MQTT you need to add next extensions:

```
./mvnw quarkus:add-extension
-Dextensions="vertx, smallrye-reactive-streams-operators
smallrye-reactive-messaging"
```

And add io.smallrye.reactive:smallrye-reactive-messaging-mqtt-1.0:0.0.10 dependency in your build tool.

Then @Outgoing, @Incoming or @Stream can be used.

MQTT configuration schema: mp.messaging.[outgoing|incoming].{stream-name}.<property>=<value>.

The connector type is smallrye-mqtt.

```
mp.messaging.outgoing.topic-price.type=
smallrye-mqtt
mp.messaging.outgoing.topic-price.topic=
prices
mp.messaging.outgoing.topic-price.host=
localhost
mp.messaging.outgoing.topic-price.port=
1883
mp.messaging.outgoing.topic-price.auto-generated-client-id=
true

mp.messaging.incoming.prices.type=
smallrye-mqtt
mp.messaging.incoming.prices.topic=
prices
mp.messaging.incoming.prices.host=
localhost
mp.messaging.incoming.prices.port=
1883
mp.messaging.incoming.prices.auto-generated-client-id=
true
```

Kafka Streams

Create streaming queries with the Kafka Streams API.

```
./mvnw quarkus:add-extension
-Dextensions="kafka-streams"
```

All we need to do for that is to declare a CDI producer method which returns the Kafka Streams org.apache.kafka.streams.Topology:

```
@ApplicationScoped
public class TopologyProducer {
    @Produces
    public Topology buildTopology() {
        org.apache.kafka.streams.StreamsBuilder.StreamsBuilder
        builder = new StreamsBuilder();
        // ...
        builder.stream()
            .join()
            // ...
            .toStream()
            .to();
        return builder.build();
    }
}
```

Previous example produces content to another stream. If you want to write interactive queries, you can use Kafka streams.

```
@Inject
KafkaStreams streams;

return streams
    .store("stream", QueryableStoreTypes.keyValueStore());
```

The Kafka Streams extension is configured via the Quarkus configuration file application.properties.

```
quarkus.kafka-streams.bootstrap-servers=localhost:9092
quarkus.kafka-streams.application-id=temperature-aggregator
quarkus.kafka-streams.application-server=${hostname}:8080
quarkus.kafka-streams.topics=weather-stations,temperature-values

kafka-streams.cache.max.bytes.buffering=10240
kafka-streams.commit.interval.ms=1000
```

IMPORTANT: All the properties within the kafka-streams namespace are passed through as-is to the Kafka Streams engine. Changing their values requires a rebuild of the application.

Reactive PostgreSQL Client

You can use Reactive PostgreSQL to execute queries to PostgreSQL database in a reactive way, instead of using JDBC way.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-reactive-pg-client"
```

Database configuration is the same as shown in Persistence section, but URL is different as it is not a *jdbc*.

```
quarkus.datasource.url=
vertx-reactive:postgresql://host:5431/db
```

Then you can inject io.reactiverse.axle.pgclient.PgPool class.

```
@Inject
PgPool client;

CompletionStage<JsonArray> =
    client.query("SELECT * FROM table")
        .thenApply(pgRowSet -> {
            JsonArray jsonArray = new JsonArray();
            PgIterator iterator = pgRowSet.iterator();
            return jsonArray;
        })
```

JWT

Quarkus implements MicroProfile JWT RBAC spec.

```
mvn quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-jwt"
```

Minimum JWT required claims: typ, alg, kid, iss, sub, exp, iat, jti, upn, groups.

You can inject token by using JsonWebToken or a claim individually by using @Claim.

```
@Inject
JsonWebToken jwt;

@Inject
@Claim(standard = Claims.preferred_username)
String name;

@Inject
@Claim("groups")
Set<String> groups;
```

Set of supported types: String, Set<String>, Long, Boolean, `javax.json.JsonValue`, Optional, org.eclipse.microprofile.jwt.ClaimValue.

And configuration in src/main/resources/application.properties:

```
mp.jwt.verify.publickey.location=
META-INF/resources/publicKey.pem
mp.jwt.verify.issuer=
https://quarkus.io/using-jwt-rbac
```

Configuration options:

Parameter	Default	Description
quarkus.smallrye-jwt.enabled	true	Determine if the jwt extension is enabled.
quarkus.smallrye-jwt.realm-name	Quarkus-JWT	Name to use for security realm.
quarkus.smallrye-jwt.auth-mechanism	MP-JWT	Authentication mechanism.

Parameter	Default	Description
mp.jwt.verify.publickey	none	Public Key text itself to be supplied as a string.
mp.jwt.verify.publickey.location	none	Relative path or URL of a public key.
mp.jwt.verify.issuer	none	iss accepted as valid.

Supported public key formats:

- PKCS#8 PEM
- JWK
- JWKS
- JWK Base64 URL
- JWKS Base64 URL

To send a token to server-side you should use Authorization header: curl -H "Authorization: Bearer eyJraWQiOi...

To inject claim values, the bean must be @RequestScoped CDI scoped. If you need to inject claim values in scope with a lifetime greater than @RequestScoped then you need to use javax.enterprise.inject.Instance interface.

```
@Inject
@Claim(standard = Claims.iat)
private Instance<Long> providerIAT;
```

RBAC

JWT groups claim is directly mapped to roles to be used in security annotations.

```
@RolesAllowed("Subscriber")
```

Keycloak

Quarkus can use Keycloak to protect resources using bearer token issued by Keycloak server.

```
mvn quarkus:add-extension
-Dextensions="io.quarkus:quarkus-keycloak"
```

You can get token information by injecting KeycloakSecurityContext object.

```
@Inject
KeycloakSecurityContext keycloakSecurityContext;
```

You can also protect resources with security annotations.

```
@GET
@RolesAllowed("admin")
```

Configure application to Keycloak service in application.properties file.

```
quarkus.keycloak.realm=quarkus
quarkus.keycloak.auth-server-url=http://localhost:8180/auth
quarkus.keycloak.resource=backend-service
quarkus.keycloak.bearer-only=true
quarkus.keycloak.credentials.secret=secret
quarkus.keycloak.policy-enforcer.enable=true
quarkus.keycloak.policy-enforcer.enforcement-mode=PERMISSIVE
quarkus.keycloak.enable-cors=true
quarkus.keycloak.cors-max-age=1000
quarkus.keycloak.cors-allowed-methods=POST, PUT, DELETE, GET
quarkus.keycloak.cors-exposed-headers=WWW-Authenticate
```

You can see all possible Configuration parameters here.

Tip you can also use src/main/resources/keycloak.json standard Keycloak configuration file.

OAuth2

Quarkus integrates with OAuth2 to be used in case of opaque tokens (none JWT) and its validation against an introspection endpoint.

```
mvn quarkus:add-extension
-Dextensions="security-oauth2"
```

And configuration in src/main/resources/application.properties:

```
quarkus.oauth2.client-id=client_id
quarkus.oauth2.client-secret=secret
quarkus.oauth2.introspection-url=http://oauth-server/introspect
```

And you can map roles to be used in security annotations.

```
@RolesAllowed("Subscriber")
```

Configuration options:

Parameter	Default	Description
quarkus.oauth2.enabled	true	Determine if the OAuth2 extension is enabled.
quarkus.oauth2.client-id		The OAuth2 client id used to validate the token.
quarkus.oauth2.client-secret		The OAuth2 client secret used to validate the token.
quarkus.oauth2.introspection-url		URL used to validate the token and gather the authentication claims.
quarkus.oauth2.role-claim	scope	The claim that is used in the endpoint response to load the roles

JAX-RS

Quarkus uses JAX-RS to define REST-ful web APIs.

```
@Path("/book")
public class BookResource {

    @GET
    @Produces(MediaType.APPLICATION_JSON)
    public List<Book> getAllBooks() {}

    @POST
    @Produces(MediaType.APPLICATION_JSON)
    public Response createBook(Book book) {}

    @DELETE
    @Path("/{isbn}")
    @Produces(MediaType.APPLICATION_JSON)
    public Response deleteBook(
        @PathParam("isbn") String isbn) {}

    @GET
    @Produces(MediaType.APPLICATION_JSON)
    @Path("search")
    public Response searchBook(
        @QueryParam("description") String description) {}
}
```

To get information from request:

Property	Description	Example
@PathParam	Gets content from request URI.	/book/{id} @PathParam("id")
@QueryParam	Gets query parameter.	/book?desc="" @QueryParam("desc")
@FormParam	Gets form parameter.	
@MatrixParam	Get URI matrix parameter.	/book;author=mkyong;country=malaysia
@CookieParam	Gets cookie param by name.	

Property	Description	Example
@HeaderParam	Gets header parameter by name.	

Valid HTTP method annotations provided by the spec are: @GET, @POST, @PUT, @DELETE, @PATCH, @HEAD and @OPTIONS.

You can create new annotations that bind to HTTP methods not defined by the spec.

```
@Target({ElementType.METHOD})
@Retention(RetentionPolicy.RUNTIME)
@HttpMethod("LOCK")
public @interface LOCK {

    @LOCK
    public void lockIt() {}
}
```

Injecting

Using @Context annotation to inject JAX-RS and Servlet information.

```
@GET
public String getBase(@Context UriInfo uriInfo) {
    return uriInfo.getBaseUri();
}
```

Possible injectable objects: SecurityContext, Request, Application, Configuration, Providers, ResourceContext, ServletConfig, ServletContext, HttpServletRequest, HttpServletResponse, HttpHeaders, Uriinfo, SseEventSink and Sse.

HTTP Filters

HTTP request and response can be intercepted to manipulate the metadata (ie headers, parameters, media type, ...) or abort a request. You only need to implement the next ContainerRequestFilter and ContainerResponseFilter JAX-RS interfaces respectively.


```
@Provider
public class LoggingFilter
    implements ContainerRequestFilter {

    @Context
    UriInfo info;

    @Context
    HttpServletRequest request;

    @Override
    public void filter(ContainerRequestContext context) {
        final String method = context.getMethod();
        final String path = info.getPath();
        final String address = request.getRemoteAddr();
        System.out.println("Request %s %s from IP %s",
            method, path, address);
    }
}
```

Exception Mapper

You can map exceptions to produce a custom output by implementing `ExceptionHandler` interface:

```
@Provider
public class ErrorMapper
    implements ExceptionMapper<Exception> {

    @Override
    public Response toResponse(Exception exception) {
        int code = 500;
        if (exception instanceof WebApplicationException) {
            code = ((WebApplicationException) exception)
                .getResponse().getStatus();
        }
        return Response.status(code)
            .entity(
                Json.createObjectBuilder()
                    .add("error", exception.getMessage())
                    .add("code", code)
                    .build()
            )
            .build();
    }
}
```

GZip Support

You can configure Quarkus to use GZip in the `application.properties` file using the next properties with `quarkus.resteasy` suffix:

Parameter	Default	Description
<code>gzip.enabled</code>	<code>false</code>	EnableGZip.

Parameter	Default	Description
<code>gzip.max-input</code>	<code>10M</code>	Configure the upper limit on deflated request body.

CORS Filter

Quarkus comes with a CORS filter that can be enabled via configuration:

```
quarkus.http.cors=true
```

Prefix is `quarkus.http`.

Property	Default	Description
<code>cors</code>	<code>false</code>	Enable CORS.
<code>cors.origins</code>	Any request valid.	CSV of origins allowed.
<code>cors.methods</code>	Any method valid.	CSV of methods valid.
<code>cors.headers</code>	Any requested header valid.	CSV of valid allowed headers.
<code>cors.exposed-headers</code>		CSV of valid exposed headers.

Fault Tolerance

Quarkus uses MicroProfile Fault Tolerance spec:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-fault-tolerance"
```

MicroProfile Fault Tolerance spec uses CDI interceptor and it can be used in several elements such as CDI bean, JAX-RS resource or MicroProfile Rest Client.

To do automatic **retries** on a method:

```
@Path("/api")
@RegisterRestClient
public interface WorldClockService {
    @GET @Path("/json/cet/now")
    @Produces(MediaType.APPLICATION_JSON)
    @Retry(maxRetries = 2)
    WorldClock getNow();
}
```

You can set fallback code in case of an error by using `@Fallback` annotation:

```
@Retry(maxRetries = 1)
@Fallback(fallbackMethod = "fallbackMethod")
WorldClock getNow() {}

public WorldClock fallbackMethod() {
    return new WorldClock();
}
```

`fallbackMethod` must have the same parameters and return type as the annotated method.

You can also set logic into a class that implements `FallbackHandler` interface:

```
public class RecoverFallback
    implements FallbackHandler<WorldClock> {
    @Override
    public WorldClock handle(ExecutionContext context) {
    }
}
```

And set it in the annotation as value `@Fallback(RecoverFallback.class)`.

In case you want to use **circuit breaker** pattern:

```
@CircuitBreaker(requestVolumeThreshold = 4,
    failureRatio=0.75,
    delay = 1000)
WorldClock getNow() {}
```

If 3 (4 x 0.75) failures occur among the rolling window of 4 consecutive invocations then the circuit is opened for 1000 ms and then be back to half open. If the invocation succeeds then the circuit is back to closed again.

You can use **bulkahead** pattern to limit the number of concurrent access to the same resource. If the operation is synchronous it uses a semaphore approach, if it is asynchronous a thread-pool one. When a request cannot be processed `BulkheadException` is thrown. It can be used together with any other fault tolerance annotation.

```
@Bulkhead(5)
@Retry(maxRetries = 4,
    delay = 1000,
    retryOn = BulkheadException.class)
WorldClock getNow() {}
```

Fault tolerance annotations:

Annotation	Properties
------------	------------

Annotation	Properties
@Timeout	unit
@Retry	maxRetries, delay, delayUnit, maxDuration, durationUnit, jitter, jitterDelayUnit, retryOn, abortOn
@Fallback	fallbackMethod
@Bulkhead	waitingTaskQueue (only valid in asynchronous)
@CircuitBreaker	failOn, delay, delayUnit, requestVolumeThreshold, failureRatio, successThreshold
@Asynchronous	

You can override annotation parameters via configuration file using `property` property
[classname/methodname/]annotation/parameter:

```
org.acme.quickstart.WorldClock/getNow/Retry/maxDuration=30
# Class scope
org.acme.quickstart.WorldClock/Retry/maxDuration=3000
# Global
Retry/maxDuration=3000
```

You can also enable/disable policies using special parameter enabled.

```
org.acme.quickstart.WorldClock/getNow/Retry/enabled=false
# Disable everything except fallback
MP_Fault_Tolerance_NonFallback_Enabled=false
```

MicroProfile Fault Tolerance integrates with MicroProfile Metrics spec. You can disable it by setting `MP_Fault_Tolerance_Metrics_Enabled` to false.

Observability

Health Checks

Quarkus relies on MicroProfile Health spec to provide health checks.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-health"
```

By just adding this extension, an endpoint is registered to `/health` providing a default health check.

```
{
  "status": "UP",
  "checks": [
  ]
}
```

To create a custom health check you need to implement the `HealthCheck` interface and annotate either with `@Readiness` (ready to process requests) or `@Liveness` (is running) annotations.

```
@Readiness
public class DatabaseHealthCheck implements HealthCheck {
    @Override
    public HealthCheckResponse call() {
        HealthCheckResponseBuilder responseBuilder =
            HealthCheckResponse.named("Database conn");

        try {
            checkDatabaseConnection();
            responseBuilder.withData("connection", true);
            responseBuilder.up();
        } catch (IOException e) {
            // cannot access the database
            responseBuilder.down()
                .withData("error", e.getMessage());
        }

        return responseBuilder.build();
    }
}
```

Builds the next output:

```
{
  "status": "UP",
  "checks": [
    {
      "name": "Database conn",
      "status": "UP",
      "data": {
        "connection": true
      }
    }
  ]
}
```

Since health checks are CDI beans, you can do:

```
@ApplicationScoped
public class DatabaseHealthCheck {

    @Produces
    @ApplicationScoped
    @Liveness
    HealthCheck check1() {
        return io.smallrye.health.HealthStatus
            .up("successful-live");
    }

    @Produces
    @ApplicationScoped
    @Readiness
    HealthCheck check2() {
        return HealthStatus
            .state("successful-read", this::isReady)
    }

    private boolean isReady() {}
}
```

You can ping liveness or readiness health checks individually by querying `/health/live` or `/health/ready`.

Metrics

Quarkus can utilize the MicroProfile Metrics spec to provide metrics support.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-metrics"
```

The metrics can be read with JSON or the OpenMetrics format. An endpoint is registered automatically at `/metrics` providing default metrics.

MicroProfile Metrics annotations:

Annotation	Description
@Timed	Tracks the duration.
@Metered	Tracks the frequency of invocations.
@Counted	Counts number of invocations.
@Gauge	Samples the value of the annotated object.
@ConcurrentGauge	Gauge to count parallel invocations.

Annotation	Description
<code>@Metric</code>	Used to inject a metric. Valid types <code>Meter</code> , <code>Timer</code> , <code>Counter</code> , <code>Histogram</code> . Gauge only on producer methods/fields.

```
@GET
//...
@Timed(name = "checksTimer",
description = "A measure of how long it takes
                to perform a hello.",
unit = MetricUnits.MILLISECONDS)
public String hello() {}

@Counted(name = "countWelcome",
description = "How many welcome have been performed.")
public String hello() {}
```

`@Gauge` annotation returning a measure as a gauge.

```
@Gauge(name = "hottestSauce", unit = MetricUnits.NONE,
description = "Hottest Sauce so far.")
public Long hottestSauce() {}
```

Injecting a histogram using `@Metric`.

```
@Inject
@Metric(name = "histogram")
Histogram historgram;
```

Tracing

Quarkus can utilize the MicroProfile OpenTracing spec.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-opentracing"
```

Requests sent to any endpoint are traced automatically.

This extension includes OpenTracing support and `Jaeger` tracer.

Jaeger tracer configuration:

```
quarkus.jaeger.service-name=myservice
quarkus.jaeger.sampler-type=const
quarkus.jaeger.sampler-param=1
quarkus.jaeger.endpoint=http://localhost:14268/api/traces
```

`@Traced` annotation can be set to disable tracing at class or method level.

```
@Inject
Tracer tracer;

tracer.activeSpan().setBaggageItem("key", "value");
```

Cloud

Native

You can build a native image by using GraalVM. The common use case is creating a Docker image so you can execute the next commands:

```
./mvnw package -Pnative -Dnative-image.docker-build=true

docker build -f src/main/docker/Dockerfile.native
                -t quarkus/getting-started .
docker run -i --rm -p 8080:8080 quarkus/getting-started
```

To configure native application, you can create a config directory at the same place as the native file and place an `application.properties` file inside. `config/application.properties`.

Kubernetes

Quarks can use `Dekorater` to generate Kubernetes resources.

```
./mvnw quarkus:add-extensions
-Dextensions="io.quarkus:quarkus-kubernetes"
```

Running `./mvnw package` the Kubernetes resources are created at `target/wiring-classes/META-INF/kubernetes/` directory.

Property	Default	Description
<code>quarkus.kubernetes.group</code>	Current username	Set Docker Username.
<code>quarkus.application.name</code>	Current project name	Project name

Generated resource is integrated with `MicroProfile Health` annotations.

Kubernetes Client

Quarkus integrates with `Fabric8` Kubernetes Client.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-kubernetes-client"
```

List of Kubernetes client parameters.

`quarkus.kubernetes-client` as prefix is skipped in the next table.

Property	Default	Description
----------	---------	-------------

Property	Default	Description
trust-certs	false	Trust self-signed certificates.
master-url		URL of Kubernetes API server.
namesapce		Default namespace.
ca-cert-file		CA certificate data.
client-cert-file		Client certificate file.
client-cert-data		Client certificate data.
client-key-data		Client key data.
client-key-algorithm		Client key algorithm.
client-key-passphrase		Client key passphrase.
username		Username.
password		Password.
watch-reconnect-interval	PT1S	Watch reconnect interval.
watch-reconnect-limit	-1	Maximum reconnect attempts.
connection-timeout	PT10S	Maximum amount of time to wait for a connection.
request-timeout	PT10S	Maximum amount of time to wait for a request.
rolling-timeout	PT15M	Maximum amount of time to wait for a rollout.

Property	Default	Description
http-proxy		HTTP proxy used to access the Kubernetes.
https-proxy	""	HTTPS proxy used to access the Kubernetes.
proxy-username		Proxy username.
proxy-password		Proxy password.
no-proxy		IP addresses or hosts to exclude from proxying

Or programmatically:

```
@Dependent
public class KubernetesClientProducer {

    @Produces
    public KubernetesClient kubernetesClient() {
        Config config = new ConfigBuilder()
            .withMasterUrl("https://mymaster.com")
            .build();
        return new DefaultKubernetesClient(config);
    }
}
```

And inject it on code:

```
@Inject
KubernetesClient client;

ServiceList myServices = client.services().list();

Service myservice = client.services()
    .inNamespace("default")
    .withName("myservice")
    .get();

CustomResourceDefinitionList crds = client
    .customResourceDefinitions()
    .list();

dummyCRD = new CustomResourceDefinitionBuilder()
    ...
    .build()
client.customResourceDefinitions()
    .create(dummyCRD);
```

Testing

Quarkus provides a Kubernetes Mock test resource that starts a mock of Kubernetes API server and sets the proper environment variables needed by Kubernetes Client.

Register next dependency: `io.quarkus:quarkus-test-kubernetes-client:test`.

```
@QuarkusTestResource(KubernetesMockServerTestResource.class)
@QuarkusTest
public class KubernetesClientTest {

    @MockServer
    private KubernetesMockServer mockServer;

    @Test
    public void test() {
        final Pod pod1 = ...
        mockServer
            .expect()
            .get()
            .withPath("/api/v1/namespaces/test/pods")
            .andReturn(200,
                new PodListBuilder()
                    .withNewMetadata()
                    .withResourceVersion("1")
                    .endMetadata()
                    .withItems(pod1, pod2)
                    .build())
            .always();
    }
}
```

Amazon Lambda

Quarkus integrates with Amazon Lambda.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-amazon-lambda"
```

And then implement `com.amazonaws.services.lambda.runtime.RequestHandler` interface.

```
public class TestLambda
    implements RequestHandler<MyInput, MyOutput> {
    @Override
    public MyOutput handleRequest(MyOutput input,
                                   Context context) {
    }
}
```

Test

You can write tests for Amazon lambdas:


```
<dependency>
  <groupId>io.quarkus</groupId>
  <artifactId>quarkus-test-amazon-lambda</artifactId>
  <scope>test</scope>
</dependency>
```

```
@Test
public void testLambda() {
    MyInput in = new MyInput();
    in.setGreeting("Hello");
    in.setName("Stu");
    MyOutput out = LambdaClient.invoke(MyOutput.class, in);
}
```

Apache Camel

Quarkus integrates wih Apache Camel.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-camel-core"
```

You can inject CamelRuntime and CamelContext instances:

```
@Inject
CamelRuntime runtime;

@Inject
CamelContext context;
```

And also observing Camel events InitializingEvent, InitializedEvent, StartingEvent, StartedEvent. StoppingEvent, StoppedEvent.

```
public void init(@Observes InitializingEvent event) {
    runtime.getContext()
        .setUuidGenerator(new DefaultUuidGenerator());
}
```

You can create RouteBuilder for routing rules:

```
public class CamelRoute extends RouteBuilder {

    @Override
    public void configure() {
        from("timer:keep-alive?" +
            "period={{camel.timer-route.period}}")
            .id("timer-route")
            .setBody(constant(""))
            .to("log:keep-alive");
    }
}
```

Custom properties are set in application.properties.

```
camel.timer-route.period=1s
```

List of Camel parameters.

quarkus. as a prefix is skipped in the next table.

Parameter	Default	Description
camel.routesUri		Uri to an XML with camel routes.

Parameter	Default	Description
camel.deferInitPhase	false	Defer context initialization phase until runtime.
camel.disableJaxb	false	Disable support for JAXB at runtime. Useful when routes loaded at build time.
camel.disableXml	false	Disable XML support in various parts of Camel.
camel.dumpRoutes	false	Dump loaded routes .

Quarkus also comes with support for Camel in form of next extensions: camel-aws-s3, camel-aws-sqs, camel-infinispan, camel-netty4-http, camel-salesforce.

WebSockets

Quarkus can be used to handling web sockets.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-undertow-websockets"
```

And web sockets classes can be used:

```
@ServerEndpoint("/chat/{username}")
@ApplicationScoped
public class ChatSocket {

    @OnOpen
    public void onOpen(Session session,
        @PathParam("username") String username) {}

    @OnClose
    public void onClose(..) {}

    @OnError
    public void onError(..., Throwable throwable) {}

    @OnMessage
    public void onMessage(...) {}

}
```

OpenAPI

Quarkus can expose its API description as OpenAPI spec and test it using Swagger UI.

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-smallrye-openapi"
```

Then you only need to access to /openapi to get OpenAPI v3 spec of services.

You can update the OpenApi path by setting quarkus.smallrye-openapi.path property.

Also, in case of starting Quarkus application in dev or test mode, Swagger UI is accessible at /swagger-ui. If you want to use it in production mode you need to set quarkus.swagger-ui.always-include property to true.

You can update the Swagger UI path by setting quarkus.swagger-ui.path property.

```
quarkus.swagger-ui.path=/my-custom-path
```

You can customize the output by using Open API v3 annotations.

```
@Schema(name="Developers", description="POJO that represents a developer.")
public class Developer {
    @Schema(required = true, example = "Alex")
    private String name;
}

@POST
@Path("/developer")
@Operation(summary = "Create deeloper",
    description = "Only be done by admin.")
public Response createDeveloper(
    @RequestBody(description = "Developer object",
        required = true,
        content = @Content(schema =
            @Schema(implementation = Developer.class)))
    Developer developer)
```

All possible annotations can be seen at org.eclipse.microprofile.openapi.annotations package.

Mail Sender

You can send emails by using Quarkus Mailer extension:

```
./mvnw quarkus:add-extension
-Dextensions="io.quarkus:quarkus-mailer"
```

You can inject two possible classes io.quarkus.mailer.Mailer for synchronous API or io.quarkus.mailer.ReactiveMailer for asynchronous API.

```
@Inject
Mailer mailer;

@Inject
ReactiveMailer reactiveMailer;
```

And then you can use them to send an email:

```
mailer.send(
    Mail.withText("to@acme.org", "Subject", "Body")
);

CompletionStage<Void> stage =
    reactiveMailer.send(
        Mail.withText("to@acme.org", "Subject", "Body")
    );
```

Mail class contains methods to add cc, bcc, headers, bounce address, reply to, attachments, inline attachments and html body.

```
mailer.send(Mail.withHtml("to@acme.org", "Subject", body)
    .addInlineAttachment("quarkus.png",
        new File("quarkus.png"),
        "image/png", "<my-image@quarkus.io>"));
```

Tip If you need deep control you can inject Vert.x mail client @Inject MailClient client;

You need to configure SMTP properties to be able to send an email:

```
quarkus.mailer.from=test@quarkus.io
quarkus.mailer.host=smtp.sendgrid.net
quarkus.mailer.port=465
quarkus.mailer.ssl=true
quarkus.mailer.username=...
quarkus.mailer.password=...
```

List of Mailer parameters. quarkus. as a prefix is skipped in the next table.

Parameter	Default	Description
mailer.from		Default address.

Parameter	Default	Description
mailer.mock	false in prod, true in dev and test.	Emails not sent, just printed and stored in a MockMailbox bean.
mailer.bounce-address		Default address.
mailer.host	mandatory	SMTP host.
mailer.port	25	SMTP port.
mailer.username		The username.
mailer.password		The password.
mailer.ssl	false	Enables SSL.
mailer.trust-all	false	Trust all certificates.
mailer.max-pool-size	10	Maximum number of open connections .
mailer.own-host-name		Hostname for HELO/EHLO and Message-ID
mailer.keep-alive	true	Connection pool enabled.
mailer.disable-esmtp	false	Disable ESMTP.
mailer.start-tls	OPTIONAL	TLS security mode. NONE, OPTIONAL, REQUIRED.
mailer.login	NONE	Login mode. NONE, OPTIONAL, REQUIRED.
mailer.auth-methods	All methods.	Space-separated list.

Parameter	Default	Description
mailer.key-store		Path of the key store.
mailer.key-store-password		Key store password.

IMPORTANT: if you enable SSL for the mailer and you want to build a native executable, you will need to enable the SSL support `quarkus.ssl.native=true`.

Testing

If `quarkus.mailer.mock` is set to `true`, which is the default value in dev and test mode, you can inject `MockMailbox` to get the sent messages.

```
@Inject
MockMailbox mailbox;

@BeforeEach
void init() {
    mailbox.clear();
}

List<Mail> sent = mailbox
    .getMessagesSentTo("to@acme.org");
```

Scheduled Tasks

You can schedule periodic tasks with Quarkus.

```
@ApplicationScoped
public class CounterBean {

    @Scheduled(every="10s")
    void increment() {}

    @Scheduled(cron="0 15 10 * * ?")
    void morningTask() {}
}
```

`every` and `cron` parameters can be surrounded with `{}` and the value is used as config property to get the value.

```
@Scheduled(cron = "{morning.check.cron.expr}")
void morningTask() {}
```

And configure the property into `application.properties`:

```
morning.check.cron.expr=0 15 10 * * ?
```

Kogito

Quarkus integrates with Kogito, a next-generation business automation toolkit from Drools and jBPM projects for adding business automation capabilities.

To start using it you only need to add the next extension:

```
./mvnw quarkus:add-extension
-Dextensions="kogito"
```

Apache Tika

Quarkus integretrs with Apache Tika to detect and extract metadata/text from different file types:

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-tika"
```

```
@Inject
io.quarkus.tika.TikaParser parser;

@POST
@Path("/text")
@Consumes({ "text/plain", "application/pdf",
    "application/vnd.oasis.opendocument.text" })
@Produces(MediaType.TEXT_PLAIN)
public String extractText(InputStream stream) {
    return parser.parse(stream).getText();
}
```

You can configure Apache Tika from `application.properties` file by using next properties prefixed with ``quarkus:`

Parameter	Default	Description
tika.tika-config-path	tika-config.xml	Path to the Tika configuration resource.
tika.append-embedded-content	true	The document may have other embedded documents. Set if autmatically append.

Spring DI

Quarkus provides a compatibility layer for Spring dependency injection.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-spring-di"
```

Some examples of what you can do. Notice that annotations are the Spring original ones.

```
@Configuration
public class AppConfiguration {

    @Bean(name = "capitalizeFunction")
    public StringFunction capitalizer() {
        return String::toUpperCase;
    }
}
```

Or as a component:

```
@Component("noopFunction")
public class NoOpSingleStringFunction
    implements StringFunction {
}
```

Also as a service and injection properties from `application.properties`.

```
@Service
public class MessageProducer {

    @Value("${greeting.message}")
    String message;

}
```

And you can inject using `Autowired` or constructor in a component and in a JAX-RS resource too.

```
@Component
public class GreeterBean {

    private final MessageProducer messageProducer;

    @Autowired @Qualifier("noopFunction")
    StringFunction noopStringFunction;

    public GreeterBean(MessageProducer messageProducer) {
        this.messageProducer = messageProducer;
    }
}
```

Spring Web

Quarkus provides a compatibility layer for Spring Web.

```
./mvnw quarkus:add-extension
-Dextensions="quarkus-spring-web"
```

Specifically supports the REST related features. Notice that infrastructure things like BeanPostProcessor will not be executed.

```
@RestController
@RequestMapping("/greeting")
public class GreetingController {

    private final GreetingBean greetingBean;

    public GreetingController(GreetingBean greetingBean) {
        this.greetingBean = greetingBean;
    }

    @GetMapping("/{name}")
    public Greeting hello(@PathVariable(name = "name")
        String name) {
        return new Greeting(greetingBean.greet(name));
    }
}
```

Supported annotations are: RestController, RequestMapping, GetMapping, PostMapping, PutMapping, DeleteMapping, PatchMapping, RequestParam, `RequestHeader, MatrixVariable, PathVariable, CookieValue, RequestBody, ResponseStatus, ExceptionHandler and RestControllerAdvice.

Resources

- <https://quarkus.io/guides/>
- <https://www.youtube.com/user/lordofthejars>

Authors :



@alexsotob
Java Champion and SW Engineer at Red Hat

0.21.1

