

Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	our organization experienced a DoS attack in this morning, which compromised the internal network for two hours until it was resolved, During the attack, our organization's network services suddenly stopped responding due to an incoming flood of ICMP packets, Normal internal network traffic could not access any network resources
Identify	We found in our investigation that malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall, This vulnerability allowed the malicious attacker to overwhelm the company's network through a denial of service (DoS) attack
Protect	**This situation never happen so will implement** 1. A new firewall rule to limit the rate of incoming ICMP packets 2. Source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets 3. Network monitoring software to detect abnormal traffic patterns
Detect	To make sure we spot this kind of trouble early next time, we are setting up network monitoring software so we can keep an eye on

	our normal traffic patterns and catch any weird spikes right away, We are also deploying an IDS/IPS system, which will act like a security guard to filter out any suspicious-looking ICMP traffic before it can do any damage
Respond	When the attack hit, our incident management team jumped in right away to contain the damage, We completely blocked all incoming ICMP packets at the firewall to stop the flood, and we took all of our non-critical network services offline so we could focus entirely on resolving the threat and preventing it from causing anymore damages
Recover	Once the attack was fully stopped, we focused on getting everything back to normal. We immediately restored our critical network services so day to day operations could run again, ensuring normal internal traffic could securely access resources Moving forward, our **recovery planning** will follow a phased approach, prioritizing core infrastructure like the firewall and primary servers before bringing non-critical services back online. To **improve our process**, we need to set up automated configuration backups for our network devices so we can instantly restore clean settings if an asset is compromised. For **communications**, our IT staff will receive real-time updates via a dedicated out of band channel, while a clear, all-clear email notification will be sent to our end-users to confirm that network resources are safe and fully operational

Reflections/Notes: This incident highlighted a critical gap in our perimeter defense, specifically the

unconfigured firewall that left our network open to a basic ICMP flood, While our manual response successfully contained the threat within two hours, relying on reactive measures slows down our recovery time and impacts productivity