

Unsupervised Feature Discovery for Time Series Fault Detection via Reliability-Aware Typed Genetic Programming

Tarimica Sean Chiwara
Department of Computer Engineering
Chinhoyi University of Technology

May 2026

Abstract

We present a fully unsupervised framework for discovering diagnostic features from raw time series data using typed Genetic Programming (GP). The framework requires only healthy-state recordings: no fault labels, no expert feature engineering, no prior knowledge of failure modes. Our key contributions are: (1) a type-safe GP that constrains evolved expressions to physically meaningful compositions, (2) a reliability-aware fitness function incorporating split-half reliability that automatically separates physics-based features from noise amplifiers, and (3) the discovery of a sensitivity-stability paradox: features optimized for measurement stability are fundamentally unsuited for early fault detection. We validate on six real-world datasets across four physical domains: the CWRU bearing benchmark (AUC = 1.000), the IMS/NASA bearing run-to-failure (19.2 hours earlier detection than baselines), EngineFaultDB automotive diagnostics (AUC = 1.000), NASA C-MAPSS turbofan prognostics (2.2% earlier detection), and the MIT-BIH arrhythmia database (0.887 AUC with novel cross-lead features). Across all domains, the GP independently discovers physically meaningful features: instantaneous power, vibration jerk, engine load composites, coolant bleed flow health indices, and cross-lead envelope dynamics, from healthy data alone.

1 Introduction

Condition monitoring of rotating machinery relies on diagnostic features extracted from vibration signals. Designing these features traditionally requires domain expertise: engineers select quantities such as RMS, kurtosis, crest factor, and envelope spectra based on decades of empirical knowledge about how specific failure modes manifest in vibration data.

This approach has two limitations. First, it is reactive: features are designed after failure modes are known, not before. A novel degradation mechanism may go undetected if no hand-crafted feature targets it. Second, it is non-transferable: features designed for bearings do not apply to gearboxes, which do not apply to automotive powertrains. Each new system requires a new round of expert feature engineering.

We ask: can useful diagnostic features be discovered automatically from healthy-state data alone, without any knowledge of what might go wrong?

Our approach uses Genetic Programming (GP) to evolve mathematical expressions that transform raw sensor signals into scalar health indicators. The key insight is that features which produce

tight, stationary, and reproducible distributions on healthy data are precisely the features that will produce anomalous readings when the system deviates from healthy behavior, regardless of the specific failure mode.

To prevent the GP from evolving expressions that merely amplify noise, we introduce split-half reliability as a fitness component: features must produce consistent values when computed on the first and second halves of each recording. This single addition transforms the framework from one that discovers a mix of physics and noise into one that overwhelmingly discovers physics.

Contributions.

1. Typed GP framework for unsupervised feature discovery in time series, with a domain-adaptable type system that ensures physical consistency of evolved expressions.
2. Reliability-aware fitness that uses split-half correlation to separate physics from noise during evolution.
3. Six-dataset validation across four physical domains: simulated pendulum, CWRU/IMS bearings, EngineFaultDB automotive, NASA C-MAPSS turbofan, and MIT-BIH ECG arrhythmia.
4. Sensitivity-stability paradox: features optimized for measurement reliability are the worst early fault detectors.
5. Novel feature discoveries: 19.2-hour early bearing detection via cross-bearing differentials, coolant bleed flow as a leading turbofan indicator, and cross-lead envelope dynamics for ECG.
6. Honest limitation analysis: operator vocabulary bounds for morphological classification domains (ECG kurtosis gap).

2 Framework

2.1 Typed Genetic Programming

Standard GP operates on untyped expression trees, allowing arbitrary compositions of operators and operands. In physical systems, this produces nonsensical expressions (e.g., adding a temperature to an acceleration). We constrain the search space with a type system that assigns physical types to terminals and enforces type-compatibility rules on operators.

Definition 1 (Type System). $\mathcal{T} = (\mathbf{T}, \Sigma, \Omega)$ consists of a set of types $\mathbf{T}$, typed terminals $\Sigma = \{(x_i, \tau_i) : \tau_i \in \mathbf{T}\}$, and typed operators Ω where each $\omega : \tau_1 \times \dots \times \tau_k \rightarrow \tau_{\text{out}}$.

The type system is domain-adaptable: for each application, one defines the relevant types, terminals, and operators. We demonstrate six instantiations:

Pendulum. Types: {Angle, Velocity, Acceleration, Energy, Scalar}. Terminals: $\{\theta : \text{Angle}, \dot{\theta} : \text{Velocity}, g = 9.81 : \text{Scalar}\}$. Operators include $\frac{d}{dt} : \text{Angle} \rightarrow \text{Velocity}$, $\sin : \text{Angle} \rightarrow \text{Scalar}$, $(\cdot)^2 : \text{Velocity} \rightarrow \text{Energy}$, etc.

Vibration (CWRU/IMS). Types: {Vibration, Energy, Scalar}. Terminals: accelerometer channels (all type Vibration). Operators include $\frac{d}{dt}$, $|\cdot|$, rolling std, same-type addition/subtraction, and cross-type products (Vibration $\times$ Vibration $\rightarrow$ Energy).

Engine (EngineFaultDB). Types: {Pressure, Rotation, Mechanical, Combustion, Emission, Ratio, Scalar}. 13 terminals spanning MAP, RPM, TPS, Force, Power, Speed, fuel consumption, and exhaust emissions. Cross-type operators: Power/RPM (torque), MAP $\times$ RPM (airflow), TPS $\times$ RPM (load).

Turbofan (C-MAPSS). Types: {Temperature, Pressure, Speed, Ratio, Flow, Control, Scalar}. 14 terminals from useful sensors. Cross-type operators: T/T (compressor ratio), T/P (specific volume), F/N (flow coefficient), $T - T$ (compressor temperature rise).

ECG (MIT-BIH). Types: {Voltage, Energy, Scalar}. Only 2 terminals: ECG₁ (MLII lead) and ECG₂ (V1/V5 lead). The minimal terminal set forces the GP to discover cross-lead combinations.

2.2 Operator Universality and Domain Portability

Comparing the six domain instantiations, a natural question arises: when adapting this framework to a new domain, how much of the operator set must be redesigned? The answer, perhaps surprisingly, is very little. All six domains share substantial operator overlap: the derivative $\frac{d}{dt}$, same-type arithmetic (+, −), cross-type multiplication, absolute value, and rolling statistics. The domain-specific additions are few.

Definition 2 (Operator Stratification). *The operator set decomposes as*

$$\Omega = \Omega_{\text{core}} \cup \Omega_{\text{domain}},$$

where Ω_{core} contains operators that recur across domains and Ω_{domain} contains operators tied to specific physics.

Concretely, we identify the following core operator set:

$$\Omega_{\text{core}} = \left\{ \frac{d}{dt}, |\cdot|, (\cdot)^2, \text{std}_w[\cdot], \text{mean}_w[\cdot], +_{\text{same}}, -_{\text{same}}, \times_{\text{cross}} \right\}.$$

These eight operators capture the four categories from which every top-performing feature is composed: amplitude ($|\cdot|$, $(\cdot)^2$), dynamics ($\frac{d}{dt}$), variability ($\text{std}_w[\cdot]$, $\text{mean}_w[\cdot]$), and cross-channel structure (+, −, ×).

Table 1: Operator set decomposition across domains

Domain	$ \Omega_{\text{core}} $	$ \Omega_{\text{domain}} $	Adaptation
Pendulum	5	2 (sin, cos)	Types + terminals
Vibration (CWRU/IMS)	6	0	Terminals only
Engine (EngineFaultDB)	7	1 ($\text{div}_{\times}$)	Types + terminals
Turbofan (C-MAPSS)	7	1 ($\text{sub}_{\times}$)	Types + terminals
ECG (MIT-BIH)	6	0	Terminals only

The practical consequence is that domain adaptation is dominated by terminal and type definitions, not by operator redesign. In no experiment did a domain-specific operator appear in the top-performing evolved feature.

Conjecture 1 (Core Operator Sufficiency). *For any time series monitoring domain in which faults manifest as changes in signal amplitude, dynamics (rate of change), or cross-channel relationships, Ω_{core} is sufficient to evolve features whose diagnostic performance matches or exceeds hand-crafted baselines designed by domain experts.*

Limitations and boundaries. The conjecture is scoped to amplitude- and dynamics-based fault signatures. The MIT-BIH ECG experiment identifies a clear boundary: morphological classification domains where faults manifest as shape changes benefit from higher-order statistical operators (kurtosis, skewness) not present in Ω_{core} . Frequency-domain faults, phase-sensitive faults, and long-range temporal dependencies also fall outside its scope.

2.3 Fitness Function

The fitness function operates on healthy-state data only. Given a candidate feature f and healthy trials $\{x_1, \dots, x_N\}$:

$$C(f) = \frac{1}{4}[T(f) + W(f) + H(f) + R(f)],$$

$$\begin{aligned} T(f) &= \frac{1}{1 + H_{\text{norm}}} \quad (\text{Tightness}) & W(f) &= \max(0, 1 - \text{CV}_{\text{chunks}}) \quad (\text{Stationarity}) \\ H(f) &= \frac{1}{1 + |\text{kurtosis}|} \quad (\text{Headroom}) & R(f) &= \max(0, r_{\text{split}}) \quad (\text{Reliability}) \end{aligned}$$

where

$$r_{\text{split}} = \text{corr}\left(\{S(f(x_i^{\text{first}}))\}_i, \{S(f(x_i^{\text{second}}))\}_i\right).$$

High reliability means the feature measures a stable physical quantity, not transient noise. Additional mechanisms: 0.5 $\times$ penalty when rolling std appears at expression root, hash-based diversity enforcement, correlation-based semantic deduplication ($|r| > 0.95$), and best-ever elitism.

2.4 Evolutionary Parameters

Population size: 200. Generations: 80 ($\approx 16,000$ candidate features evaluated per run). Maximum tree depth: 4. Tournament selection $k = 5$. Elitism: 5% (10 individuals). Reproduction: crossover 60%, mutation 30%, immigration 10%. The 60/30/10 split is moderately exploration-heavy compared to standard GP practice, reflecting the goal of discovering a diverse set of complementary features.

3 Experiment 1: Simulated Pendulum

3.1 Setup

We simulate a damped, forced pendulum governed by:

$$\frac{d^2\theta}{dt^2} = -\frac{g}{L} \sin \theta - b \frac{d\theta}{dt} + F_a \sin(F_f t),$$

with three fault types: increased damping ($b : 0.30 \rightarrow 0.375$), shortened string ($L : 1.00 \rightarrow 0.75$), and external forcing ($F_a : 0 \rightarrow 0.50$). Raw observables are $\theta(t)$ and $\dot{\theta}(t)$, sampled at 200 Hz for 25 s per trial. GP trains on 60 healthy trials only.

3.2 Results

The GP independently rediscovered the instantaneous power equation:

$$\frac{d}{dt}[\dot{\theta}^2] = 2\dot{\theta}\ddot{\theta} = -\frac{2g}{L}\dot{\theta}\sin\theta - 2b\dot{\theta}^2 + 2F_a\dot{\theta}\sin(F_f t),$$

where the three terms represent potential energy exchange, damping dissipation, and external power injection respectively. This feature achieves AUC = 1.000 for damping faults at severity 0.25.

Robustness. Five independent seeds {42, 7, 123, 99, 2024} all pass robustness checks: mean 70.9% good features (range: 57–84%), top-10 reliability > 0.99 across all seeds, 5–6/6 physics terms found.

Table 2: Pendulum results (v5 fitness, seed 42)

Metric	Value
Features with AUC > 0.70	35/50 (70%)
Features with reliability > 0.9	38/50 (76%)
Top-10 avg reliability	0.982
Physics terms found (of 6)	6/6
#1 feature	$\cos(g\theta) \cdot \text{rstd}(\text{rstd}(\dot{\theta}))$
#1 AUC (high_damp)	0.973
Mann-Whitney high_damp	$p = 0.039$

4 Experiment 2: CWRU Bearing Benchmark

4.1 Setup

The CWRU Bearing Data Center dataset provides vibration data from a 2 HP motor with seeded bearing faults at three severities (0.007", 0.014", 0.021") on inner race, ball, and outer race. Drive-end (DE) and fan-end (FE) accelerometers at 12 kHz. Windows: 3000 samples (0.25 s). GP trains on 60 normal windows from 1797 RPM. Baselines: 16 hand-crafted features (RMS, std, kurtosis, crest factor, skewness, peak-to-peak, energy, cross-channel correlation and ratio).

4.2 Results

Table 3: CWRU results

Condition	GP AUC	Base AUC	Winner
Same-speed (1797 $\rightarrow$ 1797, 9 faults)	1.000	1.000	TIE
Cross-speed (1797 $\rightarrow$ 1730, 13 faults)	1.000	1.000	TIE

The GP achieves perfect fault detection across all conditions, including cross-speed generalization to a load condition never seen during training. The CWRU dataset exhibits a ceiling effect, motivating the harder IMS benchmark.

5 Experiment 3: IMS/NASA Run-to-Failure

5.1 Setup

The IMS bearing dataset tracks 4 bearings under 6000 lbs radial load at 2000 RPM through progressive degradation to failure. Test 2 comprises 984 vibration snapshots (1 s each at 20 kHz, 4 channels) over 7 days. Bearing 1 develops an outer race fault through natural wear.

GP trains on the first 100 snapshots (all healthy). Terminals: $\{B_1, B_2, B_3, B_4\}$, all type Vibration, allowing the GP to discover cross-bearing features. Detection criterion: z -score exceeds threshold for 3 consecutive snapshots.

5.2 Results at 5-sigma

At the conservative 5σ threshold, GP ties the best baseline. Detection rate: GP 47/49 (96%) vs. baseline 8/11 (73%).

Table 4: IMS detection at 5σ

Type	Feature	Detects at	% Life
GP	$\frac{d^2}{dt^2}[B_1]$ (jerk)	snap 532	54.1%
GP	$-2 \frac{d}{dt}[B_1]$	snap 532	54.1%
Base	B_1/B_2 ratio	snap 532	54.1%
Base	B_1 RMS	snap 537	54.6%

5.3 Results at 3-sigma: GP Wins

Table 5: IMS detection at 3σ

Type	Feature	Detects	% Life	Lead
GP	$B_1 - B_3 + B_2 - \text{rstd}(B_4)$	snap 378	38.4%	+19.2 h
Base	B_1/B_3 ratio	snap 493	50.1%	—
Base	B_1/B_2 ratio	snap 532	54.1%	—

The GP-evolved feature detects degradation 19.2 hours (115 snapshots) before the best hand-crafted baseline. $B_1 - B_3$ cancels common-mode vibration, B_2 provides a second reference, and $\text{rstd}(B_4)$ adds a temporal stability term. No human engineer designed this expression; it emerged from the fitness function alone.

5.4 Pre-Failure Drift Analysis

Table 6: Feature drift (early healthy vs mid-life)

Type	Feature	Drift (σ)	Significant?
GP	$B_1 - B_3 + B_2 - \text{rstd}(B_4)$	-2.47	Yes
GP	$ B_3 + B_1$	-2.25	Yes
GP	$ B_1 - B_3 $	-2.23	Yes
Base	B_1/B_3	+2.12	Yes
Base	B_1 RMS	-0.50	No
Base	B_1 energy	-0.50	No
Base	B_1 kurtosis	-0.59	No

Three GP features exhibit significant drift ($> 2\sigma$) during the pre-failure period. Only one baseline does. Standard amplitude features (RMS, energy, std) are blind to early degradation.

5.5 What the GP Discovered

Across the first three experiments, the GP independently rediscovered: instantaneous power $\frac{d}{dt}[\dot{\theta}^2]$ (pendulum), signal amplitude $\sum |x|$ (CWRU), vibration jerk $\frac{d^2}{dt^2}[B_1]$ (IMS), cross-channel differentials $B_1 - B_3$, B_1/B_3 (IMS), and the multi-channel composite $B_1 - B_3 + B_2 - \text{rstd}(B_4)$ (IMS, novel).

6 Experiment 4: EngineFaultDB Automotive Diagnostics

6.1 Setup

EngineFaultDB [12] provides data from a C14NE spark ignition engine under controlled laboratory conditions: 55,999 samples across 14 engine variables (MAP, RPM, TPS, Force, Power, Speed, fuel consumption, CO, HC, CO₂, O₂, Lambda, AFR) across four classes (normal and 3 fault types). The type system comprises 7 physical types with 13 terminals. Cross-type operators encode domain physics: Power/RPM yields torque, MAP×RPM approximates airflow, TPS×RPM represents engine load. Data windowed into 200-sample trials; 60 healthy trials for training; 24 hand-crafted baselines including SFC, volumetric efficiency, combustion efficiency, HC/CO ratio, and O₂/CO₂ ratio.

6.2 Results and What the GP Discovered

Table 7: EngineFaultDB results

Fault	GP AUC	Baseline AUC	Winner
Fault 1	1.000	1.000	TIE
Fault 2	1.000	1.000	TIE
Fault 3	1.000	1.000	TIE

Both GP and all 24 baselines achieve AUC = 1.000. The ceiling effect limits differentiation but validates domain adaptation. Runtime: 3.4 minutes.

The top GP feature, $\text{TPS} \times \text{RPM} + 0.5(|\text{Power}| + \text{rstd}(\text{Force}))$, is an engine load composite: TPS×RPM is a standard load proxy in automotive diagnostics, discovered without domain knowledge. Cross-type operators appeared in 13/30 top features (Power/RPM: 6/10, MAP×RPM: 4/10, TPS×RPM: 3/10).

7 Experiment 5: NASA C-MAPSS Turbofan Prognostics

7.1 Setup

NASA’s C-MAPSS [13] FD001 tracks 100 turbofan engines through progressive HPC degradation. Life lengths range from 128 to 362 cycles (mean 206). The type system spans 7 physical types with 14 terminals: temperatures T24, T30, T50; pressures P30, Ps30; speeds Nf, Nc, NRf, NRc; ratio BPR and ϕ ; flows W31, W32; control htBleed. GP trains on the first 30% of each engine’s life. Anti-monoculture measures: 25% forced cross-type seeding, 50% forced cross-type immigration, deduplication at generations 20, 40, 60. Detection: $z > 3\sigma$ for 5 consecutive windows, evaluated across all 100 engines.

7.2 Results

GP detects HPC degradation 2.2% earlier in engine life than the best baseline (35.2% vs. 37.4%), equivalent to approximately 5 cycles on average-length engines. Top-10 GP features average 99.8% detection rate vs. 97.7% for top-10 baselines.

Table 8: C-MAPSS FD001 detection (top features)

Type	Feature	Median % Life	Detection Rate
GP	$W_{31} + \text{rmean}(W_{32}) + \text{rmean}(\dots)$	35.2%	100/100
GP	$ \text{rmean}(W_{31}) + \text{rmean}(W_{31}) - \dots $	36.0%	100/100
Base	T50 mean	37.4%	100/100
Base	$P_{30} - P_{s30}$ diff	37.5%	100/100
Base	P_{s30} mean	38.7%	100/100

7.3 What the GP Discovered: Coolant Bleed Flow as Leading Indicator

The GP converged on coolant bleed flow features (W31: HPT coolant bleed, W32: LPT coolant bleed). The standard prognostics literature focuses on temperatures (T24, T30, T50) and corrected speeds (NRf, NRc). The GP found that coolant bleed flows are more sensitive early indicators.

As the HPC degrades, compressor efficiency drops. The engine control system compensates by adjusting bleed flows to maintain performance targets. These adjustments occur before downstream temperature and speed changes become significant: the bleed system is a leading indicator because it responds to the controller’s attempts to compensate for degradation, while T50 only changes after compensation is insufficient.

The GP’s best feature simplifies to:

$$W_{31} + \text{rmean}(W_{32}) + \text{rmean}(2W_{31}),$$

a bleed flow health index that integrates both bleed streams with temporal smoothing to capture the progressive shift in cooling demand as the compressor degrades. Runtime: 8.6 minutes GP evolution plus 4.3 seconds timeline evaluation.

8 Experiment 6: MIT-BIH ECG Arrhythmia Detection

8.1 Setup

The MIT-BIH Arrhythmia Database [14] is the gold-standard ECG dataset: 48 patients, 2-channel ECG at 360 Hz, every heartbeat annotated by cardiologists. This experiment tests whether the framework generalizes to cardiac electrophysiology.

Beat-level windowing: 250-sample windows (≈ 694 ms) centered on annotated R-peaks. 40 patients loaded from PhysioNet, yielding 75,020 normal beats and 11,645 arrhythmia beats (V: 6,607 PVCs; R: 3,078 RBBB; A: 959 APBs; F: 794 fusion beats). GP trains on 120 pooled normal beats. Evaluation: per-patient AUC via $|z\text{-score}|$ from each patient’s own normal distribution; 28 patients with ≥ 10 arrhythmia beats used for evaluation.

Type system: {Voltage, Energy, Scalar}, 3 types, 2 terminals (ECG₁: MLII lead, ECG₂: V1/V5 lead). The minimal terminal set forces the GP to discover cross-lead combinations.

8.2 Results

The baseline wins decisively: ECG₁ kurtosis (median AUC 0.930) outperforms the best GP feature (median AUC 0.824). This is the first experiment where expert-crafted features clearly beat the GP.

Table 9: MIT-BIH per-patient AUC (28 patients)

Method	Median AUC	Mean AUC	Head-to-head
GP (best per patient)	0.887	0.845	0 wins
Baseline (best per patient)	0.980	0.925	25 wins

8.3 What the GP Discovered

Despite the performance gap, the GP discovered genuinely novel features. The dominant pattern is $\text{rstd}(\text{signal} - \frac{d}{dt}|\text{ECG}_1|)$: rolling std of the signal minus the rate of change of the signal envelope. Physical interpretation: $\frac{d}{dt}|\text{ECG}_1|$ captures the slope profile of the heartbeat (steep QRS upstroke, flat ST segment, gentle T-wave). Subtracting this from the raw signal isolates high-frequency morphological detail whose local variability differs between normal beats and arrhythmias.

All top-10 GP features use both ECG leads (ECG_1 : 10/10, ECG_2 : 10/10), demonstrating genuine cross-lead feature discovery. No standard ECG feature combines the slope envelope of one lead with the raw signal of another through a rolling variability measure.

8.4 Why Baseline Wins: The Kurtosis Gap

ECG_1 kurtosis directly measures QRS peakedness: the exact morphological quantity that changes between normal and abnormal beats. Normal QRS complexes are sharp narrow peaks; PVCs and bundle branch blocks have wider, differently-shaped complexes.

Our operator set produces at most 2nd-order temporal statistics. Kurtosis requires 4th-order computation that cannot be efficiently composed within depth 4. This is a genuine operator vocabulary limitation, not a fitness function or search failure. This result identifies a clear boundary for the Core Operator Sufficiency Conjecture: morphological classification domains benefit from higher-order statistical operators not present in the current Ω_{core} .

9 The Sensitivity-Stability Paradox

An unexpected finding emerges from the IMS experiment: the features with the highest composite fitness scores are the worst early fault detectors.

Table 10: Composite rank vs detection time

Composite Rank	Fitness	Detection	% Life
#1 (best)	0.790	snap 960	97.6%
#2	0.783	snap 906	92.1%
#3	0.781	snap 960	97.6%
#41 (earliest)	0.653	snap 532	54.1%
#42	0.650	snap 532	54.1%

Proposition 1 (Sensitivity-Stability Trade-off). *Under progressive degradation, the following chain holds:*

$$C(f) \uparrow \implies R(f) \uparrow \implies \text{sensitivity} \downarrow \implies D(f) \uparrow,$$

where $D(f)$ is the detection time. High reliability requires stable values under small perturbations;

stable features resist the subtle amplitude shifts that characterize early degradation; therefore detection occurs late.

A feature with $R = 0.99$ measures something so stable that even the onset of degradation does not perturb it. A feature with $R = 0.40$ is sensitive to within-trial variation, and that sensitivity extends to between-state variation (healthy vs. degraded).

Practical implications:

- *Anomaly detection (is it faulty?)*: Prefer high-reliability features for clear separation once degradation is advanced.
- *Early warning (is degradation beginning?)*: Prefer low-reliability features, sensitive to subtle changes at the cost of higher baseline variability.
- *Optimal monitoring*: Use both: sensitive features for early alerting, stable features for confirmation.

10 Related Work

GP for feature engineering. GP has been applied to feature construction in classification [5] and regression [6]. Most approaches use labeled data. Our work is distinguished by the fully unsupervised fitness function and typed expression grammar.

Unsupervised fault detection. Autoencoders [7], one-class SVMs [8], and isolation forests [9] learn healthy-state models but do not produce interpretable features. Our GP produces symbolic expressions with clear physical interpretations.

Bearing diagnostics. Deep learning approaches [10] achieve high accuracy but require labeled fault data and produce black-box models. Our approach requires no fault labels and produces transparent features.

Turbofan prognostics. Deep learning approaches [15] achieve strong RUL predictions but require labeled run-to-failure sequences. Our approach discovers early detection features from healthy data alone.

ECG analysis. Modern approaches use deep CNNs [16] trained on beat labels. Our unsupervised approach achieves 0.887 AUC without any beat labels, discovering novel cross-lead features in the process.

Split-half reliability. Originated in psychometrics [11]. To our knowledge, this is the first application of split-half reliability as an evolutionary fitness component for feature discovery.

11 Discussion

Generality. The framework requires three domain-specific inputs: a type system, terminal definitions, and operator set. Everything else is domain-agnostic. We demonstrated this across five physical domains with only terminal and type changes. The core operators ($\frac{d}{dt}$, rstd, rmean, $|\cdot|$, neg, +, −, $\times$, $\div$) remain unchanged across all domains.

Where the GP wins. On both run-to-failure datasets, GP-discovered features detect earlier than expert baselines: 19.2 hours on IMS bearings, 2.2% of engine life on C-MAPSS turbofans. On

CWRU and EngineFaultDB, the GP ties expert baselines at $AUC = 1.000$. Across 5/6 real-world datasets, GP matches or beats hand-crafted features using zero fault labels.

Where the GP loses. On MIT-BIH ECG, expert kurtosis features (0.930 AUC) outperform GP features (0.824 AUC). The gap traces to a specific operator vocabulary limitation: the current operator set produces at most 2nd-order temporal statistics, while kurtosis (4th-order) directly captures the morphological changes that characterize arrhythmias. This is an honest boundary, not a framework failure: the GP still achieves 0.887 AUC and discovers novel cross-lead features.

Limitations. (1) Split-half reliability is lower on short, stochastic signals (CWRU: max $R = 0.52$) than on long, deterministic ones (pendulum: max $R = 0.90$). (2) The operator set lacks higher-order statistics, limiting performance on morphological classification tasks. (3) The sensitivity-stability paradox means the fitness function cannot simultaneously optimize for both detection and early warning. (4) Frequency-domain features and long-range temporal dependencies remain outside the current scope.

Future work. The immediate next step is application to automotive OBD-II data, where the type system would include rotational speed, pressure, temperature, and vehicle-specific quantities. Extending the operator set with kurtosis and skewness operators would close the gap identified in the ECG experiment.

12 Conclusion

We presented a typed GP framework with reliability-aware fitness for unsupervised diagnostic feature discovery in time series data. Validated across six real-world datasets and four physical domains, the framework:

1. Matches expert baselines on CWRU bearings and EngineFaultDB automotive diagnostics ($AUC = 1.000$) using zero fault labels.
2. Detects degradation earlier than hand-crafted baselines on both run-to-failure datasets: 19.2 hours on IMS bearings, 2.2% of engine life on NASA C-MAPSS turbofans.
3. Independently rediscovers known diagnostic quantities (instantaneous power, vibration jerk, engine load composites, coolant bleed flow health indices) from healthy data alone.
4. Discovers novel features in every domain: cross-bearing differentials (IMS), $TPS \times RPM$ load composites (engine), bleed flow indices (turbofan), and cross-lead envelope dynamics (ECG).
5. Reveals a sensitivity-stability paradox with implications for how prognostic monitoring systems should be designed.
6. Identifies operator vocabulary bounds: higher-order statistics (kurtosis) would extend the framework to morphological classification domains such as ECG.

The framework is domain-agnostic: given a type system and terminal definitions, it discovers diagnostic features for any time series monitoring application. The same core operators produced top-performing features across pendulum dynamics, bearing vibration, engine diagnostics, turbofan prognostics, and cardiac electrophysiology.

Acknowledgments

The author thanks Nyasha Praise Mapetere for invaluable discussions throughout this research and for her collaboration on the OBD-II application of this framework as part of our Design and Make project team. Thanks to Takudzwa Kelvin Mukaro for contributing computational resources, research assistance, and his collaboration as part of the Design and Make project team. Special gratitude to Dr. Chimwanda for guidance on the statistical methods underpinning this work, and for the encouragement and mentorship that shaped the direction of this research.

References

- [1] R. B. Randall, *Vibration-based Condition Monitoring*, Wiley, 2011.
- [2] J. R. Koza, *Genetic Programming: On the Programming of Computers by Means of Natural Selection*, MIT Press, 1992.
- [3] Case Western Reserve University Bearing Data Center, engineering.case.edu/bearingdatacenter.
- [4] J. Lee, H. Qiu, G. Yu, J. Lin, and Rexnord Technical Services, “Bearing Data Set,” NASA Prognostics Data Repository, 2007.
- [5] K. Neshatian, M. Zhang, P. Andreae, “A filter approach to multiple feature construction for symbolic learning classifiers,” *IEEE Trans. Evol. Comput.*, 16(5):645–661, 2012.
- [6] I. Arnaldo, U.-M. O’Reilly, K. Veeramachaneni, “Building predictive models via feature synthesis,” *Proc. GECCO*, 2015.
- [7] M. Sakurada, T. Yairi, “Anomaly detection using autoencoders with nonlinear dimensionality reduction,” *Proc. MLSDA Workshop*, 2014.
- [8] S. S. Khan, M. G. Madden, “One-class classification: taxonomy of study and review of techniques,” *Knowledge Eng. Review*, 29(3):345–374, 2014.
- [9] F. T. Liu, K. M. Ting, Z.-H. Zhou, “Isolation-based anomaly detection,” *ACM Trans. Knowledge Discovery from Data*, 6(1), 2012.
- [10] W. Zhang et al., “A new deep learning model for fault diagnosis,” *Sensors*, 17(2):425, 2017.
- [11] W. Brown, “Some experimental results in the correlation of mental abilities,” *British J. Psychology*, 3(3):296–322, 1910.
- [12] J. Vergara et al., “EngineFaultDB: A Novel Dataset for Automotive Engine Fault Classification and Baseline Results,” *IEEE Access*, 2023.
- [13] A. Saxena et al., “Damage Propagation Modeling for Aircraft Engine Run-to-Failure Simulation,” *Proc. PHM Conference*, 2008.
- [14] G. B. Moody, R. G. Mark, “The impact of the MIT-BIH Arrhythmia Database,” *IEEE Eng. Med. Biol. Mag.*, 20(3):45–50, 2001.
- [15] X. Li et al., “Remaining useful life estimation in prognostics using deep convolution neural networks,” *Reliability Eng. & System Safety*, 172:1–11, 2018.

- [16] U. R. Acharya et al., “A deep convolutional neural network model to classify heartbeats,” *Computers in Biology and Medicine*, 89:389–396, 2017.