

Light

Light makes it right

Syllabus

- 3D scene
 - Object
 - Camera
 - Light
 - Rendering
 - Image
- Light
 - Light and color
 - Real world light sources
 - Light model
 - Physical light
 - Non-physical light
 - Shadow







Light is important because without light...

Light and color

- Color can not be fully described scientifically: is also result of vision system thus subjective
- **Color science:**
 - How brain processes visual stimuli into what is perceived as color
 - Use of color from artist point of view
 - Study of electromagnetic waves: nature of light
- **Color management**
 - Study of color for digital displays
- Before color we need to investigate **light**


Light frequency and color

- Light is electromagnetic wave (or particle) visible by eye
 - Visible spectrum: wavelength 400 – 700 nm
 - Different wavelengths (frequencies) are perceived as **color** - color is **perceptual (psychophysical)** phenomena rather than **physical** one.
 - White light is made of all visible colors – adding all colors from light spectrum gives white light (color additivity, e.g. display)




Light and eye

- Human visual system; back of eye (the retina) is covered with light sensitive receptors – photo-receptive cells:
 - Cone cells – responsible for trichromatic color vision
 - Three types sensitive to: red, green and blue light
 - Rod cells – sensitive to smaller amount of light but not reproducing colors



Additive and subtractive



- **Additive:**

- Main colors: **red, green, blue**
- New colors and white light is made by adding
- Usage: computer science, lighting technology – colors are created with light emission

- **Subtractive:**

- Main colors: **yellow, magenta and cyan** - white light is made by subtracting
- Usage: art, painting, printing – color from canvas is not a result of light emitted from canvas, but light reflected from canvas
 - When white light hits canvas, what is not absorbed is reflected




<https://carsonparkdesign.com/what-makes-white-on-the-screen/>



<https://www.greenleafblueberry.com/blogs/news/modern-primary-colors>

Color brightness


- 555 to 560 nm (green towards yellow) are perceived by the human eye as being the brightest
 - Blue color: the dimmest
 - Green color: the brightest
- How bright color appear to hum eye: **luminosity function**
 - Average sensitivity of human eye to different wavelengths for well lit conditions - photopic (cone rods).
- Brightness or lightness is present in **HSV** color model
- **Photometry:** science of measuring light taking in account human visual system
 - CIE photopic spectral luminous curve



Luminosity function for photopic – green - (well lit) and scotopic (low lit) – black.
https://en.wikipedia.org/wiki/Luminous_efficiency_function

Spectral power distribution

- Light is generally characterized by **spectral power distribution (SPD)**
 - range and intensity of colors it produces at each wavelength in the visible spectrum
- Sun is reference for natural light
 - Standard: **daylight illuminant - D65** by International Commission on Illumination (midday sun Western/Northern Europe)
- **Color rendering index**
 - Ability of light source to reproduce color of object seen under D65, standard by CIE (Commission Internationale de l'Eclairage)
- White color is composed of all colors in equal amount: constant SPD
 - Doesn't exist in real world: CIE; E illuminant




Perceive light as yellow since eye is less sensitive to red

https://en.wikipedia.org/wiki/Incandescent_light_bulb




<https://commons.wikimedia.org/wiki/File:Sun-in-the-sky.jpg>



http://www.openphotographicsociety.org/b_photography/colour-light-and-optics/colour/2_03-spectral-power-distribution Sun and Sky - Approximately 6,000K


Spectral reflectance curve

- SPD is also used for light reflected from objects: **spectral reflectance curve**
- **Important:** PSD for of light from light sources vs reflected light from objects
 - SPD of light source defines color and intensity
 - SPD of reflected light represents fraction of the light reflected by the surface of the object over the amount of white light illuminating the object.



Color temperature

- Object which is heated to certain temperature emits light
- Color of emitted light depends on temperature
- Black body radiation




https://www.inlineelectric.com/color_temperature

Color space and PSD

- Light from light source or reflected from the object is defined with PSD
- Human visual system can not directly perceive PSDs
- PSDs must be transformed in color models or color spaces suited for trichromatic vision
 - Note PSDs is transformed in color **hue** and color **brightness** values which we can perceive
- CIE XYZ is foundation for all color models
 - **RGB** model is most important for computer graphics

Colorspace and gamut


- **Colorspace**
 - Model to represent colors perceived by human visual system
- **Gamut**
 - Range of possible colors that can be represented by particular colorspace



Gamut of XYZ color space:
https://en.wikipedia.org/wiki/CIE_1931_color_space

XYZ colorspace


- Assumption: any color (in an additive color model) can be represented by a combination of red, green and blue light
 - Based on cone cells – trichromatic system
- Three curves: **CIE standard observer color matching functions**
 - Y curve is close to luminosity function → expressing the brightness
- Using color matching curve, PSD can be converted to X, Y and Z values
- **Gamut of XYZ color space** - gamut of human vision
 - Full range of possible colors visible by human visual system
- **XYZ colorspace:**
 - System capable representing all colors human visual system can percieve
 - Gold standard for color storage
 - **XYZ have to be transformed to RGB space to be visualized**




Gamut of XYZ color space:
https://en.wikipedia.org/wiki/CIE_1931_color_space

From PSD of lightsource to XYZ

- XYZ colorspace is obtained from PSD of light source using color matching curves
 - spectrum and the color-matching functions are discrete in a computer




PSD of light source



https://en.wikipedia.org/wiki/CIE_1931_color_space

Color matching curves




$$X = v_1$$

$$Y = v_2$$


$$Z = v_3$$

From PSD of reflected light to XYZ


- Light reflected from object is represented as spectral reflectance curve
 - Therefore it must be multiplied by white light which caused the reflection and the standard is D65.




**Spectral
Reflectance
Curves**



D65 Illuminant



**CIE Color
Matching Functions**




X = 62.04
Y = 69.72
Z = 7.34


**Tristimulus
Values**

RGB colorspace

- Similar as human visual system: represent colors as simple sum of primary colors (R, G, B).
- Visualized as cube where R, G and B are placed on axis.
- Limited gamut compared to XYZ colorspace




https://www.researchgate.net/publication/228719004_Human-entered_content-based_image_retrieval



<https://www.scratchapixel.com/lessons/digital-imaging/colors/color-space>

RGB colorspace

- Most **computer screens technology** is based on system similar to RGB color model.
 - Summing all RGB values gives white color
- RGB and XYZ are **linear** colorspace
- For rendering, RGB color space is often used
 - PSD is used in **spectral rendering** - more correct rendering, but expensive: computing XYZ from PSD for calculation takes time




Close-up of LCD screen:

<https://jakubmarian.com/the-illusion-of-rgb-screens/>

XYZ to RGB

- XYZ and RGB colorspaces are defined by three coordinates
 - They define a 3D space, which can be plotted (cube for RGB)
- Conversion of color from XYZ to RGB can be seen as moving a point from one 3D space to another.
 - Linear transformation performed using 3x3 matrix
 - Color is not changed, only expressed in different colorspace



XYZ


$$\begin{bmatrix} X \\ Y \\ Z \end{bmatrix} = \begin{bmatrix} 0.4124564 & 0.3575761 & 0.1804375 \\ 0.2126729 & 0.7151522 & 0.0721750 \\ 0.0193339 & 0.1191920 & 0.9503041 \end{bmatrix} \begin{bmatrix} R \\ G \\ B \end{bmatrix}$$

http://www.brucelindbloom.com/index.html?Eqn_RGB_XYZ_Matrix.html

<http://www.russellcottrell.com/photo/matrixCalculator.htm>


<https://www.oceanopticsbook.info/view/photometry-and-visibility/from-xyz-to-rgb>

<https://terathon.com/blog/rgb-xyz-conversion-matrix-accuracy/>



Colorspaces and transformations

- RGB and XYZ are linear colorspaces and can be transformed using 3x3 matrix
- There are other colorspaces such as sRGB, HSV, HSL are non-linear
- 3x3 matrices can not be used to convert between non-linear and linear colorspace (and vice versa)
 - Any non-linear colorspace must be converted to linear colorspace before 3x3 matrix transformation.




<https://en.wikipedia.org/wiki/SRGB>




Note: ACES colorspace

- Academy Color Encoding Specification (ACES) is developed by Academy of Motion Picture Arts & Science technology committee
- Designed to cover the full gamut
- Goal: images should always look the same regardless of used camera and display device.
- Images in ACES color space can't be directly displayed to the screen. Conversion steps:
 - Reference rendering transform
 - Output device transform: depends on display device (computer monitor, digital projector, etc.)
- Becoming defacto standard for professional production



Note: Macbeth ColorChecker

- Colors have spectral reflectances mimicking materials which are often photographed.
 - Human skin, sky, flowers, etc.
- Goal: consistent color appearance under varying lighting conditions
 - Reference for tweaking exposition and color settings of camera





Light characterization


- Quantifying light:
 - **Radiometry** – measurement of radiation, physical transmission of light
 - **Photometry** – measurement related to human visual system
 - Summary measures: computed from radiometric quantities.
 - **Colorimetry** – Color perception

Radiometric quantities

- Measuring light energy, power and power over area and/or direction.
- **Radiant flux** – flow of radiant **energy over time** (W)
- **Irradiance** – density of radiant **flux over area** (W/m²)
- **Solid angle**
 - 3D extension of the concept of plane angle: continuous set of directions in 3D space measured in steradians (sr)
 - area of the intersection patch on an enclosing sphere with radius 1
 - 4π steradians close the whole area of unit sphere
- **Radiant intensity** – flux density with respect to **solid angle** (W / sr)




https://spie.org/publications/fg11_p02_solid_angle?SSO=1



Energy over area:
https://www.pbr-book.org/3ed-2018/Color_and_Radiometry/Radiometry

Radiance


- **Radiance** – electromagnetic radiation in single ray ($\text{W} / (\text{m}^2 \text{ sr})$)
 - Density of radiant flux over area and solid angle.
 - This area is measured in a plane perpendicular to ray, if surface has orientation then cosine correction factor must be used
- **Radiance is what cameras measure** – prime importance for rendering
- The purpose of shading is to calculate radiance along a given ray from a shaded point on object to camera
 - Radiance is physically based value which is simplified with **color and intensity**
- **Radiance distribution** describes light traveling anywhere in space
 - Rendering can be seen as evaluating radiance distribution for each eye-camera direction*
- Radiance is not affected by distance
 - Surface is more distant and covers less area.



* Image-based rendering uses this concept, namely light field technique.

Radiometric quantities and PSD


- Most light waves contain mixture of many different wavelengths – **polychromatic** (light with one wavelength is called **monochromatic**).
 - Visualized using spectral power distribution (SPD) – plot showing how light's energy is distributed across wavelengths.
- All radiometric quantities have spectral distributions
 - Using full SPDs for rendering is complex*, often radiometric quantities are represented as RGB triplets.



* Area of research dealing with spectral rendering exists and it is highly active. <https://www.fxguide.com/fxfeatured/manuka-weta-digital-new-renderer/>

Photometry

- Photometry is field like radiometry but it takes visual system and perception in account.
- Each radiometric quantity has equivalent photometric quantity
 - Radiant flux → Luminous flux (lumen - lm)
 - Irradiance → Illuminance (lux - lx)
 - Radiant intensity → Luminous intensity (candela - cd)
 - Radiance → Luminance (cd / m²)
- Radiometric quantities are converted to photometric by using **CIE photopic spectral luminous curve**.





Luminosity function for photopic – green - (well lit) and scotopic (low lit) – black.

https://en.wikipedia.org/wiki/Luminous_efficiency_function


Colorimetry

- Colorimetry: relationship between PSD and perception of color
- CIE standard observer color matching functions
 - PSD → XYZ colorspace
- Define colorspaces and their gamut for visualization
- RGB color spaces are most interesting for rendering:
 - SRGB (linear colorspace with sRGB primaries and white point)



Rendering with RGB

- RGB is perceptual rather than physical quantity
- RGB in Physically based rendering is a category error
 - Correct would be to use spectral quantities for rendering and RGB conversion in the end for visualization
- For interactive and appearance-based applications (e.g., film) RGB rendering is acceptable.
 - Object surface reflection is defined using RGB rather than spectral reflectance curve
 - Light sources are described with RGB rather than PSD
- For predictive simulations rendering spectral quantities must be used.



Tristimulus vs spectral rendering:
<https://hal.inria.fr/hal-03331619/document>

Recap

- Light has physical but also perceptual properties.
- Discussion on radiometry, photometry and colorimetry was needed to understand light and its perception:
 - Color (hue)
 - Intensity
- Light in computer graphics is represented using:
 - RGB values in $[0, 1]$
 - Intensity, multiplier of RGB values


Real world light and sources of light

Light description

- Light can be described both on:
 - Microscopic scale: wave optics
 - Macroscopic scale: **geometric optics**

Light: microscopic level

- Light is quantized – it comes in individual and indivisible packets called **photons**
- At same time light is **wave-like**
- Some effects of light-matter interaction can be only explained (and thus modeled*) using **wave optics**:
 - Interference
 - polarization
 - Diffraction
 - Iridescence
 - Pleochroism and birefringent
 - Etc.
- Also, knowing microscopic background often helps in getting intuition for some shading and light transport methods**



Learn of Birefringence effect when a plastic box between two polarizers:
[wikipedia.org/wiki/Polarization_\(waves\)](https://en.wikipedia.org/wiki/Polarization_(waves))

White light interference in a soap bubble – iridescence phenomena (thin-film interference) -
https://en.wikipedia.org/wiki/Wave_interference


* It is important to note that complexity of model level depends on application. Often, in computer graphics wave effects can be “faked” to achieve desired appearance:

<https://developer.nvidia.com/gpugems/gpugems/part-i-natural-effects/chapter-8-simulating-diffraction>. On the other hand, physically based methods for achieving wave-effects is actively researched area:
https://sites.cs.ucsb.edu/~lingqi/publications/202203_practical_plt_paper_lowres.pdf

** For example photon mapping: http://web.cs.wpi.edu/~emmanuel/courses/cs563/write_ups/zackw/photon_mapping/PhotonMapping.html


Light: macroscopic level

- Light in computer graphics is often modeled at macroscopic level – **geometric optics**.
 - Assumption: features with which light interacts are relative to light wavelength (or larger)
 - Light is described with rays.
 - Microscopic light behavior is described with **index of refraction (IOR)**
- In medium of constant IOR, light energy travels in a straight line
 - It only can get **absorbed**
- Light passing from one to another medium with different IOR changes speed
 - This is described with light **scattering**
 - Interface between media is represented by **surface**
- Scattering of light on surface is described with reflection and refraction described with Snell law (light direction) and Fresnel equations (light energy).




Sources of light

- In a real world, **every** light source has a physical shape and size, e.g., Sun or very hot objects.
- Motion of atomic particles that hold electrical charge causes objects to emit electromagnetic radiation over a range of wavelengths (Maxwell's equations)
- Different way how energy is converted into electromagnetic radiation:
 - Incandescent (tungsten) lamps
 - Halogen lamps
 - Gas-discharge lamps
 - LED lights




<https://education.nationalgeographic.org/resource/sun>

Sources of light




- **Incandescent (tungsten) lamps:**
 - flow of electricity through tungsten filament heats it up and causes it to emit electromagnetic radiation with distribution of wavelengths depending on filament temperature.
 - A frosted glass enclosure is often present to absorb some of the wavelengths.



- **Halogen lamps:** tungsten filament is enclosed in halogen gas. Part of the filament in an incandescent light evaporates when it's heated. Halogen causes evaporated tungsten to return to filament

Sources of light



Helium: https://en.wikipedia.org/wiki/Gas-discharge_lamp



LED lights:
https://en.wikipedia.org/wiki/Light-emitting_diode

- **Gas-discharge lamps:** passing electrical current through hydrogen, neon, argon, or vaporized metal gas, causes light to be emitted at specific wavelengths that depend on the particular atom in the gas.
- Fluorescent coating on the bulb's interior is often used to transform the emitted frequencies to a wider range.

- **LED lights** are based on electroluminescence: they use materials that emit photons due to electrical current passing through them.

Light model

Light in big picture

- Incoming light on surface is element of reflectance equation
 - TODO
- Integrating over hemisphere is used in global illumination
 - Surfaces are also reflecting light onto surface we are shading
 - Phisical lights have area which has to be sampled
- Simplification is to sum over lights in the scene if only non-physical lights are used.
- RTR 9.4

Foundations of light modeling

- Reminder: when we discussed the material of 3D models, we mentioned **shading process** which uses material information and light information to calculate appearance of the object surface.
- **Light is emitted from a light source**, bounces around the scene, interacting with object and some (very small!) portion enters eye or camera enabling us to see objects in the scene
 - Interaction with objects is described with material model, that is **scattering model**.
 - Without light in a 3D scene (or real world) we wouldn't see anything. Resulting image would be completely black.
- If multiple light sources are present, they add up linearly
- Light sources define position and distribution of light
 - Light sources have **size, shape, color** and **intensity**.

Light models

- Discussion before showed that lights have shape, size and certain light distribution.
- Representation and modeling of light physically: with shape and size is very computationally expensive. Such lights are called **geometric area light or physical lights***
 - Interaction of physical lights with the scene can not be computed in closed form. Advanced, approximation-based methods such as Monte Carlo integration must be used
- Simplification are lights with no physical size, thus called **delta or non-physical lights**
 - enable us to control light fall-off with distance, which objects are illuminated, which objects cast shadows and so on.

* When we discussed surface material we mentioned scattering and absorption. Also, materials are able of emission. Therefore, physical lights have 3D shape and material which is emissive. Emissive material is modeled as black body meaning that it absorbs all light falling on it.

Light and shading

- Light information is used in shading: rendering step in which color of the object is calculated:
 - $\text{Shaded_color} = \text{color_unlit}(n,v) + \sum(\text{color_light} * \text{color_lit}(l,n,v))$
- For simple shading models, only direction of light is enough to compute the color
 - <example>
- Direct illumination considers only light coming from light sources
 - Parameters: distance from light source, shadows, facing of surface towards light source
- Advanced rendering takes in account direct and indirect light
 - Surfaces which reflect light
 - TODO

Light and shading

- Effect of light on surface can be visualized as rays with the density of rays hitting the surface corresponding to the light intensity.
- Density of light rays (their spacing) is proportional to cosine of angle between \mathbf{l} and \mathbf{n}
 - Ray density is proportional to dot product when positive, otherwise light comes from behind surface
 - $\text{Shaded_color} = \text{color_unlit}(\mathbf{n}, \mathbf{v}) + \sum((\text{dot}(\mathbf{l}, \mathbf{m})) \text{color_light} * \text{color_lit}(\mathbf{l}, \mathbf{n}, \mathbf{v}))^*$
 - <image>

* $\text{color_lit}()$ is actually BRDF. If it is a constant color, then this corresponds to Lambertian shading – surface is perfectly matte.

Recap: Light parameters

- Color
- Intensity
- Direction
- Position
- Shape
- Size

Light intensity and color

- For each light source (physical or non-physical) next to shape, size, position and direction we need to define:
 - Intensity – float value in $[0, \infty]$
 - Color – RGB value in $[0, 1]$

Physical lights

Physical lights

- Geometry with emissive material: shape and size
- TODO:
 - Examples
 - Hint that it will be discussed later

Non-physical lights

Non-Physical lights

- Directional (distant) lights
- Point (spherical, omnidirectional) lights
- For physically-based rendering, non-physical light should be avoided
 - Example: size of reflection of object by glossy or mirror-like surface depends on its size and distance to reflective surface. If light source has no shape nor size how reflection should look like? Hack: size parameter which is only used during shading.

Directional lights

- Directional lights are also called distance because they are considered so far from the objects in a 3D scene that they can be represented by parallel rays. As such, we only care of the direction of those parallel rays.
 - Best example of directional light is Sun light on Earth. Sun has spherical shape, but it is so far and Earth is so small compared to it that light rays reaching Earth can be considered parallel (small cone of directions – solid angle).
 - For scenes that cover small area of Earth's surface, Sun light can be assumed parallel.
 - General note: this is another example showing that it is always important to assess the application of Computer graphics and see what is really important to model.

<IMAGE: EXAMPLE OF DISTANT LIGHT>

Directional lights

- Direction light is simplest model of light source
 - No location, only direction
 - Direction (\mathbf{l}), color (\mathbf{c}) and intensity (I) are constant over 3D scene
 - $\text{light_color} = \text{light_color0}$
 - Intensity may be attenuated by shadowing

<IMAGE: EXAMPLE OF DIRECTIONAL LIGHT VECTORS IN THE SCENE>

Point lights

- Most common light sources in nature and around us are spherical (e.g., light bulbs or candle flame) or can be approximated as a collection of spherical light sources.
- As opposed to directional lights:
 - Point light **position** is important parameter, it is considered **infinitesimally small in size thus no shape**
 - **Light is emitted in all directions** (omnidirectional, isotropic) therefore, no “direction” parameter
- Point light position determines:
 - **Direction of incoming light ray** for each surface position for each object in the scene
 - **Distance** to the each surface position for each object in the scene – **light falloff**
 - **example**

Point lights: light direction and falloff

- Point lights emit radially
- **Direction and distance of point light** to point on the surface is obtained by tracing ray between these two points.
- Distance of point light to each point of surface of each object in the scene defined how much is that point illuminated – **intensity of light varies as a function of distance**.
- Energy emitted from point light is distributed across the space as sphere. As the sphere keeps expanding in the space, energy becomes spread across much larger area → more distant objects in the scene receive less light – light falloff. <INVERSE SQUARE LAW FORMULA>

<IMAGE OF POINT LIGHT, ILLUMINATED OBJECTS, SOLID ANGLE>

Inverse square light attenuation

- $\text{color_light}(r) = \text{color_light0} * (r_0 / r)^2$
 - Note the light falloff function can be any other function of distance; for stylized appearance different functions may be more interesting.
- Problems:
 - Small distances: as r goes to 0, light intensity increases to infinity
 - $\text{color_light}(r) = \text{color_light0} * (r_0 / r + \text{epsilon})^2$
 - Large distance: for efficient rendering, it is desired to light reach 0 at some point.
Otherwise, light calculation should be done no matter how far the camera is from the light

Point lights: directional light falloff

- Illumination intensity from real-world also **varies by direction**
 - Generally, different directional light falloffs: $\text{color_light} = \text{color_light}_0 * f_{\text{dist}}(\mathbf{r}) * f_{\text{dir}}(\mathbf{r})$
- Different choices of directional light falloff functions produce various light sources:
 - **Spotlights** - emit light in a cone of directions from their position

Spotlights

- Projects light in circular cone.
 - <image>
- Parameters:
 - Angle of cone
 - Angle of umbra
 - Angle of penumbra
 - <image>
- Directional falloff function
 - example

Other directional light falloff functions

- Different types of directional variation of light intensity exist
 - **IES profiles:** tabulated patterns measured from the real world
 - example
 - **Textured lights**
 - example
 - **Goniophotometric diagram** describes the angular distribution of luminance from a point light source; it is widely used in illumination engineering to characterize lights
 - example

Practical tip: modeling with lights

- Non-physical lights can be placed to simulate global illumination
 - TODO
- Placement of light greatly determines object appearance
 - TODO

Shadows

Light and shadow

- Light falling on object causes object to cast shadow – blocking light to fall on another surface

<IMAGE WITH AND WITHOUT SHADOW>

- Shadows are important for:
 - Understanding relation of objects to one another
 - Realistic image synthesis
- Simulating shadow depends on rendering algorithm (more specifically, algorithm for solving the visibility problem)
 - As we will see, in rasterization-based rendering shadows will not be inherently present. Advanced, multi-pass rendering is required to obtain visibility of objects looking from the position of light. This way, shadow map is generated and used for rendering.
 - In ray-tracing based rendering, shadows are inherently present due to way incoming light on surface is calculated

Intuition: calculating light and shadow

- How to know if point of surface will be under shadow or not?
- Generate ray from that point in light direction and if no intersections are found, shadow won't be present.
 - For point lights, we need to take in the account their maximum influence!
 - Shadow-acne problem → Later!

Sharp vs smooth shadows

- Size of light determines smoothness of shadows

Light and Shadow: Tips and Tricks

- Non-physical light sources as well as shadows they cause can be simulated efficiently
- For real-time rendering, full physically based simulation of light transport might not be feasible
- When creating 3D scene, (environment) artists understand the how the scene should be illuminated given some main sources of light. Using this knowledge they place non-physical light to fake actual light flow through the scene
- <https://80.lv/articles/dishonored-interiors-lighting-props/>

To remember

Literature

- <https://github.com/lorentzo/IntroductionToComputerGraphics/wiki/Foundations-of-3D-scene-modeling>