

Umeå University
Department of Computing Science

Parallel Programming 7.5 p
5DV152

Exercises, Chapter/Topic 3

Submitted 2017-02-16
Author: Lorenz Gerber (dv15lgr@cs.umu.se lozger03@student.umu.se)
Instructor: Lars Karlsson / Mikael Ränner

Contents

1	Introduction	1
2	3.2 - Generalization of algorithm for trapezoidal rule	1
3	3.6 - Array distributions	1
4	3.8 - Tree-structured algorithms for scatter and gather	1
5	3.9 - Vector scaling and dot product	1
6	3.11 - Prefix sums	1
7	3.13 - Generalization of vector scaling and dot product	6
8	3.16 - Diagram for a butterfly implementation of allgather	6
9	3.18 - Derived data types	6
10	3.20 - Pack and unpack	7
11	3.21 - Matrix-vector multiplication	7
	11.1 Speed comparison	7
	11.2 Observed variabilities	7
	11.3 Cluster around Minmum, mean, median	7
12	3.22 - Timing the trapezoidal rule	7
13	3.27 - Speedup and efficienci of odd-even sort	7
	References	7
A	C Source Code for Exercise 3.2	10
B	C Source Code for Exercise 3.9	11
C	C Source Code for Exercise 3.11	13
D	C Source Code for Exercise 3.13	14
E	C Source code for Exercise 3.18	17
F	C Source Code for Exercise 3.20	19

1 Introduction

This report is part of the mandatory coursework. It describes the solutions for several chosen exercises from the course book [3].

2 3.2 - Generalization of algorithm for trapezoidal rule

Two functions to adapt the *trapezoidal rule* for `calc_local_a` and `calc_local_b` were written and tested with the source code from the book (*mpi_trap.c*). The source can be found in appendix A.

3 3.6 - Array distributions

Block distribution

Block distribution can be obtained by $b = \lfloor i \div p \rfloor$ where b is the block number, i the index of n and p is the number of processes. This solution is however not fair. An improved, fair expression can be devised using ternary operators:

$$i < n \bmod p \times \lceil n \div p \rceil ? \lfloor i \div \lceil n \div p \rceil \rfloor : n \bmod p + \lfloor (i - n \bmod p \times \lceil n \div p \rceil) \div \lceil n \bmod p \rceil \rfloor$$

Cyclic distribution

Cyclic distribution is described by $b = i \bmod p$ with b as block number i as index of n and p as number of processes.

Block cyclic distribution

Block cyclic distribution can be expressed as $b = \lfloor i \div l \rfloor \bmod p$ where b is block index, i index of n , l block length and p number of processes.

4 3.8 - Tree-structured algorithms for scatter and gather

The diagram for tree-structured scatter is shown in figure 1. The arrows show the communication events which for the present case of `comm_sz = 8` and `n = 16` is 7. This is also true for the tree-structured gather shown in figure 2.

5 3.9 - Vector scaling and dot product

The Source code for the vector scaling and dot product MPI program can be found in appendix B.

6 3.11 - Prefix sums

Serial Algorithm

Assume vector x of length n and prefix sums vector y to be calculated.

```
y_0 = x_0
for (i = 1, i < n, i++)
```




Figure 1: This graph shows a tree based implementation of scatter for $\text{comm_sz} = 8$ and $n = 16$. It has 7 communication events.




Figure 2: This graph shows a tree based implementation of gather for $comm_sz = 8$ and $n = 16$. It has 7 communication events.

$$y_i = y_{i-1} + n_i$$

Parallel Algorithm

After Blelloch [1], parallel prefix-sum, or ‘Sum Scan Algorithm’ can be calculated in two steps, the ‘Up-sweep’ (Reduce) and ‘Down-sweep’. Below, pseudo code from Valdez [4] where x is the input data, n the size of the input and d the number of processeors. If $n \neq 2^k$, then n has to be extended with *zero*’s. The ‘Up-Sweep’:

```
for d = 0 to log2(n) - 1 do
  for all k = 0 to n - 1 by 2^(d+1) in parallel do
    x[k + 2^(d+1) - 1] = x[k + 2^d - 1] + x[k + 2^(d+1) - 1]
```

The ‘Down-Sweep’:

```
x[n - 1] = 0
for d = log2(n) - 1 down to 0 do
  for all k = 0 to n - 1 by 2^(d+1) in parallel do
    t = x[k + 2^d - 1]
    x[k + 2^d - 1] = x[k + 2^(d+1) - 1]
    x[k + 2^(d+1) - 1] = t + x[k + 2^(d+1) - 1]
```

Minimum Communication


An algorithm that uses for the prefix-sum of length $n = 2^k$ only k communication steps can be derived from the communication model in a hypercube as shown in figure 3.

Below follows pseudo code for parallel hypercube prefix sum (from [2]):


```
procedure PREFIX_SUMS_HCUBE(my_id, my number, d, result)
begin
  result := my_number;
  msg := result;
  for i := 0 to d - 1 do
    partner := my_id XOR 2i;
    send msg to partner;
    receive number from partner;
    msg := msg + number;
    if (partner < my_id) then result := result + number;
  endfor;
end PREFIX_SUMS_HCUBE
```

MPI Program using MPI_Scan


A minimal working example using MPI_Scan was implemented. The source code can be found in appendix C. An array of random numbers are generated on each proces. Then the prefix sums are collected onto process zero. The prefix sums of the arrays are collected index wise. Arrays of length n and p processes will result in a $n \times p$ prefix sum array.




(a) Initial distribution of values



(b) Distribution of sums before second step



(c) Distribution of sums before third step



(d) Final distribution of prefix sums

Figure 3: This figure shows the calculation of prefix sums with minimal communication phases. The figure is take from [2, chap 4.3]




Figure 4: This figure shows a butterfly allgather implementation for 8 cores and a vector of length 16.

7 3.13 - Generalization of vector scaling and dot product

An MPI program for ‘Vector Scaling and Dot Product’ using ‘MPI_Scatterv’/‘MPI_Gatherv’ was written according to the specifications. The source code can be found in appendix D.

8 3.16 - Diagram for a butterfly implementation of allgather

Figure 4 shows an diagram for an *allgather* implementation using *butterfly* communication. The examples shows the communication steps for 8 processes and a data vector length of 16.

9 3.18 - Derived data types

Here `MPI_Type_vector` was used to implement a derived data type to represent a block cyclic data distribution. The current implementation assumes that the data is even divisible by `blocksize × processes`. This allows to use only one data type definition for the full length block cyclic structe of one process. The source code can be found in appendix ??

Table 1 Median runtimes for the Matrix-Vector Multiplication. The program was run on the HPC2N ‘abisko’ cluster. Processes were assigned to individual nodes.

comm_sz	Order of Matrix (milliseconds)				
	1024	2048	4096	8192	16384
1	0.01	0.02	0.03	0.07	0.14
2	0.01	0.02	0.02	0.04	0.08
4	0.01	0.02	0.02	0.03	0.04
8	0.02	0.02	0.02	0.02	0.03
16	0.03	0.03	0.03	0.03	0.05

10 3.20 - Pack and unpack

The MPI functions `MPI_Pack` and `MPI_Unpack` were used transfer complex datastructures. As example, a new *Get_input* function for the ‘trapezoidal sum’ program was written that transfers the data from process 0 to all processes. The source code of the modified *Get_input* function can be found in appendix ??.

11 3.21 - Matrix-vector multiplication

The ‘Matrix-vector multiplication’ program from the course book was run on the HPC2N *Abisko* cluster for benchmarking and comparison to the values in the course book. Herefore the source *mpi_mat_vect_time.c* provided from the coursebooks homepage was compiled with MPI-gcc compiler on the Abisko cluster. Problemsize and process number were chosen according to the example in the course book.

11.1 Speed comparison

The absolute run-times values differ significantly from the benchmarked system in the book, see [3, p. 123] and table 1. The benchmarking was run on the ‘abisko’ cluster with the setting to run one process per node. For such a small program, this was performance wise probably not the most optimal choice: It can be seen in table 1 that all runtimes for 16 processes are longer than those for respective problem size and fewer processes. Most likely, this is due to the higher communication overhead.

11.2 Observed variabilities

11.3 Cluster around Minmum, mean, median

plot data points and markers for min, mean, median

12 3.22 - Timing the trapezoidal rule

How to choose n, the number of trapezoids. How does minima time compares to median. speedups efficiencies is it scalable?

13 3.27 - Speedup and efficienci of odd-even sort

is it scalable? Strongly or weakly?




Figure 5: This figure shows boxplot of runtimes in relation to number of processes and problem size.

Table 2 Speedups

processes	number of keys				
	200	400	800	1600	3200
2	2.05	2.09	2.05	2.02	2.09
4	4.00	4.13	4.06	4.15	4.19
8	7.33	7.92	7.65	7.55	8.18
16	11.73	13.57	13.45	13.83	13.85

Table 3 Efficiencies

processes	number of keys				
	200	400	800	1600	3200
2	1.02	1.04	1.03	1.03	1.05
4	1.00	1.03	1.02	1.04	1.05
8	0.92	0.99	0.96	0.94	1.02
16	0.73	0.85	0.84	0.86	0.87




Figure 6: This figure shows the normalized ranges of runtimes to compare minima, maxima, median and mean values. Mean values are marked by a red square and median values by a blue circle

References

- [1] G.E. Blelloch. *Vector Models for Data-Parallel Computing*. MIT Press, Cambridge MA, USA, 1990.
- [2] A Grama, A Gupta, G Karypis, and V Kumar. *Introduction to Parallel Computing*. Pearson, Essex, England, 2003.
- [3] P.S. Pacheco. *An Introduction to Parallel Programming*. Morgan Kaufman, 2011.
- [4] Stackoverflow, parallel prefix sum - fastest implementation. <http://stackoverflow.com/questions/10053629/parallel-prefix-sum-fastest-implementation>, 2012. accessed: 2017-02-04.

A C Source Code for Exercise 3.2

```
double calc_local_a(int my_rank, double a, double b, int n, int comm_sz){
    double local_a = 0;
    double h = 0;
    int local_n = 0;
    int rest_n = 0;

    h = (b-a)/n;
    local_n = n/comm_sz;

    rest_n = n%comm_sz;

    if(my_rank < rest_n){
        local_a = a + my_rank*local_n*h + my_rank*h;
    } else {
        local_a = a + my_rank*local_n*h + rest_n*h;
        local_a += (my_rank-rest_n) * h;
    }

    return local_a;
}
```

```
double calc_local_b(int my_rank, double a, double b, int n, int comm_sz){
    double h;
    int local_n;

    h = (b-a)/n;
    local_n = n/comm_sz;

    if (my_rank == (comm_sz-1)){
        return a + my_rank+1*local_n*h;
    } else {
```

```

    return calc_local_a(my_rank+1, a, b, n, comm_sz);
}
}

```

B C Source Code for Exercise 3.9

```

#include <stdio.h>
#include <mpi.h>
#include <string.h>
#include <stdlib.h>
#include <time.h>

int main(int argc, char *argv[]) {
    int my_rank, comm_sz;
    int n, local_n, local_dotp_sum = 0, scalar, result_dot;
    int* local_vec1;
    int* local_vec2;
    int* vector1;
    int* vector2;

    /* Initializing */
    MPI_Init(NULL, NULL);
    MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
    MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);
    srand(time(NULL));

    /* Obtaining Data */
    if(my_rank==0 && argc > 1){

        if(strcmp(argv[1], "r") == 0){
            printf("using random data, vector length = %d\n", 100*comm_sz);
            n = 100*comm_sz;
            vector1 = (int *) malloc(100*comm_sz * sizeof(int));
            vector2 = (int *) malloc(100*comm_sz * sizeof(int));

            for(int i = 0; i < n;i++){
                vector1[i] = rand() % 1000;
                vector2[i] = rand() % 1000;
            }
            scalar = rand() % 1000;
        }

        } else if (my_rank==0){

            printf("enter vector length\n");

```

```

scanf("%d", &n);
printf("enter integer vector 1\n");

vector1 = (int *) malloc(n * sizeof(int));
vector2 = (int *) malloc(n * sizeof(int));

for(int i = 0; i < n; i++){
    scanf("%d", &vector1[i]);
}

printf("enter integer vector 2\n");

for(int i = 0; i < n; i++){
    scanf("%d", &vector2[i]);
}

printf("enter integer scalar\n");
scanf("%d", &scalar);
}

/* Distribute Data */
MPI_Bcast(&n, 1, MPI_INT, 0, MPI_COMM_WORLD);

local_n = n/comm_sz;
local_vec1 = (int*) malloc(local_n * sizeof(int));
local_vec2 = (int*) malloc(local_n * sizeof(int));

MPI_Bcast(&scalar, 1, MPI_INT, 0, MPI_COMM_WORLD);
MPI_Scatter(vector1, local_n, MPI_INT, local_vec1, local_n, MPI_INT, 0, MPI_COMM_WORLD)
MPI_Scatter(vector2, local_n, MPI_INT, local_vec2, local_n, MPI_INT, 0, MPI_COMM_WORLD)

/* Calculations */
/* Calculate Dot Product */
for(int i = 0; i < local_n; i++){
    local_vec2[i]*=local_vec1[i];
}

/* Calculate vector-scalar product */
for(int i = 0; i < local_n; i++){
    local_vec1[i]*=scalar;
}

/* Summing for dot product */
for(int i = 0; i < local_n; i++){
    local_dotp_sum += local_vec2[i];
}

/* Collect Data */

```

```

MPI_Gather(local_vec1, local_n, MPI_INT, vector1, local_n, MPI_INT, 0, MPI_COMM_WORLD);
MPI_Reduce(&local_dotp_sum, &result_dot, 1, MPI_INT, MPI_SUM, 0, MPI_COMM_WORLD);

/* Results */
if(my_rank == 0){
    printf("dot product = %d\n", result_dot);

    printf("vector-scalar product = ");
    for(int i = 0; i < n; i++){
        printf("%d ", vector1[i]);
    }
    printf("\n");
}

/* Clean up */
if(my_rank==0){
    free(vector1);
    free(vector2);
}

free(local_vec1);
free(local_vec2);

MPI_Finalize();

return 0;
}

```

C C Source Code for Exercise 3.11

```

#include <stdio.h>
#include <stdlib.h>
#include <mpi.h>
#include <time.h>

int main(void){

    int my_rank, comm_sz;
    int* initial_vector;
    int* prefix_sums;

    MPI_Init(NULL, NULL);
    MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
    MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);
    srand(time(NULL));

```

```

initial_vector = (int *) malloc(10*sizeof(int));
prefix_sums = (int *) calloc(10, sizeof(int));

for(int i = 0; i < 10;i++){
    initial_vector[i] = rand() % 1000;
}

MPI_Scan(initial_vector, prefix_sums, 10,MPI_INT, MPI_SUM, MPI_COMM_WORLD);

for(int i = 0; i< comm_sz;i++){
    if (i == my_rank){
        for(int j = 0;j < 10;j++){
            printf("%d ", prefix_sums[j]);
        }
    }
}
printf("\n");

MPI_Finalize();
return 0;
}

```

D C Source Code for Exercise 3.13

```

#include <stdio.h>
#include <mpi.h>
#include <string.h>
#include <stdlib.h>
#include <time.h>

int main(int argc, char *argv[]) {
    int my_rank, comm_sz;
    int n, local_n, local_dotp_sum = 0, scalar, result_dot;
    int* sendcounts;
    int* displs;
    int* local_vec1;
    int* local_vec2;
    int* vector1;
    int* vector2;

    /* Initializing */
    MPI_Init(NULL, NULL);
    MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
    MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);
    srand(time(NULL));

```



```

/* Obtaining Data */
if(my_rank==0 && argc > 1){

    if(strcmp(argv[1], "r") == 0){
        printf("using random data, vector length = %d\n", 100*comm_sz);
        n = 100*comm_sz;
        vector1 = (int *) malloc(100*comm_sz * sizeof(int));
        vector2 = (int *) malloc(100*comm_sz * sizeof(int));

        for(int i = 0; i < n;i++){
vector1[i] = rand() % 1000;
vector2[i] = rand() % 1000;
        }
        scalar = rand() % 1000;
    }

} else if (my_rank==0){

    printf("enter vector length\n");
    scanf("%d", &n);
    printf("enter integer vector 1\n");

    vector1 = (int *) malloc(n * sizeof(int));
    vector2 = (int *) malloc(n * sizeof(int));

    for(int i = 0; i < n; i++){
        scanf("%d", &vector1[i]);
    }

    printf("enter integer vector 2\n");

    for(int i = 0; i < n; i++){
        scanf("%d", &vector2[i]);
    }

    printf("enter integer scalar\n");
    scanf("%d", &scalar);
}

/* Distribute Data */
MPI_Bcast(&n, 1, MPI_INT, 0, MPI_COMM_WORLD);

/* Fixing sendcounts for general n */
sendcounts = (int *) malloc(comm_sz * sizeof(int));
displs = (int *) calloc(comm_sz, sizeof(int));

for(int i = 0; i < comm_sz;i++){
    if(n % comm_sz > i){

```

```

        sendcounts[i] = (n/comm_sz) + 1;
    } else {
        sendcounts[i] = (n/comm_sz);
    }

}

for(int i = 1; i <comm_sz; i++){
    displs[i] = displs[i-1]+sendcounts[i];
}

local_n = sendcounts[my_rank];

local_vec1 = (int*) malloc(local_n * sizeof(int));
local_vec2 = (int*) malloc(local_n * sizeof(int));

MPI_Bcast(&scalar, 1, MPI_INT, 0, MPI_COMM_WORLD);
MPI_Scatterv(vector1, sendcounts, displs, MPI_INT, local_vec1, sendcounts[my_rank], MPI_COMM_WORLD);
MPI_Scatterv(vector2, sendcounts, displs, MPI_INT, local_vec2, sendcounts[my_rank], MPI_COMM_WORLD);

/* Calculations */
/* Calculate Dot Product */
for(int i = 0; i < local_n; i++){
    local_vec2[i]*=local_vec1[i];
}

/* Calculate vector-scalar product */
for(int i = 0; i < local_n; i++){
    local_vec1[i]*=scalar;
}

/* Summing for dot product */
for(int i = 0; i < local_n; i++){
    local_dotp_sum += local_vec2[i];
}

/* Collect Data */
MPI_Gatherv(local_vec1, sendcounts[my_rank], MPI_INT, vector1, sendcounts, displs, MPI_COMM_WORLD);
MPI_Reduce(&local_dotp_sum, &result_dot, 1, MPI_INT, MPI_SUM, 0, MPI_COMM_WORLD);

/* Results */
if(my_rank == 0){
    printf("dot product = %d\n", result_dot);

    printf("vector-scalar product = ");
    for(int i = 0; i < n; i++){

```

```

        printf("%d ", vector1[i]);
    }
    printf("\n");
}

/* Clean up */
if(my_rank==0){
    free(vector1);
    free(vector2);
}

free(local_vec1);
free(local_vec2);

MPI_Finalize();

return 0;
}

```

E C Source code for Exercise 3.18

```

#include <stdio.h>
#include <mpi.h>
#include <stdlib.h>

```

```

int Read_vector(int block_length, double* vector, double** slice, int vector_length, int
int Print_vector(int block_length, double** slice, double* vector, int vector_length, int

int main(void) {
    int my_rank, comm_sz;
    double vec[18] = {0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17};
    double readback[18] = { 0 };
    double * slice;

    MPI_Init(NULL, NULL);
    MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
    MPI_Comm_size(MPI_COMM_WORLD, &comm_sz);

    Read_vector(2, vec, &slice, 18, my_rank, comm_sz);
    Print_vector(2, &slice, readback, 18, my_rank, comm_sz);

    /* Print out the result */
    if(my_rank == 0){
        printf("The vector after round Read_vector and Print_vector on Core 0:\n");

```

```

        for(int i = 0; i < 18; i++){
            printf("i %d: %f\n", i, readback[i]);
        }
    }

    /* Clean up */
    MPI_Finalize();
    free(slice);
    return 0;
}

```

```

int Read_vector(int block_length, double* vector, double** slice, int vector_length, int

```

```

    /* calc block cyclic distro */
    int no_cycles = vector_length / (block_length * comm_sz);
    int cycle_block_length = block_length * comm_sz;
    int slice_length = no_cycles * block_length;

    /* define data type */
    MPI_Datatype block_cyclic;
    MPI_Type_vector(no_cycles, block_length, cycle_block_length, MPI_DOUBLE, &block_cyclic);
    MPI_Type_commit(&block_cyclic);
    MPI_Status info;

    if (my_rank == 0){

        for (int i = 1; i < comm_sz;i++){
            MPI_Send(&vector[i*block_length],1,block_cyclic,i,99,MPI_COMM_WORLD);
        }
        *slice = (double *) calloc(slice_length, sizeof(double));
        MPI_Sendrecv(&vector[0], 1, block_cyclic, 0, 99,
        *slice, slice_length, MPI_DOUBLE, 0, 99, MPI_COMM_WORLD, &info);
    } else {
        *slice = (double *) calloc(slice_length, sizeof(double));
        MPI_Recv(*slice,slice_length,MPI_DOUBLE, 0, 99, MPI_COMM_WORLD, &info);
    }

    /* Clean up */
    MPI_Type_free(&block_cyclic);

    return 0;
}

```

```

int Print_vector(int block_length, double** slice, double* vector, int vector_length, int

```

```

    /* calc block cyclic distro */

```

```

int no_cycles = vector_length / (block_length * comm_sz);
int cycle_block_length = block_length * comm_sz;
int slice_length = no_cycles * block_length;

/* define data type */
MPI_Datatype block_cyclic;
MPI_Type_vector(no_cycles, block_length, cycle_block_length, MPI_DOUBLE, &block_cyclic)
MPI_Type_commit(&block_cyclic);
MPI_Status info;

if(my_rank != 0){
    MPI_Send(*slice,slice_length,MPI_DOUBLE, 0, 99, MPI_COMM_WORLD);

} else {
    for (int i = 1; i < comm_sz;i++){
        MPI_Recv(&vector[i*block_length],1,block_cyclic,i,99,MPI_COMM_WORLD, &info);
    }
    MPI_Sendrecv(*slice, slice_length, MPI_DOUBLE, 0, 99, &vector[0], 1,
block_cyclic, 0, 99, MPI_COMM_WORLD, &info);
}

/* Clean up */
MPI_Type_free(&block_cyclic);

return 0;
}

```

F C Source Code for Exercise 3.20

```

/*-----
* Function:      Get_input
* Purpose:       Get the user input:  the left and right endpoints
*               and the number of trapezoids
* Input args:    my_rank:  process rank in MPI_COMM_WORLD
*               comm_sz:  number of processes in MPI_COMM_WORLD
* Output args:   a_p:  pointer to left endpoint
*               b_p:  pointer to right endpoint
*               n_p:  pointer to number of trapezoids
*/
void Get_input(int my_rank, int comm_sz, double* a_p, double* b_p,
               int* n_p) {

    char pack_buf[100];
    int position = 0;

    if (my_rank == 0) {
        printf("Enter a, b, and n\n");
    }
}

```

```
scanf("%lf %lf %d", a_p, b_p, n_p);

MPI_Pack(&a_p, 1, MPI_DOUBLE, pack_buf, 100, &position, MPI_COMM_WORLD);
MPI_Pack(&b_p, 1, MPI_DOUBLE, pack_buf, 100, &position, MPI_COMM_WORLD);
MPI_Pack(&n_p, 1, MPI_INT, pack_buf, 100, &position, MPI_COMM_WORLD);
}

MPI_Bcast(pack_buf, 100, MPI_PACKED, 0, MPI_COMM_WORLD);

if(my_rank != 0) {
    MPI_Unpack(pack_buf, 100, &position, a_p, 1, MPI_DOUBLE, MPI_COMM_WORLD);
    MPI_Unpack(pack_buf, 100, &position, b_p, 1, MPI_DOUBLE, MPI_COMM_WORLD);
    MPI_Unpack(pack_buf, 100, &position, n_p, 1, MPI_INT, MPI_COMM_WORLD);
}
} /* Get_input */
```