ESP8266 AT Command Set

Function	AT Command	Response
Working	AT	OK
Restart	AT+RST	OK [System Ready, Vendor:www.ai-thinker.com]
Firmware version	AT+GMR	AT+GMR 0018000902 OK
List Access Points	AT+CWLAP	AT+CWLAP +CWLAP:(4,"RochefortSurLac",- 38,"70:62:b8:6f:6d:58",1) +CWLAP:(4,"LiliPad2.4",-83,"f8:7b:8c:1e:7c:6d",1) OK
Join Access Point	AT+CWJAP? AT+CWJAP="SSID","Password"	Query AT+CWJAP? +CWJAP: "Rochefort SurLac" OK
Quit Access Point	AT+CWQAP=? AT+CWQAP	Query OK
Get IP Address	AT+OFSR	AT+CIFSR 192.168.0.105 OK
Set Parameters of	AT+ CWSAP?	Query
Access Point	AT+ CWSAP= <ssid>,<pwd>,<chl>, <ecn></ecn></chl></pwd></ssid>	ssid, pwd chl = channel, ecn = encryption
WiFi Mode	AT+CWMODE? AT+CWMODE=1 AT+CWMODE=2 AT+CWMODE=3	Query STA AP BOTH
Set up TOP or UDP	AT+CIPSTART=?	Query
connection	(QPMUX=0) AT+QPSTART = <type>,<addr>,<port> (QPMUX=1) AT+QPSTART= <id><type>,<addr>,<port></port></addr></type></id></port></addr></type>	id = 0-4, type = TOP/UDP, addr = IP address, port = port
TCP/UDP	AT+ QPMUX?	Query
Connections	AT+ QPMUX=0	Single
	AT+ QPMUX=1	Multiple
Check join devices' IP	AT+CWUF	
TCP/IP Connection Status	AT+CIPSTATUS	AT+CIPSTATUS? no this fun
Send TOP/IP data	(CIPMUX=0) AT+CIPSEND= <length>; (CIPMUX=1) AT+CIPSEND=<id>,<length></length></id></length>	
Close TCP / UDP connection	AT+CIPCLOSE= <id>> or AT+CIPCLOSE</id>	
Set as server	AT+ CIPSERVER= < mode>[, <port>]</port>	mode 0 to close server mode; mode 1 to open; port = port
Set the server	AT+CIPSTO?	Query
timeout	AT+CIPSTO= <time></time>	<ti>dime>0~28800 in seconds</ti>
Baud Rate*	AT+ClOBAUD? Supported: 9600, 19200, 38400, 74880, 115200, 230400, 460800, 921600	Query AT+Clobaud? +Clobaud:9600 OK
Check IP address	AT+OFSR	AT+CIFSR 192.168.0.106 OK
Firmware Upgrade (from Goud)	AT+QUPDATE	+GPUPDATE:1 found server +GPUPDATE:2 connect server +GPUPDATE:3 got edition +GPUPDATE:4 start update
Received data	+IPD	(QPMUX=0): + IPD, <len>: (QPMUX=1): + IPD, <id>, <len>: <data></data></len></id></len>
Watchdog Enable*	AT+CSYSWDTENABLE	Watchdog, auto restart when program errors occur: enable
Watchdog Disable*	AT+CSYSWDTDISABLE	Watchdog, auto restart when program errors occur: disable

^{*} New in V0.9.2.2 (from http://www.electrodragon.com/w/Wi07c)