

Expected delivery of **lab\_07.zip** must include:

- zipped project folder of the exercises 1 and 2
- this document compiled possibly in pdf format.

## Eurovision 2022 in Turin!



### Exercise 1)

The **Eurovision Song Contest 2022** will be held at the PalaOlimpico in **Turin**, Italy, following the country's victory at the 2021 contest with the song "Zitti e buoni" by *Måneskin*.

Write a program in **ARM assembly** language to manage the sale of contest tickets. PalaOlimpico is organized in different sectors with different prices. For example, you have the following lists to be initialized in a pool:

```
Sector_prices DCD 0x01, 25, 0x02, 40, 0x03, 55, 0x04, 65, 0x05, 80
               DCD 0x06, 110
```

```
Sector_quantity DCD 0x02, 250, 0x05, 250, 0x03, 550, 0x01, 150, 0x04,
                  DCD 100, 0x06, 200
```

```
Num_sectors DCB 6
```

*Sector\_prices* is a table where each entry consists of two integer values: the ID of the sector (4 bytes) and the price of each ticket in that sector (4 bytes).

*Sector\_quantity* is a table where each entry consists of two integer values: the ID of the sector (4 bytes) and the number of places available in that sector (4 bytes).

*Num\_sectors* is a 1 byte constant and indicates the number of sectors available in PalaOlimpico.

Write a program to respond to a purchase request.

The request is stored in the following pool, where you have a set of 2 items: the sector ID (hexadecimal) and the wished quantity. The variable `Tickets_requests` stores the amount of ticket requests.

For instance, in the following example the user wishes to buy tickets from three different sectors:

```
Tickets DCD 0x05, 2, 0x03, 10, 0x01, 120
Ticket_requests DCD 3
```

If the tickets are available, update the `Sector_quantity` and store the total cost of the purchase in a 4-byte variable stored in RAM, named *total\_tickets*; otherwise, if the sector is sold out (or the desired quantity is not available), store zero in the same variable, and 0x01 in R11 to underline that the procedure has not been completed.

Moreover, if the desired number of tickets is greater than 10, apply a 50% group discount for **Black Friday**.

## Exercise 2) Experiment the SVC instruction.

Write an ARM assembly program that invokes an SVC instruction when running a user routine with unprivileged access level.

By means of invoking a SuperVisor Call, we want to implement the squared power ( $x^2$ ) or the **integer approximation of the square root** of a number ( $\lfloor \sqrt{x} \rfloor$ ). The approximation of the square root is calculated by iterating on all natural numbers  $n$  in ascending order until the following condition is satisfied:  $n^2 \leq x$ . The value of  $x$  is stored in R0.

The SVC instruction is encoded as follows:



- Bits [15:8]: Opcode of the SVC Assembly ARM Instruction
- Bits [7:0]: This field indicates the operation that must be performed, according to its content.
  - If the content is equal to 0, the squared power must be done,
  - Else if the content is equal to 1, the integer approximation of the square root must be done.
  - Else, NOP operations.

**Example:** SVC 1 and R0=0x11  
Your algorithm must return 4.

The result of your code must be saved in the PSP and returned as specified in the figure below. Then, outside the *SVC\_handler*, save the result in a 4-byte variable *SQResult*.

Stack	
	<i>result_here</i>
+28	xPSR
+24	PC
+20	LR
+16	R12
+12	R3
+8	R2
+4	R1
SP→	R0

Q1: Describe how the stack structure is used by your project and which stack you are using and why.

Il Reset Handler quando viene eseguito si trova in thread mode con accesso privilegiato ma forzando il valore del registro CONTROL questo passa in modo privilegiato e quindi usa lo stack puntato da PSP anziché da MSP. La SVC invece quando viene eseguita si trova in handler mode con accesso privilegiato quindi anche essa si troverà a usare il PSP

Q2: What needs to be changed in the SVC handler if the access level of the caller is privileged? Please report the code chunk that satisfies this request.

Se anche il reset handler fosse eseguito in modo privilegiato allora anche esso userebbe il MSP e quindi lo stack privilegiato per salvare lo stato dell'esecuzione prima di chiamare la svc. Se questo fosse verificato allora bisogna modificare la SVC Handler in modo che usi il MSP per recuperare i valori dei registri salvati.