



POLITECNICO
MILANO 1863

SCUOLA DI INGEGNERIA INDUSTRIALE
E DELL'INFORMAZIONE

SMBUD Project - Spark

Author(s): **Gabriele Ginestroni**

Giacomo Gumiero

Lorenzo Iovine

Nicola Landini

Francesco Leone

Group Number: **10**

Academic Year: 2022-2023

Contents

Contents	i
1 Introduction	1
2 Data Structure	3
3 Dataframe Structure	5
3.1 Article Structure	5
3.2 Author Structure	6
3.3 Venue Structure	7
4 Commands and Queries	9
4.1 Commands	9
4.1.1 Insert a new author	9
4.1.2 Insert a new author	10
4.1.3 Insert a new venue	11
4.1.4 Insert a new article in his author dataframe	11
4.1.5 Update the number of citations of referenced publications	11
4.1.6 Deleting an author from the database	12
4.2 Queries	12
4.2.1 Query 1 - WHERE, JOIN	12
4.2.2 Query 2 - WHERE, LIMIT, LIKE	13
4.2.3 Query 3 - WHERE, IN, NESTED QUERY	13
4.2.4 Query 4 - GROUP BY, JOIN, AS	15
4.2.5 Query 5 - WHERE, GROUP BY	16
4.2.6 Query 6 - GROUP BY, HAVING, AS	17
4.2.7 Query 7 - WHERE, GROUP BY, HAVING, AS	18
4.2.8 Query 8 - WHERE, NESTED QUERY, GROUP BY	19
4.2.9 Query 9 - WHERE, GROUP BY, HAVING, 1 JOIN	20

4.2.10	Query 10 - WHERE, GROUP BY, HAVING, 2 JOINS	21
4.2.11	Query 11 - EXTRA	22
4.2.12	Query 12 - EXTRA	23

1 | Introduction

In this chapter will be presented the problem specification and the hypothesis under which the database is implemented.

2 | Data Structure

In this part of the project we used the same two JSONs used in the MONGODB implementation.

3 | Dataframe Structure

3.1. Article Structure

```

1 root
2 |-- _id: string (nullable = true)
3 |-- title: string (nullable = true)
4 |-- authors: array (nullable = true)
5 |   |-- element: struct (containsNull = true)
6 |   |   |-- idAuth: string (nullable = true)
7 |   |   |-- org: string (nullable = true)
8 |-- n_citation: integer (nullable = true)
9 |-- abstract: string (nullable = true)
10 |-- doi: string (nullable = true)
11 |-- keywords: array (nullable = true)
12 |   |-- element: string (containsNull = true)
13 |-- isbn: string (nullable = true)
14 |-- page_start: string (nullable = true)
15 |-- page_end: string (nullable = true)
16 |-- year: integer (nullable = true)
17 |-- fos: array (nullable = true)
18 |   |-- element: string (containsNull = true)
19 |-- references: array (nullable = true)
20 |   |-- element: string (containsNull = true)
21 |-- issue: string (nullable = true)
22 |-- volume: string (nullable = true)
23 |-- publisher: string (nullable = true)
24 |-- venue_raw: string (nullable = true)

```

The structure just shown represents an *Article*; its attributes are:

- **_id** is the identifier of a publication.
- **title** represents the title of the publication.
- **authors** is an array that contains: **idAuth** of the authors of the article and the **org** field which represent the affiliation.

- **n_citation** is the number of times that the publication has been mentioned.
- **abstract** is a string containing a brief summary of the contents of the paper.
- **doi** Digital Object Identifier is a persistent and standardized identifier.
- **keywords** is an array containing keywords of the publication.
- **isbn** is an identification code of the venue of the publication.
- **page_start** defines the starting page of the publication.
- **page_end** defines the last page of the publication.
- **year** represents the year of publication.
- **fos** is an array containing the fields of study of the publication.
- **references** set of ObjectIds of the referenced articles.
- **issue** refers to how many times a periodical has been published during that year.
- **volume** is the volume of the venue in which the article has been published.
- **publisher** is the name of the publisher of the article.
- **venue_raw** is the name or the abbreviation of the venue (regardless the year, issue or volume) in which the publication was presented.

3.2. Author Structure

```

1 root
2 |-- _id: string (nullable = true)
3 |-- name: string (nullable = true)
4 |-- nationality: string (nullable = true)
5 |-- articles: array (nullable = true)
6 |   |-- element: string (containsNull = true)
7 |-- bio: string (nullable = true)
8 |-- email: string (nullable = true)
9 |-- orcid: string (nullable = true)
10 |-- dob: timestamp (nullable = true)

```

The structure just shown represents an *Author*; its attributes are:

- **_id** is the identifier of an author.
- **name** is the name of the author.

- **nationality** is the nationality of the author.
- **articles** is a set of articles identifier of the publications of the author.
- **bio** is a string that describes the author.
- **email** is the email address of the author.
- **orcid** Open Researcher and Contributor ID is a unique identifier for authors of scientific articles.
- **dob** is the birth date of the author.

3.3. Venue Structure

```
1 root
2 |-- raw: string (nullable = true)
3 |-- type: integer (nullable = true)
4 |-- artIds: array (nullable = false)
5 |     |-- element: string (containsNull = false)
6 |-- city: string (nullable = true)
```

The structure just shown represents a *Venue*. This dataframe was obtained using data imported from the article JSON shown before. *Venue* attributes are the following:

- **raw** is the name or the abbreviation of the venue (regardless the year, issue or volume) in which the publication was presented.
- **type** indicates the type of the publication.
- **artIds** is a set of articles identifier associated to the venue.
- **city** represents the location of the venue an it is randomly populated.

4.1.2. Insert a new author

Assuming it is not present in the dataset, we created a new row with the values for a new article written by the author created in section 4.1.1. In order to set the authors, we instantiated an array `new_authors`.

```

1 new_authors = [Row("638db170ae9ea0d19fad7a79", "Politecnico di Milano")
2               , Row("638db170ae9ea0d19fad7a7a", "
3                   Politecnico di Milano")]
4
5 new_article = Row(
6     _id="638db237d794b76f45c77916",
7     title="An extensive study of C-SMOTE, a Continuous Synthetic
8           Minority Oversampling Technique for
9           Evolving Data Streams",
10    authors=new_authors,
11    n_citation=3,
12    abstract = "Streaming Machine Learning (SML) studies algorithms that
13               update their models,\
14               given an unbounded and often non-stationary flow of data
15               performing a single pass. Online \
16               class imbalance learning is a branch of SML that combines the
17               challenges of both class imbalance\
18               and concept drift. In this paper, we investigate the binary
19               classification problem by
20               rebalancing\
21               an imbalanced stream of data in the presence of concept drift,
22               accessing one sample at a time.",
23    doi="10.1016/j.eswa.2022.116630",
24    keywords=["Evolving Data Stream","Streaming","Concept drift","
25              Balancing"],
26    isbn="123-4-567-89012-3",
27    page_start="39",
28    page_end="46",
29    year=2022,
30    fos=["Computer Science","Stream Reasoning","Big Data"],
31    references=["53e99fe4b7602d97028bf743","53e99fddb7602d97028bc085"],
32    issue="1",
33    volume="196",
34    publisher="Elsevier",
35    venue_raw="ESA"
36 )

```

```
27 df_articles = df_articles.union(spark.createDataFrame([new_article]))
```

4.1.3. Insert a new venue

Assuming it is not present in the dataset, we created a new row with the values for a new venue *ESA* hosted in *Montreal*.

Note: in field `artIds` we set the article created in section 4.1.2.

```
1 new_venue = Row(
2     raw="ESA",
3     type=1,
4     artIds=["638db237d794b76f45c77916"],
5     city="Montreal"
6 )
7
8 df_venues = df_venues.union(spark.createDataFrame([new_venue]))
```

4.1.4. Insert a new article in his author dataframe

Through this command we inserted the article created in section 4.1.2 to its authors. In order to do that, we selected the authors through the ids and we add the article id to their field `articles`.

Note: one of the author is the one created in section 4.1.1.

```
1 df_authors = df_authors.withColumn(
2     "articles",
3     f.when(f.col("_id") == "638db170ae9ea0d19fad7a79",
4         f.array_union(df_authors.articles, f.array(f.lit("
5             638db237d794b76f45c77916"))))\
6     .when(f.col("_id") == "638db170ae9ea0d19fad7a7a",
7         f.array_union(df_authors.articles, f.array(f.lit("
8             638db237d794b76f45c77916"))))
9     .otherwise(f.col("articles"))
10 )
```

4.1.5. Update the number of citations of referenced publications

Through the following snippet of code is possible to increment the `n_citations` field of the *Publications* referenced by the article created in section 4.1.2.

Note: field `n_citations` is updated for both the referenced articles.

```

1 df_articles = df_articles.withColumn(
2     "n_citation",
3     f.when(f.col("_id") == "53e99fe4b7602d97028bf743",
4         df_articles.n_citation+1) \
5     .when(f.col("_id") == "53e99fddb7602d97028bc085",
6         df_articles.n_citation+1)
7     .otherwise(f.col("n_citation"))
8 )

```

4.1.6. Deleting an author from the database

Through the following snippet of code is possible to delete an author from the database. In order to do that we started from filtering on the identifier of the author to be removed and we deleted it.

```

1 df_authors.filter(f.col("_id") == "638db170ae9ea0d19fad7a79").show()
2 df_authors = df_authors.filter(f.col("_id") != "638db170ae9ea0d19fad7a79")

```

4.2. Queries

We have identified the following queries in order to show the system's basic functionalities. In the following sections title we wrote the basic requirements for every query, that, for ease of read, are represented as SQL clauses.

4.2.1. Query 1 - WHERE, JOIN

This query returns the type of the venue of an article with a the following title: *"Locality Sensitive Outlier Detection: A ranking driven approach"*.

Description: starting from the articles dataframe, a join is performed with the venues dataframe on the article's `venue_raw` field. After that, we filter the articles with the given title. Finally, we project over title,venue raw and venue type.

```

1 df_articles.join(df_venues, df_articles.venue_raw == df_venues.raw, "
2     inner")\
3     .filter(f.col("title") == "Locality Sensitive Outlier

```



```

1                                     Detection: A ranking driven approach
2                                     ")\"
3     .select("title", "raw", "type")\
4     .show(truncate=False)

```

```

+-----+-----+-----+
|title                                     |raw |type|
+-----+-----+-----+
|Locality Sensitive Outlier Detection: A ranking driven approach|ICDE|0  |
+-----+-----+-----+

```

4.2.2. Query 2 - WHERE, LIMIT, LIKE

This query returns the articles whose title string contains *"Machine Learning"*.

Description: we filter the articles whose title contains "Machine Learning" using the like operator. Results are then limited to 3 tuples and projected over the article title.

```

1 df_articles.filter(f.col("title").like("%Machine Learning%"))\
2     .limit(3)\
3     .select("title")\
4     .show(truncate=False)

```

```

+-----+
|title
+-----+
|Editorial: The Terminology of Machine Learning
|Machine Learning, Proceedings of the Twenty-Second International Conference (ICML 2005), Bonn, Germany, August 7-11, 2005|
|Medical Expert Evaluation of Machine Learning Results for a Coronary Heart Disease Database
+-----+

```

4.2.3. Query 3 - WHERE, IN, NESTED QUERY

This query finds authors that has the same nationality of at least one of the authors of *"Locality Sensitive Outlier Detection: A ranking driven approach"* article.

Description: this query has been splitted in 2 queries:

- *First query:* articles are filtered to find the article with the given title. After that, the authors array is exploded to perform a join on its idAuth field with the authors dataframe. Finally, nationalities of the article's authors are collected into a list using the `collect_set`.

`collect_set`, as the name suggests, discards duplicates, so the final list is a set of nationalities.

- *Second query:* starting from the authors' dataframe, we filtered all the authors whose nationality is present inside the list created with the previous query.

```
1 nationalities_list = df_articles.filter(f.col("title") == "Locality  
    Sensitive Outlier Detection: A  
    ranking driven approach")\  
2 .select(f.explode(df_articles.authors.  
    idAuth).alias("idAuth"))\  
3 .join(df_authors, on=f.col("idAuth") ==  
    df_authors._id)\  
4 .select("nationality")\  
5 .agg(f.collect_set("nationality")).  
    collect()[0][0]  
6  
7 df_authors.filter(f.col("nationality")\  
8     .isin(nationalities_list))\  
9 .select("name","nationality")\  
10 .show(truncate=False)
```

name	nationality
Ye Wang	dk
Srinivasan Parthasarathy	jp
Shirish Tatikonda	gr
Moshe Zukerman	jp
Michael Wiegand	jp
GeunSik Jo	jp
Carla Achury	gr
Kong-Aik Lee	jp
Shahram Shah-Heydari	gr
Wenfang Tan	dk
Ayoub Alsarhan	gr
Anjali Agarwal	jp
David Haccoun	jp
Silvio Macedo	dk
John Wan Tung Lee	gr
Geoff Holmes	dk
Zornitsa Kozareva	jp
Peter Murray-Rust	jp
Rajkumar Buyya	jp
Srikumar Venugopal	jp

only showing top 20 rows

4.2.4. Query 4 - GROUP BY, JOIN, AS

This query finds the 3 most frequent keywords of articles written by italian authors.

Description: starting from the authors dataframe, we keep only italian authors and explode the articles field, renaming the new obtained field to **articles**. After that, duplicates are discarded.

In the second part of the query, we load the full articles's rows using a join. Then, keywords array is exploded. Keywords are grouped and counted. The groups are finally sorted and limited to show the top 3 keywords.

```

1 df_italian = df_authors.filter(f.col("nationality") == "it")\
2     .select(f.explode("articles")).withColumnRenamed(
3     "col", "articles")\
    .distinct()

```

```

4
5 df_keywords = df_italian.join(df_articles, df_italian.articles ==
6                               df_articles._id, "inner")\
7                               .select("articles", f.explode("keywords"))\
8                               withColumnRenamed("col", "keywords")\
9                               .groupby("keywords")\
10                              .agg(f.count("keywords").alias("n_occurences"))\
                              .sort("n_occurences", ascending=False)\
                              .limit(3).show()

```

```

+-----+-----+
| keywords | n_occurences |
+-----+-----+
| data mining | 27 |
| computer science | 22 |
| internet | 17 |
+-----+-----+

```

4.2.5. Query 5 - WHERE, GROUP BY

This query finds the cities with more than 65 venues.

Description: the venues dataframe is grouped with respect to the city to perform the count. After that, we keep only cities with more than 65 venues and sort the result in descending order.

```

1 df_venues\
2   .groupby("city")\
3   .count()\
4   .filter(f.col("count") > 65)\
5   .sort("count", ascending=False).show()

```

city	count
Athens	76
Tokyo	73
Prague	71
Sofia	70
Madrid	70
Paris	69
Budapest	66

4.2.6. Query 6 - GROUP BY, HAVING, AS

This query finds the field of studies that appears more than 15 times.

Description: We use the explode function to convert the fos array into multiple rows, then we rename the resulting column to fos, group by fos and count the number of occurrences.

After that, we keep rows with more than 15 occurrences, sort the remaining rows in descending order based on the number of occurrences, and show the top rows.

```

1 df_articles\
2   .select("_id", "title", f.explode("fos")).withColumnRenamed("col", "
                                     fos")\
3   .groupby("fos")\
4   .agg(f.count("fos").alias("n_occurencies"))\
5   .filter(f.col("n_occurencies") > 15)\
6   .sort("n_occurencies", ascending=False)\
7   .show(truncate=False)

```

fos	n_occurencies
Computer science	3988
Artificial intelligence	1246
Mathematics	1194
Algorithm	575
Computer network	452
Computer vision	395
Distributed computing	388
Engineering	374
Pattern recognition	333
Data mining	327
Theoretical computer science	326
Discrete mathematics	294
Mathematical optimization	293
World Wide Web	264
Machine learning	263
Combinatorics	239
Control theory	227
Information retrieval	222
Programming language	217
Knowledge management	203

only showing top 20 rows

4.2.7. Query 7 - WHERE, GROUP BY, HAVING, AS

This query finds all the volumes with at least 5 articles in the dataset, published after 2000.

Description: This query filters the articles in the articles dataframe to only those published after the year 2000, then groups the remaining articles by `venue_raw` and `volume`, counts the number of articles per group, filters the groups to only those with more than 4 articles, and finally displays the results.

```

1 df_articles\
2     .filter(f.col("year") > 2000)\
3     .groupby("venue_raw", "volume")\
4     .agg(f.count("volume").alias("num_articles"))\
5     .filter(f.col("num_articles") > 4)\

```

```
6 .show(truncate = False)
```

venue_raw	volume	num_articles
Applied Mathematics and Computation	218	5
Pattern Recognition	45	5
Expert Syst. Appl.	39	5
Applied Mathematics and Computation	217	5
IEICE Transactions	97-A	5
Expert Syst. Appl.	37	5

4.2.8. Query 8 - WHERE, NESTED QUERY, GROUP BY

The following query is divided in two queries:

8a. find the venue with highest number of articles

8b. find the number of articles published per year on that venue

```
1 top_venue = df_venues\
2     .select("raw",f.size("artIds").alias("count"))\
3     .orderBy("count",ascending = False)\
4     .limit(1)
5
6 df_articles_year = df_articles\
7     .filter(f.col("venue_raw") == top_venue.collect
8             () [0] [0])\
9     .groupBy("year")\
10    .count()\
11    .orderBy("count",ascending=False)\
12    .select(f.lit(top_venue.collect() [0] [0]).alias("
    VenueRAW"),"year",f.col("count").
    alias("articles_count"))\
    .show(truncate=False)
```

VenueRAW	year	articles_count
Clinical Orthopaedics and Related Research	2010	11
Clinical Orthopaedics and Related Research	2011	8
Clinical Orthopaedics and Related Research	2009	7
Clinical Orthopaedics and Related Research	2008	5
Clinical Orthopaedics and Related Research	2007	3
Clinical Orthopaedics and Related Research	2000	2
Clinical Orthopaedics and Related Research	2012	1
Clinical Orthopaedics and Related Research	2006	1
Clinical Orthopaedics and Related Research	2013	1
Clinical Orthopaedics and Related Research	2005	1
Clinical Orthopaedics and Related Research	2001	1

4.2.9. Query 9 - WHERE, GROUP BY, HAVING, 1 JOIN

The following query finds the articles, published after 2000, with more than 13 different nationalities of its authors.

```

1 df_articles_nationalities = df_articles.alias("art")\
2     .filter(f.col("year") > 2000)\
3     .select("art._id","art.title", f.explode
4         ("art.authors.idAuth").alias("author
5         "))\
6     .join(df_authors.alias("auth"), on=f.col
7         ("author") == df_authors._id)\
8     .groupBy("art._id")\
9     .agg(f.first("title").alias("title"),f.
        countDistinct("nationality").alias("
        different_nationalities"), f.
        collect_set("nationality").alias("
        nationalities_list"))\
10    .filter(f.col("different_nationalities")
11        > 13)\
12    .orderBy("different_nationalities",
13        ascending=False)\
14    .select("title","different_nationalities
15        ",f.sort_array("nationalities_list")
16        .alias("nationalities_list"))\

```



```
10 | .show(truncate=False)
```

```
+-----+-----+
|title                                     |
|different_nationalities|nationalities_list|
+-----+-----+
|Being user-oriented: Convergences, divergences, and the potentials for systematic dialogue between disciplines and between researchers, designers, and providers|17|[be, de, dk, fr, gr, hu, it, jp, nl, no, pl, pt, ro, ru, se, tr, us]|
|A Low-Power Single-Weight-Combiner 802.11abg SoC in 0.13 μm CMOS for Embedded Applications Utilizing An Area and Power Efficient Cartesian Phase Shifter and Mixer Circuit|17|[de, dk, es, fr, gr, hu, it, jp, nl, no, pl, ro, ru, se, tr, uk, us]|
|A 7Gb/s/pin GDDR5 SDRAM with 2.5ns bank-to-bank active time and no bank-group restriction|15|[de, dk, fr, gr, hu, it, jp, no, pl, pt, ro, ru, se, tr, uk]|
|Cluster Analysis and Decision Trees of MR Imaging in Patients Suffering Alzheimer's|14|[be, de, es, gr, jp, nl, no, pt, ro, ru, se, tr, uk, us]|
+-----+-----+
```

4.2.10. Query 10 - WHERE, GROUP BY, HAVING, 2 JOINS

This query finds all the authors that published on more than 2 Journals.

```
1 df_exploded_authors = df_authors.alias("auth")\
2     .select("auth._id", "auth.name", f.explode("auth.
3         articles").alias("article"))\
4     .join(df_articles.alias("art"), on=f.col("
5         article") == df_articles._id)\
6     .select("auth._id", "auth.name", "art._id", "art.
7         venue_raw")\
8     .join(df_venues.alias("ven"), on=f.col("
9         venue_raw") == df_venues.raw)\
10    .filter(f.col("type") == 1)\
    .groupBy("auth._id")\
    .agg(f.first("name").alias("name"), f.
        countDistinct("raw").alias("
        venue_count"), f.concat_ws(" - ", f.
        collect_set("raw")).alias("
        venues_list"))\
    .filter(f.col("venue_count") > 2)\
    .orderBy("venue_count", ascending=False).show(3,
        truncate=False)
```

title	authorsList
Design principles for developing stream processing applications drade, Jeffrey David Harris, John Cox, Olivier Verscheure, Paul Jones, William Szewczyk	Bugra Gedik, Chitra Venkatramani, Deepak S. Turaga, Henrique An 26
Building an information retrieval test collection for spontaneous conversational speech as W. Oard, G. Craig Murray, James Mayfield, Jianqiang Wang, Liliya Kharevych, Martin Franz, Samuel Gustman, Stephanie Strassel, Xiaoli Huang	26

4.2.11. Query 11 - EXTRA

This query returns all the articles written by authors whose names combined have all 26 letters of the alphabet.

```

1 df_authors.select("name", f.explode("articles").alias("idArt")) \
2     .groupBy("idArt") \
3     .agg(f.collect_set("name").alias("authorsList")) \
4     .select("idArt", "authorsList", (f.size(f.array_distinct(f.
5         split(f.regex_replace(f.lower(f.
6             concat_ws(",", "authorsList")), "[^a-
7             z]", ""), ""))) - 1).alias("
8         differentLetters")) \
9     .filter(f.col("differentLetters") == 26) \
10    .join(df_articles, on=f.col("idArt") == df_articles._id) \
11    .select("title", f.concat_ws(",", f.sort_array("authorsList")
12        ).alias("authorsList"), "
13        differentLetters") \
14    .show(truncate=False)

```

title	authorsList
Design principles for developing stream processing applications drade, Jeffrey David Harris, John Cox, Olivier Verscheure, Paul Jones, William Szewczyk	Bugra Gedik, Chitra Venkatramani, Deepak S. Turaga, Henrique An 26
Building an information retrieval test collection for spontaneous conversational speech as W. Oard, G. Craig Murray, James Mayfield, Jianqiang Wang, Liliya Kharevych, Martin Franz, Samuel Gustman, Stephanie Strassel, Xiaoli Huang	26

4.2.12. Query 12 - EXTRA

This query returns all articles written in affiliation with *Politecnico of Milano*.

```

1 df_articles\
2   .select("title",f.explode("authors").alias("affiliation"))\
3   .filter(f.col("affiliation.org").like("%Poli%Mil%"))\
4   .join(df_authors, on=f.col("affiliation.idAuth") == df_authors._id)
5   \
6   .select("title", "name", "affiliation.org") \
7   .orderBy("title","name")\
   .show(truncate=False)

```

```

+-----+-----+-----+
|title|name|org|
+-----+-----+-----+
|The Fire and The Mountain": tangible and social interaction in a museum exhibition for children|Franca Garzotto|Politecnico di Milano, Milano, Italy|
|The Fire and The Mountain": tangible and social interaction in a museum exhibition for children|Francesca Rizzo|Politecnico di Milano, Milano, Italy|
|A Logical Model for Agent Communication Languages|Marco Colombetti|Politecnico di Milano Milano, Italy University of Lugano Lugano, Switzerland|
|A Logical Model for Agent Communication Languages|Mario Verdicchio|Dipartimento di Elettronica ed Informazione Politecnico di Milano Milan, Italy|
|A posteriori dual-mixed adaptive finite element error control for Lamé and Stokes equations|Riccardo Sacco|Dipartimento di Matematica " F. Brioschi", Politecnico di Milano, via Bonardi 9, 20133, Milano, Rocquencourt, Italy|
|Coordinated cutting plane generation via multi-objective separation.|Edoardo Amaldi|Dipartimento di Elettronica ed Informazione,Politecnico di Milano,Milano,Italy|
|Coordinated cutting plane generation via multi-objective separation.|Stefano Coniglio|Dipartimento di Elettronica ed Informazione,Politecnico di Milano,Milano,Italy|
|Coordinated cutting plane generation via multi-objective separation.|Stefano Gualandi|Dipartimento di Elettronica ed Informazione,Politecnico di Milano,Milano,Italy|
|Hierarchy-based mining of association rules in data warehouses|Giuseppe Psaila|Politecnico di Milano, Dipartimento di Elettronica e Informazione, Piazza L. Da Vinci, 32, I-20133 Milano, Italy|
|Hierarchy-based mining of association rules in data warehouses|Pier Luca Lanzi|Politecnico di Milano, Dipartimento di Elettronica e Informazione, Piazza L. Da Vinci, 32, I-20133 Milano, Italy|
|ICT and mobile health to improve clinical process delivery. a research project for therapy management process innovation.|Nicola Restifo|Fondazione Politecnica di Milano, Milano, Italy|
|ICT and mobile health to improve clinical process delivery. a research project for therapy management process innovation.|Paolo Locatelli|Fondazione Politecnica di Milano, Milano, Italy|
|ICT and mobile health to improve clinical process delivery. a research project for therapy management process innovation.|Roberta Facchini|Fondazione Politecnica di Milano, Milano, Italy|
|Live goals for adaptive service compositions|Liliana Pasquale|Politecnico di Milano, Milano, Italy|
|Live goals for adaptive service compositions|Luciano Baresi|Politecnico di Milano, Milano, Italy|
|Parallel conjugate gradient with Schwarz preconditioner applied to fluid dynamics problems|A. Quarteroni|Politecnico di Milano, P.zza Leonardo da Vinci, 32, I-20133 Milano, Italy|
|Refining and Compressing Abstract Model Checking|Elisa Quintarelli|Dipartimento di Elettronica e Informazione, Politecnico di Milano, Piazza Leonardo da Vinci 32, 20133 Milano, Italy|
|Risk analysis of underground infrastructures in urban areas|Massimiliano De Ambroggi|Dipartimento di Management, Economics and Industrial Engineering, Politecnico di Milano, Piazza Leonardo da Vinci 32, Milan 20132, Italy|
|Risk analysis of underground infrastructures in urban areas|Ottavio Grande|Dipartimento di Management, Economics and Industrial Engineering, Politecnico di Milano, Piazza Leonardo da Vinci 32, Milan 20132, Italy|
|Risk analysis of underground infrastructures in urban areas|Paolo Trucco|Dipartimento di Management, Economics and Industrial Engineering, Politecnico di Milano, Piazza Leonardo da Vinci 32, Milan 20132, Italy|
+-----+-----+-----+
only showing top 20 rows

```