FOOT meeting

TOF-wall: test with cosmic rays

L. Marini

INFN Pisa

November 2021

- 1. TOF-wall detector
- 2. Experimental setup
- 3. Data analysis
 - 3.1. Flowchart
 - 3.2. Amplitude
 - 3.3. Charge
 - 3.4. Hitmap

TOF-wall detector

- TW used to measure the energy loss ΔE of the passing particles and to provide their arrival time.
- Made of 40 bars of EJ-200 plastic scintillator arranged in two orthogonal layers of 20 each.
- At each end of each bar, the two series of two SiPMs were connected in parallel.




Figure: Scheme of TOF-Wall bar numbering

Experimental setup

- The light produced in the bars is collected at each end.
- Each group of four SiPMs provides a single summed analogical signal.
- The output signal of each side of each bar was input to a waveform digitizer board, WaveDREAM, hosted in the WaveDAQ integrated trigger and data acquisition system.




Figure: Thanks M. Morrocchi!

Experimental setup






Figure: Schematic representation of the setup

Data acquisition



Flowchart



Algorithm applied on all the waveDREAMs of the TOF wall.

WaveDREAM board 165 - Amplitude histograms




Figure: Channels from 0 to 7.

¹Data in GoogleDrive/FOOT/Cosmici/3GSample-oct23

WaveDREAM board 165 - Amplitude histograms





Figure: Channels from 8 to 15.

2




Charge





- \bullet Compute charge Q through the integral of the waveform (for each individual event).
- ullet For each event, Q_{tot} evalutated from the collected charge on each side of the bar .


Charge



Good agreement with the expected Landau distribution.



Hit-Map TOFwall



Board 157, channel 2 and 3 disabled



Maybe a problem with the connector?

BAR 12 X-View

