

Problem 2 (Uphill paths), Cell 6: $U(Q_9)$

Team submission

BAINSA Hackathon, 26 September 2026

1 Cell 6

Official setting. As in Cell 1 (§A.1). For C6, hand in all three of: the value; an explicit labelling that attains it, in the same format; and a proof that no labelling gives fewer uphill paths.

Task. Determine $U(Q_9)$.

Status. Partial. We do *not* determine $U(Q_9)$. We prove $2328 \leq U(Q_9) \leq 2400$ (Cell 5) and reduce the remaining gap to a question about decycling sets of Q_9 . We conjecture $U(Q_9) = 2400$ (Conjecture 1.2), and give the evidence we have. The labelling of Cell 5 (§E.4) is our candidate for the optimum.

1.1 What is proved

Proposition 1.1. (a) $2328 \leq U(Q_9) \leq 2400$ and $227 \leq \nabla(Q_9) \leq 236$.

(b) Every labelling f of Q_9 with fewer than 2400 uphill paths has a set R_f of expensive vertices ($N \geq 2$) that is a decycling set with at most 235 vertices. It also satisfies $\sum_{u \in R_f} (N(u) - 2) \text{out}(u) \leq 2399 - 512 - 8|R_f|$.

(c) In particular, if $\nabla(Q_9) = 236$, then $U(Q_9) = 2400$, attained by L_{C_9} .

(d) Let R be a decycling set of Q_9 contained in one parity class. Then $|R| \geq 231$; and $|R| \geq 236$ if one uses the known value $A(8, 3) = 20$ [4].

Proof. (a) is Proposition E.1 and Theorem E.5. (b) is Proposition A.3 with $d = 9$ together with Lemma A.2(c). (c) follows from (b) and (a). For (d), assume by symmetry that $R \subseteq E_9$, and let $C = E_9 \setminus R$. All odd vertices lie outside R . Two words of C at distance 2 would span a 4-cycle with their two (odd) common neighbours, so C has pairwise distances ≥ 4 . By Lemma E.3, $|C| \leq 25$, so $|R| \geq 256 - 25 = 231$. The maximum size of such a code equals $A(8, 3) = 20$ (puncture one coordinate, respectively add a parity bit), which gives $|R| \geq 236$. $\square$

So a labelling beating 2400 must come from a decycling set of Q_9 with at most 235 vertices. By (d), such a set contains vertices of *both* parities, unlike every optimal set we know for $d \leq 8$ (Corollary D.3).

1.2 Conjecture and evidence

Conjecture 1.2. $\nabla(Q_9) = 236$, and hence $U(Q_9) = 2400$.

Evidence (not a proof).

- For $2 \leq d \leq 8$ we proved $\nabla(Q_d) = 2^{d-1} - A(d-1, 3)$. In each case the optimum is attained by a parity class minus a code (Corollary D.3). The conjecture is the same formula at $d = 9$.
- Up to $d = 8$ this formula is squeezed between two simple lower bounds: the counting bound (Lemma A.7) and doubling (Lemma D.1). At $d = 9$ the two bounds give only 225 and 224, while the formula gives 236. The gap is 11. This is why $d = 9$ is the first open case.
- Local search found nothing below 236. We ran simulated annealing over sets R of fixed size $r \in \{228, \dots, 235\}$, minimising the cycle rank of $Q_9 - R$. Starts were random or $E_9 \setminus C_9$ with vertices removed. Moves swapped a vertex of R with a vertex of the complement, and runs had up to $6 \cdot 10^6$ moves. No decycling set of size ≤ 235 turned up; the best set of size 235 left one independent cycle. A SAT search for a decycling set of size 225 (with the subcube bounds of Cell 5 added) did not finish within half an hour. These runs are exploratory and are not part of any proof.

1.3 What a proof would need

By Proposition 1.1(c), it suffices to show that Q_9 has no decycling set of size $224 + s$ for $3 \leq s \leq 11$ (sizes 227–235). The proof of Theorem E.5 covers $s \leq 2$. Two ingredients would have to be strengthened:

- (i) *Types of light copies.* For $s \geq 3$ the heavy copies of a fixed D can separate $\{0, 1\}^D$, so the light copies need not all have the same type. One would need the structure of decycling sets of Q_6 with 29, 30, ... vertices, or copies of other dimensions, for instance Q_5 with $\nabla(Q_5) = 14$ and 16 copies per class.
- (ii) *The code bound.* Step 4 of that proof uses $|C_0| \leq 25$ (Lemma E.3). With $A(8, 3) = 20$ in its place, Step 4 gives $|C| \leq 20 + \sum_{z \in Z} |C \cap N(z)|$, to be compared with $|C| = 32 - s + |Z|$. This is a contradiction while the odd part Z is small. For example, when $|Z| \leq 3$ each $|C \cap N(z)| \leq 3$, and $|C| \leq 20 + 3|Z| < 32 - s + |Z|$ as soon as $2|Z| < 12 - s$. For a large Z it is not.

A decycling set of size ≤ 235 would not settle the question by itself either. By Proposition 1.1(b), it improves on 2400 only if the extra term $\sum_{u \in R} (N(u) - 2)\text{out}(u)$ can be kept small, for instance if it is independent.

Remark 1.3 (Literature). Decycling (feedback vertex) sets of hypercubes have been studied before, e.g. [2, 1, 5]. We did not use these papers and have not checked which of our values $\nabla(Q_d)$, $d \leq 8$, appear there. We claim no novelty for these values. The connection with uphill paths, the exact formula of Proposition A.3, the resulting values of $U(Q_d)$, and the bound $\nabla(Q_9) \geq 227$ were obtained independently here.

A Results used: Cell 1 ($U(Q_3)$ and $U(Q_4)$), as handed in for that cell

Official setting.

Let G be a finite simple graph on n vertices. A *labelling* of G is a bijection f from $V(G)$ to $\{1, 2, \dots, n\}$. Fix a labelling. A vertex v is a *valley* if every neighbour w of v has $f(w) > f(v)$; an isolated vertex counts as a valley. An *uphill path* is a sequence $(v_1, v_2, \dots, v_k)$ with $k \geq 1$ in which v_1 is a valley, v_i and v_{i+1} are adjacent for each i , and $f(v_1) < f(v_2) < \dots < f(v_k)$. A valley on its own ($k = 1$) counts as an uphill path. Let $U(G)$ be the smallest possible number of uphill paths, taken over all labellings of G . (IMO 2022 Problem 6 asks for U of the $n \times n$ grid graph; the answer is $2n^2 - 2n + 1$.) The d -dimensional hypercube Q_d has vertex set $\{0, 1\}^d$, and two vertices are adjacent

when they differ in exactly one coordinate; Q_d has 2^d vertices and $d \cdot 2^{d-1}$ edges. For C1 to C4, hand in the values and, for each value, an explicit labelling that attains it, as a list of the 2^d vertices in increasing label order, written as 0/1 strings.

Task. Determine $U(Q_3)$ and $U(Q_4)$, and give a labelling attaining each value.

Status. Solved, by hand. No computation is needed; the labellings were also counted mechanically (`code/uphill_eval.py`).

Answer and where it is proved.

- $U(Q_3) = 14$ and $U(Q_4) = 34$ (Theorem A.8); labellings in §A.8.
- The proof rests on an exact formula for the number of uphill paths (Proposition A.3). It gives $U(Q_d) \geq 2^d + (d-1)\nabla(Q_d)$ for every d , where ∇ is the decycling number (Theorem A.4). In the other direction, every even-weight code with minimum distance 4 gives a labelling (Proposition A.6).
- Sections A.1–A.6 hold for every d and are used by all the later cells of this problem.

A.1 Counting uphill paths

Fix a graph G and a labelling f . A *lower neighbour* of v is a neighbour w with $f(w) < f(v)$, and a *higher neighbour* is a neighbour w with $f(w) > f(v)$. Write $\text{out}(v)$ for the number of higher neighbours of v . So v is a valley if and only if it has no lower neighbour. Let $N(v) = N_f(v)$ be the number of uphill paths whose last vertex is v , and $P(f) = \sum_v N(v)$ the number of uphill paths. Then $U(G) = \min_f P(f)$.

Lemma A.1 (Recursion). *$N(v) = 1$ if v is a valley, and $N(v) = \sum_w N(w)$, summed over the lower neighbours w of v , otherwise. In particular $N(v) \geq 1$ for every v .*

Proof. If $(v_1, \dots, v_k)$ is an uphill path with $v_k = v$ and $k \geq 2$, then v_{k-1} is a lower neighbour of v and $(v_1, \dots, v_{k-1})$ is an uphill path ending at v_{k-1} . Conversely, if w is a lower neighbour of v , then every uphill path ending at w extends by v to an uphill path ending at v . These two maps are inverse to each other. The one-vertex sequence (v) is an uphill path if and only if v is a valley, and a valley has no lower neighbours. The inequality $N(v) \geq 1$ follows by induction on $f(v)$: a non-valley has at least one lower neighbour. $\square$

A.2 Vertices with a single uphill path

Put $S = S_f = \{v : N(v) = 1\}$ and $R = R_f = \{v : N(v) \geq 2\}$. Write $G[X]$ for the subgraph induced by X , and $e(X)$ for its number of edges.

Lemma A.2. (a) *If w is a lower neighbour of v , then $N(v) \geq N(w)$. A vertex of S that is not a valley has exactly one lower neighbour, and it lies in S .*

(b) *Every edge between $s \in S$ and $u \in R$ satisfies $f(s) < f(u)$. Every higher neighbour of a vertex of R lies in R .*

(c) *$G[S]$ is a forest. Every valley of G lies in S , and every component of $G[S]$ contains exactly one valley.*

Proof. (a) By Lemma A.1, $N(v)$ is a sum of terms ≥ 1 that includes $N(w)$. If $v \in S$ is not a valley, then this sum equals 1, so it has a single term, equal to 1.

(b) If $f(u) < f(s)$, then u is a lower neighbour of s and (a) gives $N(s) \geq N(u) \geq 2$, a contradiction. Likewise, a higher neighbour v of $u \in R$ has $N(v) \geq N(u) \geq 2$.

(c) Valleys have $N = 1$. Every edge of $G[S]$ has a higher end v , and by (a) the lower end is the unique lower neighbour of v . So $e(S)$ equals the number of non-valleys in S . Let K be a component of $G[S]$, with n_K vertices. Its vertex of smallest label has no lower neighbour in K . By (a) it has no lower neighbour in G at all, so it is a valley. Counting as above inside K , $e(K) = n_K - (\text{number of valleys in } K) \leq n_K - 1$. A connected graph has $e(K) \geq n_K - 1$. Hence K is a tree and contains exactly one valley. $\square$

A.3 An exact formula

Proposition A.3 (Exact formula). *For every graph G and every labelling f ,*

$$P(f) = |V(G)| + \sum_{u \in R} (\deg u - 1) + \sum_{u \in R} (N(u) - 2) \text{out}(u).$$

All terms of the last sum are ≥ 0 . In particular, if G is d -regular, then $P(f) \geq |V(G)| + (d-1)|R_f|$.

Proof. Sum the recursion of Lemma A.1 over all v . Each pair $(w, \text{higher neighbour } v \text{ of } w)$ contributes $N(w)$ once, so

$$P(f) = \#\{\text{valleys}\} + \sum_w N(w) \text{out}(w).$$

Let c be the number of components of $G[S]$. By Lemma A.2(c), there are c valleys and $e(S) = |S| - c$. For $w \in S$ we have $N(w) = 1$. Moreover, $\sum_{w \in S} \text{out}(w) = e(S) + e(S, R)$, because each edge inside S is counted at its lower end, each S - R edge is counted at its end in S (Lemma A.2(b)), and edges inside R are not counted. For $w \in R$, all higher neighbours lie in R (Lemma A.2(b)), so $\sum_{w \in R} \text{out}(w) = e(R)$. Using $e(S, R) = \sum_{u \in R} \deg u - 2e(R)$, we get

$$P(f) = c + (|S| - c) + e(S, R) + \sum_{u \in R} N(u) \text{out}(u) = |S| + \sum_{u \in R} \deg u + \sum_{u \in R} (N(u) - 2) \text{out}(u),$$

and $|S| = |V(G)| - |R|$. Finally $N(u) \geq 2$ on R . $\square$

A.4 Decycling sets

A set $R \subseteq V(G)$ is a *decycling set* (or feedback vertex set) if $G - R = G[V \setminus R]$ is a forest. The *decycling number* $\nabla(G)$ is the smallest size of a decycling set. By Lemma A.2(c), R_f is a decycling set for every labelling f .

Theorem A.4 (Lower bound). *If G is d -regular, then $U(G) \geq |V(G)| + (d-1)\nabla(G)$. In particular, $U(Q_d) \geq 2^d + (d-1)\nabla(Q_d)$ for every $d \geq 1$.*

Proof. Proposition A.3 and $|R_f| \geq \nabla(G)$. $\square$

Proposition A.5 (Upper bound). *Let G be d -regular and let R be a decycling set that is independent (no edge inside R). Then some labelling has exactly $|V(G)| + (d-1)|R|$ uphill paths. Consequently, if Q_d has an independent decycling set of size $\nabla(Q_d)$, then $U(Q_d) = 2^d + (d-1)\nabla(Q_d)$.*

Proof. Give the smallest labels to $V \setminus R$, tree by tree. Inside each tree of the forest $G - R$, use breadth-first order from a root. Then give the remaining labels to R , in any order. The neighbours of a vertex $v \notin R$ are its tree neighbours and some vertices of R , and the latter come later. In breadth-first order, a non-root vertex comes after its parent and before its children. So a root is a valley, and a non-root vertex has exactly one lower neighbour, its parent. By induction along the order, $N(v) = 1$ for all $v \notin R$. A vertex $u \in R$ has all its d neighbours outside R , all labelled earlier, so $N(u) = d$. The total is $(|V| - |R|) + d|R|$. The last sentence then follows from Theorem A.4. $\square$

A.5 Code labellings

For $x \in \{0, 1\}^d$, let $|x|$ be its weight (number of ones). Let E_d and O_d be the sets of vertices of even and of odd weight. Every edge of Q_d joins E_d to O_d , so both sets are independent and have size 2^{d-1} . The distance $|x \oplus y|$ of two vertices of E_d is even.

Proposition A.6 (Code labelling). *Let $d \geq 2$, and let $C \subseteq E_d$ have pairwise distances ≥ 4 . Consider the labelling L_C that lists first the vertices of C , then all of O_d , then $E_d \setminus C$ (each block in any order). It has exactly*

$$P(L_C) = 2^d + (d-1)(2^{d-1} - |C|)$$

uphill paths. Moreover, $E_d \setminus C$ is an independent decycling set of Q_d . Hence $\nabla(Q_d) \leq 2^{d-1} - |C|$ and $U(Q_d) \leq 2^d + (d-1)(2^{d-1} - |C|)$.

Proof. We use Lemma A.1. A codeword has only odd neighbours, all labelled later, so it is a valley: $N = 1$. The earlier neighbours of an odd vertex x are exactly its neighbours in C . Two of them would be at distance 2 from each other, so there is at most one. Hence $N(x) = 1$: either x is a valley, or it has a single lower neighbour, with $N = 1$. A vertex $y \in E_d \setminus C$ has d odd neighbours, all labelled earlier, so $N(y) = d$. Summing, $P = |C| + 2^{d-1} + d(2^{d-1} - |C|)$. In this labelling $R_{L_C} = E_d \setminus C$ (as $d \geq 2$), which is decycling by Lemma A.2(c) and independent since it lies in E_d . $\square$

A.6 A counting bound for the decycling number

Lemma A.7. *Let G be d -regular with n vertices and m edges, and let $R \neq V(G)$ be a decycling set. Let c be the number of components of $G - R$. Then*

$$(d-1)|R| = m - n + c + e(R) \geq m - n + 1.$$

For Q_d this reads $(d-1)|R| \geq (d-2)2^{d-1} + 1$.

Proof. $G - R$ is a forest with $n - |R|$ vertices and c components, so it has $n - |R| - c$ edges. The edges meeting R number $d|R| - e(R)$. Adding up gives $m = n - |R| - c + d|R| - e(R)$. $\square$

A.7 Q_3 and Q_4

Theorem A.8. $U(Q_3) = 14$ and $U(Q_4) = 34$. Also $\nabla(Q_3) = 3$ and $\nabla(Q_4) = 6$.

Proof. $d = 3$: Lemma A.7 gives $2\nabla(Q_3) \geq 5$, so $\nabla(Q_3) \geq 3$, and Theorem A.4 gives $U(Q_3) \geq 8 + 2 \cdot 3 = 14$. The code $C = \{000\}$ in Proposition A.6 gives a labelling with $8 + 2 \cdot (4 - 1) = 14$ uphill paths and a decycling set of size 3.

$d = 4$: Lemma A.7 gives $3\nabla(Q_4) \geq 17$, so $\nabla(Q_4) \geq 6$ and $U(Q_4) \geq 16 + 3 \cdot 6 = 34$. The code $C = \{0000, 1111\}$ (distance 4) gives $16 + 3 \cdot (8 - 2) = 34$ and a decycling set of size 6. $\square$

Remark A.9. An exhaustive check over all $8! = 40\,320$ labellings of Q_3 (`uphill_eval.py --brute 3`) also returns 14. The proof above does not use it. For $d = 2$ the same argument gives $U(Q_2) = U(C_4) = 5$. In words, Proposition A.3 says that an optimal labelling must make few vertices “expensive” ($N \geq 2$), and those vertices must still break every cycle. For an arbitrary graph, the edge count in the proof of Lemma A.7 reads $|E| = |S| - c + \sum_{u \in R} \deg u - e(R)$. Combined with Proposition A.3, it gives $P(f) \geq |E| + c + e(R) \geq |E| + 1$. This is the lower bound $2n^2 - 2n + 1$ of the grid problem [3].

A.8 The labellings

Vertices in increasing label order (the number before each row is the label of its first entry). The labellings are L_C of Proposition A.6: first the codewords, then the odd vertices, then the remaining even vertices, each block in increasing binary order.

Q_3 , $C = \{000\}$, 14 uphill paths:

1: 000 001 010 100 111 011 101 110

Q_4 , $C = \{0000, 1111\}$, 34 uphill paths:

1: 0000 1111 0001 0010 0100 0111 1000 1011

9: 1101 1110 0011 0101 0110 1001 1010 1100

Both counts were confirmed with the exact evaluator `code/uphill.eval.py`, which applies Lemma A.1 directly.

B Results used: Cell 2 ($U(Q_5)$), as handed in for that cell

Official setting. As in Cell 1 (§A.1): $U(G)$ is the least number of uphill paths over all labellings of G . Values are handed in together with an explicit labelling, listed as the 2^d vertices in increasing label order.

Task. Determine $U(Q_5)$, and give a labelling attaining it.

Status. Solved. The upper bound is by hand. The lower bound is **computer-assisted**: one SAT computation, below one second, repeated with two solvers.

Answer. $U(Q_5) = 88$, and $\nabla(Q_5) = 14$ (Theorem B.2). The labelling is in §B.2.

B.1 The decycling number of Q_5

The counting bound of Lemma A.7 gives only $4\nabla(Q_5) \geq 3 \cdot 16 + 1$, that is, $\nabla(Q_5) \geq 13$, and so $U(Q_5) \geq 84$. This bound is not attained.

Lemma B.1 (computer-assisted). *Q_5 has no decycling set with 13 or fewer vertices. Hence $\nabla(Q_5) \geq 14$.*

Method, and why the computation proves the lemma. This is claim (L5) of `code/uphill.lower.py`. The variables are x_v ($v \in V(Q_5)$), with x_v meaning $v \in R$. The formula F contains:

- (a) a CNF encoding (sequential counter) of $\sum_v x_v \leq 13$;
- (b) for every 4-cycle K of Q_5 , the clause $\bigvee_{v \in K} x_v$;
- (c) the clauses $\bigvee_{v \in K} x_v$ for cycles K found during the loop below.

Each clause of type (b) or (c) says that R meets the cycle K , and every decycling set does this. So every decycling set of size at most 13 satisfies F at every stage.

Loop. The solver returns a model R , or reports UNSAT. If it returns R , we compute $Q_5 - R$ with `networkx`. If this graph has a cycle, we add the clauses of a cycle basis of every cyclic component (type (c)) and ask again. The new clauses are violated by the current model, so no model is returned twice. Hence the loop ends, after finitely many rounds. It ends in one of two ways: a model R for which $Q_5 - R$ is a forest (a decycling set of size ≤ 13), or UNSAT.

Result. UNSAT, after 348 rounds in 0.4s with CaDiCaL 1.5.3, and after 357 rounds in 0.3s with Glucose 4, both through `python-sat`. Since every decycling set of size ≤ 13 would be a model, none exists. The only facts used are the correctness of the cardinality encoding and of the SAT solvers. Running two independent solvers guards against a solver bug. $\square$

Theorem B.2. $\nabla(Q_5) = 14$ and $U(Q_5) = 88$.

Proof. Lower bound: Lemma B.1 and Theorem A.4 give $U(Q_5) \geq 32 + 4 \cdot 14 = 88$. Upper bound: $C = \{00000, 11110\}$ lies in E_5 and has distance 4. By Proposition A.6, $E_5 \setminus C$ is a decycling set of size $16 - 2 = 14$, and the labelling L_C has $32 + 4 \cdot 14 = 88$ uphill paths. $\square$

Remark B.3. A set $C \subseteq E_5$ with pairwise distances ≥ 4 has at most two elements. Suppose it had three. Translating by one of them (an even vector, which preserves E_5 and all distances), we may assume $C = \{0, a, b\}$. Then $|a| = |b| = 4$, so a and b are 4-subsets of a 5-set and meet in at least 3 coordinates. This gives $|a \oplus b| \leq 2$, a contradiction. So Proposition A.6 cannot give less than 88, and Lemma B.1 shows that no labelling can.

B.2 The labelling

L_C with $C = \{00000, 11110\}$: codewords, then the 16 odd vertices, then the remaining 14 even vertices, each block in increasing binary order. It has 88 uphill paths (checked with `code/uphill_eval.py`).

```
1: 00000 11110 00001 00010 00100 00111 01000 01011
9: 01101 01110 10000 10011 10101 10110 11001 11010
17: 11100 11111 00011 00101 00110 01001 01010 01100
25: 01111 10001 10010 10100 10111 11000 11011 11101
```

C Results used: Cell 3 ($U(Q_6)$), as handed in for that cell

Official setting. As in Cell 1 (§A.1).

Task. Determine $U(Q_6)$, and give a labelling attaining it.

Status. Solved. The upper bound is by hand. The lower bound is **computer-assisted**: one SAT computation, about 10 s, repeated with two solvers.

Answer. $U(Q_6) = 204$, and $\nabla(Q_6) = 28$ (Theorem C.2). The labelling is in §C.2.

C.1 The decycling number of Q_6

Lemma A.7 gives $5\nabla(Q_6) \geq 4 \cdot 32 + 1$, that is, $\nabla(Q_6) \geq 26$. The true value is 28.

Lemma C.1 (computer-assisted). Q_6 has no decycling set with 27 or fewer vertices. Hence $\nabla(Q_6) \geq 28$.

Method. This is claim (L6) of `code/uphill_lower.py`. It uses the same counterexample-guided SAT loop as Lemma B.1, with $d = 6$ and bound $\sum_v x_v \leq 27$. The argument there shows that every decycling set of size ≤ 27 satisfies the formula at every stage, and that the loop ends. The result is UNSAT: after 685 rounds in about 10 s with CaDiCaL 1.5.3, and after 689 rounds in about 8 s with Glucose 4. $\square$

Theorem C.2. $\nabla(Q_6) = 28$ and $U(Q_6) = 204$.

Proof. Lower bound: by Lemma C.1 and Theorem A.4, $U(Q_6) \geq 64 + 5 \cdot 28 = 204$. Upper bound: let

$$C = \{000000, 111100, 110011, 001111\},$$

the linear code spanned by 111100 and 110011. All its nonzero words have weight 4, so its pairwise distances are 4. By Proposition A.6, $E_6 \setminus C$ is a decycling set of size $32 - 4 = 28$, and L_C has $64 + 5 \cdot 28 = 204$ uphill paths. $\square$

Remark C.3. Cell 5 needs a stronger fact: every decycling set of Q_6 of size 28 lies inside E_6 or inside O_6 . This is Lemma E.2, claim (P6) of the same script. It is stated and proved there, where it is used.

C.2 The labelling

L_C for the code C above: the 4 codewords, then the 32 odd vertices, then the remaining 28 even vertices, each block in increasing binary order. It has 204 uphill paths (checked with `code/uphill_eval.py`).

```

1: 000000 001111 110011 111100 000001 000010 000100 000111
9: 001000 001011 001101 001110 010000 010011 010101 010110
17: 011001 011010 011100 011111 100000 100011 100101 100110
25: 101001 101010 101100 101111 110001 110010 110100 110111
33: 111000 111011 111101 111110 000011 000101 000110 001001
41: 001010 001100 010001 010010 010100 010111 011000 011011
49: 011101 011110 100001 100010 100100 100111 101000 101011
57: 101101 101110 110000 110101 110110 111001 111010 111111

```

D Results used: Cell 4 ($U(Q_7)$ and $U(Q_8)$), as handed in for that cell

Official setting. As in Cell 1 (§A.1).

Task. Determine $U(Q_7)$ and $U(Q_8)$, and give a labelling attaining each value.

Status. Solved. The proof is by hand from $\nabla(Q_6) = 28$ (Cell 3). That fact is computer-assisted, so this cell inherits its computation (Lemma C.1) and needs no new one.

Answer. $U(Q_7) = 464$ and $U(Q_8) = 1040$; $\nabla(Q_7) = 56$ and $\nabla(Q_8) = 112$ (Theorem D.2). The labellings are in §D.3.

D.1 Doubling

Lemma D.1 (Doubling). $\nabla(Q_d) \geq 2 \nabla(Q_{d-1})$ for every $d \geq 2$.

Proof. Fixing the last coordinate splits Q_d into two disjoint induced copies of Q_{d-1} . If R is a decycling set of Q_d , then the part of R in each copy is a decycling set of that copy: an induced subgraph of a forest is a forest. So each copy contains at least $\nabla(Q_{d-1})$ vertices of R . $\square$

Theorem D.2. $\nabla(Q_7) = 56$, $\nabla(Q_8) = 112$, $U(Q_7) = 464$ and $U(Q_8) = 1040$.

Proof. Lower bounds: by Lemma C.1 and Lemma D.1, $\nabla(Q_7) \geq 2 \cdot 28 = 56$ and $\nabla(Q_8) \geq 2 \cdot 56 = 112$. By Theorem A.4, $U(Q_7) \geq 128 + 6 \cdot 56 = 464$ and $U(Q_8) \geq 256 + 7 \cdot 112 = 1040$.

Upper bounds: let $C_7 \subseteq \{0,1\}^7$ be the linear code spanned by 1111000, 1100110 and 1010101. Its 7 nonzero words are the sums of nonempty subsets of the generators:

1111000, 1100110, 1010101, 0011110, 0101101, 0110011, 1001011.

All have weight 4. So $C_7 \subseteq E_7$, $|C_7| = 8$ and all distances are 4 (this is the simplex code, i.e. the dual of the Hamming code of length 7). Let $C_8 \subseteq \{0,1\}^8$ be the extended Hamming code, spanned by 11110000, 11001100, 10101010 and 11111111. Its 16 words are $C'_7 \cup (C'_7 \oplus 11111111)$, where C'_7 is the set of words of C_7 with a 0 appended. The words of C'_7 have weights 0 and 4, and their complements have weights 8 and 4. The distance between x and $y \oplus 11111111$, for $x, y \in C'_7$, is $8 - |x \oplus y| \in \{8, 4\}$. So $C_8 \subseteq E_8$ has minimum distance 4 and $|C_8| = 16$. Proposition A.6 gives decycling sets of sizes $64 - 8 = 56$ and $128 - 16 = 112$, and labellings with $128 + 6 \cdot 56 = 464$ and $256 + 7 \cdot 112 = 1040$ uphill paths. $\square$

D.2 Summary for $d \leq 8$

Corollary D.3. For $2 \leq d \leq 8$, $U(Q_d) = 2^d + (d-1)\nabla(Q_d) = 2^d + (d-1)(2^{d-1} - K_d)$, where K_d is the size of the code used:

d	2	3	4	5	6	7	8
K_d	1	1	2	2	4	8	16
$\nabla(Q_d)$	1	3	6	14	28	56	112
$U(Q_d)$	5	14	34	88	204	464	1040
counting bound $\lceil \frac{(d-2)2^{d-1}+1}{d-1} \rceil$	1	3	6	13	26	54	110

In every case the optimum is attained by a code labelling L_C , and the set R_f of expensive vertices is one parity class minus a code.

Proof. $d = 2$ and $d = 3, 4$: Cell 1. $d = 5$: Cell 2. $d = 6$: Cell 3. $d = 7, 8$: Theorem D.2. $\square$

Remark D.4. The values $K_d = 1, 1, 2, 2, 4, 8, 16$ are the maximum sizes $A(d-1, 3)$ of binary codes of length $d-1$ and minimum distance 3. Adding a parity bit turns such a code into a code in E_d with minimum distance 4, and conversely. The proofs above do not use this. For $d = 9$ the same formula would give $\nabla(Q_9) \leq 256 - A(8, 3) = 236$, because $A(8, 3) = 20$ [4]. This is the starting point of Cells 5 and 6.

D.3 The labellings

In both lists: the codewords, then all odd vertices, then the remaining even vertices, each block in increasing binary order. The counts (464 and 1040) were checked with `code/uphill_eval.py`.

Q_7 , $C = C_7$ (8 codewords), 464 uphill paths:

```

1: 0000000 0011110 0101101 0110011 1001011 1010101 1100110 1111000
9: 0000001 0000010 0000100 0000111 0001000 0001011 0001101 0001110
17: 0010000 0010011 0010101 0010110 0011001 0011010 0011100 0011111
25: 0100000 0100011 0100101 0100110 0101001 0101010 0101100 0101111
33: 0110001 0110010 0110100 0110111 0111000 0111011 0111101 0111110
41: 1000000 1000011 1000101 1000110 1001001 1001010 1001100 1001111
49: 1010001 1010010 1010100 1010111 1011000 1011011 1011101 1011110
57: 1100001 1100010 1100100 1100111 1101000 1101011 1101101 1101110
65: 1110000 1110011 1110101 1110110 1111001 1111010 1111100 1111111
73: 0000011 0000101 0000110 0001001 0001010 0001100 0001111 0010001
81: 0010010 0010100 0010111 0011000 0011011 0011101 0100001 0100010
89: 0100100 0100111 0101000 0101011 0101110 0110000 0110101 0110110
97: 0111001 0111010 0111100 0111111 1000001 1000010 1000100 1000111
105: 1001000 1001101 1001110 1010000 1010011 1010110 1011001 1011010
113: 1011100 1011111 1100000 1100011 1100101 1101001 1101010 1101100
121: 1101111 1110001 1110010 1110100 1110111 1111011 1111101 1111110

```

Q_8 , $C = C_8$ (16 codewords), 1040 uphill paths:

```

1: 00000000 00001111 00110011 00111100 01010101 01011010 01100110 01101001 10010110
10: 10011001 10100101 10101010 11000011 11001100 11110000 11111111 00000001 00000010
19: 00000100 00000111 00001000 00001011 00001101 00001110 00010000 00010011 00010101
28: 00010110 00011001 00011010 00011100 00011111 00100000 00100011 00100101 00100110
37: 00101001 00101010 00101100 00101111 00110001 00110010 00110100 00110111 00111000
46: 00111011 00111101 00111110 01000000 01000011 01000101 01000110 01001001 01001010
55: 01001100 01001111 01010001 01010010 01010100 01010111 01011000 01011011 01011101
64: 01011110 01100001 01100010 01100100 01100111 01101000 01101011 01101101 01101110
73: 01110000 01110011 01110101 01110110 01111001 01111010 01111100 01111111 10000000
82: 10000011 10000101 10000110 10001001 10001010 10001100 10001111 10010001 10010010
91: 10010100 10010111 10011000 10011011 10011101 10011110 10100001 10100010 10100100
100: 10100111 10101000 10101011 10101101 10101110 10110000 10110011 10110101 10110110
109: 10111001 10111010 10111100 10111111 11000001 11000010 11000100 11000111 11001000
118: 11001011 11001101 11001110 11010000 11010011 11010101 11010110 11011001 11011010

```

```

127: 11011100 11011111 11100000 11100011 11100101 11100110 11101001 11101010 11101100
136: 11101111 11110001 11110010 11110100 11110111 11111000 11111011 11111101 11111110
145: 00000011 00000101 00000110 00001001 00001010 00001100 00010001 00010010 00010100
154: 00010111 00011000 00011011 00011101 00011110 00100001 00100010 00100100 00100111
163: 00101000 00101011 00101101 00101110 00110000 00110101 00110110 00111001 00111010
172: 00111111 01000001 01000010 01000100 01000111 01001000 01001011 01001101 01001110
181: 01010000 01010011 01010110 01011001 01011100 01011111 01100000 01100011 01100101
190: 01101010 01101100 01101111 01110001 01110010 01110100 01110111 01111000 01111011
199: 01111101 01111110 10000001 10000010 10000100 10000111 10001000 10001011 10001101
208: 10001110 10010000 10010011 10010101 10011010 10011100 10011111 10100000 10100011
217: 10100110 10101001 10101100 10101111 10110001 10110010 10110100 10110111 10111000
226: 10111011 10111101 10111110 11000000 11000101 11000110 11001001 11001010 11001111
235: 11010001 11010010 11010100 11010111 11011000 11011011 11011101 11011110 11100001
244: 11100010 11100100 11100111 11101000 11101011 11101101 11101110 11110011 11110101
253: 11110110 11111001 11111010 11111100

```

E Results used: Cell 5 (bounds for $U(Q_9)$), as handed in for that cell

Official setting. As in Cell 1 (§A.1). For C5, hand in either a labelling of Q_9 in the same format (its uphill paths are counted mechanically) or a proof of the lower bound.

Task. Give bounds for $U(Q_9)$: a labelling of Q_9 , or a proof of a lower bound.

Status. **Solved** in the sense of the cell: we hand in *both* parts.

- A labelling with 2400 uphill paths (§E.4; by hand, and counted mechanically).
- A proof that every labelling has at least 2328 uphill paths (Theorem E.5). It is **computer-assisted**: it uses two SAT facts about Q_6 , (L6) and (P6), which take about 2 minutes. The rest is by hand.

The exact value is open (Cell 6).

Answer.

$$2328 \leq U(Q_9) \leq 2400, \quad 227 \leq \nabla(Q_9) \leq 236.$$

For comparison, the counting bound of Lemma A.7 gives $\nabla(Q_9) \geq \lceil 1793/8 \rceil = 225$, that is, $U(Q_9) \geq 2312$. Doubling (Lemma D.1) gives only $\nabla(Q_9) \geq 224$.

E.1 Upper bound

Proposition E.1. *Let $C_9 \subseteq E_9$ be the following 20 words:*

```

000000000 000101011 000110101 001000111 001011100 001110010 010001101
010111110 011011011 011101000 100011010 100101100 101001001 101111111
110010111 110100010 110111001 111001110 111010000 111100101

```

Every word has even weight, and any two words are at distance ≥ 4 . Hence $\nabla(Q_9) \leq 256 - 20 = 236$, and the labelling L_{C_9} has $512 + 8 \cdot 236 = 2400$ uphill paths.

Proof. The two properties of C_9 are finite checks (all $\binom{20}{2} = 190$ distances), done by `code/uphill_construct.py`. The rest is Proposition A.6. The count 2400 of the listed labelling was also obtained with the evaluator `code/uphill_eval.py`. $\square$

C_9 was found by a SAT search for 20 even words at pairwise distance ≥ 4 . Twenty is the maximum, because $A(8, 3) = 20$ [4]; we do not use this.

E.2 Three lemmas

For a vertex x let $N(x)$ be its set of neighbours, and for $X \subseteq V$ let $N(X) = \bigcup_{x \in X} N(x)$. (Here N is not the path count of Cell 1; that count does not appear in this section.) e_i is the i -th unit vector.

Lemma E.2 (computer-assisted). *Every decycling set of Q_6 with 28 vertices lies inside E_6 or inside O_6 .*

Method. This is claim (P6) of `code/uphill_lower.py`. It runs the counterexample-guided SAT loop of Lemma B.1, with $d = 6$, the bound $\sum_v x_v \leq 28$, and two more clauses: $\bigvee_{v \in O_6} x_v$ and $\bigvee_{v \in E_6} x_v$. Every decycling set of size ≤ 28 that meets both parity classes satisfies the formula at every stage. The solver (CaDiCaL 1.5.3) answers UNSAT after 6053 rounds, in about 105 s. So no such set exists. $\square$

Lemma E.3 (Delsarte bound). *If $C \subseteq E_9$ has pairwise distances ≥ 4 , then $|C| \leq 25$.*

Proof. For $0 \leq k \leq 9$ and $x \in \{0, 1\}^9$ with $|x| = i$, put $K_k(i) = \sum_{|w|=k} (-1)^{x \cdot w} = \sum_j (-1)^j \binom{i}{j} \binom{9-i}{k-j}$. The second expression follows by counting the words w with j ones inside the support of x . Let $A_i = |C|^{-1} \#\{(a, b) \in C^2 : |a \oplus b| = i\}$. Then $A_0 = 1$, $\sum_i A_i = |C|$, and $A_i = 0$ for $i \notin \{0, 4, 6, 8\}$, since distances in E_9 are even. For each k ,

$$|C| \sum_i A_i K_k(i) = \sum_{a, b \in C} \sum_{|w|=k} (-1)^{(a \oplus b) \cdot w} = \sum_{|w|=k} \left(\sum_{a \in C} (-1)^{a \cdot w} \right)^2 \geq 0.$$

The values needed are

i	0	4	6	8
$K_1(i)$	9	1	-3	-7
$K_2(i)$	36	-4	0	20
$K_3(i)$	84	-4	8	-28

so $\Lambda = (6K_1 + 3K_2 + K_3)/10$ takes the values 24.6, -1, -1, -1 at $i = 0, 4, 6, 8$. Adding the three inequalities with weights 6, 3, 1 gives $0 \leq \sum_i A_i \Lambda(i) = 24.6 - (A_4 + A_6 + A_8) = 24.6 - (|C| - 1)$. So $|C| \leq 25.6$. $\square$

The certificate (6, 3, 1)/10 is the optimal dual solution of Delsarte's linear program [4]. The table is recomputed exactly by claim (D9) of `code/uphill_lower.py`.

Fix a set D of three coordinates. For $a \in \{0, 1\}^D$, the copy $Q^{D,a} = \{x : x|_D = a\}$ induces a Q_6 . The eight copies partition $V(Q_9)$. Two copies are *adjacent* if their indices a differ in one coordinate j ; then $x \mapsto x \oplus e_j$ maps one copy onto the other. The parity of x in Q_9 is its parity inside the copy plus $|a|$. So each parity class of a copy lies in E_9 or in O_9 .

Lemma E.4. *Let R be a decycling set of Q_9 , and let $Q^{D,a}, Q^{D,a'}$ be adjacent copies. Suppose that each contains exactly 28 vertices of R , and that each of the two sets is contained in a parity class of Q_9 . Then it is the same parity class for both.*

Proof. Suppose $R \cap Q^{D,a} \subseteq E_9$ and $R \cap Q^{D,a'} \subseteq O_9$, and let $S = V \setminus R$. In $Q^{D,a}$, S contains the 32 odd vertices and 4 even ones. Each even vertex has 6 neighbours in the copy, all odd, so $S \cap Q^{D,a}$ spans 24 edges. Likewise $S \cap Q^{D,a'}$ has 36 vertices and spans 24 edges. The map $x \mapsto x \oplus e_j$ sends the 32 odd vertices of $Q^{D,a}$ onto the 32 even vertices of $Q^{D,a'}$. All 64 lie in S , which gives 32 more edges inside S . So $S \cap (Q^{D,a} \cup Q^{D,a'})$ has 72 vertices and at least 80 edges, and it is not a forest. But it is an induced subgraph of the forest $Q_9 - R$. $\square$

E.3 Lower bound

Theorem E.5. $\nabla(Q_9) \geq 227$. Consequently $U(Q_9) \geq 512 + 8 \cdot 227 = 2328$.

Proof. The second statement follows from the first by Theorem A.4. Let R be a decycling set of Q_9 with $r = |R| \leq 226$; we derive a contradiction. By Lemma A.7, $8r \geq 7 \cdot 256 + 1$, so $r \geq 225$. Write $r = 224 + s$ with $s \in \{1, 2\}$, and let $S = V \setminus R$.

Step 1: light and heavy copies. Fix D . For each a , $R \cap Q^{D,a}$ is a decycling set of the copy, so it has at least 28 elements (Lemma C.1). The eight numbers add up to $224 + s$. So at most s copies are *heavy* (more than 28), and at least $8 - s \geq 6$ are *light* (exactly 28). By Lemma E.2, R meets a light copy inside a single parity class of the copy, hence inside E_9 or inside O_9 : we call this the *type* of the copy.

Step 2: one type. Seen as vertices of $Q_3 = \{0, 1\}^D$, the light copies of D are what remains after deleting at most two vertices. Q_3 is 3-connected, so this set is connected. By Lemma E.4, all light copies of D have the same type τ_D . If $\tau_D \neq \tau_{D'}$ for two choices of D , then R contains at least $6 \cdot 28 = 168$ vertices of each parity, so $r \geq 336$, which is false. So all light copies, for all D , have the same type. The translation $x \mapsto x \oplus e_1$ is an automorphism of Q_9 that exchanges E_9 and O_9 , so we may assume that this type is even.

Step 3: the odd part. Let $Z = R \cap O_9$ and $C = E_9 \setminus R = S \cap E_9$. Then $R = (E_9 \setminus C) \cup Z$, so $r = 256 - |C| + |Z|$, that is,

$$|C| - |Z| = 32 - s \geq 30. \quad (1)$$

Light copies meet R only in even vertices, so for every D the set Z lies in the union of the heavy copies of D . If $s = 1$, there is one heavy copy for each D . Any coordinate i belongs to some D , so all elements of Z agree in every coordinate, and $|Z| \leq 1$. If $s = 2$, suppose $z_1, z_2, z_3 \in Z$ are distinct. Pick coordinates i, j, k with $(z_1)_i \neq (z_2)_i$, $(z_1)_j \neq (z_3)_j$ and $(z_2)_k \neq (z_3)_k$, and a 3-set $D \supseteq \{i, j, k\}$. Then z_1, z_2, z_3 lie in three different copies of D , all heavy. That is more than $s = 2$. So $|Z| \leq s$ in both cases.

Step 4: C is almost a code. Note that $S \supseteq O_9 \setminus Z$.

- (i) Let $C_0 = C \setminus N(Z)$ and $a \neq b \in C_0$. If $|a \oplus b| = 2$, then a and b have exactly two common neighbours p, q , both odd. Neither lies in Z , since otherwise $a \in N(Z)$. So $p, q \in S$, and a, p, b, q is a 4-cycle in $Q_9 - R$, which is impossible. So C_0 has pairwise distances ≥ 4 , and $|C_0| \leq 25$ by Lemma E.3.
- (ii) Let $z \in Z$ and $I = \{i : z \oplus e_i \in C\}$, so that $|C \cap N(z)| = |I|$. For $i \neq j$ in I , the vertices $a_i = z \oplus e_i$ and $a_j = z \oplus e_j$ have the common neighbours z and $w_{ij} = z \oplus e_i \oplus e_j$. The latter is odd, and it lies in S unless $w_{ij} \in Z$. Let H be the graph on I with an edge ij whenever $w_{ij} \in S$. A cycle $i_1 i_2 \dots i_m i_1$ in H ($m \geq 3$) gives the cycle $a_{i_1}, w_{i_1 i_2}, a_{i_2}, \dots, a_{i_m}, w_{i_m i_1}$ in $Q_9 - R$. Its vertices are distinct: the a 's are even, the w 's are odd, and w_{ij} determines $\{i, j\}$. So H is a forest. Now $w_{ij} \in Z \setminus \{z\}$ for at most $|Z| - 1$ pairs, so H is the complete graph on I minus at most $|Z| - 1 \leq 1$ edges. A forest on $|I|$ vertices has at most $|I| - 1$ edges. So $\binom{|I|}{2} \leq |I| - 1$ if $|Z| = 1$, which gives $|I| \leq 2$; and $\binom{|I|}{2} - 1 \leq |I| - 1$ if $|Z| = 2$, which gives $|I| \leq 3$.

Hence $|C| \leq |C_0| + \sum_{z \in Z} |C \cap N(z)|$, which is at most 25, $25 + 2 = 27$ or $25 + 2 \cdot 3 = 31$ for $|Z| = 0, 1, 2$.

Step 5: contradiction. By (1), $|C| \geq 30 + |Z|$, which is 30, 31 or 32 for $|Z| = 0, 1, 2$. In each case this exceeds the bound of Step 4. $\square$

Remark E.6 (Where the argument stops). For $s = 3$, Step 2 fails as written: deleting the three neighbours of a vertex disconnects Q_3 , so one light copy may have the other type. Step 4 is also wasteful. Lemma E.3 gives 25, while the true maximum is 20. Going further would need a finer analysis of the heavy copies. We did not complete it; see Cell 6.

E.4 The labelling of Q_9

LC_9 : the 20 codewords of Proposition E.1, then the 256 odd vertices, then the remaining 236 even vertices, each block in increasing binary order. It has 2400 uphill paths (counted with `code/uphill_eval.py`; the file is `uphill/labellings/Q9.txt`).

```

1: 000000000 000101011 000110101 001000111 001011100 001110010 010001101 010111110 011011011 011101000
11: 100011010 100101100 101001001 101111111 110010111 110100010 110111001 111001110 111010000 111100101
21: 000000001 000000010 000000100 000000111 000001000 000001011 000001101 000001110 000010000 000010011
31: 000010101 000010110 000011001 000011010 000011100 000011111 000100000 000100011 000100101 000100110
41: 000101001 000101010 000101100 000101111 000110001 000110010 000110100 000110111 000111000 000111011
51: 000111101 000111110 001000000 001000011 001000101 001000110 001001001 001001010 001001100 001001111
61: 001010001 001010010 001010100 001010111 001011000 001011011 001011101 001011110 001100001 001100010
71: 001100100 001100111 001101000 001101011 001101101 001101110 001110000 001110011 001110101 001110110
81: 001111001 001111010 001111100 001111111 010000000 010000011 010000101 010000110 010001001 010001010
91: 010001100 010001111 010010001 010010010 010010100 010010111 010011000 010011011 010011101 010011110
101: 010100001 010100010 010100100 010100111 010101000 010101011 010101101 010101110 010110000 010110011
111: 010110101 010110110 010111001 010111010 010111100 010111111 011000001 011000010 011000100 011000111
121: 011001000 011001011 011001101 011001110 011010000 011010011 011010101 011010110 011011001 011011010
131: 011011100 011011111 011100000 011100011 011100101 011100110 011101001 011101010 011101100 011101111
141: 011110001 011110010 011110100 011110111 011111000 011111011 011111101 011111110 100000000 100000011
151: 100000101 100000110 100001001 100001010 100001100 100001111 100010001 100010010 100010100 100010111
161: 100011000 100011011 100011101 100011110 100100001 100100010 100100100 100100111 100101000 100101011
171: 100101101 100101110 100110000 100110011 100110101 100110110 100111001 100111010 100111100 100111111
181: 101000001 101000010 101000100 101000111 101001000 101001011 101001101 101001110 101010000 101010011
191: 101010101 101010110 101011001 101011010 101011100 101011111 101100000 101100011 101100101 101100110
201: 101101001 101101010 101101100 101101111 101110001 101110010 101110100 101110111 101111000 101111011
211: 101111101 101111110 110000001 110000010 110000100 110000111 110001000 110001011 110001101 110001110
221: 110010000 110010011 110010101 110010110 110011001 110011010 110011100 110011111 110100000 110100011
231: 110100101 110100110 110101001 110101010 110101100 110101111 110110001 110110010 110110100 110110111
241: 110111000 110111011 110111101 110111110 111000000 111000011 111000101 111000110 111001001 111001010
251: 111001100 111001111 111010001 111010010 111010100 111010111 111011000 111011011 111011101 111011110
261: 111100001 111100010 111100100 111100111 111101000 111101011 111101101 111101110 111110000 111110011
271: 111110101 111110110 111111001 111111010 111111100 111111111 000000011 000000101 000000110 000000101
281: 000001010 000001100 000001111 000010001 000010010 000010100 000010111 000011000 000011011 000011101
291: 000011110 000100001 000100010 000100100 000100111 000101000 000101101 000101110 000110000 000110011
301: 000110110 000111001 000111010 000111100 000111111 001000001 001000010 001000100 001001000 001001011
311: 001001101 001001110 001010000 001010011 001010101 001010110 001011001 001011010 001011111 001100000
321: 001100011 001100101 001100110 001101001 001101010 001101100 001101111 001110001 001110100 001110111
331: 001111000 001111011 001111101 001111110 010000001 010000010 010000100 010000111 010001000 010001011
341: 010001110 010010000 010010011 010010101 010010110 010011001 010011010 010011100 010011111 010100000
351: 010100011 010100101 010100110 010101001 010101010 010101100 010101111 010110001 010110010 010110100
361: 010110111 010111000 010111011 010111101 011000000 011000011 011000101 011000110 011001001 011001010
371: 011001100 011001111 011010001 011010010 011010100 011010111 011011000 011011101 011011110 011100001
381: 011100010 011100100 011100111 011101011 011101101 011101110 011110000 011110011 011110101 011110110
391: 011111001 011111010 011111100 011111111 100000001 100000010 100000100 100000111 100001000 100001011
401: 100001101 100001110 100010000 100010011 100010101 100010110 100011001 100011100 100011111 100100000
411: 100100011 100100101 100100110 100101001 100101010 100101111 100110001 100110010 100110100 100110111
421: 100111000 100111011 100111101 100111110 101000000 101000011 101000101 101000110 101001010 101001100
431: 101001111 101010001 101010010 101010100 101010111 101011000 101011011 101011101 101011110 101100001
441: 101100010 101100100 101100111 101101000 101101011 101101101 101101110 101110000 101110011 101110101
451: 101110110 101111001 101111010 101111100 110000000 110000011 110000101 110000110 110001001 110001010
461: 110001100 110001111 110010001 110010010 110010100 110011000 110011011 110011101 110011110 110100001
471: 110100100 110100111 110101000 110101011 110101101 110101110 110110000 110110011 110110101 110110110
481: 110110101 110111100 110111111 111000001 111000010 111000100 111000111 111001000 111001011 111001101
491: 111010011 111010101 111010110 111011001 111011010 111011100 111011111 111100000 111100011 111100110
501: 111101001 111101010 111101100 111101111 111110001 111110010 111110100 111110111 111111000 111111011
511: 111111101 111111110

```

References

- [1] S. Bau, L. W. Beineke, The decycling number of graphs, *Australas. J. Combin.* 25 (2002) 285–298.
- [2] P. Focardi, F. L. Luccio, D. Peleg, Feedback vertex set in hypercubes, *Inform. Process. Lett.* 76 (2000) 1–5.
- [3] International Mathematical Olympiad 2022, Problem 6 (uphill paths in a Nordic square).
- [4] F. J. MacWilliams, N. J. A. Sloane, *The Theory of Error-Correcting Codes*, North-Holland, 1977.

- [5] D. A. Pike, Decycling hypercubes, *Graphs Combin.* 19 (2003) 547–550.