



Department of Mathematics, University of Udine

Support Vector Machines and their use in IR

Lorenzo Zanolin.

lorenzo.zanolin@spes.uniud.it

May x, 2023




- 1 SVM over linearly separable data
- 2 SVM over non linearly separable data
- 3 SVM use in IR



Vector Space


Suppose you have to classify whether a document is *relevant* or not. We can think to use *terms* as features to divide properly the data. We will use a *t-dimensional* vector space to represent our documents.

Suppose you have to classify whether a document is *relevant* or not. We can think to use *terms* as features to divide properly the data. We will use a *t-dimensional* vector space to represent our documents.




For simplicity, we can reason using a 2D Space.

Data can be separated using a *decision boundary*, which is an *hyperplane*.



For simplicity, we can reason using a 2D Space.
Data can be separated using a *decision boundary*, which is an *hyperplane*.





Support Vectors

In the previous example the *decision boundary* is a line, represented by the equation $a + bt_1 + ct_2 = 0$.


We can introduce two *parallels* hyperplanes (lines) to the decision boundary, called *support vectors* whose equations are

$$\begin{cases} a + bt_1 + ct_2 = 1 \\ a + bt_1 + ct_2 = -1 \end{cases} \quad (1)$$

In the previous example the *decision boundary* is a line, represented by the equation $a + bt_1 + ct_2 = 0$.

We can introduce two *parallels* hyperplanes (lines) to the decision boundary, called *support vectors* whose equations are

$$\begin{cases} a + bt_1 + ct_2 = 1 \\ a + bt_1 + ct_2 = -1 \end{cases} \quad (1)$$





For convenience, we can rewrite the three equations using *vectorization* notation.

$$\begin{cases} b^T t + a = 0 \\ b^T t + a = \pm 1 \end{cases} \quad (2)$$

For convenience, we can rewrite the three equations using *vectorization* notation.

$$\begin{cases} b^T t + a = 0 \\ b^T t + a = \pm 1 \end{cases} \quad (2)$$

Intuitively, we can define the *margin* of the two support vectors as the distance between them.





For convenience, we can rewrite the three equations using *vectorization* notation.

$$\begin{cases} b^T t + a = 0 \\ b^T t + a = \pm 1 \end{cases} \quad (2)$$

Intuitively, we can define the *margin* of the two support vectors as the distance between them.


Consider an arbitrary point x_1 that lies on support vector s_1 . Since s_1, s_2 are parallel, consider the closest point to x_1 belonging to s_2 , say x_2 .





Their distance is $\lambda \|b\| = \frac{2}{\sqrt{b^T b}}$.

Vector λb represents the distance between the two margins.



Their distance is $\lambda \|b\| = \frac{2}{\sqrt{b^T b}}$.

Vector λb represents the distance between the two margins.

SVM [2, 1] are used to find the *maximum margin linear classifier*, thus we want to maximize the margin.

Remembering we want to classify documents, our goal is to find specific b s.t. given a document x belonging to class y the decision boundary behave the following:

$$\begin{cases} b^T x + a \geq 1 & \text{if } y = 1 \\ b^T x + a \leq -1 & \text{if } y = -1 \end{cases} \quad (3)$$

Remembering we want to classify documents, our goal is to find specific b s.t. given a document x belonging to class y the decision boundary behave the following:

$$\begin{cases} b^T x + a \geq 1 & \text{if } y = 1 \\ b^T x + a \leq -1 & \text{if } y = -1 \end{cases} \quad (3)$$

We can define the *cost function* as a system of equations.

$$\begin{cases} \min_{b,a} \frac{\sqrt{b^T b}}{2} \\ \text{subject to } y_i(b^T x_i + a) \geq 1 \quad \forall x_i \end{cases} \quad (4)$$



Soft-Margin

In real world problem it is not likely to get an exactly separate line dividing the data within the space. It would be better for the smooth boundary to ignore few data points than be curved or go in loops, around the outliers.



In real world problem it is not likely to get an exactly separate line dividing the data within the space. It would be better for the smooth boundary to ignore few data points than be curved or go in loops, around the outliers.

So, we will use *slack variables* to introduce a penalty for each misclassified point.



In real world problem it is not likely to get an exactly separate line dividing the data within the space. It would be better for the smooth boundary to ignore few data points than be curved or go in loops, around the outliers.

So, we will use *slack variables* to introduce a penalty for each misclassified point.

The new cost function will be

$$\begin{cases} \min_{b,a} \frac{\sqrt{b^T b}}{2} + C \sum_i \xi_i \\ \text{subject to } y_i(b^T x_i + a) \geq 1 - \xi_i \quad \text{and } \xi_i > 0 \quad \forall x_i \end{cases} \quad (5)$$




The larger is C the stricter the classification is, since a larger C will give more evidence to slack variables.

$$\begin{cases} \min_{b,a} \frac{\sqrt{b^T b}}{2} + C \sum_i \xi_i \\ \text{subject to} & y_i(b^T x_i + a) \geq 1 - \xi_i \quad \text{and } \xi_i > 0 \quad \forall x_i \end{cases} \quad (6)$$

The larger is C the stricter the classification is, since a larger C will give more evidence to slack variables.

$$\begin{cases} \min_{b,a} \frac{\sqrt{b^T b}}{2} + C \sum_i \xi_i \\ \text{subject to } y_i(b^T x_i + a) \geq 1 - \xi_i \quad \text{and } \xi_i > 0 \quad \forall x_i \end{cases} \quad (6)$$






Non linearly separable data

What if our data is not linearly separable?


Non linearly separable data

What if our data is not linearly separable? It should be better to reason in a bigger dimensional space.



Non linearly separable data

What if our data is not linearly separable? It should be better to reason in a bigger dimensional space.



But augmenting dimensions costs a lot...



Kernel Trick

Consider the function $\phi : \mathbb{R}^3 \mapsto \mathbb{R}^{10}$ used to map points in a new vector space. Calculating the *similarity* $\phi(x_i)^T \phi(x_j)$ between each point may be intractable.



Kernel Trick

Consider the function $\phi : \mathbb{R}^3 \mapsto \mathbb{R}^{10}$ used to map points in a new vector space. Calculating the *similarity* $\phi(x_i)^T \phi(x_j)$ between each point may be intractable.

Here *Kernel Trick* [4] comes handy.



Consider the function $\phi : \mathbb{R}^3 \mapsto \mathbb{R}^{10}$ used to map points in a new vector space. Calculating the *similarity* $\phi(x_i)^T \phi(x_j)$ between each point may be intractable.

Here *Kernel Trick* [4] comes handy.

It consists of a simple linear algebra reformulation,

$$\phi(x_i)^T \phi(x_j) = K(x_i, x_j) = (1 + x_i^T x_j)^2. \quad (7)$$



Consider the function $\phi : \mathbb{R}^3 \mapsto \mathbb{R}^{10}$ used to map points in a new vector space. Calculating the *similarity* $\phi(x_i)^T \phi(x_j)$ between each point may be intractable.

Here *Kernel Trick* [4] comes handy.

It consists of a simple linear algebra reformulation,

$$\phi(x_i)^T \phi(x_j) = K(x_i, x_j) = (1 + x_i^T x_j)^2. \quad (7)$$

Instead of doing the complex computations in the 10-dimensional space, we reach the same result within the 3-dimensional space by calculating the dot product.



There are lots of Kernel functions, an example is the *Gaussian*.



Gaussian Kernel

There are lots of Kernel functions, an example is the *Gaussian*.

The idea behind is to use all n training points as *landmarks*.

Then we can calculate the similarities of each point and all the landmarks.



There are lots of Kernel functions, an example is the *Gaussian*.

The idea behind is to use all n training points as *landmarks*.

Then we can calculate the similarities of each point and all the landmarks.

$$\forall l_i \text{ similarity}(x, l^{(i)}) = \exp\left(-\frac{\|x - l^{(i)}\|^2}{2\sigma^2}\right) \quad (8)$$

There are lots of Kernel functions, an example is the *Gaussian*.

The idea behind is to use all n training points as *landmarks*.

Then we can calculate the similarities of each point and all the landmarks.

$$\forall l_i \text{ similarity}(x, l^{(i)}) = \exp\left(-\frac{\|x - l^{(i)}\|^2}{2\sigma^2}\right) \quad (8)$$

The result will be a mapping for each point in a n -dimensional space. Finally, we can identify an hyperplane which can divide correctly the two classes of points.



An hybrid technique used in the IR field will be presented; it uses two components:

- **K-Means:** model for *unsupervised classification*;
- **SVM:** model for *supervised classification*.

An hybrid technique used in the IR field will be presented; it uses two components:

- **K-Means:** model for *unsupervised classification*;
- **SVM:** model for *supervised classification*.

K-means algorithm is one of the most used clustering algorithms. It consists of partitioning unlabeled objects into k classes, where k is no predefined.

A brief explanation will follow.



K-means


The aim is to create clusters that contain *similar documents*.

Given a training set $x^{(1)}, x^{(2)}, \dots, x^{(m)}$, the algorithm [5] used is the following:


The aim is to create clusters that contain *similar documents*.

Given a training set $x^{(1)}, x^{(2)}, \dots, x^{(m)}$, the algorithm [5] used is the following:


```
1:  $K \leftarrow \text{randomValue}$                                 ▷ multiple K will be tried
2: procedure K-MEANS( $K$ )
3:   initialize cluster centroids  $\mu_1, \dots, \mu_k$  randomly.
4:   repeat until convergence{
5:     for  $i \leftarrow 1$  to  $m$  do
6:        $c^{(i)} = \arg \min_j \|x^{(i)} - \mu_j\|$            ▷ Closest centroid to  $x^{(i)}$ 
7:     end for
8:     for  $k \leftarrow 1$  to  $K$  do
9:        $\mu_j = \frac{\sum_{i=1}^m 1\{c^{(i)}=j\} x^{(i)}}{\sum_{i=1}^m 1\{c^{(i)}=j\}}$        ▷ New centroid of cluster  $k$ 
10:    end for
11:  }
12: end procedure
```




(a)




(b)




(c)



(d)



(e)




(f)




The proposed system [3] can be summarized by the following figure:


The proposed system [3] can be summarized by the following figure:



Documents clustering




Documents clustering



First part consist of text pre-processing, followed by a vector representation of each document.

Next, there is the clustering phase.




First part consist of text pre-processing, followed by a vector representation of each document.

Next, there is the clustering phase.


Using *k-means*, documents are classified into classes of similar vectors according to the retained terms and the similarity used.

Finally, terms are classified as *Trivial*, *Decisive* or *Standard*. Only the last two are preserved and used as indicator of the class.


Queries classification



Queries classification




A given user query is first stemmed and represented by a vector (as for documents).



A given user query is first stemmed and represented by a vector (as for documents).

Then, SVM are used to classify queries; for each cluster C_i there will be an SVM_i responsible of determining the membership of each query q_j to it.



A given user query is first stemmed and represented by a vector (as for documents).

Then, SVM are used to classify queries; for each cluster C_i there will be an SVM_i responsible of determining the membership of each query q_j to it.

So, this process allows the selection of documents from the returned class to return first.



- [1] Nello Cristianini and John Shawe-Taylor. "Support Vector Machines". In: *An Introduction to Support Vector Machines and Other Kernel-based Learning Methods*. Cambridge University Press, 2000, pp. 93–124. DOI: 10.1017/CBO9780511801389.008.
- [2] Vikramaditya Jakkula. "Tutorial on support vector machine (svm)". In: *School of EECS, Washington State University* 37.2.5 (2006), p. 3.
- [3] Hamid Khalifi, Abderrahim Elqadi, and Youssef Ghanou. "Support vector machines for a new hybrid information retrieval system". In: *Procedia Computer Science* 127 (2018), pp. 139–145.
- [4] B. Scholkopf et al. "Input space versus feature space in kernel-based methods". In: *IEEE Transactions on Neural Networks* (1999). DOI: 10.1109/72.788641.



- [5] Kristina P. Sinaga and Miin-Shen Yang. "Unsupervised K-Means Clustering Algorithm". In: *IEEE Access* 8 (2020), pp. 80716–80727. DOI: 10.1109/ACCESS.2020.2988796.