




Lecture 9

Unrealizability

The problem statement




Unrealizable Synthesis Problems



Why Prove Unrealizability?


From Proving Optimality to Proving Unrealizability [pdl17, cav18]



```
exec bash
(define-fun wD ((x (BitVec 8)) (y (BitVec 8)))
  (let ((x60 (bvadd #x01 x)) (not (bvule x (bvadd #x70 #x0a)
    (not (= y (bvadd #x40 #x01))) (and (not (=
    )) (bvadd #x60 #x03) (ite (and (= (bvadd #x50
    0a) x) (= y (bvadd #x70 #x07))) (bvadd #x20
    add #x40 #x07) (ite (and (= (bvadd #x50 #x08)
    (= y (bvadd #x70 #x07))) (bvadd #x10 #x0f)
    (and (= (bvadd #x50 #x04) x) (= y (bvadd #x
    (bvadd #x70 #x07))) (bvadd #x10 #x03) (ite (a
    3) (ite (and (= (bvadd #x40 #x06) x) (= y (bv
    )) (= y (bvadd #x70 #x07))) #x03 (ite (and (=
    e (and (= (bvadd #x40 #x09) x) (= y (bvadd #x
    (bvadd #x60 #x07))) (bvadd #x10 #x02) (ite
    0e) (ite (and (= (bvadd #x40 #x04) x) (= y (b
    d #x60 #x07))) (bvadd #x10 #x0e) (ite (and (=
    vadd #x50 #x02) x) (= y (bvadd #x60 #x07)))
    #x07))) (bvadd #x0 #x0a) (ite (and (= (bvad
    d (= x (bvadd #x30 #x03)) (= y (bvadd #x60 #x
    dd #x50 #x01))) (bvadd #xf0 #x05) (ite (and
    bvadd #x30 #x08) x) (= y (bvadd #x50 #x01)))
    0 #x01))) (bvadd #xd0 #x09) (ite (and (= (bva
    nd (= x (bvadd #x30 #x03)) (= y (bvadd #x50
    add #x60 #x07))) (bvadd #x60 #x06) (ite (and
    x08) x) (= y (bvadd #x40 #x01))) #xf0 (ite (a
    (= (bvadd #x30 #x06) x) (= y (bvadd #x40 #x0
    #x40 #x01))) (bvadd #xd0 #x0c) (ite (and (=
    add #x40 #x0b) x) (= y (bvadd #x70 #x07))) (b
    #x07))) (bvadd #x50 #x0b) (ite (and (= (bvadd
    (= (bvadd #x40 #x08) x) (= y (bvadd #x40 #x0
    d #x50 #x01))) (bvadd #x10 #x09) (ite (and (=
    vadd #x50 #x03) x) (= y (bvadd #x50 #x01)))
    (ite (and (= (bvadd #x50 #x09) x) (= y (bvad
    x30 (ite (and (= (bvadd #x40 #x05) x) (= y (b
    )) (bvadd #x40 #x0c) (ite (and (= (bvadd #x40
    f) x) (= y (bvadd #x50 #x01))) (bvadd #x30 #x
    (ite (and (= (bvadd #x50 #x02) x) (= y (bvad
    (= y (bvadd #x40 #x01))) (bvadd #x20 #x04)
    (and (= (bvadd #x40 #x06) x) (= y (bvadd #x40
    bvadd #x40 #x01))) (bvadd #x30 #x08) (ite (an
    )) (ite (and (= (bvadd #x40 #x0b) x) (= y (bva
    #x40 #x01))) (bvadd #x40 #x08) (ite (and (=
    (and (= (bvadd #x40 #x02) x) (= y (bvadd #x
    x07))) (bvadd #x10 #x06) (ite (and (= (bvadd
    (= (bvadd #x50 #x07) x) (= y (bvadd #x60 #x0
    #x60 #x07))) (bvadd #x20 #x0a) (ite (and (=
    bvadd #x40 #x01)) (= y (bvadd #x60 #x07))) #
    d #x60 #x01) (ite (and (= (bvadd #x40 #x09) x
    40 #x05) x) (= y (bvadd #x50 #x01))) (bvadd
    )) (bvadd #x40 #xd) (ite (and (= (bvadd #x40
    8) x) (= y (bvadd #x50 #x01))) (bvadd #x10 #x
    (ite (and (= (bvadd #x50 #x02) x) (= y (bvad
    (= y (bvadd #x50 #x01))) (bvadd #x20 #x05)
    (and (= (bvadd #x40 #x06) x) (= y (bvadd #x50
    bvadd #x60 #x07))) (bvadd #xb0 #x0e) (ite (an
    )) (ite (and (= (bvadd #x60 #x0d) x) (= y (b
```


From Proving Optimality to Proving Unrealizability

[pdi17, cav18]



From Proving Optimality to Proving Unrealizability


[pldi17, cav18]



From Proving Optimality to Proving Unrealizability [pdi17, cav18]

Size = 9


```
(define-fun ((x (BitVec 8)) (y (BitVec 8))) (bvand (bvlshl (DD x) #x02) (bvlshr (DD y) #x06)))
```



From Proving Optimality to Proving Unrealizability [pldi17, cav18]

Size = 9

```
(define-fun ((x (BitVec 8)) (y (BitVec 8))) (bvand (bvlshl (DD x) #x02) (bvlshr (DD y) #x06)))
```



X is optimal **iff** this synthesis problem is **unrealizable**

Why is this hard?

Specification

$$\Phi(P) : \forall x, y. P \geq x \wedge P \geq y \\ \wedge (P = x \vee P = y)$$

Search space

Start := Start+Start

| x | y | 0 | 1

SyGuS
solver

Unrealizable

Proof that


$$\neg \exists Q \text{ s.t. } \Phi(Q) \\ \wedge Q \in L(G)$$

Infinite grammar makes
the problem undecidable

Soundness of CEGIS for unrealizability

$Sy \upharpoonright E$ unrealizable

No solution over E



Sy unrealizable

No solution

Proving unrealizability for SyGuS over examples

Outline of the algorithm

$Sy \uparrow E := (\Phi, G, E)$

construct

```
int[4] Start(x_0,y_0,x_1,y_1,x_2,y_2,x_3,y_3){  
  if(??){return (0,0,0,0);}           // Start -> 0  
  if(??){return (1,1,1,1);}           // Start -> 1  
  if(??){return (x_0,x_1,x_2,x_3);}    // Start -> x  
  if(??){return (y_0,y_1,y_2,y_3);}    // Start -> y  
  else{                                // Start -> Start + Start  
    int[4] L = Start(x_0,y_0,x_1,y_1);  
    int[4] R = Start(x_0,y_0,x_1,y_1);  
    return (L[0]+R[0],L[1]+R[1],L[2]+R[2],L[3]+R[3]);}  
}  
int[4] P = Start(0,0,0,1,1,0,2,0);  
assert (P[0]!=0 || P[1]!=1 || P[2]!=1 || P[3]!=2);
```


$Sy \uparrow E$ unrealizable

assert always holds

Reachability Problem

Nondeterministic
choice

```
void main(){  
    int x = 0;  
    while(nd()){  
        x++;  
    }  
    assert(x<0)  
}
```



Reachability solvers:

CPA-checker

Uautomizer

Seahorn

Goal: can the **assert** be falsified?

Sy^E to Re^E

Set input to E

$$\vec{x} \leftarrow E$$




f_G is non-deterministically drawn from $L(G)$

$$\vec{o} \leftarrow f_G(\vec{x})$$

Check if \vec{o} doesn't satisfy φ \longleftrightarrow $f_G(\vec{x})$ satisfy φ on E

assert($\neg\varphi(o, x)$, x_i))

$Sy \uparrow E$  unrealizable

Set input to E

$$\vec{x} \leftarrow E$$

Examples E :

$(x_0, y_0) = (0, 0)$

$(x_1, y_1) = (0, 1)$

$x_0 = 0;$

$y_0 = 0;$

$x_1 = 0;$

$y_1 = 1;$

Sy^E **to** Re^E

Set input to E

$$\vec{x} \leftarrow E$$

f_G is non-deterministically drawn from $L(G)$

$$\vec{o} \leftarrow f_G(\vec{x})$$

Check if \vec{o} doesn't satisfy φ

assert($\neg\varphi(o, \vec{x})$, x_i))



Check if \vec{o} doesn't satisfy φ

```
assert( $\neg \wedge x_i \in E. \varphi(o_i, x_i)$ )
```

```
void main(){  
    ...  
    assert(!(spec(x0,y0,o0)&&spec(x1,y1,o1)));  
}  
bool spec(x,y,o){  
    return (o>=x)&&(o>=y)&&(o==x || o==y);  
}
```

$\Phi(f) : \forall x, y. f(x, y) \geq x \wedge f(x, y) \geq y \wedge (f(x, y) = x \vee f(x, y) = y)$

Sy^E to Re^E

Set input to E

$$\vec{x} \leftarrow E$$

f_G is non-deterministically drawn from $L(G)$

$$\vec{o} \leftarrow f_G(\vec{x})$$



Check if \vec{o} doesn't satisfy φ

assert($\neg \varphi(o, \vec{x})$, x_i))

f_G is non-deterministically drawn from $L(G)$

$$\vec{o} \leftarrow f_G(\vec{x})$$

`o0 = fStart(x0,y0);`

```
int fStart(x0,y0){  
    if(nd()){ return 0;}    \\ Start -> 0  
    if(nd()){ return 1;}    \\ Start -> 1  
    if(nd()){ return x0;}    \\ Start -> x  
    if(nd()){ return y0;}    \\ Start -> y  
    if(nd()){                \\ Start -> +(Start,Start)  
        left = fStart(x0,y0);  
        right = fStart(x0,y0);  
        return left + right;  
    }
```

Example 0

$o_0 = \text{fStart}(x_0, y_0);$

o_0 is $f_G(x_0, y_0)$ for **some** f_G in $L(G)$

Example 1

$o_1 = \text{fStart}(x_1, y_1);$

o_1 is $f_G(x_1, y_1)$ for **some** f_G in $L(G)$



The two f_G can be different!

f_G is non-deterministically drawn from $L(G)$

$$\vec{o} \leftarrow f_G(\vec{x})$$

```
(o0,o1) = fStart(x0,y0,x1,y1);
```

```
<int,int> fStart(x0,y0,x1,y1){  
    if(nd()){ return (0,0);}    \\ Start -> 0  
    if(nd()){ return (1,1);}    \\ Start -> 1  
    if(nd()){ return (x0,x1);}  \\ Start -> x  
    if(nd()){ return (y0,y1);}  \\ Start -> y  
    if(nd()){                   \\ Start -> +(Start,Start)  
        (a0,a1) = fStart(x0,y0,x1,y1);  
        (b0,b1) = fStart(x0,y0,x1,y1);  
        return (a0+b0,a1+b1);}  
}
```

Outline of the algorithm

$Sy \uparrow E := (\Phi, G, E)$

construct

```
int[4] Start(x_0,y_0,x_1,y_1,x_2,y_2,x_3,y_3){  
  if(??){return (0,0,0,0);}           // Start -> 0  
  if(??){return (1,1,1,1);}           // Start -> 1  
  if(??){return (x_0,x_1,x_2,x_3);}    // Start -> x  
  if(??){return (y_0,y_1,y_2,y_3);}    // Start -> y  
  else{                                // Start -> Start + Start  
    int[4] L = Start(x_0,y_0,x_1,y_1);  
    int[4] R = Start(x_0,y_0,x_1,y_1);  
    return (L[0]+R[0],L[1]+R[1],L[2]+R[2],L[3]+R[3]);}  
}  
int[4] P = Start(0,0,0,1,1,0,2,0);  
assert (P[0]!=0 || P[1]!=1 || P[2]!=1 || P[3]!=2);
```

$Sy \uparrow E$ unrealizable



Sy unrealizable



assert always holds

Nay: Illustrative Example

[PLDI20] Exact and Approximate Methods for Proving Unrealizability of Syntax-Guided Synthesis Problems

Example of an Unrealizable Problem

$$\begin{aligned} f(1) &= 5 \\ x \neq 1 &\rightarrow f(x) = 3x \end{aligned}$$

Start \rightarrow Expr₁ | Expr₂
?

Solution \in Expr₁ \rightarrow $x + x + \text{Expr}_1$ | 1

Solution \in Expr₂ \rightarrow $x + x + x + \text{Expr}_2$ | 0

?

Example of an Unrealizable Problem

$$f(1) = 5$$

$$x \neq 1 \rightarrow f(x) = 3x$$

$$x = 1 \quad \exists \lambda. 2\lambda 1 + 1 = 5$$

$$x = 2 \quad \wedge 2\lambda 2 + 1 = 6$$

	Start \rightarrow Expr ₁ Expr ₂		
Solution \in	? Expr ₁ \rightarrow $x + x + \text{Expr}_1$ 1	2λx + 1 :	1, 2x + 1, 4x + 1, ...
			$\exists \lambda \forall x. 2\lambda x + 1$ satisfies the specification
Solution \in	Expr ₂ \rightarrow $x + x + x + \text{Expr}_2$ 0		
	?		

Example of an Unrealizable Problem

$$f(1) = 5$$

$$x \neq 1 \rightarrow f(x) = 3x$$

$$\begin{array}{ll}
 & f(1) \\
 x = 1 & \exists \lambda. 2\lambda 1 + 1 = \overbrace{5} \\
 x = 2 & \wedge 2\lambda 2 + 1 = \underbrace{6} \\
 & f(2)
 \end{array}$$

	Start \rightarrow Expr ₁ Expr ₂		
Solution \in	? Expr ₁ $\rightarrow x + x +$ Expr ₁ 1	2λx + 1 :	1, 2x + 1, 4x + 1, ...
			$\exists \lambda \forall x. 2\lambda x + 1$ satisfies the specification
Solution \in	Expr ₂ $\rightarrow x + x + x +$ Expr ₂ 0		
	?		

Example of an Unrealizable Problem

$$f(1) = 5$$

$$x \neq 1 \rightarrow f(x) = 3x$$

$$\begin{array}{ll}
 & f(1) \\
 x = 1 & \exists \lambda. 2\lambda 1 + 1 = 5 \\
 x = 2 & \wedge \underbrace{2\lambda 2 + 1 = 6}_{\text{odd}} \quad \underbrace{}_{f(2)}
 \end{array}$$

Solution  $\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$

$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$

$2\lambda x + 1 :$ $1, 2x + 1, 4x + 1, \dots$

$\exists \lambda \forall x. 2\lambda x + 1$ satisfies the specification

Solution \in $\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$

?

Example of an Unrealizable Problem

$$f(1) = 5$$


$$x \neq 1 \rightarrow f(x) = 3x$$

divisible by 3

$$\exists \lambda. \overbrace{3\lambda}^{\text{divisible by 3}} 1 = 5$$


$$\wedge 3\lambda 2 = 6$$

Start $\rightarrow \text{Expr}_1 \mid \text{Expr}_2$

Solution  $\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$

$$2\lambda x + 1 : 1, 2x + 1, 4x + 1, \dots$$

$\exists \lambda \forall x. 2\lambda x + 1$ satisfies the specification

Solution  $\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$

$$3\lambda x : 0, 3x, 6x, \dots$$

$\exists \lambda \forall x. 3\lambda x$ satisfies the specification

?

Example of an Unrealizable Problem

$$f(1) = 5$$
$$x \neq 1 \rightarrow f(x) = 3x$$

Start $\rightarrow \text{Expr}_1 \mid \text{Expr}_2$


Solution ~~✗~~ $\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$

Solution ~~✗~~ $\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$

$2\lambda x + 1$ or $3\lambda x$

$2\lambda x + 1$

$3\lambda x$



No Solution
Unrealizable

SyGuS with Examples

SyGuS problem

sy

$$\begin{aligned} f(1) &= 5 \\ x \neq 1 &\rightarrow f(x) = 3x \end{aligned}$$

$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$

$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$

$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$

SyGuS with examples problem

sy^E where $E := \{1, 2\}$

$x = 1$

$x = 2$

$f(1) = 5$

$f(2) = 6$

$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$

$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$

$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$

Algorithm for Proving Unrealizability

High-level Idea

$E:$

$$f(1) = 5$$
$$f(2) = 6$$

Grammar

$$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$$

$$\begin{array}{l} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ \quad \mid 1 \end{array}$$

$$\begin{array}{l} \text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \\ \quad \mid 0 \end{array}$$



Equations

$$V_{\text{Start}} = \dots$$

$$V_{\text{Expr}_1} = \dots$$

$$V_{\text{Expr}_2} = \dots$$



Solution

$$2\lambda x + 1 \text{ or } 3\lambda x$$

$$2\lambda x + 1$$

$$3\lambda x$$

High-level Idea

E :

$$f(1) = 5$$

$$f(2) = 6$$

$$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1$$

| 1



Substitute x with input examples

$$\text{Expr}_1 \rightarrow (1, 2) + (1, 2) + \text{Expr}_1$$

| (1, 1)



Construct equation

$$V_{\text{Expr}_1} = \{(1, 2)\} + \{(1, 2)\} + V_{\text{Expr}_1}$$

$\cup \{(1, 1)\}$



Evaluate algebraic operators

$$V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1}$$

$\cup \{(1, 1)\}$

$$2\lambda x + 1$$

High-level Idea

E :

$$f(\textcolor{red}{1}) = \textcolor{red}{5}$$

$$f(\textcolor{blue}{2}) = \textcolor{blue}{6}$$

$$\begin{array}{c} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ | 1 \end{array}$$

$$2\lambda x + 1$$

$$\begin{aligned} V_{\text{Expr}_1} &= \{(\textcolor{red}{2}, \textcolor{blue}{4})\} + V_{\text{Expr}_1} \\ &\cup \{(\textcolor{red}{1}, \textcolor{blue}{1})\} \end{aligned}$$

High-level Idea

E:

$$f(\textcolor{red}{1}) = \textcolor{red}{5}$$

$$f(\textcolor{blue}{2}) = \textcolor{blue}{6}$$

$$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$$

$$\begin{array}{c} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ \mid 1 \end{array}$$

$$\begin{array}{c} \text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \\ \mid 0 \end{array}$$

$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$\begin{array}{l} V_{\text{Expr}_1} = \{(\textcolor{red}{2}, \textcolor{blue}{4})\} + V_{\text{Expr}_1} \\ \cup \{(\textcolor{red}{1}, \textcolor{blue}{1})\} \end{array}$$

$$\begin{array}{l} V_{\text{Expr}_2} = \{(\textcolor{red}{3}, \textcolor{blue}{6})\} + V_{\text{Expr}_2} \\ \cup \{(\textcolor{red}{0}, \textcolor{blue}{0})\} \end{array}$$

$$2\lambda x + \textcolor{red}{1} \text{ or } 3\lambda x$$

$$2\lambda x + \textcolor{red}{1}$$

$$3\lambda x$$

High-level Idea

$E:$

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

$$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$$

$$\begin{array}{l} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ \quad \mid 1 \end{array}$$

$$\begin{array}{l} \text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \\ \quad \mid 0 \end{array}$$



Equation

$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$\begin{array}{l} V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \quad \cup \{(1, 1)\} \end{array}$$

$$\begin{array}{l} V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \quad \cup \{(0, 0)\} \end{array}$$

$$\begin{array}{l} V_{\text{Start}} = \{(1, 1) + \lambda(2, 4)\} \\ \quad \cup \{(0, 0) + \lambda(3, 6)\} \end{array}$$

$$V_{\text{Expr}_1} = \{(1, 1) + \lambda(2, 4)\}$$

$$V_{\text{Expr}_2} = \{(0, 0) + \lambda(3, 6)\}$$

Solution

$$2\lambda x + 1 \text{ or } 3\lambda x$$

$$2\lambda x + 1$$

$$3\lambda x$$

High-level Idea

E :

$$f(\textcolor{red}{1}) = \textcolor{red}{5}$$

$$f(\textcolor{blue}{2}) = \textcolor{blue}{6}$$

Grammar

$$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$$

$$\begin{array}{l} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ \quad \mid 1 \end{array}$$

$$\begin{array}{l} \text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \\ \quad \mid 0 \end{array}$$



Equation

$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$\begin{array}{l} V_{\text{Expr}_1} = \{(\textcolor{red}{2}, \textcolor{blue}{4})\} + V_{\text{Expr}_1} \\ \quad \cup \{(\textcolor{blue}{1}, \textcolor{blue}{1})\} \end{array}$$

$$\begin{array}{l} V_{\text{Expr}_2} = \{(\textcolor{blue}{3}, \textcolor{blue}{6})\} + V_{\text{Expr}_2} \\ \quad \cup \{(\textcolor{blue}{0}, \textcolor{blue}{0})\} \end{array}$$

Solution

$$2\lambda x + 1 \text{ or } 3\lambda x$$

$$2\lambda x + 1$$


$$3\lambda x$$

$$\begin{array}{l} V_{\text{Start}} = \{(\textcolor{blue}{1}, \textcolor{blue}{1}) + \lambda(\textcolor{red}{2}, \textcolor{blue}{4})\} \\ \quad \cup \{(\textcolor{blue}{0}, \textcolor{blue}{0}) + \lambda(\textcolor{blue}{3}, \textcolor{blue}{6})\} \end{array}$$


$$V_{\text{Expr}_1} = \{(\textcolor{blue}{1}, \textcolor{blue}{1}) + \lambda(\textcolor{red}{2}, \textcolor{blue}{4})\}$$

$$V_{\text{Expr}_2} = \{(\textcolor{blue}{0}, \textcolor{blue}{0}) + \lambda(\textcolor{blue}{3}, \textcolor{blue}{6})\}$$

High-level Idea



High-level Idea




Logical approach: Constrained Horn Clauses (CHC)

Iterative approach: Newton's method



How do I solve this?

High-level Idea



Logical approach: Constrained Horn Clauses (CHC)

Iterative approach: Newton's method



How do I solve this?

Solving Equations with Horn Clauses

E :

$$f(1) = 5$$

$$f(2) = 6$$

Equation

$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \cup \{(1, 1)\}$$

$$V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \cup \{(0, 0)\}$$

$$\forall x. x \in V_{\text{Expr}_1} \vee x \in V_{\text{Expr}_2} \rightarrow x \in V_{\text{Start}}$$

$$\forall x. x \in V_{\text{Expr}_1} \rightarrow ((2, 4) + x) \in V_{\text{Expr}_1} \wedge (1, 1) \in V_{\text{Expr}_1}$$

$$\forall x. x \in V_{\text{Expr}_2} \rightarrow ((3, 6) + x) \in V_{\text{Expr}_2} \wedge (0, 0) \in V_{\text{Expr}_2}$$

$$\text{assert } (5, 6) \in V_{\text{Start}}$$

Solving Equations with Horn Clauses

E:

$$\begin{aligned} f(1) &= 5 \\ f(2) &= 6 \end{aligned}$$

Equation

$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \cup \{(1, 1)\}$$

$$V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \cup \{(0, 0)\}$$

$$\forall x. x \in V_{\text{Expr}_1} \vee x \in V_{\text{Expr}_2} \rightarrow x \in V_{\text{Start}}$$

$$\forall x. x \in V_{\text{Expr}_1} \rightarrow ((2, 4) + x) \in V_{\text{Expr}_1} \wedge (1, 1) \in V_{\text{Expr}_1}$$

$$\forall x. x \in V_{\text{Expr}_2} \rightarrow ((3, 6) + x) \in V_{\text{Expr}_2} \wedge (0, 0) \in V_{\text{Expr}_2}$$

$$\text{assert } (5, 6) \in V_{\text{Start}}$$

- Complete, but undecidable
- Solvable by off-the-shelf Constrained Horn Clauses (CHC) solver

High-level Idea

$E:$

$$f(0) = 0$$

$$f(1) = 5$$

$$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$$

$$\begin{array}{l} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ \mid 1 \end{array}$$

$$\begin{array}{l} \text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \\ \mid 0 \end{array}$$


$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$\begin{array}{l} V_{\text{Expr}_1} = \{(0, 2)\} + V_{\text{Expr}_1} \\ \cup \{(1, 1)\} \end{array}$$

$$\begin{array}{l} V_{\text{Expr}_2} = \{(0, 3)\} + V_{\text{Expr}_2} \\ \cup \{(0, 0)\} \end{array}$$

Logical approach: Constrained Horn Clauses (CHC)

Iterative approach: Newton's method



Solving Equations with Semi-linear Sets

Domain: integers

Operators: +

Grammar

$$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$$
$$\begin{array}{l} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ \quad \mid 1 \end{array}$$
$$\begin{array}{l} \text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \\ \quad \mid 0 \end{array}$$

Equation

$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$
$$\begin{array}{l} V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \quad \cup \{(1, 1)\} \end{array}$$
$$\begin{array}{l} V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \quad \cup \{(0, 0)\} \end{array}$$

Value of V can be modeled as semi-linear sets

Semi-linear Sets

$$V_{\text{Start}} = \{(\textcolor{red}{1}, \textcolor{blue}{1}) + \lambda(\textcolor{red}{2}, \textcolor{blue}{4})\} \\ \cup \{(\textcolor{red}{0}, \textcolor{blue}{0}) + \lambda(3, 6)\}$$

$$V_{\text{Expr}_1} = \{(\textcolor{red}{1}, \textcolor{blue}{1}) + \lambda(2, 4)\}$$

$$V_{\text{Expr}_2} = \{(\textcolor{red}{0}, \textcolor{blue}{0}) + \lambda(3, 6)\}$$

$\left. \begin{array}{l} \text{Semi-linear set} \\ \text{Linear set} \end{array} \right\} \begin{array}{l} \{(\textcolor{red}{1}, \textcolor{blue}{1}), (\textcolor{red}{3}, \textcolor{blue}{5}), (\textcolor{red}{5}, \textcolor{blue}{9}), \dots\} \cup \{(\textcolor{red}{0}, \textcolor{blue}{0}), (\textcolor{red}{3}, \textcolor{blue}{6}), (\textcolor{red}{6}, \textcolor{blue}{12}), \dots\} \\ \{(\textcolor{red}{1}, \textcolor{blue}{1}), (\textcolor{red}{3}, \textcolor{blue}{5}), (\textcolor{red}{5}, \textcolor{blue}{9}), \dots\} \end{array}$

Solving Equations with Semi-linear Sets

Domain: integers

Operators: +

Grammar

$$\text{Start} \rightarrow \text{Expr}_1 \mid \text{Expr}_2$$
$$\begin{array}{l} \text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \\ \quad \mid 1 \end{array}$$
$$\begin{array}{l} \text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \\ \quad \mid 0 \end{array}$$

Equation

$$V_{\text{Start}} = V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$
$$\begin{array}{l} V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \quad \cup \{(1, 1)\} \end{array}$$
$$\begin{array}{l} V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \quad \cup \{(0, 0)\} \end{array}$$


Value of V can be modeled as semi-linear sets

Fact: These equations can be solved iteratively in no more than n rounds with n number of equations [Esparza et al. 2010]

Conditional Linear Integer Arithmetic (CLIA)

Domain:

Operators:

Conditional Linear Integer Arithmetic (CLIA)

Domain: integers, Boolean

Operators: $+$, \wedge , \vee , \neg , if then else, $<$, $==$

Semantics of If-Then-Else using semi-linear sets

E :

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

$\text{Start} \rightarrow \text{ITE}(\text{BExpr}, \text{Start}, \text{Start})$
 $\quad \mid \text{Expr}_1 \mid \text{Expr}_2$

$\text{BExpr} \rightarrow x = 1$

$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$

$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$

Semantics of If-Then-Else using semi-linear sets

E :

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

Start \rightarrow ITE(BExpr, Start, Start)
| Expr₁ | Expr₂

BExpr $\rightarrow x = 1$

Expr₁ $\rightarrow x + x + \text{Expr}_1 \mid 1$

Expr₂ $\rightarrow x + x + x + \text{Expr}_2 \mid 0$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

Semantics of If-Then-Else using semi-linear sets

E :

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

$\text{Start} \rightarrow \text{ITE}(\text{BExpr}, \text{Start}, \text{Start})$
 $\quad \mid \text{Expr}_1 \mid \text{Expr}_2$

$\text{BExpr} \rightarrow x = 1$

$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$

$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = (1, 2) == (1, 1)$$

Semantics of If-Then-Else using semi-linear sets

E :

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

$$\text{Start} \rightarrow \text{ITE}(\text{BExpr}, \text{Start}, \text{Start}) \\ \mid \text{Expr}_1 \mid \text{Expr}_2$$

$$\text{BExpr} \rightarrow x = 1$$

$$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 \mid 1$$

$$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 \mid 0$$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = (1, 2) == (1, 1)$$

$$V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \cup \{(1, 1)\}$$

$$V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \cup \{(0, 0)\}$$

Semantics of If-Then-Else using semi-linear sets

$E:$

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

$$\text{Start} \rightarrow \text{ITE}(\text{BExpr}, \text{Start}, \text{Start}) \\ | \text{Expr}_1 | \text{Expr}_2$$

$$\text{BExpr} \rightarrow x = 1$$

$$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 | 1$$

$$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 | 0$$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = (1, 2) == (1, 1)$$

$$V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \cup \{(1, 1)\}$$

$$V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \cup \{(0, 0)\}$$

$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = \{(T, F)\}$$



Semantics of If-Then-Else using semi-linear sets

E :

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

$$\text{Start} \rightarrow \text{ITE}(\text{BExpr}, \text{Start}, \text{Start}) \\ | \text{Expr}_1 | \text{Expr}_2$$

$$\text{BExpr} \rightarrow x = 1$$

$$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 | 1$$

$$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 | 0$$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = (1, 2) == (1, 1)$$

$$V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \cup \{(1, 1)\}$$

$$V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \cup \{(0, 0)\}$$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = \{(T, F)\}$$

$$V_{\text{Expr}_1} = \{(1, 1) + \lambda(2, 4)\}$$

$$V_{\text{Expr}_2} = \{(0, 0) + \lambda(3, 6)\}$$

} constants

Semantics of If-Then-Else using semi-linear sets

E :

$$f(1) = 5$$

$$f(2) = 6$$

Grammar

$$\text{Start} \rightarrow \text{ITE}(\text{BExpr}, \text{Start}, \text{Start}) \\ | \text{Expr}_1 | \text{Expr}_2$$

$$\text{BExpr} \rightarrow x = 1$$

$$\text{Expr}_1 \rightarrow x + x + \text{Expr}_1 | 1$$

$$\text{Expr}_2 \rightarrow x + x + x + \text{Expr}_2 | 0$$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = (1, 2) == (1, 1)$$

$$V_{\text{Expr}_1} = \{(2, 4)\} + V_{\text{Expr}_1} \\ \cup \{(1, 1)\}$$

$$V_{\text{Expr}_2} = \{(3, 6)\} + V_{\text{Expr}_2} \\ \cup \{(0, 0)\}$$



$$V_{\text{Start}} = \text{ITE}(\{(T, F)\}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup \{(1, 1) + \lambda(2, 4)\} \\ \cup \{(0, 0) + \lambda(3, 6)\}$$



$$V_{\text{Start}} = \text{ITE}(V_{\text{BExpr}}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup V_{\text{Expr}_1} \cup V_{\text{Expr}_2}$$

$$V_{\text{BExpr}} = \{(T, F)\}$$

$$V_{\text{Expr}_1} = \{(1, 1) + \lambda(2, 4)\}$$

$$V_{\text{Expr}_2} = \{(0, 0) + \lambda(3, 6)\}$$


} constants

Semantics of If-Then-Else using semi-linear sets

$$\begin{aligned} V_{\text{Start}} &= \text{ITE}(\{(T, F)\}, V_{\text{Start}}, V_{\text{Start}}) \\ &\cup \{(1, 1) + \lambda(2, 4)\} \\ &\cup \{(0, 0) + \lambda(3, 6)\} \end{aligned}$$


Semantics of If-Then-Else using semi-linear sets

$$V_{\text{Start}} = \text{ITE}(\{(T, F)\}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup \{(1, 1) + \lambda(2, 4)\} \\ \cup \{(0, 0) + \lambda(3, 6)\}$$



Semantics of If-Then-Else using semi-linear sets

$$V_{\text{Start}} = \text{ITE}(\{(\text{T}, \text{F})\}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup \{(\text{1}, \text{1}) + \lambda(2, 4)\} \\ \cup \{(\text{0}, \text{0}) + \lambda(3, 6)\}$$




$$V_{\text{Start}}^{(\bullet, -)} = V_{\text{Start}}^{(\bullet, -)} \\ \cup \{(\text{1}, -) + \lambda(\text{0}, -)\} \\ \cup \{(\text{0}, -) + \lambda(\text{0}, -)\}$$

$$V_{\text{Start}}^{(-, \bullet)} = V_{\text{Start}}^{(-, \bullet)} \\ \cup \{(-, \text{1}) + \lambda(-, \text{2})\} \\ \cup \{(-, \text{0}) + \lambda(-, \text{3})\}$$

Semantics of If-Then-Else using semi-linear sets

$$V_{\text{Start}} = \text{ITE}(\{(\text{T}, \text{F})\}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup \{(\text{1}, \text{1}) + \lambda(2, 4)\} \\ \cup \{(\text{0}, \text{0}) + \lambda(3, 6)\}$$




$$V_{\text{Start}}^{(\bullet, -)} = V_{\text{Start}}^{(\bullet, -)} \\ \cup \{\text{1} + \lambda \text{2}\} \\ \cup \{\text{0} + \lambda \text{3}\}$$

$$V_{\text{Start}}^{(-, \bullet)} = V_{\text{Start}}^{(-, \bullet)} \\ \cup \{\text{1} + \lambda \text{4}\} \\ \cup \{\text{0} + \lambda \text{6}\}$$

Semantics of If-Then-Else using semi-linear sets

$$V_{\text{Start}} = \text{ITE}(\{(\text{T}, \text{F})\}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup \{(\text{1}, \text{1}) + \lambda(2, 4)\} \\ \cup \{(\text{0}, \text{0}) + \lambda(3, 6)\}$$




$$V_{\text{Start}}^{(\bullet, -)} = V_{\text{Start}}^{(\bullet, -)} \\ \cup \{(\text{1}, \text{0}) + \lambda(0, 0)\} \\ \cup \{(\text{0}, \text{0}) + \lambda(0, 0)\}$$

$$V_{\text{Start}}^{(-, \bullet)} = V_{\text{Start}}^{(-, \bullet)} \\ \cup \{(\text{0}, \text{1}) + \lambda(0, 2)\} \\ \cup \{(\text{0}, \text{0}) + \lambda(0, 3)\}$$

$$\text{ITE}(\{(\text{T}, \text{F})\}, V_{\text{Start}}, V_{\text{Start}}) = V_{\text{Start}}^{(\bullet, -)} + V_{\text{Start}}^{(-, \bullet)}$$

Semantics of If-Then-Else using semi-linear sets

$$V_{\text{Start}} = \text{ITE}(\{(T, F)\}, V_{\text{Start}}, V_{\text{Start}}) \\ \cup \{(1, 1) + \lambda(2, 4)\} \\ \cup \{(0, 0) + \lambda(3, 6)\}$$




$$V_{\text{Start}} = V_{\text{Start}}^{(\bullet, \bullet)} = V_{\text{Start}}^{(\bullet, -)} + V_{\text{Start}}^{(-, \bullet)} \\ \cup \{(1, 1) + \lambda(0, 2)\} \\ \cup \{(0, 0) + \lambda(0, 3)\}$$

$$V_{\text{Start}}^{(\bullet, -)} = V_{\text{Start}}^{(\bullet, -)} \\ \cup \{(1, 0) + \lambda(0, 0)\} \\ \cup \{(0, 0) + \lambda(0, 0)\}$$

$$V_{\text{Start}}^{(-, \bullet)} = V_{\text{Start}}^{(-, \bullet)} \\ \cup \{(0, 1) + \lambda(0, 2)\} \\ \cup \{(0, 0) + \lambda(0, 3)\}$$

Decidable Fragments of SyGuS with Examples



Theorem

Given a CLIA SyGuS problem sy and a finite set of examples E , it is decidable whether the SyGuS problem sy^E is (un)realizable

Nope: contributions

First to be able to prove unrealizability for infinite program spaces

CEGIS for unrealizability

- Also shows that in practice a few examples are often enough

Reduction of unrealizability to unreachability

- Can use existing tools

Sound for both synthesis and unrealizability

- If Nope terminates and gives an answer, this answer is correct

Can be used to optimize syntactic objectives

Nope: limitations

Incomplete

Why might Nope run forever?

Can Nope run forever if the problem is realizable?

In practice only works for < half of the benchmarks

Scales poorly with the size of grammar, number of examples

Limited to SyGuS

Nope: questions

Behavioral constraints? Structural constraints? Search strategy?

- First-order specs (like in SyGuS)
- Regular tree grammars (like in SyGuS)
- Enumerative for synthesis + reduction to reachability for unrealizability

Nope: questions

Example of an unrealizable program over bitvectors

$f(x)=1$

$G := (\text{Start} := 0)$

Sure, but this search space is finite 😞

$f(x,y)=\text{Or}(x,y)$

$G := (\text{Start} := x \mid y \mid \text{Not}(\text{Start}) \mid \text{And}(\text{Start}, \text{Start}))$ This is realizable!

$f(1010)=0001$

$G := (\text{Start} := x \mid \text{Not}(\text{Start}))$ Correct!

Nope: questions

Why does Nope use examples in its encoding instead of directly encoding the full specification (i.e., proving unrealizability for all inputs at once)? What would one need to change?

- We can't have quantifiers in the verification problem!

Nope: questions

Can the same encoding be used to synthesize programs instead of proving unrealizability?

- Yes, in fact a “failing test” is effectively a program encoding
- Similar idea to constraint-based search!

Next

