

1 Racket

1.1 Comments

- > single line comment: ;
- > multi-line comment: #| ... |#
- > multi-line comments can be nested

```
; single line comment
#|
  multi-line-comment
    can span
    multiple lines
  end of comment
|#
```

1.2 Datum evaluation

- > (`quote` `<datum>`) OR '`<datum>` leaves the datum as-is
- > (`unquote` `<datum>`) OR ,`<datum>` is the opposite of `quote`
- > (`quasiquote` `<datum>`) OR ,@`<datum>` allows to apply the unquote where needed

```
'(1 2 3); => (1 2 3)
(1 ,(+ 1 1) 3) ; => '(1 2 3)
```

1.3 Predicates

- > all predicates end with ?
- > checks if a number is even: `even?`
- > checks if a number is odd: `odd?`
- > check if a datum is true: `true?`
- > check if a number is positive: `positive?`
- > check if a number is negative: `negative?`
- > check if a number is zero: `zero?`

```
(even? 2) ; => #t
(odd? 2) ; => #f
(true? #t) ; => #t
```

1.3.1 Equivalence

- > check if two numbers are equal: =

- > checks if two objects or numbers are the same: `eq?`
- > checks if two objects are the same: `eqv?`
- > checks if two objects are the same: `equal?`

```
(= 1 1) ; => #t
(eq? 1 1) ; => #t
(eqv? 1 1) ; => #t
(equal? 1 1) ; => #t
```

1.4 Data types

- > integer: 9125
- > binary: #b10001110100101
- > octal: #o21645
- > hexadecimal: #x23a5
- > real: 91.25
- > rational: 91/25
- > complex: 91+25i
- > boolean: #t, #f
- > character: #\A, #\λ, #\u30BB
- > null element: '(), null
- > lists: '(1 2 3)

```
(define x 5) ; => x = 5
(define y "Hello, world!") ; => y = "Hello, world!"
(define z #t) ; => z = #t
(define w #\A) ; => w = #\A
null ; => '()
```

1.4.1 Basic operations

- > all operations are in prefix notation (`<operator>` `<operand>` ...)

Operations on numbers

- > arithmetic operations: +, -, *, /
- > exponentiation: `expt`
- > exponentiation by e: `exp`
- > logarithm: `log`
- > quotient: `quotient`

- > remainder: `remainder`
- > largest and smallest of two numbers: `max, min`
- > add 1: `add1`
- > subtract 1: `sub1`
- > greatest common divisor: `gcd`
- > least common multiple: `lcm`

```
(+ 1 2 3) ; => 6
(- 1 2 3) ; => -4
(expt 2 3) ; => 8
(exp 2) ; => e ** 2 = 7.38905609893065
(log 10) ; => 2.302585092994046
(quotient 5 2) ; => 2
(remainder 5 2) ; => 1
(max 1 2) ; => 2
(min 1 2) ; => 1
(add1 5) ; => 6
(sub1 5) ; => 4
(gcd 12 18) ; => 6
(lcm 12 18) ; => 36
```

Operations on strings

- > string length: `string-length`
- > string append: `string-append`
- > string to list: `string->list`
- > list to string: `list->string`
- > get n-th character: `string-ref`

```
(string-length "Hello, world!") ; => 13
(string-append "Hello, " "world!") ; => "Hello, world!"
(string->list "Hello") ; => '(#\H #\e #\l #\l #\o)
(list->string '(\#\H #\e #\l #\l #\o)) ; => "Hello"
(string-ref "Hello" 0) ; => #\H
```

Operations on bools

- > logic operations: `and, or, not, xor`
- > implication: `implies`

```
(and #t #f) ; => #f
(or #t #f) ; => #t
(not #t) ; => #f
```

```
(xor #t #f) ; => #t
(implies #t #f) ; => #f
```

1.5 Functions

- > anonymous functions: `(lambda (<arg1> <arg2> ...) <body>)`
- > named functions: `(define (<name> <arg1> <arg2> ...) <body>)`
- > old way: `(define <name> (lambda (<arg1> <arg2> ...) <body>))`

```
(lambda (x) (+ x 1)) ;
(define (add1 x) (+ x 1)) ;
```

1.5.1 Higher order functions

- > apply a function to each element of a list: `map`
- > apply a filter: `filter`
- > apply a function to each element of a list and flatten the result: `apply`
- > fold a list: `foldl, foldr`

```
(map add1 '(1 2 3)) ; => '(2 3 4)
(filter even? '(1 2 3 4)) ; => '(2 4)
(apply append '((1 2) (3 4))) ; => '(1 2 3 4)
(foldl + 0 '(1 2 3)) ; => 6
(foldr + 0 '(1 2 3)) ; => 6
```

1.6 Variables

- > parallel binding: `let`
- > serial binding: `let*`
- > recursive binding: `letrec`
- > recursive serial binding: `letrec*`

```
(let ((x 5) (y 2)) (list x y)) ; => '(5 2)
(let* ((x 1) (y (add1 x))) (list x y)) ; // '(1 2)
```

1.7 Mutation

- > all mutators end with !
- > `set!` is used to mutate variables
- > `vector-set!` is used to mutate vectors

```
(define x 5) ; => x = 5
(set! x 6) ; => x = 6
(define v (vector 2 2 3 4)) ; => v = '#(2 2 3 4)
(vector-set! v 0 1) ; => v = '#(1 2 3 4)
```

1.8 Collections

1.8.1 Structs

- > definition: (`struct` <struct-name> (<field> ...))
- > constructor: (`define` <name> <struct-name> <field-value> ...)
- > getter: <struct-name>-<field-name>
- > setter: `set-<struct-name>-<field-name>!`
- > predicate: <struct-name>?
- > structs and fields are immutable by default
- > use `#:mutable` keyword on struct or field to make it mutable

```
(struct point (x y)) ; => point
(define p (point 1 2)) ; => p = (point 1 2)
(point-x p) ; => 1
(point? p) ; => #t

(struct mut-point (x y #:mutable)) ; => point
(define mp (mut-point 1 2)) ; => mp = (mut-point 1 2)
(set-mut-point-x! mp 5) ; => mp = (mut-point 5 2)
```

1.8.2 Pairs

- > definition: (`cons` <first> <second>)
- > getter of first element: `car`
- > getter of second element: `cdr`
- > car and cdr can be composed: `caddr`, `caaar`
- > pairs are immutable

```
(cons 1 2) ; => '(1 . 2)
(car '(1 . 2)) ; => 1
(cdr '(1 . 2)) ; => 2
(caar '((1 . 2) . 3)) ; => 1
(cadr '((1 . 2) . 3)) ; => 2
(cdar '((1 . 2) . 3)) ; => 2
(caddr '((1 . 2) . 3)) ; => 3
```

1.8.3 Lists

- > lists are composed of pairs
- > manually defined via `quote`: '(1 2 3)
- > empty list: '()
- > list of length n: (`build-list` <n> <procedure>)
- > list of length n with initial value <init>: (`make-list` <n> <init>)

- > lists are made by pairs

- the `car` contains the first value
- the `cdr` contains the the rest of the list
- the last pair has `cdr` equal to '()

```
'(1 2 3) ; => '(1 2 3)
'(1 . (2 . (3 . ()))) ; => '(1 2 3)
```

Operations on lists

- > list length: `length`
- > add an element at the beginning: `cons`
- > add an element at the end: `append`
- > take the first element: `first`
- > take the last element: `last`
- > take the n-th element: `list-ref` <list> <n>
- > take the n-th element after pos: `list-tail` <list> <pos>
- > take the first n elements: `take` <list> <n>
- > take the last n elements: `drop` <list> <n>
- > count the occurrences of an element: `count` <predicate> <list>
- > apply a filter: `filter` <predicate>
- > apply a function to each element: `map` <function>
- > get the reverse of a list: `reverse`
- > get the elements after the first: `rest`

```
(length '(1 2 3)) ; => 3
(cons 1 '(2 3)) ; => '(1 2 3)
(append '(1 2) '(3 4)) ; => '(1 2 3 4)
(first '(1 2 3)) ; => 1
(last '(1 2 3)) ; => 3
(list-ref '(1 2 3) 1) ; => 2
(list-tail '(1 2 3) 1) ; => '(2 3)
(take '(1 2 3) 2) ; => '(1 2)
(drop '(1 2 3) 1) ; => '(2 3)
(count even? '(1 2 3 4)) ; => 2
(filter even? '(1 2 3 4)) ; => '(2 4)
(map add1 '(1 2 3)) ; => '(2 3 4)
(reverse '(1 2 3)) ; => '(3 2 1)
(rest '(1 2 3)) ; => '(2 3)
```

Lists folding

- > lists can be folded from the left with `foldl`
- > lists can be folded from the right with `foldr`
- > the accumulator is the first argument of the function
- > the list is the second argument of the function
- > the function is applied to the accumulator and the first element of the list

```
(foldl + 0 '(1 2 3 4)) ; => 10
(foldr * 1 '(1 2 3 4)) ; => 24
```

1.8.4 Vectors

- > definition: `#(<element> ...)`
- > getter: `vector-ref`
- > vector are immutable, fixed size and zero-indexed

```
#(1 2 3) ; => '#(1 2 3)
(vector-ref '#(1 2 3) 0) ; => 1
```

1.8.5 Sets

- > definition: `(set <element> ...)`
- > convert a list to a set: `list->set`
- > add an element: `set-add`
- > remove an element: `set-remove`
- > test if an element is in the set: `set-member?`
- > sets don't allow duplicates, are unordered and mutable
- > methods return a new set instead of changing the original one

```
(set 1 2 3) ; => '#(1 2 3)
(list->set '(1 2 3)) ; => '#(1 2 3)
(set-add (set 1 2 3) 4) ; => '#(1 2 3 4)
(set-remove (set 1 2 3) 2) ; => '#(1 3)
(set-member? (set 1 2 3) 2) ; => #t
```

1.8.6 Hash

- > definition: `(hash <key> <value> ...)`
- > add a key-value pair: `hash-set`
- > remove a key-value pair: `hash-remove`
- > get a value from a key: `hash-ref`
- > test if a key is in the hash: `hash-has-key?`

```
(hash 1 2 3 4) ; => '#hash((1 . 2) (3 . 4))
(hash-set (hash 1 2 3 4) 5 6) ; => '#hash((1 . 2) (3 . 4)
(5 . 6))
(hash-remove (hash 1 2 3 4) 3) ; => '#hash((1 . 2) (4 . 4))
(hash-ref (hash 1 2 3 4) 1) ; => 2
(hash-has-key? (hash 1 2 3 4) 1) ; => #t
```

1.9 Control flow

1.9.1 Conditionals

if

- > if: `(if <predicate> <then> <else>)`
- > when: `(when <predicate> <then>)`
- > unless: `(unless <predicate> <else>)`

```
(if #t 1 2) ; => 1
(when #t 1) ; => 1
(when #f 1) ; => #<void>
(unless #t 1) ; => #<void>
(unless #f 1) ; => 1
```

cond - case

- > cond: `(cond [<predicate> <then>] ... [<else> <else-then>])`
- > case: `(case <value> [<case-clause> <then>] ... [<else> <else-then>])`
- > the `else` clause is optional
- > in cond, the value is evaluated against each predicate
- > in case, the value is evaluated against each clause whose quote is `eqv?`

```
(case (+ 7 5)
  [(1 2 3) 'small]
  [(10 11 12) 'big]
  [else 'neither]) ; => 'big
(let ((x 0))
  (cond ((positive? x) 'positive)
        ((negative? x) 'negative)
        (else 'zero))) ; => 'zero
```

pattern matching

- > match: `(match <value> [<pattern> <then>] ... [_ <else-then>])`

```
(define (fizzbuzz? n)
  (match (list (remainder n 3) (remainder n 5))
    [(list 0 0) 'fizzbuzz]
    [(list 0 _) 'fizz]
    [(list _ 0) 'buzz]
    [_ #f]))

(fizzbuzz? 15) ; => 'fizzbuzz
(fizzbuzz? 37) ; => #f
```

1.9.2 Loops

when

- > when: (when <predicate> <then>)
- > also available as named let

```
;; named let
(let label ((x 0)) ; initialize x as 0
  (when (< x 10) ; iterate while x < 10
    (display x) ; print x
    (newline)
    (label (+ x 1)))) ; increment x, go back to label

(define (loop i)
  (when (< i 10)
    (printf "i=~a\n" i)
    (loop (add1 i))))
(loop 5) ; => i=5, i=6, i=7, i=8, i=9
```

for

- > for in a range: (for ([<var> <start> <end>])<body>)
- > for over lists: (for ([<var> <list>])<body>)
- > for is available for other collections

```
(for ([i 10])
  (printf "i=~a\n" i)) ; => i=0, i=1, ...
(for ([i (in-range 5 10)])
  (printf "i=~a\n" i)) ; => i=5, i=6, ...

(for ([i (in-list '(1 i s t))])
  (displayln i))

(for ([i (in-vector #(v e c t o r))])
```

```
(displayln i))

(for ([i (in-string "string")])
  (displayln i))

(for ([i (in-set (set 'x 'y 'z))])
  (displayln i))

(for ([k v] (in-hash (hash 'a 1 'b 2 'c 3))))
  (printf "key:~a value:~a\n" k v))
```

1.10 Macros and syntax rules

- > macros are defined via `define-syntax`(<name> <expansion>)
- > syntax rules are defined via `syntax-rules`(<pattern> <expansion>)
- > macros are expanded at compile time
- > syntax rule are pairs (<pattern> <expansion>)
- > the ... operator indicates repetitions of patterns
- > the _ operator is used to match any syntax object

```
(define-syntax while
  (syntax-rules () ; no other keyword is needed
    ((_ condition body ...) ; pattern P
     (let loop () ; expansion of P
       (when condition
         ((begin body ...
                  (loop)))))))
```

1.11 Continuations

- > two ways to call a continuation:
 - `call-with-current-continuation` <procedure>
 - `call/cc` <procedure>
- > saving the continuation: `save!` <continuation>

1.12 Exceptions

- > exceptions are implemented via continuations
- > raise an exception: `raise`
- > catch an exception: `with-handlers`

```
(with-handlers ([exn:fail? (lambda (e) (printf "error:
~a\n" e))])
  (raise (exn:fail "error message"))) ; => error: error
message
```

2 Erlang

3 Haskell