

```

program : program_head routine DOT
program_head : PROGRAM ID SEMI
routine : routine_head ID routine_body
name_list : name_list COMMA ID | ID
sub_routine : routine_head routine_body
routine_head : label_part const_part type_part var_part routine_part
label_part : ε
const_part : CONST const_expr_list | ε
const_expr_list : const_expr_list NAME EQUAL const_value SEMI
                  | NAME EQUAL const_value SEMI
const_value : INTEGER | REAL | CHAR | STRING | SYS_CON
type_part : TYPE type_decl_list | ε
type_decl_list : type_decl_list type_definition | type_definition
type_definition : NAME EQUAL type_decl SEMI
type_decl : simple_type_decl | array_type_decl | record_type_decl
array_type_decl : ARRAY LB simple_type_decl RB OF type_decl
record_type_decl : RECORD field_decl_list END OF
field_decl_list : field_decl_list field_decl | field_decl
field_decl : name_list COLON type_decl SEMI
simple_type_decl : SYS_TYPE | NAME | LP name_list RP
                  | const_value DOTDOT const_value
                  | MINUS const_value DOTDOT const_value
                  | MINUS const_value DOTDOT MINUS const_value
                  | NAME DOTDOT NAME
var_part : VAR var_decl_list | ε
var_decl_list : var_decl_list var_decl | var_decl
var_decl : name_list COLON type_decl SEMI
routine_part : routine_part function_decl | routine_part procedure_decl
               | function_decl | procedure_decl
function_decl : FUNCTION ID parameters COLON simple_type_decl
procedure_decl : procedure_head SEMI sub_routine SEMI
parameters : LP para_decl_list RP | ε
para_decl_list : para_decl_list SEMI para_type_list
para_type_list : var_para_list COLON simple_type_decl
                  | val_para_list COLON simple_type_decl
var_para_list : VAR name_list
val_para_list : name_list
routine_body : compound_stmt
stmt_list : stmt_list stmt SEMI | ε
stmt : INTEGER COLON non_label_stmt | non_label_stmt
non_label_stmt : assign_stmt | proc_stmt | compound_stmt | if_stmt | repeat_stmt |
                  while_stmt
                  | for_stmt | case_stmt | goto_stmt

```

stmt本身不包括COLON

```

assign_stmt : ID ASSIGN expression
            | ID LB expression RB ASSIGN expression
            | ID DOT ID ASSIGN expression
proc_stmt : ID
          | ID LP args_list RP
          | SYS_PROC
          | SYS_PROC LP args_list RP
          | READ LP factor RP
compound_stmt : BEGIN stmt_list END
if_stmt : IF expression THEN start else_clause
else_clause : ELSE stmt | ε
repeat_stmt : REPEAT stmt_list UNTIL expression
while_stmt : WHILE expression DO stmt
for_stmt : FOR ID ASSIGN expression direction expression DO stmt
direction : TO | DOWNTO
case_stmt : CASE expression OF case_expr_list END
case_expr_list : case_expr_list case_expr | case_expr
case_expr : const_value COLON stmt SEMI
           | ID COLON stmt SEMI
goto_stmt : GOTO INTEGER
expression_list : expression_list COMMA expression | expression
expression : expression GE expr | expression GT expr | expression LE expr
           | expression LT expr | expression EQUAL expr
           | expression UNEQUAL expr | expr
expr : expr PLUS term | expr MINUS term | expr OR term | term
term : term MUL factor | term DIV factor | term DIV factor
      | term MOD factor | term AND factor | factor
factor : NAME | NAME LP args_list RP | SYS_FUNCT
        SYS_FUNCT LP args_list RP | const_value | LP expression RP
        | NOT factor | MINUS factor | ID LB expression RB
        | ID DOT ID
args_list : args_list COMMA expression | expression
说明:

```

LP 为“(”	PLUS 为“+”
RP 为“)”	MINUS 为“-”
LB 为“[”	ID 为标识符
RB 为“]”	GE 为“>=”
DOT 为“.”	GT 为“>”
COMMA 为“; ”	LE 为“<=”
COLON 为“,”	LT 为“<”
MUL 为“*”	EQUAL 为“=”
DIV 为“/”	ASSIGN 为“:=”