Last Updated: 03/12/2026 01:09:53

Product List Query

POST API path:/b2b-overseas-api/v1/buyer/product/skus/v1 -
moz-
alt-

Update Log

Date	Details
08/28/2025	New interface added
01/22/2026	Querying based on added time is supported, with new request parameters: queryTimeType, startTime, and endTime added to specify the time type and range. The response includes the new addedTime field.

Use Case

Query the product list on GIGAB2B. Only the products in Buyer's Saved Items List or products with stockpiled inventory can be accessed.

Rate Limiting Rule

10 requests per 10 seconds

Header Parameters

Parameter Name	Data Type	Required ?	Description	Default Value
Content-Type	string	true		application/json
timestamp	string	true	The time is converted to milliseconds, the number of seconds that have passed since January 1, 1970 (UTC). Only requests within 20 minutes are processed.	
nonce	string	true	10-digit random	
sign	string	true	Signature	
client-id	string	true	Open API account applied by user	

Query Parameters

None

Request Body Parameters

Parameter Name	Data Type	Required ?	Description	Default Value
page	integer	false	Page number, no smaller than 1. The calculation rule for the range of returned orders is: from pageSize*(page-1)+1 to pageSize*page. For example, if page=10 and pageSize=100, then the orders returned on page 10 are from the 901st to the 1000th. By default, it starts from the first page.	
pageSize	integer	false	The size of each page, indicating the number of order lines included in each page. Min 100 order lines and max 10000 order lines.The default value is 5,000 when left blank.	
sort	integer	false	Product sorting by: 1:updatTime:asc; 2:updatTime:desc; 3:datePosted:asc; 4:datePosted:desc	
firstArrivalDate	string	false	The date when the product’s first batch of inventory arrived at the warehouse. Format: yyyy-MM-dd. Example: if firstArrivalDate=A, then products with First Arrival Date no earlier than A will be returned.	
lastUpdatedAfter	string	false	When this field is filled, query the SKU with updateTime later than the filled time; No limit when left blank.	
queryTimeType	integer	false	Supported queryTimeType: 1 - Last update time: will invalidate the lastUpdatedAfter request parameter if selected. 2 - Added time: The latest time when a product was added to My Saved Items. Note: startTime/endTime must be provided after the queryTimeType is selected, and vice versa.	
startTime	string	false	Format: yyyy-MM-dd HH:mm:ss. Default time zone: UTC-8. Note: This field must be provided with both endTime and queryTimeType fields together; otherwise, it becomes invalid.	
endTime	string	false	Defining a time range with startTime. Format: yyyy-MM-dd HH:mm:ss. Default time zone: UTC-8. Note: This field must be provided with both startTime and queryTimeType fields together; otherwise, it becomes invalid.	

Example Request

```
{
 "lastUpdatedAfter":"2024-02-19 02:16:48",
 "firstArrivalDate":"2025-02-19",
 "sort":4,
 "page":1,
 "pageSize":200
"queryTimeType":2,
"startTime":"2025-07-01 00:00:00",
"endTime":"2026-01-01 00:00:00"
}
```

-
moz-
alt-
content

Response Parameters

Parameter Name	Data Type	Required ?	Description	Default Value
success	boolean	true	Indicates whether the request was successful	
code	string	true	Error code. Both successful and failed requests will include this response.	
data	object	false	Response data	
pageInfo	object	false	pageInfo	
page	integer	false	page number	
totalPage	integer	false	total page number	
pageSize	integer	false	page size	
totalNum	integer	false	total number	
records	array	false	data	
sku	string	false	Item Code on GIGAB2B	
productName	string	false	Product name	
updateTime	string	false	Last update time. Time zone: GMT-8.Fomart:yyyy-MM-dd HH:mm:ss	
firstArrivalDate	string	false	The date when the product’s first batch of inventory arrived at the warehouse. Format: yyyy-MM-dd. Note: The previous name is “firstAvailableDate”	
addedTime	string	false	The latest time when a product was added to My Saved Items. Format: yyyy-MM-dd HH:mm:ss. Time zone: UTC-8.	
requestId	string	true	The unique identifier of the request.	
msg	string	false	Error message. The content may be blank for secondary errors.	
subMsg	string	false	Detailed error message description.	
recommend	string	false	Error Diagnostics URL	

Example Response

```
{
 "success": true,
 "code": "200",
 "data": {
  "pageInfo": {
   "page": 1,
   "totalPage": 1,
   "pageSize": 200,
   "totalNum": 7
  },
  "records": [
   {
    "sku": "W275236P204180",
    "productName": "test productName1",
    "updateTime": "2025-07-23 18:51:43",
    "firstArrivalDate": "2025-07-23",
    "addedTime": "2025-01-01 00:51:43"
   },
   {
    "sku": "W275236P204179",
    "productName": "test productName2",
    "updateTime": "2025-07-23 18:51:33",
    "firstArrivalDate": "2025-07-23",
    "addedTime": "2025-01-01 00:51:43"
   },
   {
    "sku": "B215P204169",
    "productName": "test productName3",
    "updateTime": "2025-07-22 23:53:42",
    "firstArrivalDate": "2025-07-23",
    "addedTime": "2025-01-01 00:51:43"
   },
   {
    "sku": "W2727S00101",
    "productName": "test productName4",
    "updateTime": "2025-07-06 20:20:31",
    "firstArrivalDate": "2025-07-06",
    "addedTime": "2025-01-01 00:51:43"
   },
   {
    "sku": "W2727S00006",
    "productName": "test productName5",
    "updateTime": "2025-03-20 02:16:48",
    "firstArrivalDate": "2025-02-20",
    "addedTime": "2025-01-01 00:51:43"
   },
   {
    "sku": "W2727S00005",
    "productName": "test productName6",
    "updateTime": "2025-02-20 22:53:54",
    "firstArrivalDate": "2025-02-20",
    "addedTime": "2025-01-01 00:51:43"
   },
   {
    "sku": "W2727P197262",
    "productName": "test productName7",
    "updateTime": "2025-02-19 23:18:59",
    "firstArrivalDate": "2025-02-19",
    "addedTime": "2025-01-01 00:51:43"
   }
  ]
 },
 "requestId": "17db2e89f2b68ff9",
 "msg": "success",
 "subMsg": null,
 "recommend": null
}
```

-
moz-
alt-
content

Error Code

Error Code	Error Message	Error Description	Solution	Other
200	Request success.			
401	Interface not available.		Retry with an alternative available interface, or contact Marketplace Online Service	
404	The path does not exist.		Check the interface path	
500	System exception, pleases contact online service		Try again later and contact Marketplace Online Service	
400001	Too many requests. Rate limit exceeded		Review rate limiting rules in the document	
400003	Parameter format or syntax error, please check and try again.			
400004	Invalid sign		Verify the signature and its components	
400005	Sign required		Add signature to request header	
400006	Timestamp required		Add timestamp to request header	
400007	Invalid timestamp format		Verify the timestamp	
400008	Request expired: Timestamp exceeds 20-minute validity window.		Initiate the request again	
400009	Nonce required		Add a nonce to request header	
4000010	Invalid nonce			
B20002	Invalid data: Format error/Invalid character length/Value not in enum range/Package not in this shipment.	The lastUpdatedAfter format is incorrect.		
B20002	Invalid data: Format error/Invalid character length/Value not in enum range/Package not in this shipment.	The page format is incorrect.	Pagination parameter (page, default=1) is empty or page number < 1	
B20002	Invalid data: Format error/Invalid character length/Value not in enum range/Package not in this shipment.	The limit format is incorrect.	Pagination parameter (limit, default=5000) is empty, or exceeds the range of 1 to 100	
B20002	Invalid data: Format error/Invalid character length/Value not in enum range/Package not in this shipment.	Only 1 or 2 can be filled in the queryTimeType field.		
B20002	Invalid data: Format error/Invalid character length/Value not in enum range/Package not in this shipment.	The startTime format is incorrect. It must be in yyyy-MM-dd HH:mm:ss.		
B20002	Invalid data: Format error/Invalid character length/Value not in enum range/Package not in this shipment.	The endTime format is incorrect. It must be in yyyy-MM-dd HH:mm:ss.		
B20002	Invalid data: Format error/Invalid character length/Value not in enum range/Package not in this shipment.	Product query by last update time only supports the following two mutually exclusive modes: Use lastUpdatedAfter to query SKU with updateTime on/after the filled time (if lastUpdatedAfter=A, then SKUs with updateTime on/after A will be returned); Query with the provided queryTimeType field and startTime/endTime range (e.g.: queryTimeType=1, and time range defined by startTime and endTime fields).		
B20001	Required fields cannot be blank.	queryTimeType is required when both startTime and endTime fields are provided.		
B20001	Required fields cannot be blank.	Both startTime and endTime fields are required when the queryTimeType field is provided.		

GIGACLOUD TECHNOLOGY