

BLACK TEA MOTORBIKES

BONFIRE





BONFIRE SPEC SHEET

"A bike built for whatever you call a road."

Everything, from frame, to wheels, drivetrain & lights have been carefully sourced and assembled in Munich to create a bike that convinces through an agile, torquey, and exciting experience is possible while maintaining its vintage charm.

The reduction in weight & the simple-to-use electric drivetrain make riding easier, more fun & more attractive for everyone with less experience.

To further enhance the usability across motorcycle models, Black Tea Motorbikes uses a Uniform Battery System:

All motorcycle models are powered by the same battery. Newer Motorcycles can be used with older batteries & vice versa. This ensures that our Riders can benefit from the latest progress in technology.

This Spec Sheet provides you with all technical details & specifications. If you still have questions regarding technical aspects, you can contact us under service@blackteamotorbikes.com.

Dimensions

Length: 1900 mm
Width: 700 mm
Height: 1250 mm
Wheelbase: 1300 mm
Fork Angle: 24.5 °

Weight & Load

Gross Vehicle Weight Restriction: 260 kg
Total Curb "Wet" Weight (1 battery): 97,5 kg
Total "Dry" Weight: 86 kg

Body

Frame, Swing Arm, Box, Side Panels & Fenders are made from high-quality steel
Frame: Steel Tube Chassis
Anti-Theft Protection: Steering Lock

Drivetrain

Type: Hub Permanent magnet motor (PSM)
Rated Power: 3 kW (5 HP) at 450 RPM
Peak Power: 5,4 kW (8 HP) at 480 RPM
Torque: 195 Nm
Environmental Protection: IP54

Ride Modes

USA: 50 mph top speed
EU: 45km/h restricted top speed
Ride Modes: Eco, Normal & Sport
Features: Ride Modes with different torque, acceleration & top speed

Range per Battery

Eco Mode: 75 km
Normal Mode: 65 km
Speed Mode: 55 km (WMTC-II tested)

Charging

Type: External charger for standard outlets
0-80%: 3 hours
Charge Current: 10 A

Battery

Cells: Premium 18650 Li-Ion cells
Configuration: 14S12P
Voltage: 51.8 V
Capacity: 35 Ah / 1.8 kWh
Peak Current: ~95 A
Battery Voltage Range: 45 – 58.8 V
Dimensions: 310 x 220 x 100 mm
Weight: 11.5 kg
Connector: QS8-S Anti Spark
Life Cycle: Rated for 800 Charge Cycles
Features: Removable, Two batteries fit in the Bonfire, Can be charged while installed

ECU

Controller Type: Electronic Sine Wave (BLDC)
Environmental Protection: IP66
Features: Enhanced Regenerative Braking, Hardware Over-Current and Over-Voltage Protection, Low Voltage Battery Protection, Fault Codes, Aluminium Housing for Maximum Heat Dissipation

Electronics & Dashboard

Throttle Type: Full Twist DOMINO Hall (IP66)
Display: Battery SoC, voltage, speedometer, odometer, trip meter, ride mode, time and tell-tales.

Brakes & Recuperation

Type: Dual-Piston Hydraulic Disc Brake
Front: 220 mm Disc with 3 mm thickness
Rear: 220 mm Disc with 3 mm thickness
Brake Fluid Type: DOT 4
Regenerative Braking: As you release the throttle you feel the bike slowing down

Suspension

Front: Hydraulic forks featuring 31mm tubes for extra rigidity and strength.
Travel: 200mm
Rear: Adjustable 335mm dual shocks

Wheels

Hub: Aluminum hubs with 12 mm axle
Rim: 1.85 x 18" 36 spoked aluminum rims
Tires: 3.00 x 18" Heidenau Off-Road or Street
Maximum Possible Tire Width: 3.50 "

Regulatory

Classification: L1e-B (EU) / Motor-Driven Cycle (USA)
License requirement: AM or B (EU) / M1 (USA)