

BLACK TEA MOTORBIKES

BONFIREY





BONFIRE Y SPEC SHEET

"Fun-to-ride commuter and weekend explorer. Engineered for the daily commute as well as the outback."

Everything, from frame, to wheels, drivetrain & lights have been carefully sourced and assembled in Munich to create a bike that convinces through an agile, torquey and exciting experience is possible while maintaining its vintage charm.

Bonfire Y comes with a unique dual battery system. Unlike traditional electric motorcycles, the batteries are connected in series. Thereby delivering plenty of power to leave everyone behind.

Two batteries are used simultaneously to improve acceleration & top speed through a high voltage drivetrain while offering the convenience and safety of low voltage batteries.

This Spec Sheet provides you with all technical details & specifications. If you still have questions regarding technical aspects, you can contact us under service@blackteamotorbikes.com.

Dimensions

Length: 1900 mm
Width: 700 mm
Height: 1250 mm
Wheelbase: 1300 mm
Fork Angle: 24.5 °

Weight & Load

Gross Vehicle Weight Restriction: 260 kg
Total Curb "Wet" Weight: 120 kg
Total "Dry" Weight: 87 kg

Body

Frame, Swing Arm, Box, Side Panels & Fenders are made of high-quality steel
Frame: Steel Tube Chassis
Anti-Theft Protection: Steering Lock & Alarm

Drivetrain

Type: Hub Permanent magnet motor (PSM)
Rated Power: 11 kW (15 HP) at 900 RPM
Peak Power: 16 kW (22 HP) at 960 RPM
Torque: 250 Nm
Environmental Protection: IP54

Ride Modes

Top Speed: 120 km/h
Ride Modes: Eco, Normal & Sport
Features: Ride Modes with different torque, acceleration & top speed

Range

Eco Mode: 130 km
Normal Mode: 100 km
Speed Mode: 60 km

Charging

Type: 2 x External charger for standard outlets
0-80%: 3 hours
Charge Current: 2 x 20 A

Battery

Cells: Premium 21700 Li-Ion cells
Configuration: 2 battery packs in serial
Voltage: 96 V
Capacity: 55 Ah / 5.2 kWh
Peak Current: ~150 A
Battery Voltage Range: 84 - 113 V
Dimensions: 310 mm x 220 mm x 100 mm
Weight: 2 x 14 kg
Connector: QS10-S Anti Spark
Life Cycle: Rated for 800 Charge Cycles
Features: Removable, Two batteries fit in the Bonfire, Can be charged while installed

ECU

Controller Type: Electronic Sine Wave (BLDC)
Environmental Protection: IP66
Features: Enhanced Regenerative Braking, Hardware Over-Current and Over-Voltage Protection, Low Voltage Battery Protection, Fault Codes, Aluminium Housing for Maximum Heat Dissipation

Electronics & Dashboard

Throttle Type: Full Twist DOMINO Hall (IP66)
Display: Battery SoC, voltage, speedometer, odometer, trip meter, ride mode, time and tell-tales.

Brakes & Recuperation

Type: CBS Hydraulic Disc Brake
Front: 265 mm Disc with 4 mm thickness
Rear: 180 mm Disc with 3 mm thickness
Brake Fluid Type: DOT 4
Regenerative Braking: Activates when you brake

Suspension

Front: Hydraulic forks featuring 31mm tubes for extra rigidity and strength.
Travel: 200mm
Rear: Adjustable 335mm dual shocks

Wheels

Rim (front): 1.85 x 18" 36 spoked rims
Rim (rear): 2.15 x 18" 36 spoked rims
Tire (front): 3.50 x 18" Heidenau K36
Tire (front): 90/90 x 18" Heidenau K60
Tire (front): 110/80 x 18" Heidenau K36 or K60

Regulatory

Classification: L3e-A1 (EU) / Motorcycle (USA)
License requirement: A1 or B196 (EU) / M2 (USA)

BLACK TEA MOTORBIKES

