

BLACK TEA MOTORBIKES

BONFIRES



BLACK TEA MOTORBIKES

Dimensions

Length: 1900 mm
Width: 700 mm
Height: 1250 mm
Wheelbase: 1300 mm
Fork Angle: 24.5 °

Weight & Load

Gross Vehicle Weight Restriction: 260 kg
Total Curb "Wet" Weight (1 battery): 100 kg
Total "Dry" Weight: 88 kg

Body

Frame, Swing Arm, Box, Side Panels & Fenders are made from high-quality steel
Frame: Steel Tube Chassis
Anti-Theft Protection: Steering Lock

Drivetrain

Type: Hub Permanent magnet motor (PSM)
Rated Power: 3 kW (5 HP) at 450 RPM
Peak Power: 5,4 kW (8 HP) at 480 RPM
Torque: 195 Nm
Environmental Protection: IP54

Speed

Top Speed: 45km/h restricted top speed
Ride Modes: Eco, Normal & Sport
Features: Ride Modes with different torque, acceleration & top speed

Range per Battery

Eco Mode: 75 km
Normal Mode: 65 km
Speed Mode: 55 km (WMTC-II tested)

Charging

Type: External charger for standard outlets
5 A charger: 6 hours
10 A charger: 3 hours

Battery

Cells: Premium 18650 Li-Ion cells
Configuration: 14S12P
Voltage: 51.8 V
Capacity: 35 Ah / 1.8 kWh
Peak Current: ~90 A
Battery Voltage Range: 44 – 58.8 V
Dimensions: 310 x 220 x 100 mm
Weight: 11.5 kg
Connector: QS8-S Anti Spark
Life Cycle: Rated for 800 Charge Cycles
Features: Removable, Two batteries fit in the Bonfire, Can be charged while installed

ECU

Controller Type: Electronic Sine Wave (BLDC)
Environmental Protection: IP66
Features: Enhanced Regenerative Braking, Hardware Over-Current and Over-Voltage Protection, Low Voltage Battery Protection, Fault Codes, Aluminium Housing for Maximum Heat Dissipation

Electronics & Dashboard

Throttle Type: Full Twist DOMINO Hall (IP66)
Display: Battery SoC, voltage, speedometer, odometer, trip meter, ride mode, and tell- tales.
Remote Key for starting vehicle & alarm

Brakes & Recuperation

Type: Combined Hydraulic Brake System (CBS)
Front: 265 mm Disc with 3 mm thickness
Rear: 180 mm Disc with 3 mm thickness
Brake Fluid Type: DOT 4
Regenerative Braking: As you release the throttle you feel the bike slowing down

Suspension

Front: Hydraulic forks featuring 31mm tubes for extra rigidity and strength.
Travel: 200mm
Rear: Adjustable 335mm dual shocks

Wheels

Rim (front): 1.85 x 18" 36 spoked rims
Rim (rear): 2.15 x 18" 36 spoked rims
Tire (front): 3.50 x 18" Heidenau K36
Tire (front): 90/90 x 18" Heidenau K60
Tire (front): 110/80 x 18" Heidenau K36 or K60

Regulatory

Class: L1e-B (EU) / Motor-Driven Cycle (USA)
License requirement: AM or B (EU) / M1 (USA)

BLACK TEA MOTORBIKES



BLACK TEA MOTORBIKES

Dimensions

Length: 1900 mm
Width: 700 mm
Height: 1250 mm
Wheelbase: 1300 mm
Fork Angle: 24.5 °

Weight & Load

Gross Vehicle Weight Restriction: 260 kg
Total Curb "Wet" Weight (1 battery): 100 kg
Total "Dry" Weight: 88 kg

Body

Frame, Swing Arm, Box, Side Panels & Fenders are made from high-quality steel
Frame: Steel Tube Chassis
Anti-Theft Protection: Steering Lock

Drivetrain

Type: Hub Permanent magnet motor (PSM)
Rated Power: 3 kW (5 HP) at 550 RPM
Peak Power: 4 kW (8 HP) at 600 RPM
Torque: 195 Nm
Environmental Protection: IP54

Speed

Top Speed: 85km/h
Ride Modes: Eco, Normal & Sport
Features: Ride Modes with different torque, acceleration & top speed

Range per Battery

Eco Mode: 75 km
Normal Mode: 65 km
Speed Mode: 55 km (WMTC-II tested)

Charging

Type: External charger for standard outlets
5 A charger: 6 hours
10 A charger: 3 hours

Battery

Cells: Premium 18650 Li-Ion cells
Configuration: 14S12P
Voltage: 51.8 V
Capacity: 35 Ah / 1.8 kWh
Rated Current: ~80 A
Battery Voltage Range: 44 - 58.8 V
Dimensions: 310 x 220 x 100 mm
Weight: 11.5 kg
Connector: QS8-S Anti Spark
Life Cycle: Rated for 800 Charge Cycles
Features: Removable, Two batteries fit in the Bonfire, Can be charged while installed

ECU

Controller Type: Electronic Sine Wave (BLDC)
Environmental Protection: IP66
Features: Enhanced Regenerative Braking, Hardware Over-Current and Over-Voltage Protection, Low Voltage Battery Protection, Fault Codes, Aluminium Housing for Maximum Heat Dissipation

Electronics & Dashboard

Throttle Type: Full Twist DOMINO Hall (IP66)
Display: Battery SoC, voltage, speedometer, odometer, trip meter, ride mode, and tell-tales.
Remote Key for starting vehicle & alarm

Brakes & Recuperation

Type: CBS Hydraulic Disc Brake
Front: 265 mm Disc with 4 mm thickness
Rear: 180 mm Disc with 3 mm thickness
Brake Fluid Type: DOT 4
Regenerative Braking: Activates when you brake

Suspension

Front: Hydraulic forks featuring 31mm tubes for extra rigidity and strength.
Travel: 200mm
Rear: Adjustable 335mm dual shocks

Wheels

Rim (front): 1.85 x 18" 36 spoked rims
Rim (rear): 2.15 x 18" 36 spoked rims
Tire (front): 3.50 x 18" Heidenau K36
Tire (front): 90/90 x 18" Heidenau K60
Tire (front): 110/80 x 18" Heidenau K36 or K60

Regulatory

Classification: L3e-A1 (EU) / Motorcycle (USA)
License requirement: A1 or B196 (EU) / M2 (USA)

BLACK TEA MOTORBIKES

BONFIRE X



BLACK TEA MOTORBIKES

Dimensions

Length: 1900 mm
Width: 700 mm
Height: 1250 mm
Wheelbase: 1300 mm
Fork Angle: 24.5 °

Weight & Load

Gross Vehicle Weight Restriction: 260 kg
Total Curb "Wet" Weight (1 battery): 112 kg
Total "Dry" Weight: 88 kg

Body

Frame, Swing Arm, Box, Side Panels & Fenders are made from high-quality steel
Frame: Steel Tube Chassis
Anti-Theft Protection: Steering Lock

Drivetrain

Type: Hub Permanent magnet motor (PSM)
Rated Power: 5,1 kW (5 HP) at 750 RPM
Peak Power: 8 kW (8 HP) at 800 RPM
Torque: 195 Nm
Environmental Protection: IP54

Speed

Top Speed: 100km/h
Ride Modes: Eco, Normal & Sport
Features: Ride Modes with different torque, acceleration & top speed

Range per Battery

Eco Mode: 110 km
Normal Mode: 70 km
Speed Mode: 55 km (WMTC-II tested)

Charging

Type: External charger for standard outlets
5 A charger: 6 hours
10 A charger: 3 hours

Battery

Cells: Premium 18650 Li-Ion cells
Configuration: 2 x 14S12P
Voltage: 104 V
Capacity: 35 Ah / 3.6 kWh
Rated Current: ~80 A
Battery Voltage Range: 88 - 117.6 V
Dimensions: 310 x 220 x 100 mm
Weight: 11.5 kg
Connector: QS8-S Anti Spark
Life Cycle: Rated for 800 Charge Cycles
Features: Removable, Two batteries fit in the Bonfire, Can be charged while installed

ECU

Controller Type: Electronic Sine Wave (BLDC)
Environmental Protection: IP66
Features: Enhanced Regenerative Braking, Hardware Over-Current and Over-Voltage Protection, Low Voltage Battery Protection, Fault Codes, Aluminium Housing for Maximum Heat Dissipation

Electronics & Dashboard

Throttle Type: Full Twist DOMINO Hall (IP66)
Display: Battery SoC, voltage, speedometer, odometer, trip meter, ride mode, and tell-tales.
Remote Key for starting vehicle & alarm

Brakes & Recuperation

Type: CBS Hydraulic Disc Brake
Front: 265 mm Disc with 4 mm thickness
Rear: 180 mm Disc with 3 mm thickness
Brake Fluid Type: DOT 4
Regenerative Braking: Activates when you brake

Suspension

Front: Hydraulic forks featuring 31mm tubes for extra rigidity and strength.
Travel: 200mm
Rear: Adjustable 335mm dual shocks

Wheels

Rim (front): 1.85 x 18" 36 spoked rims
Rim (rear): 2.15 x 18" 36 spoked rims
Tire (front): 3.50 x 18" Heidenau K36
Tire (front): 90/90 x 18" Heidenau K60
Tire (front): 110/80 x 18" Heidenau K36 or K60

Regulatory

Classification: L3e-A1 (EU) / Motorcycle (USA)
License requirement: A1 or B196 (EU) / M2 (USA)

BLACK TEA MOTORBIKES



BLACK TEA MOTORBIKES

Drivetrain

Rated Power: 5,1 kW (15 HP) at 900 RPM
Peak Power: 8 kW (22 HP) at 960 RPM
Torque: 180 Nm
Type: PSM Hub Motor

Ride Modes

Top Speed: 100 km/h
Ride Modes: Eco, Normal & Sport
Features: Ride Modes with different torque, acceleration & top speed

Dimensions

Length: 1900 mm
Width: 700 mm
Height: 1250 mm
Wheelbase: 1300 mm
Fork Angle: 24.5 °

Weight & Load

Gross Vehicle Weight Restriction: 260 kg
Total Curb "Wet" Weight: 113 kg
Total "Dry" Weight: 88 kg

Body

Frame, Swing Arm, Box, Side Panels & Fenders are made of high-quality steel
Frame: Steel Tube Chassis
Anti-Theft Protection: Steering Lock & Alarm

Range

Eco (80 km/h): 100 km
Normal (100 km/h): 80 km
Speed (120 km/h): 50 km

Charging

Type: 2 x External charger for standard outlets
5 A charger: 6 hours
10 A charger: 3 hours

Battery

Cells: 21700 Li-Ion cells
Configuration: 2 battery packs, Removable
Voltage: 96 V
Capacity: 55 Ah / 5.2 kWh
Peak Current: ~160 A
Dimensions: 310 mm x 230 mm x 100 mm
Weight: 2 x 14 kg
Connector: QS10-S Anti Spark
Life Cycle: Rated for 800 Charge Cycles

ECU

Controller Type: Electronic Sine Wave (BLDC)
Environmental Protection: IP66
Features: Enhanced Regenerative Braking, Hardware Over-Current and Over-Voltage Protection, Low Voltage Battery Protection, Fault Codes, Aluminium Housing for Maximum Heat Dissipation

Electronics & Dashboard

Throttle Type: Full Twist DOMINO Hall (IP66)
Display: Battery SoC, voltage, speedometer, odometer, trip meter, ride mode, and tell-tales.
Remote Key for starting vehicle & alarm

Brakes & Recuperation

Type: CBS Hydraulic Disc Brake
Front: 265 mm Disc with 4 mm thickness
Rear: 180 mm Disc with 3 mm thickness
Brake Fluid Type: DOT 4
Regenerative Braking: Activates when you brake

Suspension

Front: Hydraulic forks featuring 31mm tubes
Travel: 200mm
Rear: Adjustable 335mm dual shocks

Wheels

Rim (front): 1.85 x 18" 36 spoked rims
Rim (rear): 2.15 x 18" 36 spoked rims
Tire (front): 3.50 x 18" Heidenau K36
Tire (front): 90/90 x 18" Heidenau K60
Tire (rear): 110/80 x 18" Heidenau K36 or K60

Regulatory

Classification: L3e-A1 (EU) / Motorcycle (USA)
License requirement: A1 or B196 (EU)