



LOST BOYS CYBER

THREAT INTELLIGENCE • MALWARE ANALYSIS • DETECTION ENGINEERING



UNK_DeadDrop Developer Phishing and Cryptocurrency Theft Campaign

Threat Intelligence Report

Classification	TLP:CLEAR
Published	2026-06-22
Version	1.0
Author	Lost Boys Cyber
Report Type	Threat Intelligence Report

TLP:CLEAR | Lost Boys Cyber | UNK_DeadDrop Developer Phishing and Cryptocurrency Theft Campaign - Threat Intelligence Report

Published: 2026-06-22 | TLP:CLEAR | Version: 1.0 | Author: Lost Boys Cyber

AI Generation: This report was generated with AI assistance and is provided for informational purposes only. All findings, IOCs, detection rules, hunting queries, attribution assessments, and recommendations must be independently reviewed and validated by a qualified security professional before operational use.

Table of Contents

1. Executive Summary
2. Intelligence Requirements
3. Source Review & Confidence
4. Threat Actor / Campaign Overview
5. Tactics, Techniques, and Procedures
6. Infrastructure and Indicators
7. Victimology and Targeting
8. Detection Engineering
 - 8.1. Detection Summary
 - 8.2. Sigma / Detection Content
 - 8.3. Hunt Query
9. Threat Hunting
 - 9.1. Hunt Hypothesis
 - 9.2. Hunt Query
10. Risk Assessment
11. Recommended Actions
12. References

UNK_DeadDrop Developer Phishing and Cryptocurrency Theft Campaign

1. Executive Summary

Proofpoint reports UNK_DeadDrop, a likely North Korea-aligned cluster using broad phishing and trusted developer workflows to target software developers and steal cryptocurrency. The item is selected because developer compromise can rapidly become source-code, package, cloud-token, and CI/CD compromise.

This report was produced from current public reporting available during the 2026-06-22 UTC automation window. It does not add unverified IOCs or attribution claims beyond the cited sources.

2. Intelligence Requirements

Question	Current Answer	Confidence
Who is affected?	Software developers, cryptocurrency-adjacent developers, and organizations with high-value source/build access.	Medium
What should defenders prioritize?	Hunt for the behavioral signals and control-plane activity described in Detection Engineering and Threat Hunting.	High
Are hard IOCs available in the selected sources?	Not consistently available from accessible source snippets during this run; this report emphasizes behavior-based detection and source links.	Medium

3. Source Review & Confidence

Source	Contribution	Confidence
Proofpoint	Primary campaign reporting	High
RH-ISAC	Secondary sector summary	Medium
Proofpoint Threat Insight index	Publication and related campaign context	Medium

4. Threat Actor / Campaign Overview

The campaign uses social engineering around repositories and developer trust channels. Organizations should not scope this only as user phishing; developer endpoints, GitHub/GitLab access, package tokens, SSH keys, and browser wallets should be included in hunt and response playbooks.

5. Tactics, Techniques, and Procedures

Tactic / Phase	Observed Technique	Evidence
Initial Access	Phishing via developer/repository themes	Proofpoint describes broad phishing targeting developers
Credential Access	Theft of cryptocurrency and likely developer secrets	Campaign objective includes cryptocurrency theft
Collection	Repository and endpoint artifact access	Developer targeting creates access to

		source and build materials
--	--	----------------------------

6. Infrastructure and Indicators

Indicator / Infrastructure	Type	Operational Use
No durable hard IOC published in extracted snippets	Source limitation	Use cited primary reports for any latest hashes/domains and prefer behavior hunts below.
Target-facing legitimate services	Abuse surface	Adversaries use normal web, identity, repository, advertising, or email workflows depending on campaign.

7. Victimology and Targeting

Software developers, cryptocurrency-adjacent developers, and organizations with high-value source/build access.

8. Detection Engineering

8.1. Detection Summary

Signal	Telemetry Source	Analytic Goal
New administrative rule, repository, installer, or authentication pattern inconsistent with baseline	Identity, SaaS, EDR, proxy	Surface initial access or control-plane abuse.
Script or binary execution shortly after user interaction with a lure or exposed service	EDR process telemetry	Identify payload staging and hands-on-keyboard follow-through.
External transfer or suspicious sign-in following initial signal	Network, cloud audit, identity	Detect collection/exfiltration or account takeover.

8.2. Sigma / Detection Content

<pre> title: Suspicious Campaign Follow-On Activity - unk-deaddrop-developer-phishing-cryptocurrency-theft status: experimental description: Behavioral analytic for campaign-aligned suspicious execution, authentication, or control-plane changes. Tune service names to the environment and campaign. logsource: category: process_creation detection: selection_scripting: Image endswith: - \powershell.exe - \cmd.exe - \wscript.exe - \cscript.exe - \python.exe - /bin/sh - /bin/bash selection_lure_context: CommandLine contains: - git clone - npm install - curl - wget - encodedcommand - Add-MailboxRule - Set-TransportRule </pre>
--

```

condition: selection_scripting and selection_lure_context
fields:
- Image
- CommandLine
- ParentImage
- User
- Computer
falsepositives:
- Developer administration and approved automation; require owner validation.
level: medium

```

8.3. Hunt Query

```

DeviceProcessEvents
| where Timestamp > ago(30d)
| where ProcessCommandLine has_any ("git clone", "npm install", "curl", "wget", "Add-MailboxRule",
"Set-TransportRule", "powershell -enc")
| where InitiatingProcessFileName has_any ("chrome.exe", "msedge.exe", "firefox.exe", "outlook.exe",
"teams.exe", "powershell.exe", "cmd.exe")
| project Timestamp, DeviceName, AccountName, InitiatingProcessFileName, FileName, ProcessCommandLine

```

9. Threat Hunting

9.1. Hunt Hypothesis

Developer endpoint activity involving newly cloned unknown repositories followed by script execution, wallet access, token file reads, or outbound connections to newly registered domains.

9.2. Hunt Query

```

DeviceNetworkEvents
| where Timestamp > ago(30d)
| where InitiatingProcessFileName has_any ("powershell.exe", "cmd.exe", "python.exe", "node.exe",
"git.exe", "java.exe", "splunkd.exe")
| summarize connections=count(), first_seen=min(Timestamp), last_seen=max(Timestamp),
remote_count=dcount(RemoteUrl) by DeviceName, InitiatingProcessFileName, InitiatingProcessCommandLine,
AccountName
| where connections > 10 or remote_count > 3

SignInLogs
| where TimeGenerated > ago(30d)
| summarize failures=countif(ResultType != 0), successes=countif(ResultType == 0),
countries=dcount(Location) by UserPrincipalName, AppDisplayName, IPAddress
| where failures > 20 or (successes > 0 and countries > 2)

```

10. Risk Assessment

Dimension	Assessment	Rationale
Likelihood	Medium to High	Selected because reporting is recent and defender-actionable.
Impact	High	Campaigns affect identity, research data, developer systems, or credential stores.
Confidence	medium	Based on primary/vendor reporting and corroborating public coverage.

11. Recommended Actions

Priority	Owner	Action
Critical	SOC	Run the included hunts against identity, endpoint, proxy, and SaaS logs.

High	Platform / identity owners	Reduce exposed administrative surfaces and enforce phishing-resistant MFA where supported.
High	Endpoint team	Review application allowlists, browser-download controls, and developer workstation monitoring.
Medium	Threat intel	Monitor the cited primary reports for newly published IOCs and update sidecar files.

12. References

- [Proofpoint] <https://www.proofpoint.com/us/blog/threat-insight/dont-fear-repo-unkdeaddrop-phishing-campaign-targets-developers-steal>
- [RH-ISAC] https://rhisac.org/threat-intelligence/unk_deaddrop-phishing-campaign-targets-developers-to-steal-cryptocurrency/
- [Proofpoint Threat Insight index] <https://www.proofpoint.com/us/blog/threat-insight>