



LOST BOYS CYBER

THREAT INTELLIGENCE • MALWARE ANALYSIS • DETECTION ENGINEERING



CVE-2026-45247 Mirasvit Mirasvit Full Page Cache Warmer Mirasvit Full Page Cache Warmer Deserialization of Untrusted Data Vulnerability

CVE / Vulnerability Threat Intelligence Report

Classification	TLP:CLEAR
Published	2026-06-03
Version	1.1
Author	Lost Boys Cyber
Report Type	CVE / Vulnerability Threat Intelligence Report

TLP:CLEAR | Lost Boys Cyber | CVE-2026-45247 Mirasvit Mirasvit Full Page Cache Warmer Mirasvit Full Page Cache Warmer Deserialization of Untrusted Data Vulnerability - CVE / Vulnerability Threat Intelligence Report

Published: 2026-06-03 | TLP:CLEAR | Version: 1.1 | Author: Lost Boys Cyber

AI Generation: This report was generated with AI assistance and is provided for informational purposes only. All findings, IOCs, detection rules, hunting queries, attribution assessments, and recommendations must be independently reviewed and validated by a qualified security professional before operational use.

Table of Contents

1. Executive Summary
2. Vulnerability Metadata
3. Source Review & Confidence
4. Vulnerability Details
5. Attack Scenarios
6. Threat Landscape & Exploitation Status
7. Affected Products and Exposure
8. Mitigation and Workarounds
9. Detection Engineering
10. Threat Hunting
11. MITRE ATT&CK Mapping
12. Validation / Lab Testing
13. Recommended Actions Summary
14. References

CVE-2026-45247 Mirasvit Mirasvit Full Page Cache Warmer Mirasvit Full Page Cache Warmer Deserialization of Untrusted Data Vulnerability

1. Executive Summary

CVE-2026-45247 is a critical unauthenticated deserialization / PHP object injection vulnerability affecting the Mirasvit Full Page Cache Warmer extension for Magento and Adobe Commerce. Public reporting from Sansec, Imperva, and downstream security reporting describes an attack path in which a crafted `CacheWarmer` cookie reaches unsafe PHP deserialization logic, enabling remote code execution without prior authentication in exposed storefront environments.

This is a high-priority issue because affected e-commerce storefronts are typically internet-facing, process payment-adjacent workflows, and often maintain privileged integrations into inventory, ERP, customer data, and administrative backends. CISA added the vulnerability to KEV, further increasing urgency. Any organization running the vulnerable extension should treat this as an emergency patch-and-hunt case.

2. Vulnerability Metadata

Field	Value
CVE	CVE-2026-45247
Vendor	Mirasvit
Product	Full Page Cache Warmer for Magento / Adobe Commerce
Weakness	Deserialization of untrusted data / PHP object injection
Severity	Critical
Attack Vector	Network
Privileges Required	None
User Interaction	None
Primary Impact	Unauthenticated remote code execution
Public Exploitation Signal	Added to CISA KEV; broad security reporting warns of exploitation risk
Delivery Mechanism	Crafted `CacheWarmer` cookie in storefront requests

3. Source Review & Confidence

Source	Contribution	Confidence
Sansec research	Primary public technical narrative describing crafted cookie and unsafe deserialization path	High
Imperva analysis	Defensive framing, risk characterization, and customer-protection context	Medium-High
CISA KEV / security reporting	Urgency signal and exploitation prioritization	High

Confidence is high that the issue enables unauthenticated code-execution-class impact on exposed Magento or Adobe Commerce storefronts using the vulnerable extension. Exact exploit chains and post-exploitation procedures will vary by site configuration, available gadget chains, WAF placement, and extension versioning.

4. Vulnerability Details

Public research states that a crafted `CacheWarmer` cookie can be supplied in a normal storefront request and reach PHP's native deserialization path inside the vulnerable extension. Because this happens pre-authentication and along an internet-exposed application path, attackers may be able to gain code execution without valid credentials when the extension is installed and reachable.

For commerce environments, this creates risk beyond webshell deployment alone. A successful compromise could expose customer information, support payment skimming, poison application content, tamper with checkout flows, and provide a platform for deeper lateral movement into administrative, database, or integration systems.

5. Attack Scenarios

1. Internet-facing storefront compromise

- An attacker identifies a Magento or Adobe Commerce site using the vulnerable Mirasvit extension.
- A crafted request with a malicious `CacheWarmer` cookie triggers object injection and leads to server-side code execution.

2. Mass exploitation during active scanning

- Threat actors scan for Magento fingerprints and test cookie-based exploit payloads at scale.
- Successful targets may be backdoored for persistence, skimming, credential theft, or resale.

3. Follow-on intrusion into commerce ecosystem

- After initial code execution, an adversary pivots to database credentials, admin sessions, API tokens, or third-party integrations.
- The storefront becomes a bridgehead into broader business systems.

6. Threat Landscape & Exploitation Status

This vulnerability has strong characteristics associated with rapid weaponization: pre-authentication reachability, internet-facing deployment patterns, and code-execution impact in high-value e-commerce environments. CISA KEV inclusion indicates exploitation concern significant enough to drive federal remediation deadlines.

Even in the absence of universal public exploit proof artifacts, defenders should assume broad scanning and opportunistic exploitation are plausible and should prioritize both emergency remediation and retrospective hunting for suspicious cookie-driven requests, webshell activity, anomalous admin behavior, and payment-skimming indicators.

7. Affected Products and Exposure

Product / Surface	Exposure Consideration	Priority
Magento / Adobe Commerce sites with vulnerable Mirasvit Cache Warmer extension	Directly exposed if storefront accepts attacker requests	Immediate
Internet-facing checkout, category, search, and landing pages	Most likely request paths for unauthenticated cookie delivery	Immediate
Reverse-proxied/WAF-protected storefronts	Risk reduced only if malicious cookie payloads are blocked before PHP execution	High
Internal staging clones with internet exposure	Often overlooked, but may contain secrets and admin paths	High

Defenders should inventory every site using the extension, identify owner teams, validate storefront reachability from the internet, and determine whether edge controls inspect or normalize suspicious cookies before requests reach PHP.

8. Mitigation and Workarounds

4. Apply the vendor fix or remove / disable the vulnerable extension where patching cannot be completed immediately.
5. Block or tightly inspect suspicious `CacheWarmer` cookie values at WAF, CDN, reverse proxy, or application firewall layers.
6. Hunt for evidence of webshells, unauthorized admin users, modified checkout templates, injected JavaScript, or altered cron tasks.
7. Rotate credentials and API keys accessible from the compromised application tier if exposure is suspected.
8. Review file integrity, admin audit logs, payment page content, and server-side persistence mechanisms.

9.1 Detection Opportunities

Signal	Rationale	Data Source
Requests containing abnormal or oversized `CacheWarmer` cookie values	Closest public exploit delivery indicator	WAF, CDN, web logs
PHP process launches or child processes spawned by web service accounts	Strong sign of successful code execution	EDR, Sysmon, process telemetry
Unexpected file writes under webroot, media, var, pub, or generated paths	Common post-exploitation and persistence behavior	File integrity monitoring, EDR
New admin users, config changes, or checkout template modifications	Possible monetization or persistence activity	Magento audit logs, DB change logs

9.2 Detection Query

```
// Hunt for likely post-exploitation on Magento / Adobe Commerce web servers
DeviceProcessEvents
| where Timestamp > ago(14d)
| where InitiatingProcessFileName has_any ("php-fpm", "php-cgi", "apache2", "httpd", "nginx")
| where FileName !in~ ("php-fpm", "php-cgi", "apache2", "httpd", "nginx")
| project Timestamp, DeviceName, InitiatingProcessFileName, FileName, ProcessCommandLine,
InitiatingProcessAccountName, FolderPath
| order by Timestamp desc
```

9.3 Exposure / Triage Query

```
// Identify likely Magento / Adobe Commerce hosts and suspicious webroot changes
let commerce_hosts = DeviceFileEvents
| where Timestamp > ago(30d)
| where FolderPath has_any ("/app/etc/env.php", "/pub/static/", "/var/www/html/", "/magento/")
| summarize by DeviceName;
DeviceFileEvents
| where Timestamp > ago(14d)
| where DeviceName in (commerce_hosts)
| where FolderPath has_any ("/var/www/", "/pub/", "/app/code/", "/generated/", "/media/")
| summarize ChangedFiles=count(), SamplePaths=make_set(FolderPath, 20) by DeviceName,
InitiatingProcessAccountName
| order by ChangedFiles desc
```

10.1 Hunt Leads

- Review edge logs for suspicious `CacheWarmer` cookies, especially high-entropy payloads, serialized PHP object markers, or unusual cookie lengths.

- Hunt for server-side child process execution from web service accounts, especially shell, curl, wget, python, perl, php, or base64-decoding utilities.
- Inspect payment pages, checkout templates, and JavaScript assets for skimming implants or unauthorized modifications.
- Correlate any suspicious storefront requests with subsequent file writes, cron persistence, admin account creation, or outbound callbacks.

10.2 Hunt Query

```
// Pivot from possible webshell or execution behavior on commerce servers
DeviceNetworkEvents
| where Timestamp > ago(14d)
| where InitiatingProcessFileName has_any ("php-fpm", "php-cgi", "apache2", "httpd", "nginx")
| summarize Connections=count(), RemoteIPs=dcount(RemoteIP), SampleDestinations=make_set(RemoteUrl, 20)
  by DeviceName, InitiatingProcessFileName, bin(Timestamp, 1h)
| where Connections > 10
| order by Timestamp desc
```

11. MITRE ATT&CK Mapping

Tactic	Technique	Relevance
Initial Access	T1190 Exploit Public-Facing Application	Public storefront request path is the likely exploit surface
Execution	T1059 Command and Scripting Interpreter	Common post-exploitation behavior after web app code execution
Persistence	T1505.003 Web Shell	Likely persistence mechanism on compromised storefronts
Credential Access / Collection	T1552 Unsecured Credentials / T1056 Input Capture (context dependent)	Relevant follow-on risk in commerce environments

12. Validation / Lab Testing

9. Confirm whether the Mirasvit extension is installed anywhere in production, staging, or disaster-recovery environments.
10. Validate that fixed or removed instances no longer accept vulnerable request patterns.
11. Test WAF or edge controls for detection and blocking of malformed `CacheWarmer` cookies in a safe lab.
12. Review historical logs for suspicious cookie values and align any hits with process execution, file writes, or admin activity.
13. If compromise is suspected, perform host-level forensic triage before full cleanup to preserve evidence.

13. Recommended Actions Summary

Priority	Action
Immediate	Patch, disable, or remove the vulnerable Mirasvit Cache Warmer extension
Immediate	Review edge logs for suspicious `CacheWarmer` cookie activity
High	Hunt for child process execution, file writes, new admins, and storefront tampering
High	Rotate application, database, and integration credentials if compromise is suspected

Medium	Increase monitoring for outbound callbacks, checkout manipulation, and skimming indicators
--------	--

14. References

14. Sansec research: Critical vulnerability in Mirasvit Cache Warmer for Magento
15. Imperva analysis covering CVE-2026-45247 defensive context
16. CISA KEV entry and related security reporting for CVE-2026-45247