



# LOST BOYS CYBER

THREAT INTELLIGENCE • MALWARE ANALYSIS • DETECTION ENGINEERING



## BianLian MAR

Research Report

|                       |                 |
|-----------------------|-----------------|
| <b>Classification</b> | TLP:CLEAR       |
| <b>Published</b>      | 2026-06-13      |
| <b>Version</b>        | 1.0             |
| <b>Author</b>         | Lost Boys Cyber |
| <b>Report Type</b>    | Research Report |

TLP:CLEAR | Lost Boys Cyber | BianLian MAR - Research Report

Published: 2026-06-13 | TLP:CLEAR | Version: 1.0 | Author: Lost Boys Cyber

AI Generation: This report was generated with AI assistance and is provided for informational purposes only. All findings, IOCs, detection rules, hunting queries, attribution assessments, and recommendations must be independently reviewed and validated by a qualified security professional before operational use.

## **Table of Contents**

1. Executive Summary
2. Intelligence Requirement
3. Source Review and Confidence
4. Key Findings
5. Threat Context
6. Detection and Hunting
7. Recommendations
8. References

## 1. Executive Summary

This report analyzes the Windows x64 sample `de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f` and correlates the file with public reporting on the BianLian intrusion set. Static triage, lightweight reverse-engineering, and local VirtualBox detonation all support the same conclusion: the sample is a Go-based BianLian-associated backdoor / proxy implant rather than the family's historic file-encrypting payload.

The highest-confidence conclusion is not based on one weak string match but on the convergence of multiple evidence classes:

- Go 1.18.3 runtime artefacts and a stripped PE32+ x64 layout.
- Embedded source/build paths referencing `/golang/socks/out/155.94.160.241/2016-7160/client/...`.
- Function and package artefacts including `main.connectForSocks`, `mimux`, and `soso`.
- Local sandbox execution showing `sample.exe` initiate a real outbound TCP connection from `192.168.56.20:58644` to `155.94.160.241:2016`.
- Public BianLian reporting from CISA, Unit 42, and HPE/Juniper describing a custom Go backdoor with SOCKS/tunneling behavior and `mimux` / `soso` modules.

The dynamic run did not show a second-stage payload, ransomware behavior, data staging, or meaningful HTTP/DNS activity attributable to the sample. That absence should not reduce urgency. For this malware family, access tooling is itself the operational danger: it provides covert ingress, relay capability, and an execution foothold that can support hands-on-keyboard activity, lateral movement, credential abuse, and extortion operations.

| Field                    | Assessment                                                                                                                  |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Malware family / cluster | BianLian-associated Go backdoor / proxy implant                                                                             |
| Confidence               | High for family alignment; medium-high for full operational role in a live intrusion                                        |
| Platform                 | Windows x64                                                                                                                 |
| Key confirmed IOC        | `155.94.160.241:2016`                                                                                                       |
| Static hallmarks         | `main.connectForSocks`, `mimux`, `soso`, Go 1.18.3, embedded build paths                                                    |
| Dynamic hallmarks        | `sample.exe` launched, no child processes, outbound TCP to `155.94.160.241:2016`, local listening socket on `0.0.0.0:58644` |
| Most likely role         | Post-compromise access, relay, or tunneling implant                                                                         |
| Priority action          | Hunt for the IOC, isolate impacted hosts, and investigate adjacent credential / remote-access activity                      |

## 2. Intelligence Requirement

The objective of this analysis was to determine whether the submitted sample is associated with BianLian, characterize its function through static, dynamic, and code-oriented analysis, extract actionable indicators, and provide defensive content suitable for immediate enterprise detection and threat hunting.

This report specifically answers the following questions:

- Is the sample technically consistent with public reporting on BianLian tooling?
- Does the binary behave like an encryptor, a loader, a backdoor, or a tunneling implant?
- What host and network evidence was observed during local sandbox execution?
- What indicators, ATT&CK mappings, detections, and hunt hypotheses should defenders prioritize now?

### 3. Source Review and Confidence

This assessment combines first-party evidence from the submitted sample and local sandbox execution with public-source enrichment from authoritative reporting.

| Source                                           | Type                               | Relevance                                                                                                            | Confidence contribution |
|--------------------------------------------------|------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------|
| Submitted sample archive and extracted PE        | Primary evidence                   | Hashes, file structure, embedded strings, build paths, function artefacts                                            | High                    |
| Local TRASHcan / VirtualBox detonation artefacts | Primary evidence                   | Process execution, TCP connections, DNS / HTTP behavior, generated detection artefacts                               | High                    |
| CISA AA23-136A / 2024 update                     | Government advisory                | Confirms BianLian uses victim-specific Go backdoors, SOCKS5 tunneling, valid-account abuse, and extortion tradecraft | High                    |
| HPE / Juniper 2024 activity analysis             | Vendor threat research             | Describes BianLian Go backdoors using `mimux` and `soso` modules and a hardcoded C2 design                           | High                    |
| Unit 42 threat assessment                        | Vendor incident-response reporting | Supports BianLian's move from double extortion toward access-and-extortion operations                                | High                    |
| Auto-generated sandbox triage detections         | Derived local artefacts            | Useful for lead generation, but must be analyst-triaged for false positives                                          | Medium                  |

Assessment caveats:

- The sandbox run confirms execution and one network connection, but it did not surface full post-compromise behavior, likely because the specimen was detonated in an isolated host-only lab with fake services and no real operator infrastructure behind the C2.
- The only behavioral alert generated by the sandbox was an autorun finding for OneDrive under the analyst profile. That artefact is consistent with baseline Windows user activity and is not persuasive evidence of malware persistence in this run.
- Reverse-engineering in this workflow was code-oriented and evidence-driven rather than full decompilation. The conclusions rely on function names, package artefacts, path strings, and runtime behavior rather than a complete control-flow reconstruction.

#### 4.1 Sample Metadata

| Field     | Value                                                              |
|-----------|--------------------------------------------------------------------|
| SHA256    | `de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f` |
| SHA1      | `e3efe133d1ff69afedb91f359070dbe6d45a5ef6`                         |
| MD5       | `6564ffc14ab803a961453a118a33830e`                                 |
| File size | 3,489,796 bytes                                                    |

|                             |                                                                                             |
|-----------------------------|---------------------------------------------------------------------------------------------|
|                             |                                                                                             |
| File type                   | PE32+ executable for MS Windows 6.01 (GUI), x86-64                                          |
| Signature status            | Unsigned                                                                                    |
| Build / language indicators | Go runtime artefacts, `go1.18.3`, large `.text` and `.rdata` segments                       |
| Sections                    | `.text`, `.rdata`, `.data`, `.idata`, `.reloc`, `.symtab`                                   |
| Binary properties           | NX enabled, PIC enabled, stripped, overlay present                                          |
| Build timestamp             | `Thu Jan 1 00:00:00 1970` (not operationally meaningful; consistent with Go-linked samples) |

## 4.2 Static and Reverse-Engineering Findings

| Finding                                     | Evidence                                                                                                                                                                             | Assessment                                                                                      |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| Go-based implant                            | `rabin2 -I` showed a stripped 64-bit PE with Go-style section layout and runtime strings including `go1.18.3`                                                                        | Consistent with BianLian public reporting that the actor uses custom Go backdoors               |
| SOCKS / tunneling functionality             | String and symbol artefacts included `main.connectForSocks`, `soso. (*Server).ServeConn`, `soso. (*NoAuthAuthenticator).Authenticate`, `soso. (*UserPassAuthenticator).Authenticate` | Strong indicator that the malware provides proxy or relay functionality                         |
| Multiplexed session handling                | Embedded package/function artefacts for `mimux.Server`, `mimux. (*Session).Accept`, `mimux. (*Session).recvLoop`, and related stream/session handling                                | Aligns with a backdoor architecture built for multiplexed C2 or pivot traffic                   |
| Hardcoded operator infrastructure reference | Raw strings contained `155.94.160.241:2016`                                                                                                                                          | Suggests a compiled-in C2 or relay endpoint rather than purely user-supplied runtime parameters |
| Embedded developer build paths              | Strings showed `/home/admin/prjct/golang/socks/out/155.94.160.241/2016-7160/client/main.go` and adjacent `vendor/mimux/*.go` and `vendor/soso/*.go` files                            | High-value code-analysis evidence tying the specimen to a specific SOCKS client build tree      |
| No locker-stage artefacts observed          | No convincing hits for `.bianlian`, ransom-note artefacts, `vssadmin`, `wbadmin`, or typical encryptor workflow strings                                                              | Supports classification as an access implant rather than the final encryption component         |

The most important code-analysis outcome is that the sample's string and path corpus does not merely resemble generic Go malware. It exposes a developer project structure explicitly oriented around a SOCKS client, includes named internal modules that match public BianLian reporting, and references the same IP/port pair later observed at runtime.

### 4.3 Dynamic Analysis Findings

The sample was detonated locally in the `win-malware-lab` VirtualBox guest using the TRASHcan local sandbox workflow. After resolving two lab issues during setup (host-only adapter state and an allowed-run-root capture policy), the final detonation completed successfully and produced process, network, and behavioral artefacts.

Sandbox run details:

| Field                   | Value                                                                                    |
|-------------------------|------------------------------------------------------------------------------------------|
| Run directory           | `/home/lost0x01/internal-secops-portal/data/sandbox-runs/2026-06-12_233117_de31a4125eb7` |
| VM                      | `win-malware-lab`                                                                        |
| Snapshot                | `clean-guestadditions-sysmon`                                                            |
| Guest IP                | `192.168.56.20`                                                                          |
| Host-only gateway / DNS | `192.168.56.1`                                                                           |
| Detonated path          | `C:\Analysis\Sample\sample.exe`                                                          |
| Sample process ID       | `7084`                                                                                   |

Observed execution results:

| Observation                                  | Evidence                                                                                                                                                           | Assessment                                                                                                |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Sample executed successfully                 | `processes.json` and `process_tree_raw.json` show `sample.exe` launched from `C:\Analysis\Sample\sample.exe` under the sandbox PowerShell runner                   | Confirms the file is runnable and not merely a corrupted or decoy artefact                                |
| No child processes spawned                   | `process_tree_raw.json` showed no descendants from process `7084`                                                                                                  | Suggests the specimen did not act as a simple dropper or launcher during this run                         |
| Outbound TCP to hardcoded IOC                | `tcp_connections.json` captured process `7084` connecting from `192.168.56.20:58644` to `155.94.160.241:2016`                                                      | High-confidence behavioral confirmation of the embedded network indicator                                 |
| Local listening socket present               | The same process owned `0.0.0.0:58644` in a listening state before/alongside the remote connection                                                                 | Consistent with relay, proxy, or local tunnel handling behavior                                           |
| No malware-attributable DNS or HTTP activity | `analysis.md` reported no suspicious domains, no malware HTTP requests, and no Suricata alerts; observed HTTP requests were background Windows / Microsoft traffic | Supports the hypothesis that the sample prefers direct IP C2 rather than domain-based staging in this run |
| No convincing persistence established        | The only sandbox behavior alert referenced a pre-existing-looking OneDrive autorun path in the analyst user profile                                                | Treat as baseline noise / false positive, not malware-confirmed persistence                               |

Dynamic interpretation:

- The single most important runtime observation is that execution produced the exact network IOC predicted by the static analysis: `155.94.160.241:2016`.
- The presence of a listening socket and an outbound C2 connection is more consistent with a tunneling / backdoor role than with a ransomware locker.
- The absence of follow-on payloads, registry changes, scheduled tasks, or service creation should be interpreted cautiously. A backdoor can still be fully valid even when the lab does not provide a reachable operator workflow or second-stage tasking.

#### 4.4 Classification and ATT&CK Mapping

The total evidence supports a high-confidence classification of this specimen as BianLian-associated access malware, specifically a Go-based backdoor / proxy implant used to establish or maintain command-and-control and facilitate operator access.

| ATT&CK Tactic                             | Technique                     | Relevance                                                                                                                                      |
|-------------------------------------------|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Command and Control                       | T1071                         | Backdoor communications over application-layer protocols remain plausible even though this run showed direct TCP rather than rich HTTP traffic |
| Command and Control                       | T1090 / T1090.001 / T1090.002 | SOCKS / proxy and relay behavior is strongly indicated by `connectForSocks`, `soso`, and the local listening socket                            |
| Ingress Tool Transfer / Remote Services   | T1105 / T1219                 | Public reporting shows BianLian operators pair custom backdoors with remote access tooling                                                     |
| Valid Accounts / External Remote Services | T1078 / T1133                 | CISA and Unit 42 reporting associate BianLian with stolen credentials, RDP, and VPN exposure                                                   |
| Exploit Public-Facing Application         | T1190                         | CISA reporting links BianLian activity to exploitation paths including ProxyShell                                                              |
| Persistence                               | T1547.001                     | Common actor tradecraft, but not confirmed for this specimen in this run                                                                       |
| Exfiltration                              | T1048 / T1567.002             | Relevant to broader BianLian operations, though not directly observed in detonation                                                            |
| Impact                                    | T1486                         | Historically associated with the actor, but not evidenced by this sample                                                                       |

## 5. Threat Context

BianLian has evolved from a conventional ransomware-and-extortion operation into a cluster that often emphasizes access, data theft, and extortion pressure even when file encryption is absent. That shift matters when evaluating this specimen. Defenders should not dismiss the sample simply because it does not look like a locker.

Public reporting consistently describes the group as:

- Gaining access through exposed remote services, stolen credentials, or exploitable public-facing systems.
- Deploying custom Go backdoors and SOCKS-style tunneling components.
- Maintaining hands-on-keyboard access for reconnaissance, privilege escalation, lateral movement, and extortion preparation.
- Using stealthier access-and-exfiltration tradecraft in cases where encryption is reduced or omitted.

This sample fits that operational profile unusually well. It combines direct evidence of proxy-oriented code structure with a confirmed network connection to the same hardcoded endpoint exposed in its build path and strings. In practical terms, a defender encountering this specimen should assume they are seeing an intrusion-enablement tool that may sit earlier in the kill chain than overt impact actions.

| Threat-context question                                      | Assessment                                                                      |
|--------------------------------------------------------------|---------------------------------------------------------------------------------|
| Does the sample fit authoritative BianLian reporting?        | Yes, strongly                                                                   |
| Is this likely the final ransomware encryptor?               | No, the evidence points away from a locker role                                 |
| Does the absence of encryption reduce risk materially?       | No; persistent access tooling is often the more important early-warning signal  |
| Should this be investigated as an isolated malware hit only? | No; treat it as a probable intrusion lead and scope for adjacent actor activity |

### 6.1 Immediate Detection Priorities

| Detection focus                                                                                        | Why it matters                                        | Example telemetry                                                          |
|--------------------------------------------------------------------------------------------------------|-------------------------------------------------------|----------------------------------------------------------------------------|
| `155.94.160.241:2016`                                                                                  | Statically predicted and dynamically confirmed IOC    | Firewall logs, EDR network events, Zeek conn logs, proxy telemetry         |
| Processes listening on uncommon local ports and then connecting outbound to the same operator workflow | Matches the observed listener-plus-C2 pattern         | EDR socket telemetry, Sysmon Event ID 3, network sensor telemetry          |
| Files or memory containing `mimux`, `soso`, or `main.connectForSocks`                                  | Rare strings with strong family specificity           | File scanning, memory scanning, retro-hunts in EDR content indexes         |
| Unsigned Go executables on Windows hosts where they are operationally unusual                          | Good triage lead for cluster hunting                  | EDR inventory, software allow-listing exceptions, file prevalence analysis |
| Suspicious remote-access activity around RDP, VPN, or administrative logons                            | Consistent with broader BianLian intrusion operations | Authentication logs, Windows security logs, VPN logs, jump-host telemetry  |

### 6.2 Indicators of Interest

| Type              | Value                                                              | Confidence | Notes                                                  |
|-------------------|--------------------------------------------------------------------|------------|--------------------------------------------------------|
| SHA256            | `de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f` | High       | Submitted sample hash                                  |
| SHA1              | `e3efe133d1ff69afedb91f359070dbe6d45a5ef6`                         | High       | Static triage                                          |
| MD5               | `6564ffc14ab803a961453a118a33830e`                                 | High       | Static triage                                          |
| IP                | `155.94.160.241`                                                   | High       | Present in strings/build paths and observed at runtime |
| Port              | `2016/TCP`                                                         | High       | Present in strings/build paths and observed at runtime |
| Function / string | `main.connectForSocks`                                             | High       | Strong behavioral clue for                             |

|                     |                                                                     |      |                                              |
|---------------------|---------------------------------------------------------------------|------|----------------------------------------------|
|                     |                                                                     |      | tunneling logic                              |
| Package / string    | `mimux`                                                             | High | Matches public reporting on BianLian tooling |
| Package / string    | `soso`                                                              | High | Matches public reporting on BianLian tooling |
| Build-path fragment | `/golang/socks/out/<br>155.94.160.241/2016-7160/<br>client/main.go` | High | Strong code-analysis artefact                |

### 6.3 Sigma Detection Lead

```

title: Potential BianLian Go Backdoor Strings Or Direct IOC
id: 63e02f37-3c75-4d90-a64f-bianlian-mimux-soso-2016
status: experimental
logsource:
  product: windows
  category: file_event
detection:
  selection_hash:
    Hashes|contains:
      - 'de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f'
  selection_name:
    TargetFilename|endswith: '\\sample.exe'
  selection_content:
    FileContent|contains|all:
      - 'mimux'
      - 'soso'
      - 'main.connectForSocks'
  condition: selection_hash or selection_content or selection_name
falsepositives:
  - Malware-analysis labs
  - Internal research repositories containing the specimen
level: high

```

### 6.4 Microsoft Defender XDR / Sentinel KQL Hunt

```

let sample_sha256 = "de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f";
let c2_ip = "155.94.160.241";
let c2_port = 2016;
let rare_strings = dynamic(["mimux", "soso", "main.connectForSocks", "connectForSocks"]);
DeviceNetworkEvents
| where RemoteIP == c2_ip or (RemoteIP == c2_ip and RemotePort == c2_port)
| project Timestamp, DeviceName, InitiatingProcessFileName, InitiatingProcessCommandLine, LocalPort,
RemoteIP, RemotePort, Protocol, ReportId
| union (
  DeviceFileEvents
  | where SHA256 =~ sample_sha256
  | project Timestamp, DeviceName, ActionType, FileName, FolderPath, SHA256,
InitiatingProcessFileName, InitiatingProcessCommandLine, ReportId
)
| union (
  DeviceProcessEvents
  | where ProcessCommandLine has_any (rare_strings) or InitiatingProcessCommandLine has_any
(rare_strings)
  | project Timestamp, DeviceName, FileName, ProcessCommandLine, InitiatingProcessFileName,
InitiatingProcessCommandLine, SHA256, ReportId
)
| sort by Timestamp desc

```

### 6.5 Splunk Hunt

```
(index=sysmon OR index=edr OR index=windows OR index=network)
```

```
(
  dest_ip="155.94.160.241"
  OR dest_port="2016"
  OR CommandLine="*connectForSocks*"
  OR CommandLine="*mimux*"
  OR CommandLine="*soso*"
  OR sha256="de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f"
)
| stats min(_time) as first_seen max(_time) as last_seen values(host) as hosts values(user) as users
values(Image) as images values(CommandLine) as cmd values(dest_ip) as dest_ips values(dest_port) as
dest_ports by sha256 parent_process process_name
| convert ctime(first_seen) ctime(last_seen)
```

## 6.6 YARA Rule

```
rule WIN_BianLian_Go_Backdoor_Mimux_Soso_ConfirmedC2
{
  meta:
    author = "Lost Boys Cyber"
    description = "Detects a BianLian-associated Go backdoor using mimux/soso artefacts and confirmed
C2 indicator"
    sha256 = "de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f"
    date = "2026-06-12"
  strings:
    $mz = { 4D 5A }
    $s1 = "mimux" ascii
    $s2 = "soso" ascii
    $s3 = "main.connectForSocks" ascii
    $s4 = "155.94.160.241" ascii
    $s5 = "/golang/socks/out/155.94.160.241/2016-7160/client/main.go" ascii
  condition:
    $mz at 0 and 3 of ($s1,$s2,$s3,$s4,$s5)
}
```

## 6.7 Hunt Hypotheses

- Hosts that contacted `155.94.160.241:2016` may also show valid-account abuse, remote desktop enablement, or unusual administrative session activity in the same window.
- Endpoints containing this specimen may have been used as relay points rather than encryption victims, so network pivoting and credential movement deserve equal priority to malware eradication.
- Additional BianLian tooling may exist on affected systems even when this sample itself does not create persistence or drop secondary binaries during lab execution.
- Because the sample uses a direct IP at runtime, detections focused only on suspicious domains may miss comparable variants.

## 7. Recommendations

| Priority  | Recommendation                                                                                           | Rationale                                                                                               |
|-----------|----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Immediate | Block and alert on `155.94.160.241` and specifically review historical flows to `2016/TCP`               | This IOC was both embedded and behaviorally confirmed                                                   |
| Immediate | Quarantine any host containing SHA256 `de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f` | Prevent reuse of a confirmed access implant                                                             |
| Immediate | Scope authentication and remote-access telemetry for the affected host(s)                                | BianLian frequently relies on valid accounts, RDP, VPN access, and hands-on-keyboard follow-on activity |
| High      | Hunt for unsigned Go executables with `mimux`, `soso`, or `connectForSocks`                              | Strong family-specific pivot for retro-                                                                 |

|        |                                                                                                   |                                                                                                 |
|--------|---------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
|        | artefacts across the estate                                                                       | hunting                                                                                         |
| High   | Investigate hosts for listener behavior paired with outbound operator traffic                     | Matches the local-listener plus C2-connection pattern seen in detonation                        |
| High   | Review adjacent systems for staging, exfiltration, remote tooling, and lateral-movement artefacts | The specimen appears positioned earlier than the final impact phase                             |
| Medium | Preserve the specimen and sandbox artefacts for deeper reversing if this case escalates           | Full decompilation could recover configuration nuances, error handling, and operator tradecraft |
| Medium | Add direct-IP network detections alongside domain-based controls                                  | This run showed no malware-attributable DNS activity before C2 contact                          |

Operational note: the absence of ransom-note or encryption artefacts should not be treated as exculpatory. In BianLian cases, early access tooling may be the most valuable detection opportunity defenders get before extortion pressure becomes visible.

## 8. References

- CISA, `#StopRansomware: BianLian Ransomware Group`, AA23-136A, <https://www.cisa.gov/news-events/cybersecurity-advisories/aa23-136a>
- CISA / FBI / ASD ACSC, `#StopRansomware: BianLian Data Extortion Group` PDF update, <https://www.cisa.gov/sites/default/files/2024-11/aa23-136a-joint-csa-stopransomware-bianlian-ransomware-group.pdf>
- Palo Alto Networks Unit 42, `Threat Assessment: BianLian`, <https://unit42.paloaltonetworks.com/bianlian-ransomware-group-threat-assessment/>
- HPE Threat Research, `BianLian Ransomware Group: 2024 Activity Analysis`, <https://community.hpe.com/t5/hpe-threat-labs/bianlian-ransomware-group-2024-activity-analysis/ba-p/7266394>
- Submitted evidence archive: `/home/lost0x01/internal-secops-portal/data/uploads/20260612\_225918\_549706/de31a4125eb74d0b7cbf2451b40fdb2d66d279a8b8fd42191660b196a9ac468f.7z`
- Successful local sandbox run directory: `/home/lost0x01/internal-secops-portal/data/sandbox-runs/2026-06-12\_233117\_de31a4125eb7`
- Key local artefacts reviewed in this workflow: `analysis.md`, `summary.json`, `behavior\_summary.json`, `guest\_artifacts/process\_tree\_raw.json`, `guest\_artifacts/processes.json`, `guest\_artifacts/tcp\_connections.json`, `static\_triage.json`, `rule.yar`, and `sigma\_behavior.yml`