LOST BOYS CYBER

THREAT INTELLIGENCE • MALWARE ANALYSIS • DETECTION ENGINEERING

Binance $6.3 Billion Cyber Heist — TraderTraitor Social Engineering and Wallet-Control Risk

Threat Report

Classification	TLP:CLEAR
Published	2026-11-05
Version	1.0
Author	Lost Boys Cyber
Report Type	Threat Report

Published: 2026-11-05 | TLP:CLEAR | Version: 1.0 | Author: Lost Boys Cyber

AI Generation: This report was generated with AI assistance and is provided for informational purposes only. All findings, IOCs, detection rules, hunting queries, attribution assessments, and recommendations must be independently reviewed and validated by a qualified security professional before operational use.

Table of Contents

1. Executive Summary
2. Key Judgments
3. Intelligence Requirements and Scope
4. Source Review and Confidence
5. Incident Timeline
6. Threat Actor and Attribution Assessment
7. Reported Intrusion and Theft Sequence
    7.1. Recruitment Pretext and Trust Building
    7.2. User Execution on a Work Endpoint
    7.3. Control-Plane and Lateral Access Risk
    7.4. Impact and Operational Response
8. Tactics, Techniques, and Procedures
9. Exposure and Control Review
10. Indicators, Observables, and Source Limitations
11. Detection Engineering
    11.1. Detection Hypothesis 1 — Recruitment-lure download on a privileged endpoint
    11.2. Detection Hypothesis 2 — Wallet-control changes or high-value transfers without expected quorum
    11.3. Validation and Tuning
12. Threat Hunting
    12.1. Hunt 1 — Unapproved execution from browser or collaboration context
    12.2. Hunt 2 — AI-agent and automation activity from risky sessions
    12.3. Hunt 3 — Wallet workflow policy and transaction anomaly review
13. Incident Response and Containment Guidance
14. Recommended Actions
15. Analyst Bottom Line
16. References

Binance $6.3 Billion Cyber Heist — TraderTraitor Social Engineering and Wallet-Control Risk

Classification: TLP:CLEAR Published: 2026-11-05 Version: 1.0 Author: Lost Boys Cyber Report Type: Threat Report

AI Generation: This report was generated with AI assistance and is provided for informational purposes only. All findings, IOCs, detection rules, hunting queries, attribution assessments, and recommendations must be independently reviewed and validated by a qualified security professional before operational use.

1. Executive Summary

On or about 29 October 2026, attackers stole more than $6 billion in virtual assets from Binance-controlled wallets. The FBI attributes the theft to North Korean malicious cyber activity it calls TraderTraitor. Public loss estimates vary by source: the FBI says more than $6 billion, NPR and BBC report $6.3 billion, and Chainalysis reports $6.4 billion. The value discrepancy is consistent with timing and valuation-method differences; the operational conclusion is unchanged: this was a critical, record-scale digital-asset theft.

Binance's initial account, corroborated by NPR and BBC reporting, describes a patient social-engineering intrusion rather than a publicly disclosed blockchain protocol flaw. The reported chain began with reconnaissance and a stopped attempt in June, followed by a fake recruitment approach to an engineer in September. During a staged second interview, the engineer downloaded a malicious “assignment” onto a work laptop. BBC reports that the compromised endpoint and an internal AI tool were then used to reach two additional engineering laptops before unauthorized withdrawals were executed. NPR reports that the final theft took roughly 20 minutes after months of preparation.

This incident demonstrates that the highest-value wallet-control environment is only as strong as its endpoint, identity, software-assistant, and transaction-approval boundaries. No publicly verified malware hash, domain, IP address, or wallet-address set was available in reviewed sources. Accordingly, this report supplies behavior-based detections, hunt hypotheses, and control recommendations—not invented static indicators.

2. Key Judgments

Judgment	Confidence	Basis
The theft exceeded $6 billion in virtual assets on or about 2026-10-29.	High	FBI primary alert; Binance acknowledgement; NPR, BBC, and Chainalysis reporting.
FBI attribution identifies DPRK-associated TraderTraitor activity as responsible.	High	FBI alert and Binance statement relayed by BBC.
The initial access path was a targeted fake-recruitment/social-engineering campaign against an engineer.	High	Binance initial findings described by NPR and BBC.
A malicious downloaded assignment compromised the engineer work endpoint.	High	NPR and BBC reporting of Binance findings.
The campaign combined human trust-building with technical staging over months.	High	NPR reports June testing and September recruitment progression.
Internal AI-tool access was a material lateral-access/control-plane risk in this incident.	Medium	BBC reports its use to gain control of two further laptops; detailed technical mechanics have not been released.
Any single engineer endpoint should be unable to autonomously authorize large	High	Defensive design conclusion from the incident class; not a claim about Binance's

wallet movement.		prior architecture.

3. Intelligence Requirements and Scope

This report answers four defender questions:

Question	Answer status
What is publicly confirmed?	Covered with source-qualified facts and a separate confidence model.
How did the intrusion progress?	Covered as a staged recruitment-to-endpoint-to-wallet-control sequence.
What should comparable firms detect and hunt now?	Covered with Sigma, KQL, audit hypotheses, and an operational triage plan.
Which static IOCs should be blocked?	No verified public static network, malware, or wallet IOCs were released in reviewed sources. Track behavioral observables instead.

Scope: this is a current threat-intelligence and defensive-response report. It does not reverse engineer a sample, assert access to Binance internal telemetry, or describe operationally actionable theft methods.

4. Source Review and Confidence

The source corpus contains a primary FBI attribution notice, Binance incident statements, and independent reporting by NPR, BBC, and Chainalysis. The FBI alert is authoritative for attribution and incident timing. Binance is authoritative for what it says occurred in its environment, but its evolving investigation should be expected to refine mechanics. NPR and BBC corroborate the reported intrusion narrative; Chainalysis provides blockchain-analysis context. See `sources.md` for source-by-source limitations.

Claim area	Preferred source	Confidence caveat
Actor attribution	FBI	Attribution statements can evolve, but this is the strongest available public source.
Intrusion mechanics	Binance, corroborated by NPR/BBC	Technical details remain preliminary and source-controlled.
Asset valuation	FBI/Binance plus NPR/BBC/Chainalysis	Preserve source-specific values rather than treating a live-price estimate as fixed.
Recovery/freeze activity	Binance and law enforcement statements	Do not treat a stated replenishment/reserve position as proof that stolen assets were recovered.

5. Incident Timeline

Date / period	Reported activity	Assessment
June 2026	Attackers reportedly tested or penetrated Binance security systems; Binance detected and stopped that attempt.	Initial reconnaissance/access testing; attackers may have learned environment details despite failure.

September 2026	An engineer was contacted on a legitimate job-hunting platform by an apparent project director for a fictitious company.	High-touch recruitment lure and credibility establishment.
September 2026	A purported HR representative conducted an initial interview and shared credible-seeming social accounts, images, and videos.	Trust-building before payload delivery.
Second interview	The engineer, on a work laptop, was instructed to download an “assignment” through a social-chat interaction.	User execution of malicious content on a privileged endpoint.
Post-compromise	BBC reports malicious code used obfuscation, the compromised endpoint and an internal AI tool enabled access to two additional laptops, and attackers proceeded toward wallet control.	Lateral/control-plane expansion; exact tool and identity mechanisms remain undisclosed.
2026-10-29	Unauthorized withdrawals from Binance-controlled wallets occurred; FBI dates the theft on or about this day.	Impact event.
After incident	Binance suspended withdrawals globally, later restored service, worked with law enforcement, and reported reserve/replenishment actions.	Containment and customer-impact response.
2026-10-31 to 2026-11-05	FBI attribution and victim/third-party updates were published.	Attribution, tracing, and investigation remain active.

6. Threat Actor and Attribution Assessment

The FBI publicly attributes this incident to the Democratic People's Republic of Korea. The FBI calls the relevant malicious cyber activity TraderTraitor. BBC reports that Binance subsequently said FBI information indicated DPRK responsibility. NPR describes the unit as a North Korean military unit and notes the FBI identification.

Attribution should be handled with discipline. “TraderTraitor,” “DPRK,” and “Lazarus Group” are not interchangeable technical indicators. In this report, **TraderTraitor** is used for the FBI-referenced campaign label; “DPRK-linked” is used for the state attribution. Do not auto-attribute future recruitment lures, malicious downloads, or crypto theft solely because they resemble this case.

Attribution element	Assessment	Confidence
Responsible state nexus	DPRK	High
Campaign / activity label	TraderTraitor	High
Individual operators	Not public	Not assessed
Specific malware family	Not public	Not assessed
Wallet-address set	Not public in reviewed sources	Not assessed
Broader Lazarus nomenclature	Public reporting sometimes uses it as related context; not required for this report's analytic conclusion	Medium

7. Reported Intrusion and Theft Sequence

7.1. Recruitment Pretext and Trust Building

The social-engineering operation blended legitimate platforms with an elaborate false identity. NPR reports use of a job-hunting platform, a fictitious company, purported HR and executive personnel, and social accounts containing personal material. This is not generic bulk phishing. It is a tailored operation directed at a high-value employee and designed to survive normal user skepticism.

Defensive implication: finance, fintech, exchange, wallet, and custody organizations should consider recruitment outreach a privileged-identity attack surface. Workforce education is necessary but insufficient; high-value roles need hardened devices, segregated work patterns, safe file-review procedures, and telemetry that correlates messaging/browser downloads with subsequent execution and privileged access.

7.2. User Execution on a Work Endpoint

The decisive social-engineering request was reportedly an “assignment” downloaded during a second interview while the targeted engineer used a work laptop. BBC reports that the delivered code used obfuscation techniques. The public record does not identify file format, hash, delivery URL, or execution mechanism.

Defensive implication: allowlisting and endpoint controls should distinguish standard engineering activity from unreviewed code, archives, installers, disk images, scripts, and signed-but-untrusted binaries received through external recruiting channels. A corporate workstation used to support wallet infrastructure should not be treated as a general-purpose interview/test environment.

7.3. Control-Plane and Lateral Access Risk

BBC reports the attackers leveraged the compromised computer and an internal AI tool to gain control over two additional engineers' laptops. This should be treated as an urgent control-review question, not an invitation to speculate about a particular AI product or flaw. The disclosed facts do not establish whether the AI tool was compromised, misconfigured, impersonated, delegated excess privilege, or merely available from a compromised session.

Defensive implication: any AI assistant, automation agent, remote-support tool, developer platform, identity broker, or internal workflow tool that can retrieve secrets, execute actions, initiate sessions, generate code, or influence privileged endpoints must be modeled as part of the wallet-control plane. Apply least privilege, explicit action approval, high-fidelity audit logging, session isolation, and break-glass revocation.

7.4. Impact and Operational Response

BBC reports withdrawals were suspended globally and later restored, while Binance worked with law enforcement to trace and freeze affected assets. The company reported reserves and replenishment actions for impacted assets. Customer remediation and recovery status should be monitored separately from technical containment: replenishing customers, freezing assets, and recovering stolen funds are different outcomes.

8. Tactics, Techniques, and Procedures

Tactic	ATT&CK	Reported or inferred behavior	Confidence
Initial Access	T1566.001 Spearphishing Attachment	Malicious “assignment” sent during fake recruitment process.	High
Execution	T1204.002 User Execution: Malicious File	Engineer downloaded/ran malicious content on work laptop.	High
Defense Evasion	T1027 Obfuscated Files or Information	BBC reports obfuscation techniques.	Medium

Credential / Session Access	T1078 Valid Accounts	A compromised internal endpoint enabled further access; exact authentication material not disclosed.	Medium
Lateral Movement	T1021 / internal control-plane use	Two further engineer laptops reportedly compromised through the initial endpoint and internal AI tool; exact technique undisclosed.	Medium
Collection / Impact	Wallet-control transaction abuse	Unauthorized virtual-asset withdrawals from exchange-controlled wallets. ATT&CK does not neatly model the asset-transfer business process.	High

9. Exposure and Control Review

Comparable organizations should immediately inventory and test the following trust boundaries.

Control plane	Failure mode to test	Minimum control objective
Privileged engineering endpoints	External file/download leads to code execution or token theft.	Separate hardened device profiles; application control; EDR tamper protection; rapid isolation.
Identity and session layer	A compromised workstation can reuse browser, SSO, VPN, or developer sessions.	Phishing-resistant MFA; device-bound sessions; continuous risk checks; rapid token revocation.
AI assistants and automation agents	Assistant can retrieve secrets, perform privileged actions, or reach peers without human confirmation.	Least privilege, short-lived scoped tokens, per-action confirmation, immutable audit logs, kill switch.
Wallet signing / transaction workflow	One endpoint or one identity can initiate and execute material value transfer.	Quorum approval, transaction simulation, address allowlists, human out-of-band verification, time locks, velocity limits.
Treasury operations	Emergency response cannot arrest suspicious flow quickly enough.	Circuit breakers, freeze authority, pre-approved incident runbooks, 24x7 contact paths.
Recruitment and external collaboration	Job lures access work endpoints and privileged workflows.	Separate interview environment; allowlisted sharing; policy for external code/tasks; role-specific training.

10. Indicators, Observables, and Source Limitations

No source reviewed for this report released a verified malware hash, IP address, domain, filename, URL, certificate, or thief wallet address. The IOC appendix therefore records durable **observables** rather than pretending that campaign names or generic terms are blocklist-ready.

Observable	Confidence	Defender action
Fake recruiting contact to a wallet/treasury engineer	High	Preserve messages, recruiter-platform metadata, file links, meeting invitations,

		and identity artifacts; escalate to security.
Unapproved “assignment” download/run on privileged endpoint	High	Isolate endpoint; acquire volatile data; revoke sessions; scope files/processes/network.
Browser/chat app leading to script/installer/archive execution	High	Alert and triage with endpoint role context.
Sudden AI-agent, remote-tool, or developer-platform actions from an engineer session	Medium	Correlate with device health, user presence, approval records, secret access, and peer-endpoint activity.
Unusual wallet-policy change or large withdrawal request	High	Pause transaction; require independent quorum; review source identity, destination, simulation and approval chain.

Do not block on the phrase “TraderTraitor,” a generic recruitment domain, or arbitrary crypto-wallet addresses not confirmed by investigators. See `iocs.csv` for machine-readable observables and handling guidance.

11. Detection Engineering

Detection should prioritize the handoffs that attacker tradecraft must cross: external content to endpoint execution, endpoint to privileged session, privileged session to agent/automation action, and wallet-control request to final transaction. Tune all detections to high-value endpoint labels and approved software workflows before production alerting.

11.1. Detection Hypothesis 1 — Recruitment-lure download on a privileged endpoint

If a threat actor delivers a malicious interview assignment to a privileged engineer, browser or chat-client activity will create executable, script, archive, disk-image, or shortcut content in user-controlled directories. EDR file telemetry can identify the handoff before privileged access begins.

```
title: Potential Recruitment-Lure Download on Privileged Engineering Endpoint
id: 7d9165bd-4a33-4a2f-a5d2-3d21a069d0b8
status: experimental
description: Detects executable or script downloads by browser processes on high-value engineering,
treasury, or wallet-infrastructure endpoints. Inspired by reporting on the 2026 Binance intrusion; tune
by endpoint role and approved tooling.
references:
  - https://www.npr.org/2026/11/03/nx-s1-6027799/binance-crypto-exchange-cyber-heist
  - https://www.bbc.com/news/articles/ck5ynwz9gy67o
author: Lost Boys Cyber
date: 2026-11-05
tags:
  - attack.initial_access
  - attack.t1566.001
  - attack.execution
  - attack.t1204.002
logsource:
  product: windows
  category: file_event
detection:
  selection_path:
    TargetFilename|contains:
      - '\\Downloads\\'
      - '\\Temp\\'
      - '\\AppData\\Local\\Temp\\'
  selection_ext:
    TargetFilename|endswith:
      - '.exe'
      - '.msi'
      - '.dll'
```

```
      - '.js'
      - '.jse'
      - '.vbs'
      - '.vbe'
      - '.ps1'
      - '.lnk'
      - '.iso'
      - '.zip'
  selection_browser:
    Image|endswith:
      - '\\chrome.exe'
      - '\\msedge.exe'
      - '\\firefox.exe'
  condition: selection_path and selection_ext and selection_browser
fields:
  - Image
  - TargetFilename
  - User
  - Hashes
  - Computer
falsepositives:
  - Approved software downloads
  - Development tooling and package retrieval
level: high
```

11.2. Detection Hypothesis 2 — Wallet-control changes or high-value transfers without expected quorum

If an attacker reaches an exchange/wallet control plane, there should be a join of identity events, policy changes, AI/automation actions, approval records, and transaction requests. Implement this logic in the organization's own application/SIEM schema because public sources do not disclose Binance fields.

Required telemetry	Alert condition	Triage question
Wallet transaction audit log	High-value transaction request followed by execution with fewer than expected independent approvers.	Was the policy altered, bypassed, or applied correctly?
Identity provider / PAM	New device, token refresh, MFA reset, or unusual session preceding transaction.	Does the session bind to a healthy, expected device and user?
AI-agent audit log	Secret retrieval, tool invocation, endpoint action, or lateral workflow initiated from a risky session.	Was action explicitly approved and within role scope?
EDR	Recent suspicious download/process/remote-access lineage on an approver endpoint.	Is a user/device compromise driving the transaction?

11.3. Validation and Tuning

1. Run the Sigma rule first in audit mode for high-value device groups.
2. Baseline approved software downloads, CI artifacts, package managers, and IT imaging workflows.
3. Simulate a benign downloaded test file in an isolated lab or test device; confirm the intended telemetry chain without executing untrusted code.
4. Validate that a high-value wallet transaction cannot complete if any required approver, health signal, or out-of-band confirmation is missing.
5. Track maturity: Level 1 awareness; Level 2 rule present; Level 3 tuned with endpoint-role enrichment; Level 4 transaction controls automatically halt risky transfers and open an incident.

12. Threat Hunting

12.1. Hunt 1 — Unapproved execution from browser or collaboration context

Hypothesis: a recruitment/social-engineering lure on a privileged endpoint will create a process chain from browser or collaboration software to a script, installer, archive-derived executable, or suspicious interpreter.

```
// Hunt for unapproved binary/script execution on wallet or treasury endpoints.
// Populate HighValueDevices from CMDB or device tags before operational use.
let HighValueDevices = DeviceInfo
| where Tags has_any ("wallet-infrastructure", "treasury", "privileged-engineering")
| distinct DeviceId;
DeviceProcessEvents
| where Timestamp > ago(30d)
| where DeviceId in (HighValueDevices)
| where InitiatingProcessFileName in~ ("chrome.exe", "msedge.exe", "firefox.exe", "teams.exe",
"slack.exe")
| where FileName endswith_cs ".exe" or FileName endswith_cs ".msi" or FileName endswith_cs ".dll" or
FileName endswith_cs ".ps1" or FileName endswith_cs ".js" or FileName endswith_cs ".vbs"
| project Timestamp, DeviceName, AccountName, FileName, FolderPath, ProcessCommandLine,
InitiatingProcessFileName, InitiatingProcessCommandLine, SHA256
| order by Timestamp desc
```

A true positive is an unexpected external-content process chain on a high-value endpoint, especially when followed by identity changes, unusual developer/AI-agent activity, or wallet workflow access. Expected noise includes approved browser-downloaded installers and developer package workflows; tune with signed publisher, software catalog, and device-role allowlists.

12.2. Hunt 2 — AI-agent and automation activity from risky sessions

Hypothesis: a compromised engineering session used to access an internal assistant/automation plane will show novel tool calls, secret reads, peer actions, or unusually broad scope relative to the account baseline.

```
// Pseudocode/schema adaptation required: normalize agent audit events into AgentAudit_CL.
AgentAudit_CL
| where TimeGenerated > ago(30d)
| where DeviceRisk_s in ("high", "medium") or SessionRisk_s in ("high", "medium")
| where Action_s in ("secret.read", "tool.invoke", "endpoint.control", "session.delegate",
"wallet.policy.read", "wallet.transaction.request")
| summarize Actions=make_set(Action_s), Targets=make_set(Target_s), First=min(TimeGenerated),
Last=max(TimeGenerated) by UserPrincipalName_s, SessionId_s, DeviceId_s
| join kind=leftouter (
    SigninLogs
    | where TimeGenerated > ago(30d)
    | project SigninTime=TimeGenerated, UserPrincipalName, AppDisplayName, IPAddress,
ConditionalAccessStatus
) on $left.UserPrincipalName_s == $right.UserPrincipalName
| order by Last desc
```

A true positive is a risky or anomalous session performing secret/tool/endpoint/wallet activity outside normal role scope. If agent logs do not exist, document this as a telemetry gap and prioritize immutable audit events before further AI-agent rollout.

12.3. Hunt 3 — Wallet workflow policy and transaction anomaly review

Hypothesis: attacker-driven wallet movement will be preceded by policy, address-book, signer, session, permission, or transaction-approval anomalies.

```
index=wallet_audit earliest=-30d
| search event_type IN
("transaction_requested","transaction_approved","transaction_executed","addressbook_changed","signer_ch
anged","policy_changed","breakglass_used")
| stats values(event_type) as events values(actor) as actors values(source_device) as devices
values(destination) as destinations values(approval_id) as approvals values(result) as results by
transaction_id
| eval suspicious=if(mvcount(actors)<2 OR mvfind(events,"policy_changed")>=0 OR
mvfind(events,"breakglass_used")>=0,1,0)
```

```
| where suspicious=1
| table transaction_id events actors devices destinations approvals results suspicious
```

Adapt the event names to the wallet platform. Alert on policy changes adjacent to transfers, novel destination addresses, same-device quorum approvals, break-glass use, or a transaction whose approvers lack independently verifiable device/session health.

13. Incident Response and Containment Guidance

For a suspected recruitment-lure compromise involving a treasury, wallet, exchange, or custody employee:

Priority	Action	Why
0–15 minutes	Suspend wallet transaction execution or raise approval threshold; isolate the affected endpoint; preserve volatile evidence.	Prevent continued asset movement while retaining forensic evidence.
15–60 minutes	Revoke device-bound sessions, SSO tokens, VPN sessions, API keys, developer credentials, and agent/automation tokens reachable from the endpoint.	A password reset alone may not invalidate active sessions or delegated tokens.
1–4 hours	Identify all peer devices, remote sessions, AI-agent tool calls, privileged actions, and wallet-policy changes linked to the user/device.	Scope lateral and control-plane exposure.
4–24 hours	Review transaction requests/approvals/destinations, signer state, address-book changes, and emergency/break-glass events. Coordinate tracing/freeze activity through authorized legal and law-enforcement channels.	Separate customer remediation, asset tracing, and technical eradication.
24–72 hours	Reimage affected systems; rotate high-value secrets; conduct targeted hunting; validate quorum and circuit-breaker controls via tabletop/test.	Establish durable containment and prevent repeat path.

Evidence to preserve: full endpoint triage package, browser history/download records, email and job-platform communications, chat meeting invites, file hashes/URLs, EDR timeline, identity sign-in/token logs, PAM records, agent/automation audit events, wallet-policy history, transaction approval history, and secure time-synchronized logs.

14. Recommended Actions

Priority	Action	Owner	Target
Critical	Require transaction quorum with independently validated approvers, separate devices, destination allowlists, velocity caps, and emergency halt capability.	Wallet/Treasury Engineering	Immediate
Critical	Identify endpoints/users with wallet, signing, treasury, or privileged automation access; enforce hardened-device and	Security Engineering	7 days

	EDR policy.		
Critical	Inventory AI assistants, agents, RPA, remote support, and developer automation that can read secrets or initiate actions; reduce scopes and add auditability.	Platform/AI Security	7 days
High	Create a recruitment-lure response process for privileged staff: safe environment for interview tasks, required reporting, and out-of-band verification.	HR + Security	14 days
High	Correlate EDR, IdP, PAM, agent audit, and wallet audit logs in one incident workflow.	SOC / Detection Engineering	14 days
High	Validate session revocation and token rotation can be executed without blocking emergency asset protection.	Identity + IR	14 days
Medium	Run a tabletop: malicious recruitment download → engineer compromise → agent abuse → suspicious wallet transfer.	Purple Team	30 days
Medium	Test recovery communications that distinguish customer reimbursement, exchange liquidity, frozen assets, and recovered assets.	Legal/Comms/IR	30 days

15. Analyst Bottom Line

The Binance event is a warning against treating crypto theft solely as a wallet-key or blockchain-security problem. Public reporting describes a mature human intrusion operation that targeted the people and internal systems surrounding high-value wallet control. The defensive center of gravity is therefore the junction of endpoint security, identity/session containment, AI/automation governance, and transaction design.

Organizations managing material digital assets should assume that a patient adversary can make a fake employer, interview, assignment, and online persona appear credible. Their architecture must ensure that compromise of a single engineer—or even several collaborating endpoints—cannot silently become a multi-billion-dollar transaction.

16. References

- [1] FBI — North Korea Responsible for $6 Billion+ Binance Attack: https://www.fbi.gov/investigate/cyber/alerts/2026/north-korea-responsible-for-6-billion-binance-attack
- [2] Binance — Initial Findings and Response Update: https://www.binance.com/en/blog/community/3229153443759566763
- [3] NPR — A Binance engineer thought he was interviewing for a job. Then the hackers pounced: https://www.npr.org/2026/11/03/nx-s1-6027799/binance-crypto-exchange-cyber-heist

- [4] BBC — Binance says fake job interviews used as part of $6.3bn crypto hack: https://www.bbc.com/news/articles/ck5ynwz9gy67o
- [5] Chainalysis — Binance Hack: Tracing the $6.4 Billion Theft to North Korea: https://www.chainalysis.com/blog/binance-exploit-latest-findings-and-response/
- [6] MITRE ATT&CK — Spearphishing Attachment: https://attack.mitre.org/techniques/T1566/001/