

Suspicious Word Macro Backdoor - dba90bd5fdf0

Malware Analysis Report

Field	Value
Classification	TLP:CLEAR
Published	2026-06-02
Version	1.0
Author	Lost Boys Cyber
Report Type	Malware Analysis

TLP:CLEAR | Lost Boys Cyber | Suspicious Word Macro Backdoor dba90bd5fdf0 - Malware Analysis Report

Published: 2026-06-02 | TLP:CLEAR | Version: 1.0 | Author: Lost Boys Cyber

AI Generation: This report was generated with AI assistance and is provided for informational purposes only. All findings, IOCs, detection rules, hunting queries, attribution assessments, and recommendations must be independently reviewed and validated by a qualified security professional before operational use.

Table of Contents

1. Executive Summary
2. Sample Metadata
3. Source Review & Confidence
4. Payload Variants and Delivery
5. Infection Chain Analysis
6. Technical Analysis
7. Indicators of Compromise
8. MITRE ATT&CK Mapping
9. Detection Engineering
10. Threat Hunting
11. Triage and Incident Response
12. Validation and Emulation
13. Recommendations
14. References and Refresh Notes

1. Executive Summary

Lost Boys Cyber analyzed a password-protected archive containing a Microsoft Word OLE document with VBA auto-execution. The document creates a VBScript payload at `C:\ProgramData\Temp_FU4.txt` and in the current user's Startup folder as `Temp_FU4.vbs`, giving the operator persistence after user login.

The reconstructed VBScript is a lightweight polling backdoor. It builds a victim identifier from `whoami`, rotates across two hard-coded IP addresses, sleeps for 120 to 180 seconds, retrieves commands over HTTP, executes received commands with `cmd /c`, and posts command output back as JSON.

The local sandbox captured host-only VM traffic but did not collect guest artifacts for this run, so dynamic host-behavior findings are limited. The strongest evidence is static/code analysis of the Office macro and reconstructed VBS payload. Network C2 indicators are therefore assessed as configuration indicators with medium confidence until confirmed in live telemetry.

2. Sample Metadata

Field	Value
Archive path	/home/lost0x01/Downloads/dba90bd5fdf0321a28f21fccb3a77ee1ed5d73e
Archive SHA256	7f2cea75a4a99b561fac723e74f607803d2594385c0dbfaab5dbee6598dd3e3
Extracted sample SHA256	dba90bd5fdf0321a28f21fccb3a77ee1ed5d73e863e4520ce8eb8fca670189c3
Extracted sample SHA1	2f9010846ff11471d6c84018834112bf6022a296
Extracted sample MD5	d98cd6a09d0af803b68354f0db432e30
Extracted size	441,856 bytes
File type	Composite Document File V2, Microsoft Word OLE document
Author metadata	Windows User
Last saved by	Frank
Creating application	Microsoft Office Word
Created	2021-12-20 11:43:00
Last saved	2021-12-20 11:52:00
Reconstructed payload SHA256	cfc1c6d8a3f5f2ec89d2f5c893c7f56b178596c18e3f58e57553b43b424c898
PCAP SHA256	7c17a969d1b734b97dea58536c60ce675a78be53ae97e3f98c883187ea43eb3

3. Source Review & Confidence

Source	Contribution	Confidence
Local static files under <code>Static/dba90bd5fdf0</code>	Hashes, OLE metadata, macro extraction, decoded VBS payload	High
Local sandbox run <code>Runs/2026-06-02_143842_dba90bd5fdf0</code>	PCAP, DNS/HTTP fake-service logs, Suricata output, sandbox summary	Medium
ARIN RDAP	Netblock owner and allocation context for C2 IPs	Medium
Shodan InternetDB	Hostname and exposed-service snapshot for <code>192.227.147.152</code>	Medium
AKMalware public writeup	External corroboration that this hash is a malicious Word document sample	Medium
MITRE ATT&CK	Technique mapping reference	High

Source limitation: abuse.ch MalwareBazaar and ThreatFox API enrichment returned `Unauthorized` from this environment during report generation, so those results are not used as confirmed external intelligence.

4. Payload Variants and Delivery

The delivered object is a macro-enabled Word OLE document inside a password-protected archive. The Word meta-data indicates it was created and saved on 2021-12-20. The document contains a **Document_Open** auto-execution routine, which means the malicious macro is intended to run when a user opens the document with macros enabled.

The VBA macro uses string fragmentation and junk-token substitution to hide a second-stage VBScript payload. The macro writes the decoded script to:

Path	Purpose
C:\ProgramData\Temp_FU4.txt	Intermediate payload staging
%APPDATA%\Microsoft\Windows\Start Menu\Programs\Startup\Temp_FU4.vbs	User Startup persistence

This chain is consistent with a document-delivered script backdoor rather than a compiled PE loader.

5. Infection Chain Analysis

1. User opens the Word document and enables macro execution.
2. **Document_Open** invokes the macro routine.
3. The macro reconstructs a hidden VBScript payload from fragmented strings.
4. The macro writes the VBS payload to ProgramData and the user Startup folder.
5. The VBS launches its polling loop.
6. The VBS generates a victim ID using `whoami`, prefixed with `TR-`.
7. The VBS rotates between two C2 IPs.
8. Every 120 to 180 seconds, the VBS requests `/getCommand?guid=<victim_id>`.
9. If the response is not empty and not `EMPTY`, the VBS executes it via `cmd /c`.
10. Command output is written to `C:\ProgramData\GXji.txt`, read back, deleted, and posted to `/getTarget-Info?guid=<victim_id>&status=1`.

6. Technical Analysis

6.1 Static Analysis

The file is an OLE Word document with VBA macro streams. `olevba` identified **Document_Open**, **CreateObject**, hex/base64-like obfuscation, and **Temp_FU4.vbs** as suspicious indicators. Static extraction produced these key artifacts:

Artifact	Path
OLE macro output	Static/dba90bd5fdf0/olevba.txt
Deobfuscated macro output	Static/dba90bd5fdf0/olevba_deobf.txt
Reconstructed VBS	Static/dba90bd5fdf0/payload_vbs_deobf.vbs
OLE streams	Static/dba90bd5fdf0/ole_streams/

The VBA macro calls `createTextFile` for the ProgramData and Startup paths. The payload reconstruction routine uses a token-removal pattern and then writes the resulting VBS to disk.

6.2 Code Analysis

The VBS payload contains these core routines:

Function	Behavior
model_JKDZ	Decodes substitution-obfuscated strings using the key <code>i6aqpklwuj8395ryzo1h4b07et2mdsfvgxcn</code>
model_ZJUX	Runs <code>whoami</code> , replaces <code>\</code> with <code>-</code> , and prefixes the victim ID with <code>TR-</code>
model_LCZD	Rotates through configured C2 servers
model_III	Sleeps for $(\text{Rnd}() * 60 + 120) * 1000$, producing a 120 to 180 second delay
model_WCDW	Performs HTTP GET with <code>Microsoft.XMLHTTP</code>
model_AZYL	Executes received commands through <code>cmd /c</code> , redirects output to <code>C:\ProgramData\GXji.txt</code> , reads and deletes the file
model_OCJMZ	Posts command output as JSON with <code>MSXML2.XMLHTTP</code>
model_IQW	Main polling loop

Decoded configuration:

Field	Value
C2 IP 1	192.227.147.152
C2 IP 2	107.174.68.60
User-Agent	Mozilla/4.0 (compatible; ms-office; MSOffice 16)
Command endpoint	<code>http://<c2>/getCommand?guid=<victim_id></code>
Result endpoint	<code>http://<c2>/getTargetInfo?guid=<victim_id>&status=1</code>
Result JSON key	<code>commandResult</code>
Execution primitive	<code>cmd /c <operator_command></code>
Output staging	<code>C:\ProgramData\GXji.txt</code>

Analyst assessment: this is a command-execution backdoor with persistence and basic host profiling. It does not contain advanced credential theft or lateral movement logic in the recovered payload, but arbitrary command execution gives the operator the ability to stage additional tooling.

6.3 Dynamic Analysis

The sandbox run used the local RAIccoon VirtualBox lab:

Field	Value
VM	win-malware-lab
Snapshot	clean-guestadditions-sysmon
Interface	vboxnet0
Host-only gateway/DNS	192.168.56.1
Guest IP	192.168.56.20
Capture duration	80.418 seconds
Packets	1,120
PCAP size	184 kB

Observed network traffic was dominated by Windows baseline activity:

Observation	Count / Value
Fake HTTP rows	79
ctldl.windowsupdate.com	68 requests
www.msftconnecttest.com	11 requests
Suricata alerts	0
Suspicious DNS domains from parser	0
Guest artifacts parsed	No

Dynamic limitation: the sandbox run did not capture `guest_artifacts.zip`, and the VBS polling interval can delay C2 activity by up to 180 seconds. The PCAP did not confirm beacon traffic to the decoded C2 endpoints during the captured window. Treat dynamic execution as incomplete and use the static/code findings as the primary basis for detections.

6.4 OSINT Enrichment

Indicator	Source	Result	Confidence
192.227.147.152	ARIN RDAP	Netblock 192.227.128.0 - 192.227.255.255, registrant HostPapa	Medium
107.174.68.60	ARIN RDAP	Netblock 107.172.0.0 - 107.175.255.255, registrant HostPapa	Medium
192.227.147.152	Shodan InternetDB	Hostname 192-227-147-152-host.colocrossing.com, port 22, OpenSSH 9.6p1 on Ubuntu	Medium
107.174.68.60	Shodan InternetDB	No information available	Low
Sample SHA256	AKMalware	Public writeup exists for this exact Word sample hash	Medium

The IPs should be handled as C2 configuration indicators, not standalone proof of compromise. Hosting providers and VPS infrastructure can be reused or reassigned.

7. Indicators of Compromise

7.1 Indicator Summary

Indicator Class	Count	Confidence	Recommended Use
SHA256 hashes	3	High	Exact-match sweep
IP addresses	2	Medium	Network hunt and enrichment
Domains	0	Low	No malicious domain decoded
URLs	2 patterns	Medium	Proxy and EDR command-line hunt
Host indicators	4	High	Behavioral detection

7.2 Source Notes

Source	Contribution
Local static analysis	Confirmed hashes, file type, macro behavior, VBS code
Local sandbox	Confirmed incomplete dynamic run and baseline network traffic
ARIN/Shodan	Infrastructure context for decoded C2 IPs
External writeup	Hash-level corroboration

7.3 File Hashes

Type	Indicator	Confidence	Handling
SHA256	dba90bd5fdf0321a28f21fccb3:	High	Sweep mail, EDR, web gateway, quarantine if confirmed
SHA1	2f9010846ff11471d6c8401883:	High	Secondary exact-match sweep
MD5	d98cd6a09d0af803b68354f0db:	High	Legacy tool sweep only
SHA256	7f2cea75a4a99b561fac723e74:	High	Archive-level evidence tracking
SHA256	cfc1c6d8a3f5f2ec89d2f5c893:	High	Reconstructed payload tracking

7.4 Network Indicators

Type	Indicator	Confidence	Handling
IP	192.227.147.152	Medium	Hunt proxy, firewall, DNS, EDR netconn; enrich before blocking
IP	107.174.68.60	Medium	Hunt proxy, firewall, DNS, EDR netconn; enrich before blocking

7.5 URL / Config Indicators

Type	Indicator	Confidence	Handling
URL pattern	http://<c2>/getCommand?gui	Medium	Hunt HTTP proxy and EDR network events
URL pattern	http://<c2>/getTargetInfo?	Medium	Hunt HTTP POST telemetry and command-result exfil
User-Agent	Mozilla/4.0 (compatible; ms-office; MSOffice 16)	Medium	Use with endpoint/process context, not standalone

7.6 Host Indicators

Type	Indicator	Confidence	Notes
File path	C:\ProgramData\Temp_FU4.tx	High	VBS staging path from macro
File path	%APPDATA%\Microsoft\Windows\Menu\Programs\Startup\Temp	High	Persistence path
File path	C:\ProgramData\GXji.txt	High	Command-output staging path
Process	wscript.exe or cscript.exe executing Temp_FU4.vbs	High	Expected execution host
Process	cmd.exe /c <operator_command> child of script host	High	Command execution behavior

7.7 IOC Usage Guidance

File hashes and host paths are high-confidence sample-specific indicators. The two IP addresses are configuration indicators and should be combined with the decoded URI paths, user-agent, script-host parent process, and command execution behavior. The User-Agent string is suspicious in this context but should not be used alone because legacy/automation clients can imitate Office-like headers.

8. MITRE ATT&CK Mapping

Tactic	Technique	Evidence
Initial Access	T1566.001 - Spearphishing Attachment	Word document delivery is consistent with attachment-based phishing; delivery source not independently confirmed
Execution	T1204.002 - Malicious File	User must open the Word document and enable macro execution
Execution	T1059.005 - Visual Basic	VBA macro and VBS payload execute script logic
Execution	T1059.003 - Windows Command Shell	Payload runs received commands through cmd /c
Persistence	T1547.001 - Registry Run Keys / Startup Folder	Payload writes Temp_FU4.vbs into the user Startup folder
Defense Evasion	T1027 - Obfuscated Files or Information	Macro hides payload with fragmented strings and substitution junk
Discovery	T1033 - System Owner/User Discovery	Payload runs whoami to build victim ID
Command and Control	T1071.001 - Web Protocols	HTTP GET/POST polling over port 80
Command and Control	T1105 - Ingress Tool Transfer	Arbitrary command channel can retrieve and stage follow-on tools, though not observed in this sample

9. Detection Engineering

9.1 Sigma - Startup VBS Persistence From Office

```
title: Office Macro Writes VBS To User Startup Folder
id: 72e2bbd4-5306-4fb8-b87d-dba90bd5fdf0
status: experimental
description: Detects Office-spawned script persistence through a VBS file written to the user Startup folder.
references:
  - local-analysis:dba90bd5fdf0321a28f21fccb3a77ee1ed5d73e863e4520ce8eb8fca670189c3
author: Lost Boys Cyber
date: 2026-06-02
tags:
  - attack.persistence
  - attack.t1547.001
  - attack.execution
  - attack.t1059.005
logsource:
  product: windows
  category: file_event
detection:
  selection_path:
    TargetFilename|contains:
      - '\\Microsoft\\Windows\\Start Menu\\Programs\\Startup\\'
    TargetFilename|endswith: '.vbs'
  selection_office:
    Image|endswith:
      - '\\WINWORD.EXE'
      - '\\EXCEL.EXE'
      - '\\POWERPNT.EXE'
  condition: selection_path and selection_office
falsepositives:
  - Rare administrative macro automation
  - Legacy logon script deployment
level: high
```

9.2 Sigma - VBS Backdoor Command Execution

```
title: Script Host Spawns Hidden Command Shell With ProgramData Output Redirection
id: 4d8ef972-1b14-4dc8-83d7-dba90bd5fdf0
status: experimental
description: Detects VBS-style backdoor execution where script host launches cmd.exe and redirects output into ProgramData.
references:
  - local-analysis:dba90bd5fdf0321a28f21fccb3a77ee1ed5d73e863e4520ce8eb8fca670189c3
author: Lost Boys Cyber
date: 2026-06-02
tags:
  - attack.execution
  - attack.t1059.003
  - attack.t1059.005
logsource:
  product: windows
  category: process_creation
detection:
  selection_parent:
    ParentImage|endswith:
      - '\\wscript.exe'
      - '\\cscript.exe'
  selection_child:
    Image|endswith: '\\cmd.exe'
    CommandLine|contains|all:
      - '/c'
      - 'ProgramData'
      - '>'
  condition: selection_parent and selection_child
falsepositives:
  - Enterprise logon scripts that capture command output
level: high
```

9.3 KQL - Microsoft Defender For Endpoint

```
let C2IPs = dynamic(["192.227.147.152", "107.174.68.60"]);
DeviceNetworkEvents
| where RemoteIP in (C2IPs)
  or Url has_any ("/getCommand?guid=", "/getTargetInfo?guid=")
  or InitiatingProcessCommandLine has "Temp_FU4.vbs"
| project Timestamp, DeviceName, InitiatingProcessFileName, InitiatingProcessCommandLine,
  RemoteIP, RemotePort, Url, ReportId
```

```
DeviceFileEvents
| where FolderPath has @"\Microsoft\Windows\Start Menu\Programs\Startup\"
| where FileName == "Temp_FU4.vbs" or FileName endswith ".vbs"
| where InitiatingProcessFileName in~ ("WINWORD.EXE", "wscript.exe", "cscript.exe")
| project Timestamp, DeviceName, FileName, FolderPath, SHA256,
  InitiatingProcessFileName, InitiatingProcessCommandLine
```

9.4 SPL - Splunk Endpoint

```
index=endpoint (process_name=cmd.exe OR Image="*\\cmd.exe")
(ParentImage="*\\wscript.exe" OR ParentImage="*\\cscript.exe")
CommandLine="*/c*" CommandLine="*ProgramData*" CommandLine="*>*"
| table _time host user ParentImage Image CommandLine
```

```
index=proxy OR index=edr_net
(dest_ip IN ("192.227.147.152", "107.174.68.60") OR uri_path IN ("/getCommand", "/getTargetInfo") OR url="*getCommand?guid=*")
| table _time host user process dest_ip dest_port http_method url user_agent
```

9.5 YARA - Document And Payload Triage

```
rule LBC_WordMacro_Temp_FU4_VBS_Backdoor_dba90bd5fdf0
{
  meta:
    description = "Detects Word macro/VBS backdoor traits from sample dba90bd5fdf0"
    author = "Lost Boys Cyber"
    date = "2026-06-02"
    sha256 = "dba90bd5fdf0321a28f21fccb3a77ee1ed5d73e863e4520ce8eb8fca670189c3"
  strings:
    $ole = { D0 CF 11 E0 A1 B1 1A E1 }
    $auto = "Document_Open" ascii wide
    $vbs = "Temp_FU4.vbs" ascii wide
    $programdata = "C:\\ProgramData\\Temp_FU4.txt" ascii wide
    $xmlhttp1 = "Microsoft.XMLHTTP" ascii wide
    $xmlhttp2 = "MSXML2.XMLHTTP" ascii wide
    $cmd = "cmd /c" ascii wide
    $ua = "MSOffice 16" ascii wide
  condition:
    $ole at 0 and 4 of ($auto, $vbs, $programdata, $xmlhttp1, $xmlhttp2, $cmd, $ua)
}
```

9.6 Suricata - HTTP C2 Path Pattern

```
alert http any any -> any any (msg:"LBC Word VBS backdoor getCommand polling"; flow:to_server,established; http.uri;
  ⇐ content: "/getCommand?guid="; nocase; http.user_agent; content: "MSOffice 16"; nocase; classtype: trojan-activity; sid: 9100010;
  ⇐ rev: 1;)
alert http any any -> any any (msg:"LBC Word VBS backdoor getTargetInfo result post"; flow:to_server,established; http.method;
  ⇐ content: "POST"; http.uri; content: "/getTargetInfo?guid="; nocase; http.uri; content: "status="; nocase; classtype: trojan-activity;
  ⇐ sid: 9100011; rev: 1;)
```

Validation and tuning notes:

- Validate process rules against Sysmon Event ID 1 or EDR process creation telemetry.

- Validate file rules against Sysmon Event ID 11 or EDR file creation telemetry.
- Tune out known administrative scripts before production alerting.
- Network rules should require either the path pattern or the path plus user-agent, not only the IPs.

10. Threat Hunting

Hypothesis 1 - Office Dropped Startup Script

If the document executed, Office or a script host created Temp_FU4.vbs in a Startup folder.

```
DeviceFileEvents
| where FolderPath has @"\Start Menu\Programs\Startup\"
| where FileName endswith ".vbs" or FileName =~ "Temp_FU4.vbs"
| where InitiatingProcessFileName in~ ("WINWORD.EXE","EXCEL.EXE","POWERPNT.EXE","wscript.exe","cscript.exe")
```

Hypothesis 2 - Script Host Command Execution

If the VBS ran, wscript.exe or cscript.exe spawned cmd.exe and redirected output to ProgramData.

```
DeviceProcessEvents
| where InitiatingProcessFileName in~ ("wscript.exe","cscript.exe")
| where FileName =~ "cmd.exe"
| where ProcessCommandLine has "/c" and ProcessCommandLine has "ProgramData"
```

Hypothesis 3 - HTTP Polling Backdoor

If the payload reached C2, endpoint or proxy logs show HTTP requests to the decoded IPs or URI patterns.

```
DeviceNetworkEvents
| where RemoteIP in ("192.227.147.152","107.174.68.60")
  or Url has "/getCommand?guid="
  or Url has "/getTargetInfo?guid="
```

Expected triage:

- Confirm whether Word opened the sample and whether macros ran.
- Review user Startup folder contents and file timestamps.
- Collect the VBS payload if present and hash it.
- Pull process trees around WINWORD.EXE, wscript.exe, cscript.exe, and cmd.exe.
- Check proxy/firewall logs for the decoded C2 IPs and paths.

11. Triage and Incident Response

Priority	Owner	Timeline	Action
P1	SOC / IR	Immediate	Sweep for the sample hash, archive hash, Temp_FU4.vbs, and GXji.txt
P1	SOC / IR	Immediate	Hunt for HTTP requests to decoded C2 IPs and URI patterns
P1	Endpoint team	Immediate	Isolate any host with confirmed script execution or C2 traffic
P2	Messaging team	24 hours	Search mail telemetry for the archive/document hash and similar password-protected attachments

Priority	Owner	Timeline	Action
P2	Detection engineering	48 hours	Deploy and tune Sigma/KQL/SPL detections
P3	Threat intel	72 hours	Re-enrich C2 IPs and hash in MalwareBazaar, ThreatFox, VirusTotal, URLhaus, and passive DNS where licensed

Containment guidance:

- Do not rely only on IP blocking; the operator can move infrastructure.
- Preserve the document, VBS payload, registry/startup artifacts, and process telemetry before cleanup.
- Reset credentials for any user account on a confirmed infected endpoint because arbitrary command execution may expose local secrets.

12. Validation and Emulation

The sandbox run produced a PCAP and fake-service logs but did not collect guest artifacts. To validate the full chain:

1. Re-run the sample with a detonation duration of at least 300 seconds to cover the 120 to 180 second sleep interval.
2. Ensure Guest Control artifact collection succeeds and produces `guest_artifacts.zip`.
3. Confirm Sysmon captures file creation in ProgramData and Startup.
4. Confirm process creation for `wscript.exe` and `cmd.exe /c`.
5. Confirm network telemetry for `/getCommand?guid=` and `/getTargetInfo?guid=`.
6. Re-run Suricata with the path-based rules in this report.

13. Recommendations

Priority	Owner	Timeline	Recommendation
High	Endpoint security	0-7 days	Block or heavily restrict Office macros from internet-origin documents
High	SOC	0-7 days	Deploy hunts for Office-to-script persistence and script-host command execution
High	Network security	0-7 days	Add monitored blocks or alerts for decoded C2 IPs with expiration and revalidation
Medium	Email security	7-14 days	Strengthen controls for password-protected archives from external senders
Medium	Windows platform	7-30 days	Enable Attack Surface Reduction rules for Office child-process creation where operationally feasible

Priority	Owner	Timeline	Recommendation
Medium	Detection engineering	7-30 days	Add URI-path based detection for low-volume HTTP polling backdoors
Low	Threat intel	30 days	Periodically refresh hash and infrastructure enrichment in licensed intel sources

14. References and Refresh Notes

Local evidence:

- Static/dba90bd5fdf0/hashees.txt
- Static/dba90bd5fdf0/file.txt
- Static/dba90bd5fdf0/olevba_deobf.txt
- Static/dba90bd5fdf0/payload_vbs_deobf.vbs
- Runs/2026-06-02_143842_dba90bd5fdf0/summary.json
- Runs/2026-06-02_143842_dba90bd5fdf0/analysis.md
- Runs/2026-06-02_143842_dba90bd5fdf0/http_80.jsonl
- Runs/2026-06-02_143842_dba90bd5fdf0/suricata_eve.json

External references:

- AKMalware public hash writeup: <https://akmalware.com/2022/01/18/%D8%AA%D8%AD%D9%84%D9%8A%D9%84-%D9%85%D9%84%D9%81-%D9%88%D8%B1%D8%AF-%D8%AE%D8%A8%D9%8A%D8%AB/>
- MITRE ATT&CK T1204.002: <https://attack.mitre.org/techniques/T1204/002/>
- MITRE ATT&CK T1059.005: <https://attack.mitre.org/techniques/T1059/005/>
- MITRE ATT&CK T1547.001: <https://attack.mitre.org/techniques/T1547/001/>
- MITRE ATT&CK T1071.001: <https://attack.mitre.org/techniques/T1071/001/>
- ARIN RDAP for 192.227.147.152: <https://rdap.arin.net/registry/ip/192.227.147.152>
- ARIN RDAP for 107.174.68.60: <https://rdap.arin.net/registry/ip/107.174.68.60>
- Shodan InternetDB for 192.227.147.152: <https://internetdb.shodan.io/192.227.147.152>
- Shodan InternetDB for 107.174.68.60: <https://internetdb.shodan.io/107.174.68.60>

Refresh notes:

- Re-run abuse.ch MalwareBazaar and ThreatFox enrichment from an authenticated or permitted environment.
- Re-run dynamic detonation long enough to cover the payload sleep interval.
- Refresh IP ownership and exposed-service data before operational blocking.