

Write a program to implement the following operations of Binary Search Tree.

- i. Insert
- ii. Traverse (Inorder, Preorder, Postorder)
- iii. Delete

Program-

```
#include <stdio.h>
#include <stdlib.h>

typedef struct Node
{
    struct Node *left;
    int data;
    struct Node *right;
} node;

// Creation
node *createNode(int element)
{
    node *newnode = (node *)malloc(sizeof(node));
    newnode->data = element;
    newnode->left = newnode->right = NULL;
    return newnode;
}

// Insertion
void insertion(node **root, int element)
{
    node *prev = NULL, *newnode, *loc = *root;
    while (loc != NULL)
    {
        prev = loc;
        if (loc->data == element)
        {
            printf("Element exists.\n");
            return;
        }
        else if (element < loc->data)
            loc = loc->left;
        else
            loc = loc->right;
    }
    newnode = createNode(element);
```

```
        if (prev == NULL)
            *root = newnode;
        else if (element < prev->data)
            prev->left = newnode;
        else
            prev->right = newnode;
        return;
    }

// Traversal
void inorder(node *root)
{
    if (root != NULL)
    {
        inorder(root->left);
        printf("%d ", root->data);
        inorder(root->right);
    }
    else
    {
        printf("BST doesn't exists.\n");
    }
}

void preorder(node *root)
{
    if (root != NULL)
    {
        printf("%d ", root->data);
        preorder(root->left);
        preorder(root->right);
    }
    else
    {
        printf("BST doesn't exists.\n");
    }
}

void postorder(node *root)
{
    if (root != NULL)
    {
        postorder(root->left);
        postorder(root->right);
```

```
        printf("%d ", root->data);
    }
    else
    {
        printf("BST doesn't exists.\n");
    }
}

// Deletion
void postorder_traverse(node *root)
{
    if (root != NULL)
    {
        postorder_traverse(root->left);
        postorder_traverse(root->right);
        printf("%d ", root->data);
    }
}

void deletion(node **root, int item)
{
    if (*root == NULL)
    {
        printf("BST doesn't exists.\n");
        return;
    }
    node *par = NULL, *loc = *root, *child, *parsuc, *suc;
    while (loc != NULL && loc->data != item)
    {
        par = loc;
        if (item < loc->data)
            loc = loc->left;
        else
            loc = loc->right;
    }
    if (loc == NULL)
    {
        printf("\nNode containing %d does not exist.\n",
item);
        return;
    }
    if (loc->left == NULL && loc->right == NULL)
        child = NULL;
    else if (loc->left == NULL)
        child = loc->right;
```

```
else if (loc->right == NULL)
    child = loc->left;
else
{
    suc = loc->right;
    parsuc = loc;
    while (suc->left != NULL)
    {
        parsuc = suc;
        suc = suc->left;
    }
    if (parsuc != loc)
    {
        parsuc->left == suc->right;
        suc->right = loc->right;
    }
    suc->left = loc->left;
    child = suc;
}
if (par != NULL)
{
    if (loc == par->left)
        par->left = child;
    else
        par->right = child;
}
else
    *root = child;
printf("\n%d deleted.\n", item);
free(loc);
return;
}

int main()
{
    int num, element;
    node *root = NULL;
    while (1)
    {
        printf("\nOperations to be performed:\n");
        printf("1. Insertion.\n");
        printf("2. Deletion.\n");
        printf("3. Traversal.\n");
```

```
        printf("\nEnter the operation (1-3 or 0 to exit):  
");  
        scanf("%d", &num);  
  
        switch (num)  
        {  
            case 1:  
                printf("\nEnter the element to be  
inserted: ");  
                scanf("%d", &element);  
                insertion(&root, element);  
                break;  
  
            case 2:  
                printf("\nEnter the element to be  
deleted: ");  
                scanf("%d", &element);  
                deletion(&root, element);  
                break;  
  
            case 3:  
                printf("\nPreorder Traversal: ");  
                preorder(root);  
                printf("\nInorder Traversal: ");  
                inorder(root);  
                printf("\nPostorder Traversal: ");  
                postorder(root);  
                printf("\n");  
                break;  
  
            case 0:  
                exit(0);  
  
            default:  
                printf("Invalid option! Try again.\n");  
        }  
    }  
    return (0);  
}
```