

Single Final State for NFAs


class 4

1


Any NFA can be converted
to an equivalent NFA
with a single final state

2

Example




Equivalent NFA




3

In General

NFA



Equivalent NFA




Single
final state

4

Extreme Case

NFA without final state



Add a final state
Without transitions

5

Properties of Regular Languages

6

For regular languages L_1 and L_2
we will prove that:

Union: $L_1 \cup L_2$
 Concatenation: $L_1 L_2$
 Star: L_1^*
 Reversal: L_1^R
 Complement: $\overline{L_1}$
 Intersection: $L_1 \cap L_2$

} Are regular Languages

7

We say: Regular languages are **closed under**

Union: $L_1 \cup L_2$
 Concatenation: $L_1 L_2$
 Star: L_1^*
 Reversal: L_1^R
 Complement: $\overline{L_1}$
 Intersection: $L_1 \cap L_2$

8

Regular language L_1

Regular language L_2

$$L(M_1) = L_1$$

$$L(M_2) = L_2$$

NFA M_1

NFA M_2





Single final state



Single final state

9


Example



10

Union


NFA for $L_1 \cup L_2$



11

Example


NFA for $L_1 \cup L_2 = \{a^n b\} \cup \{ba\}$



12

Concatenation


NFA for L_1L_2



13

Example


NFA for $L_1L_2 = \{a^n b\} \{ba\} = \{a^n bba\}$



14

Star Operation

NFA for L_1^*




15

Example

NFA for $L_1^* = \{a^n b\}^*$

$$w = w_1 w_2 \dots w_k$$

$$w_i \in L_1$$



16

Reverse



NFA for L_1^R



1. Reverse all transitions
2. Make initial state final state and vice versa

17

Example



18



Complement



1. Take the **DFA** that accepts L_1
2. Make final states non-final, and vice-versa

19

Example



20

Intersection

DeMorgan's Law: $L_1 \cap L_2 = \overline{\overline{L_1} \cup \overline{L_2}}$

- L_1, L_2 regular
- $\overline{L_1}, \overline{L_2}$ regular
- $\overline{L_1} \cup \overline{L_2}$ regular
- $\overline{\overline{L_1} \cup \overline{L_2}}$ regular
- $L_1 \cap L_2$ regular

21

Example

$L_1 = \{a^n b\}$ regular
 $L_2 = \{ab, ba\}$ regular

$\Rightarrow L_1 \cap L_2 = \{ab\}$ regular

22

Regular Expressions

23

Regular Expressions

Regular expressions
describe regular languages

Example: $(a + b \cdot c)^*$

describes the language

$\{a, bc\}^* = \{\lambda, a, bc, aa, abc, bca, \dots\}$

24

Recursive Definition

Primitive regular expressions: \emptyset , λ , a

Given regular expressions r_1 and r_2

$$\left. \begin{array}{l} r_1 + r_2 \\ r_1 \cdot r_2 \\ r_1^* \\ (r_1) \end{array} \right\} \text{Are regular expressions}$$

25

Examples

A regular expression: $(a + b \cdot c)^* \cdot (c + \emptyset)$

Not a regular expression: $(a + b +)$

26

Languages of Regular Expressions

$L(r)$: language of regular expression r

Example

$$L((a + b \cdot c)^*) = \{\lambda, a, bc, aa, abc, bca, \dots\}$$

27

Definition

For primitive regular expressions:

$$L(\emptyset) = \emptyset$$

$$L(\lambda) = \{\lambda\}$$

$$L(a) = \{a\}$$

28

Definition (continued)

For regular expressions r_1 and r_2

$$L(r_1 + r_2) = L(r_1) \cup L(r_2)$$

$$L(r_1 \cdot r_2) = L(r_1) L(r_2)$$

$$L(r_1^*) = (L(r_1))^*$$

$$L((r_1)) = L(r_1)$$

29

Example

Regular expression: $(a + b) \cdot a^*$

$$\begin{aligned} L((a + b) \cdot a^*) &= L((a + b)) L(a^*) \\ &= L(a + b) L(a^*) \\ &= (L(a) \cup L(b)) (L(a))^* \\ &= (\{a\} \cup \{b\}) (\{a\})^* \\ &= \{a, b\} \{\lambda, a, aa, aaa, \dots\} \\ &= \{a, aa, aaa, \dots, b, ba, baa, \dots\} \end{aligned}$$

30

Example

Regular expression $r = (a+b)^*(a+bb)$

$$L(r) = \{a, bb, aa, abb, ba, bbb, \dots\}$$

31

Example

Regular expression $r = (aa)^*(bb)^*b$

$$L(r) = \{a^{2n}b^{2m}b : n, m \geq 0\}$$

32

Example

Regular expression $r = (0+1)^*00(0+1)^*$

$$L(r) = \{ \text{all strings with at least two consecutive 0} \}$$

33

Example

Regular expression $r = (1+01)^*(0+\lambda)$

$$L(r) = \{ \text{all strings without two consecutive 0} \}$$

34

Equivalent Regular Expressions

Definition:

Regular expressions r_1 and r_2

are **equivalent** if $L(r_1) = L(r_2)$

35

Example

$L = \{ \text{all strings without two consecutive 0} \}$

$$r_1 = (1+01)^*(0+\lambda)$$

$$r_2 = (1^*011^*)^*(0+\lambda) + 1^*(0+\lambda)$$

$L(r_1) = L(r_2) = L \Rightarrow r_1$ and r_2 are equivalent regular expr.

36

Regular Expressions and Regular Languages

37

Theorem

$$\left\{ \begin{array}{l} \text{Languages} \\ \text{Generated by} \\ \text{Regular Expressions} \end{array} \right\} = \left\{ \begin{array}{l} \text{Regular} \\ \text{Languages} \end{array} \right\}$$

38

Theorem - Part 1

$$\left\{ \begin{array}{l} \text{Languages} \\ \text{Generated by} \\ \text{Regular Expressions} \end{array} \right\} \subseteq \left\{ \begin{array}{l} \text{Regular} \\ \text{Languages} \end{array} \right\}$$

1. For any regular expression r the language $L(r)$ is regular

39

Theorem - Part 2

$$\left\{ \begin{array}{l} \text{Languages} \\ \text{Generated by} \\ \text{Regular Expressions} \end{array} \right\} \supseteq \left\{ \begin{array}{l} \text{Regular} \\ \text{Languages} \end{array} \right\}$$

2. For any regular language L there is a regular expression r with $L(r) = L$

40

Proof - Part 1

1. For any regular expression r the language $L(r)$ is regular


Proof by induction on the size of r

41

Induction Basis

Primitive Regular Expressions: \emptyset , λ , a

NFAs



42

Inductive Hypothesis

Assume
for regular expressions r_1 and r_2
that
 $L(r_1)$ and $L(r_2)$ are regular languages

43

Inductive Step

We will prove:

$L(r_1 + r_2)$
 $L(r_1 \cdot r_2)$
 $L(r_1^*)$
 $L((r_1))$

} Are regular Languages

44

By definition of regular expressions:

$$L(r_1 + r_2) = L(r_1) \cup L(r_2)$$

$$L(r_1 \cdot r_2) = L(r_1) L(r_2)$$

$$L(r_1^*) = (L(r_1))^*$$

$$L((r_1)) = L(r_1)$$

45

By inductive hypothesis we know:

$L(r_1)$ and $L(r_2)$ are regular languages

We also know:

Regular languages are closed under:

Union $L(r_1) \cup L(r_2)$

Concatenation $L(r_1) L(r_2)$

Star $(L(r_1))^*$

46

Therefore:

$L(r_1 + r_2) = L(r_1) \cup L(r_2)$
 $L(r_1 \cdot r_2) = L(r_1) L(r_2)$
 $L(r_1^*) = (L(r_1))^*$

} Are regular languages

47

And trivially:

$L((r_1))$ is a regular language

48


Proof - Part 2

2. For any regular language L there is a regular expression r with $L(r) = L$

Proof by construction of regular expression

49

Since L is regular take the NFA M that accepts it




Single final state

50


From M construct the equivalent **Generalized Transition Graph** in which transition labels are regular expressions

Example:




51

Another Example:




52

Reducing the states:



53

Resulting Regular Expression:



54

