

Context-Free Languages

class 8

1

$$\{a^n b^n : n \geq 0\} \quad \{ww^R\}$$

Regular Languages

$$a^* b^* \quad (a+b)^*$$

2

Context-Free Languages

$$\{a^n b^n\} \quad \{ww^R\}$$


Regular Languages

3

Context-Free Languages

Context-Free
Grammars

Pushdown
Automata



4

Context-Free Grammars

5

Example

A context-free grammar G : $S \rightarrow aSb$

$S \rightarrow \lambda$

A derivation:

$$S \Rightarrow aSb \Rightarrow aaSbb \Rightarrow aabb$$

6

A context-free grammar G : $S \rightarrow aSb$
 $S \rightarrow \lambda$

Another derivation:

$S \Rightarrow aSb \Rightarrow aaSbb \Rightarrow aaaSbbb \Rightarrow aaabbbb$

7

$S \rightarrow aSb$

$S \rightarrow \lambda$

$L(G) = \{a^n b^n : n \geq 0\}$

Describes parentheses: $(((()))$

8

Example

A context-free grammar G : $S \rightarrow aSa$
 $S \rightarrow bSb$
 $S \rightarrow \lambda$

A derivation:

$S \Rightarrow aSa \Rightarrow abSba \Rightarrow abba$

9

A context-free grammar G : $S \rightarrow aSa$
 $S \rightarrow bSb$
 $S \rightarrow \lambda$

Another derivation:

$S \Rightarrow aSa \Rightarrow abSba \Rightarrow abaSaba \Rightarrow abaaba$

10

$S \rightarrow aSa$

$S \rightarrow bSb$

$S \rightarrow \lambda$

$L(G) = \{ww^R : w \in \{a,b\}^*\}$

11

Example

A context-free grammar G : $S \rightarrow aSb$
 $S \rightarrow SS$
 $S \rightarrow \lambda$

A derivation:

$S \Rightarrow SS \Rightarrow aSbS \Rightarrow abS \Rightarrow ab$

12

A context-free grammar G : $S \rightarrow aSb$

$S \rightarrow SS$

$S \rightarrow \lambda$

A derivation:

$S \Rightarrow SS \Rightarrow aSbS \Rightarrow abS \Rightarrow abaSb \Rightarrow abab$

13

$S \rightarrow aSb$

$S \rightarrow SS$

$S \rightarrow \lambda$

$L(G) = \{w : n_a(w) = n_b(w),$
and $n_a(v) \geq n_b(v)$
in any prefix $v\}$

Describes

matched

parentheses: $() ((())) (())$

14

Definition: Context-Free Grammars

Grammar $G = (V, T, S, P)$

Variables

Terminal
symbols

Start
variable

Productions of the form:

$A \rightarrow x$

Variable

String of variables
and terminals

15

$G = (V, T, S, P)$

$L(G) = \{w : S \xRightarrow{*} w, w \in T^*\}$

16

Definition: Context-Free Languages

A language L is context-free

if and only if

there is a context-free grammar G
with $L = L(G)$

17

Derivation Order

1. $S \rightarrow AB$ 2. $A \rightarrow aaA$ 4. $B \rightarrow Bb$

3. $A \rightarrow \lambda$ 5. $B \rightarrow \lambda$

Leftmost derivation:

$S \xRightarrow{1} AB \xRightarrow{2} aaAB \xRightarrow{3} aaB \xRightarrow{4} aaBb \xRightarrow{5} aab$

Rightmost derivation:

$S \xRightarrow{1} AB \xRightarrow{4} ABb \xRightarrow{5} Ab \xRightarrow{2} aaAb \xRightarrow{3} aab$

18

$$S \rightarrow aAB$$

$$A \rightarrow bBb$$

$$B \rightarrow A \mid \lambda$$

Leftmost derivation:

$$S \Rightarrow aAB \Rightarrow abBbB \Rightarrow abAbB \Rightarrow abbBbbB \\ \Rightarrow abbbbB \Rightarrow abbbb$$

Rightmost derivation:

$$S \Rightarrow aAB \Rightarrow aA \Rightarrow abBb \Rightarrow abAb \\ \Rightarrow abbBbb \Rightarrow abbbb$$


19

Derivation Trees

20

$$S \rightarrow AB \quad A \rightarrow aaA \mid \lambda \quad B \rightarrow Bb \mid \lambda$$


$$S \Rightarrow AB$$



21

$$S \rightarrow AB \quad A \rightarrow aaA \mid \lambda \quad B \rightarrow Bb \mid \lambda$$


$$S \Rightarrow AB \Rightarrow aaAB$$



22

$$S \rightarrow AB \quad A \rightarrow aaA \mid \lambda \quad B \rightarrow Bb \mid \lambda$$


$$S \Rightarrow AB \Rightarrow aaAB \Rightarrow aaABb$$









23

$$S \rightarrow AB \quad A \rightarrow aaA \mid \lambda \quad B \rightarrow Bb \mid \lambda$$

$$S \Rightarrow AB \Rightarrow aaAB \Rightarrow aaABb \Rightarrow aaBb$$



24




Ambiguity

31

$$E \rightarrow E + E \mid E * E \mid (E) \mid a$$

$$a + a * a$$




32

$$E \rightarrow E + E \mid E * E \mid (E) \mid a$$

$$a + a * a$$

$E \Rightarrow E * E \Rightarrow E + E * E \Rightarrow a + E * E$
 $\Rightarrow a + a * E \Rightarrow a + a * a$

leftmost derivation




33

$$E \rightarrow E + E \mid E * E \mid (E) \mid a$$

$$a + a * a$$


Two derivation trees



34

The grammar $E \rightarrow E + E \mid E * E \mid (E) \mid a$ is ambiguous:

string $a + a * a$ has two derivation trees



35

The grammar $E \rightarrow E + E \mid E * E \mid (E) \mid a$ is ambiguous:

string $a + a * a$ has two leftmost derivations

$E \Rightarrow E + E \Rightarrow a + E \Rightarrow a + E * E$
 $\Rightarrow a + a * E \Rightarrow a + a * a$

$E \Rightarrow E * E \Rightarrow E + E * E \Rightarrow a + E * E$
 $\Rightarrow a + a * E \Rightarrow a + a * a$

36

Definition:

A context-free grammar G is **ambiguous**

if some string $w \in L(G)$ has:

two or more derivation trees

37

In other words:

A context-free grammar G is **ambiguous**

if some string $w \in L(G)$ has:


two or more leftmost derivations
(or rightmost)

38

Why do we care about ambiguity?


$a + a * a$

take $a = 2$



39


$2 + 2 * 2$



40


$2 + 2 * 2 = 6$

$2 + 2 * 2 = 8$



41

Correct result: $2 + 2 * 2 = 6$



42

- Ambiguity is **bad** for programming languages

- We want to remove ambiguity

43

We fix the **ambiguous** grammar:

$$E \rightarrow E + E \mid E * E \mid (E) \mid a$$

New **non-ambiguous** grammar: $E \rightarrow E + T$

$$E \rightarrow T$$

$$T \rightarrow T * F$$

$$T \rightarrow F$$

$$F \rightarrow (E)$$

$$F \rightarrow a$$

44

$$E \Rightarrow E + T \Rightarrow T + T \Rightarrow F + T \Rightarrow a + T \Rightarrow a + T * F \\ \Rightarrow a + F * F \Rightarrow a + a * F \Rightarrow a + a * a$$

$$E \rightarrow E + T$$


$$E \rightarrow T$$

$$T \rightarrow T * F$$

$$T \rightarrow F$$


$$F \rightarrow (E)$$

$$F \rightarrow a$$



45

Unique derivation tree



46

The grammar G : $E \rightarrow E + T$

$$E \rightarrow T$$

$$T \rightarrow T * F$$

$$T \rightarrow F$$

$$F \rightarrow (E)$$

$$F \rightarrow a$$

is **non-ambiguous**:

Every string $w \in L(G)$ has
a unique derivation tree


47

Another Ambiguous Grammar

$IF_STMT \rightarrow$ if EXPR then STMT
 | if EXPR then STMT else STMT

48

If expr1 then if expr2 then stmt1 else stmt2



49

Inherent Ambiguity

Some context free languages
have only ambiguous grammars


Example: $L = \{a^n b^n c^m\} \cup \{a^n b^m c^m\}$

$S \rightarrow S_1 \mid S_2$ $S_1 \rightarrow S_1 c \mid A$ $S_2 \rightarrow a S_2 \mid B$
 $A \rightarrow a A b \mid \lambda$ $B \rightarrow b B c \mid \lambda$

50

The string $a^n b^n c^n$

has two derivation trees



51

Compilers

52

Program

```

v = 5;
if (v > 5)
  x = 12 + v;
while (x != 3) {
  x = x - 3;
  v = 10;
}
.....
  
```

Compiler


Machine Code

```

Add v,v,0
cmp v,5
jmplt ELSE
THEN:
  add x, 12,v
ELSE:
  WHILE:
    cmp x,3
  ...
  
```

53

Compiler



54

A **parser** knows the grammar of the programming language

55


Parser

PROGRAM \rightarrow STMT_LIST
 STMT_LIST \rightarrow STMT; STMT_LIST | STMT;
 STMT \rightarrow EXPR | IF_STMT | WHILE_STMT
 | { STMT_LIST }


EXPR \rightarrow EXPR + EXPR | EXPR - EXPR | ID
 IF_STMT \rightarrow if (EXPR) then STMT
 | if (EXPR) then STMT else STMT
 WHILE_STMT \rightarrow while (EXPR) do STMT

56


The parser finds the derivation of a particular input



57









58




59

Parsing

60





Time complexity of exhaustive search

Suppose there are no productions of the form

$$A \rightarrow \lambda$$

$$A \rightarrow B$$

Number of phases for string w : $2^{|w|}$

68

For grammar with k rules

Time for phase 1: k

k possible derivations

69

Time for phase 2: k^2

k^2 possible derivations

70

Time for phase $2^{|w|}$: $k^{2^{|w|}}$

$k^{2^{|w|}}$ possible derivations

71

Total time needed for string w :


$$k + k^2 + \dots + k^{2^{|w|}}$$

phase 1 phase 2 phase $2^{|w|}$

Extremely bad!!!

72

There exist faster algorithms
for specialized grammars



73

S-grammar example:

$$S \rightarrow aS$$

$$S \rightarrow bSS$$

$$S \rightarrow c$$

Each string has a unique derivation

$$S \Rightarrow aS \Rightarrow abSS \Rightarrow abcS \Rightarrow abcc$$

74

For S-grammars:

In the exhaustive search parsing
there is only one choice in each phase

Time for a phase: 1

Total time for parsing string w : $|w|$

75

For general context-free grammars:

There exists a parsing algorithm
that parses a string $|w|$
in time $|w|^3$

(we will show it in the next class)

76