

Turing's Thesis

class 16

1

Turing's thesis:

Any computation carried out
by mechanical means
can be performed by a Turing Machine

(1930)

2

Computer Science Law:

A computation is mechanical
if and only if
it can be performed by a Turing Machine

There is no known model of computation
more powerful than Turing Machines

3

Definition of Algorithm:

An algorithm for function $f(w)$
is a
Turing Machine which computes $f(w)$

4

Algorithms are Turing Machines

When we say:

There exists an algorithm

We mean:

There exists a Turing Machine
that executes the algorithm


5

Variations of the Turing Machine

6


The Standard Model

Infinite Tape



Read-Write Head (Left or Right)

Control Unit



Deterministic

7

Variations of the Standard Model

Turing machines with:

- Stay-Option
- Semi-Infinite Tape
- Off-Line
- Multitape
- Multidimensional
- Nondeterministic

8

The variations form different
Turing Machine **Classes**

We want to prove:

Each **Class** has the same
power with the **Standard Model**

9

Same Power of two classes means:

Both classes of Turing machines accept
the same languages

10

Same Power of two classes means:

For any machine M_1 of first class
there is a machine M_2 of second class

such that: $L(M_1) = L(M_2)$


And vice-versa

11


Simulation: a technique to prove same power

Simulate the machine of one class
with a machine of the other class

First Class
Original Machine



Second Class
Simulation Machine



12

Configurations in the Original Machine correspond to configurations in the Simulation Machine

Original Machine: $d_0 \succ d_1 \succ \dots \succ d_n$

Simulation Machine: $d'_0 \succ d'_1 \succ \dots \succ d'_n$

Vertical arrows with asterisks indicate correspondence between configurations.

13

Final Configuration

Original Machine:

d_f



Simulation Machine:

d'_f

The Simulation Machine and the Original Machine accept the same language

14

Turing Machines with Stay-Option

The head can stay in the same position

Diagram of a tape with symbols $\diamond, \diamond, a, b, a, b, b, c, a, c, a, \diamond, \diamond, \diamond$. The head is positioned over the first a .

Left, Right, Stay

L,R,S: moves

15

Example:

Time 1

Diagram of a tape with symbols $\diamond, \diamond, a, a, b, a, b, b, c, a, c, a, \diamond, \diamond, \diamond$. The head q_1 is positioned over the first a .

q_1

Time 2

Diagram of a tape with symbols $\diamond, \diamond, b, a, b, a, b, b, c, a, c, a, \diamond, \diamond, \diamond$. The head q_2 is positioned over the first b .

q_2

State transition: $q_1 \xrightarrow{a \rightarrow b, S} q_2$

16

Theorem: Stay-Option Machines have the same power with Standard Turing machines

17

Proof:

Part 1: Stay-Option Machines are at least as powerful as Standard machines

Proof: a Standard machine is also a Stay-Option machine (that never uses the S move)

18


Proof:

Part 2: Standard Machines
are at least as powerful as
Stay-Option machines


Proof: a standard machine can simulate
a Stay-Option machine

19

Stay-Option Machine




Simulation in Standard Machine




Similar for Right moves

20

Stay-Option Machine



Simulation in Standard Machine




For every symbol x


21

Example

Stay-Option Machine:




Simulation in Standard Machine:






22

Standard Machine--Multiple Track Tape




23



24

Semi-Infinite Tape




25

Standard Turing machines simulate
Semi-infinite tape machines:


Trivial

26


Semi-infinite tape machines simulate
Standard Turing machines:



27




Semi-infinite tape machine with two tracks




28

Standard machine




Semi-infinite tape machine





29

Standard machine







Semi-infinite tape machine




For all symbols x

30



Theorem: Semi-infinite tape machines have the same power with Standard Turing machines

35




Off-line machines simulate
Standard Turing Machines:

Off-line machine:


1. Copy input file to tape
2. Continue computation as in Standard Turing machine

37

Standard machine




Off-line machine




1. Copy input file to tape

38

Standard machine



Off-line machine



2. Do computations as in Turing machine


39

Standard Turing machines simulate
Off-line machines:


Use a Standard machine with four track tape
to keep track of
the Off-line input file and tape contents

40

Off-line Machine




Four track tape -- Standard Machine



41

Reference point



Repeat for each state transition:


- Return to reference point
- Find current input file symbol
- Find current tape symbol
- Make transition

42


Theorem: Off-line machines
have the same power with
Standard machines

43

Multitape Turing Machines



44



45

Multitape machines simulate
Standard Machines:

Use just one tape


46

Standard machines simulate
Multitape machines:

Standard machine:

- Use a multi-track tape
- A tape of the Multiple tape machine corresponds to a pair of tracks

47



48

Reference point

#	a	b	c			
#	0	1	0			
#	e	f	g	h		
#	0	0	1	0		

Tape 1
head position

Tape 2
head position

Repeat for each state transition:

- Return to reference point
- Find current symbol in Tape 1
- Find current symbol in Tape 2
- Make transition

49

Theorem: Multi-tape machines have the same power with Standard Turing Machines

50

Same power doesn't imply same speed:

Language $L = \{a^n b^n\}$

Acceptance Time

Standard machine n^2

Two-tape machine n

51

$L = \{a^n b^n\}$

Standard machine:
Go back and forth n^2 times

Two-tape machine:

- Copy b^n to tape 2 (n steps)
- Leave a^n on tape 1 (n steps)
- Compare tape 1 and tape 2 (n steps)

52

MultiDimensional Turing Machines

Two-dimensional tape

MOVES: L,R,U,D
U: up D: down

HEAD
Position: +2, -1

53

Multidimensional machines simulate Standard machines:

Use one dimension

54


Standard machines simulate
Multidimensional machines:

Standard machine:

- Use a two track tape
- Store symbols in track 1
- Store coordinates in track 2

55

Two-dimensional machine



Standard Machine

a				b				c		symbols coordinates
1	#	1	#	2	#	-	1	#	-	

q_1

56

Standard machine:

Repeat for each transition


- Update current symbol
- Compute coordinates of next position
- Go to new position

57

Theorem: MultiDimensional Machines
have the same power
with Standard Turing Machines


58

NonDeterministic Turing Machines




Non Deterministic Choice

59



60

Input string w is accepted if this is a possible computation



61

NonDeterministic Machines simulate Standard (deterministic) Machines:

Every deterministic machine is also a nondeterministic machine

62


Deterministic machines simulate NonDeterministic machines:

Deterministic machine:

Keeps track of all possible computations


63

Non-Deterministic Choices



64

Non-Deterministic Choices





65

Simulation

Deterministic machine:

- Keeps track of all possible computations
- Stores computations in a two-dimensional tape

66



Repeat

- Execute a step in each computation:
- If there are two or more choices in current computation:
 1. Replicate configuration
 2. Change the state in the replica

69

Theorem: NonDeterministic Machines have the same power with Deterministic machines

70

Remark:

The simulation in the Deterministic machine takes time exponential time compared to the NonDeterministic machine

71