

Shri Narsingh Micro Alloys Pvt. Ltd.

Complete Website Scrape & Technical Specification Data Document

Global Website Metadata & Source Details

Target URL	https://www.shrinarsinghmicro.com/
Company Legal Name	SHRI NARSINGH MICRO ALLOYS PRIVATE LIMITED
Corporate Identity Number (CIN)	U28999GJ2021PTC121521
Date of Incorporation	24 March 2021
Key Executives	Anil Gupta (Director)

1. Home Page (shrinarsinghmicro.com)

Page Metadata:

- **Title:** Shri Narsingh Micro Alloys Pvt. Ltd.
- **Meta Description:** Leading manufacturer, supplier, and exporter of high-quality ferrous and non-ferrous trading materials, ferro alloys, and carbon raisers based in Ahmedabad, India.

Company Overview

Shri Narsingh Micro Alloys was incorporated on 24 March 2021 as a private limited company under the leadership of Anil Gupta, the respectable director of the company who believes quality is an integral than quantity. The state of the art architecture of the company is located at Hathijan Circle, Ahmedabad loaded with all the required facilities to excel in the market. Moreover, the team of professional constantly seeks business strategies along with opportunities to expand company business, has enabled Shri Narsingh Micro Alloys Pvt. Ltd. to flourish in the domestic as well as international market.

Core Pillars & Infrastructure

- **Quality:** We are committed to provide a broad array of ferrous metal that strongly in the compliance with the regulatory standards and that we ensure by performing stringent quality testing procedures.
- **Our Team:** Our team of professionals possesses excellent knowledge associated with ferrous metals and business procedure that has helped us in marking of our products in more organized and proficient manner.
- **Warehouse:** In addition to quality, we are equally focused towards service and to ensure prompt service, we have developed spacious warehouse that allows us to store enormous quantities of the ferrous metals in safe and damage free manner.

Strategic Statements

Mission: To supply products of the unrivaled quality and be a partner in progress of respected clientele.

Vision: To become a chief non ferrous trading company that provides customer satisfaction through value for money.

Value Proposition & Features

- World-Class Quality
- Timely Delivery
- Strong Logistics Support
- Affordable Prices
- Wide Distribution Network
- Reliable & Trusted Services

2. Product Catalog & Complete Technical Specifications

Catalog Pages Included: [our-products.html](#), [perlite-ore.html](#), [ferro-silicon.html](#), [silico-manganese.html](#), [ferro-manganese.html](#), [ferro-chrome.html](#), [electrolytic-manganese-metal.html](#), [ferro-titanium.html](#), [carbon-raiser-93.html](#), [graphite-petroleum-coke.html](#), [mc-silico-manganese.html](#), [lc-ferro-manganese.html](#), [mc-ferro-manganese.html](#), [ferro-molybdenum.html](#).

2.1 Perlite Ore

Main Areas of Use & Applications:

- Construction & Building Materials
- Filter Aid & Chemical Industry
- Foundry & Metallurgical Insulations
- Cryogenics & Cold Storage Insulation
- Gypsum Plasters & Boards
- Horticulture & Agriculture
- Plastic & Rubber Fillers

2.2 Ferro Silicon

Used as an essential deoxidizer and alloying element in steel manufacturing.

Grade / Chemical Parameter	Silicon (Si)	Aluminum (Al)	Carbon (C)	Sulfur (S)	Phosphorus (P)	Sizing Specifications
Ferro Silicon 75-80%	75 – 80%	1.0% & 1.5% Max	0.1% Max	0.04% Max	0.04% Max	10–50mm (Min 90%) or 10–100mm (Min 90%)
Ferro Silicon 70-75%	70 – 75%	1.0% & 1.5% Max	0.1% Max	0.04% Max	0.04% Max	10–50mm (Min 90%) or 10–100mm (Min 90%)

2.3 Silico Manganese & MC Silico Manganese

Manganese is essential to iron and steel production by virtue of its sulfur-fixing, deoxidizing, and alloying properties. Steel making, including its iron making component, has accounted for most manganese demand, presently in the range of 85% to 90% of the total demand. Among a variety of other uses, manganese is a key component of low-cost stainless steel formulations and certain widely used aluminum alloys.

Standard High Carbon Silico Manganese Specifications:

Grade	Manganese (Mn)	Silicon (Si)	Carbon (C)	Phosphorus (P)	Sulfur (S)
HC Silico Manganese 60/14	60% Min	14% Min	2.5% Max	0.35% Max	0.05% Max
HC Silico Manganese 65/15	65% Min	15% Min	2.25% Max	0.35% Max	0.04% Max

Medium Carbon (MC) Silico Manganese Specifications:

- **Form:** Solid
- **Packaging Type:** Gunny Bags
- **Usage:** Industrial / Steel Production
- **Manganese Grade:** 60%
- **Silicon Grade:** 14%
- **Size:** 1 To 5 MM

2.4 Ferro Manganese (HC, MC, LC Variants)

Variant / Grade	Manganese (Mn)	Silicon (Si)	Carbon (C)	Phosphorus (P)	Sulfur (S)	Size Available
High Carbon (HC)	65 – 70 – 75% Min	1.50% Max	6.0 – 8.0% Max	0.30% Max	0.05% Max	25 – 125 mm (or customized)
Medium Carbon (MC)	75 – 80%	1.0 – 1.5% Max	1.5 – 2.0% Max	0.40% Max	0.05% Max	As required by end user
Low Carbon (LC)	75 – 80%	1.0 – 1.5% Max	0.5% Max	0.40% Max	0.05% Max	As required by end user

Alternative Dedicated Product Listing for Medium Carbon & Low Carbon Ferro Manganese:

- **Dedicated MC Ferro Manganese Standalone Page:** Mn: 70% min, C: 1.5% max, Si: 2.5% max, P: 0.35% max. *Minimum Order Quantity:* 100 Kilogram. *Size:* 10 to 50 mm. Widely utilized in metallurgy, steel, chemical & thermit process industries.
- **Dedicated LC Ferro Manganese Standalone Page:** Mn: 70% Min / 80% Min, Si: 1.5% Max / 2.0% Max, C: 0.05% Max / 0.1% Max, P: 0.20% Max / 0.35% Max, S: 0.04% Max / 0.30% Max. *Size:* 10 to 50 mm.

2.5 Ferro Chrome

Grade Type	Chromium (Cr)	Carbon (C)	Silicon (Si)	Sulfur (S)	Phosphorus (P)	Copper (Cu)	Sizing
High Carbon Ferro Chrome	60% Min	8% Max	3.0% Max	0.04% Max	0.04% Max	0.5% Max	10 – 150 mm (Min 90%)
Low Carbon Ferro Chrome	65% Min	0.03%, 0.05%, 0.1% Max	1.0% Max	0.03% Max	0.04% Max	-	10 – 50 mm (Min 90%)

2.6 Electrolytic Manganese Metal (Flakes)

High purity material used primarily in specialty alloy formulations and steel manufacturing.

Element	Manganese (Mn)	Sulfur (S)	Carbon (C)	Phosphorus (P)	Si + Fe + Se Total	Form / Physical State
Specification Guaranteed	99.7% Min	0.5% Max	0.04% Max	0.005% Max	0.205% Max	In Flakes, or as required by end user

2.7 Ferro Titanium

Grade / Component	Titanium (Ti)	Aluminum (Al)	Silicon (Si)	Manganese (Mn)	Carbon (C)	Phosphorus (P)	Sulfur (S)
Ferro Titanium – 30%	28 – 37%	8.0% Max	4.0% Max	-	0.12% Max	0.04% Max	0.03% Max
Ferro Titanium – 70%	65 – 75%	0.5% Max	0.10% Max	0.20% Max	0.20% Max	0.04% Max	0.03% Max

Sizing for both grades: 10 – 50 mm, 50 – 70 mm, 10 – 100 mm, or as required by the end user.

2.8 Carbon Raiser 93%

We have in our repertoire a qualitative range of Carburetors (Carbon Raiser). Our personnel procure these Carburetors (Carbon Raiser) from reputed manufacturers in China and check them for its compliance with the required international quality standards.

- **Fixed Carbon Content:** 93% Specification Minimum
- **Procurement Sourcing:** Top tier global manufacturers in China

2.9 Graphite Petroleum Coke

Taking quality as our principal concern, we are betrothed in presenting an excellent quality of Graphite Petroleum Coke to the prestigious customers.

- **Usage / Application:** Casting / Foundry Foundry processes
- **Grade Standard:** Graphite Petroleum Coke standard industrial grade
- **Form:** Granules
- **Packaging Type:** Bags
- **Sizing Available:** 0.2 – 1 mm, 1 – 5 mm
- **Carbon Content:** 98.5% Guaranteed
- **Sulfur Content:** 0.05% Max
- **Minimum Order Quantity (MOQ):** 500 Kilograms

2.10 Ferro Molybdenum

We bring forth our esteemed clients a qualitative range of Ferro Molybdenum. These are a potent hardening agent and a constituent of heat treated alloy steels. The Ferro Molybdenum that we offer helps in improving corrosion resistant of stainless steel in iron and is highly effective in strengthening iron and steel.

Element / Chemical Parameter	Molybdenum (Mo)	Carbon (C)	Sulfur (S)	Phosphorus (P)	Silicon (Si)
Guaranteed Percentage	60% Min	0.15% Max	0.1% Max	0.05% Max	2.0% Max

3. Interactive Forms & Lead Interfaces

3.1 Quote Request & Inquiry Portal (enquiry.html)

The website hosts a dedicated commercial inquiry architecture supporting programmatic input formatting for domestic and export client onboarding.

Interactive Form Submission Parameters:

- Country Selection Field (Global listing supporting all countries from Afghanistan, Albania up to United States, Canada, Europe, Middle East and Africa markets)
- Contact Identity Matrix (First Name, Last Name, Corporate Email Address, Direct Phone Line / Mobile Number)
- Requirement Details (Text Area for structural specifications, target alloy volume, sizing choices, and logistical delivery terms)

4. Complete Corporate Contact & Location Data

Page Metadata:

- **Title:** Contact Us - Shri Narsingh Micro Alloys Pvt. Ltd.
- **Meta Description:** Connect with the global office of Shri Narsingh Micro Alloys Pvt. Ltd. at Vatva GIDC Ahmedabad, or access our North American supply line coordinates.

Domestic Headquarters (India)

Physical Factory Address	Shed No. 84, Akshar Industrial Park, Near Hathijan Circle, Vinzol Patiya Phase-4, GIDC, Vatva, Ahmedabad - 382445, Gujarat, India.
Corporate Registered Address	SHED-84, 583, 32, 91, Axar Ind. Estate, Behind Amba Estate, Vinzol Patiya, Vatva, GIDC, Ahmedabad, Gujarat, India, 382445.
Direct Phone Line	+91 85116 01010
Landline / Office Desk	+91 79 2999 9878
Primary Corporate Email	info@shrinarsinghmicro.com
Official Domain URL	www.shrinarsinghmicro.com

International Distribution Logistics Point (North America)

Logistics Hub Location	Regina, Saskatchewan (SK), Canada
International Mobile Line	+1 (306) 807-4929
Operating Timezone	Central Standard Time (CST), North America