



Engine	TS6.125
Engine Make	Simpson - Four stroke, Diesel, Turbocharged, Direct injection, Water cooled
Engine Power (hp)	124
Rated Speed (rpm)	2200
No. of Cylinder	6
Displacement (cm ³)	6700
Torque (Nm @ rpm)	555 Nm @ 1250 rpm
Fuel tank capacity (L)	235
Emission	US EPA Tier 3
Transmission	
Forward/Reverse Gear	8x8 Synchronized Shuttle
Steering Type	Power Steering
PTO (hp/rpm)	109 / 540 & 1000
Engine Speed @ 540 rpm of PTO	1900 rpm
Hydraulics	
Pump Type/Flow	Gear Pump, 49.2 L/min
Lift Capacity @ 610mm behind hitch points, kg	3323
3-pt Hitch	Cat. III
Controls	Position control, drop rate control, mix control, sensitivity knob, tap off and Lift-O-Matic™
Max. number of remote valves	2
Electrical System	
Alternator (A), Battery(A)	120A, 108Ah
Tires	
Front Tires	14.9-28
Rear Tires	18.4-38
Min. Turning Distance	
-w/ Brakes (mm)	6100
-w/o Brakes (mm)	7125
Dimensions and Weight	
Weight (kg)	4400
Max. Length (mm)	4770
Max. Width (mm)	2120
Max. Height (mm)	2985
Wheel Base (mm)	2650
Min. Ground Clearance (mm)	418



FILHOLLAND

Providing Solutions. Delivering Excellence.



WORLD CLASS EQUIPMENT

To be successful in your business you need your machines to be powerful, easy to use and capable of performing at their best in the toughest conditions.

Luzon : 0917-6349473
Visayas : 0917-6331734
Mindanao : 0917-6331720



CNH INDUSTRIAL GENUINE PARTS

Only genuine parts are made for your machine and designed for peak performance. We engineer, manufacture, and choose parts based on the strictest design and testing standards.

Luzon : 0917-6331795
Visayas : 0917-8061789
Mindanao : 0917-3296244



AFTER SALES SUPPORT

We strive to ensure that the latest ideas from the industry continue to be of relevance even after your machine has been delivered.

We are committed to minimize costs and the length of your idle time.

Luzon : 0917-3106399
Visayas : 0917-8327159
Mindanao : 0917-3128049



 **NEW HOLLAND**
 AGRICULTURE

YOUR SUCCESS OUR SPECIALTY





Engine	TT35
Engine Make	Simpson - Four stroke, Diesel, Naturally aspirated, Direct injection, Water cooled
Engine Power (hp)	35
Rated Speed (rpm)	2000
No. of Cylinder	3
Displacement (cm ³)	2365
Torque (Nm @ rpm)	180 Nm @ 1300 rpm
Fuel tank capacity (L)	62
Emission	US EPA Tier 3
Transmission	
Forward/Reverse Gear	8x2/8x8 Synchronized Shuttle
Steering Type	Power Steering
PTO (hp/rpm)	28.4 / 540 with Ground speed
Engine Speed @ 540 rpm of PTO	1747 rpm
Hydraulics	
Pump Type/Flow	Gear Pump, 19L/min
Lift Capacity @ 610mm behind hitch points, kg	1,500
3-pt Hitch	Cat. II
Controls	Position control, drop rate control, mix control, sensitivity knob, tap off and Lift-O-Matic™
Max. number of remote valves	2
Electrical System	
Alternator (A), Battery(A)	35A, 75Ah
Tires	
Front Tires	8.3-24
Rear Tires	13.6-28
Min. Turning Distance	
-w/ Brakes (mm)	3900
-w/o Brakes (mm)	4600
Dimensions and Weight	
Weight (kg)	1770
Max. Length (mm)	3410
Max. Width (mm)	1690
Max. Height (mm)	2300
Wheel Base (mm)	1910
Min. Ground Clearance (mm)	370



Engine	E9010
Engine Make	Iveco - Four stroke, Diesel, Turbocharged, Direct injection, Water cooled
Engine Power (hp)	90
Rated Speed (rpm)	2300
No. of Cylinder	4
Displacement (cm ³)	3908
Torque (Nm @ rpm)	340 Nm @ 1250 rpm
Fuel tank capacity (L)	90
Emission	US EPA Tier 3
Transmission	
Forward/Reverse Gear	12 x 12 Power Shuttle
Steering Type	Power Steering
PTO (hp/rpm)	78.3 / 540 & 540E
Engine Speed @ 540 rpm of PTO	2132 rpm
Hydraulics	
Pump Type/Flow	Gear Pump, 45L/min
Lift Capacity @ 610mm behind hitch points, kg	2200
3-pt Hitch	Cat. II
Controls	Position control, drop rate control, mix control, sensitivity knob, tap off and Lift-O-Matic™
Max. number of remote valves	2
Electrical System	
Alternator (A), Battery(A)	35A, 100Ah
Tires	
Front Tires	12.4 - 24-24
Rear Tires	18.4 - 30
Min. Turning Distance	
-w/ Brakes (mm)	3940
-w/o Brakes (mm)	5650
Dimensions and Weight	
Weight (kg)	3250
Max. Length (mm)	4131
Max. Width (mm)	2041
Max. Height (mm)	2482
Wheel Base (mm)	2260
Min. Ground Clearance (mm)	415



Engine	TS6.120
Engine Make	Simpson - Four stroke, Diesel, Turbocharged, Direct injection, Water cooled
Engine Power (hp)	118
Rated Speed (rpm)	2200
No. of Cylinder	4
Displacement (cm ³)	4500
Torque (Nm @ rpm)	515 Nm @ 1250 rpm
Fuel tank capacity (L)	150
Emission	US EPA Tier 3
Transmission	
Forward/Reverse Gear	8x8 Synchronized Shuttle
Steering Type	Power Steering
PTO (hp/rpm)	101 / 540 & 1000
Engine Speed @ 540 rpm of PTO	1900 rpm
Hydraulics	
Pump Type/Flow	Gear Pump, 49.2 L/min
Lift Capacity @ 610mm behind hitch points, kg	3,000
3-pt Hitch	Cat. II
Controls	Position control, drop rate control, mix control, sensitivity knob, tap off and Lift-O-Matic™
Max. number of remote valves	2
Electrical System	
Alternator (A), Battery(A)	65A, 90Ah
Tires	
Front Tires	14.9 - 24
Rear Tires	18.4-34
Min. Turning Distance	
-w/ Brakes (mm)	4500
-w/o Brakes (mm)	5150
Dimensions and Weight	
Weight (kg)	4000
Max. Length (mm)	4480
Max. Width (mm)	2120
Max. Height (mm)	2970
Wheel Base (mm)	2520
Min. Ground Clearance (mm)	418