

PlaySpace poster service

A concise dashboard tutorial for deploying the supplied Worker, connecting private R2 storage, and routing visitor downloads through the IdeaFest hostname.

Required final result

The public endpoint is **<https://poster.ideafest.id>**. QR codes, poster pages, image downloads, and the kiosk gallery will use this hostname.

Ownership boundary

- IdeaFest IT owns the Cloudflare Worker, R2 bucket, Custom Domain, access, usage, and logs.
- The PlaySpace application and camera session remain on the developer's local Mac and iPad.
- The R2 bucket stays private. Visitors only access temporary poster URLs through the Worker.
- No Cloudflare account invitation or storage credential is required for the developer.

Use these exact values

Worker	playspace-poster-api
R2 bucket	playspace-posters
Binding variable	POSTERS (must match exactly)
Lifecycle	Delete uploaded objects after 1 day; no prefix
Custom Domain	poster.ideafest.id
Deployment file	PlaySpace_Worker.js

File supplied separately

Use **PlaySpace_Worker.js** as the Worker source. The PDF intentionally does not duplicate the code.

Implementation flow: private R2 bucket -> Worker source -> POSTERS binding -> Worker Custom Domain -> health check -> kiosk connection.

Storage and deployment

1

Enable R2 and create the private bucket

Open **Cloudflare Dashboard** -> **Storage & databases** -> **R2** -> **Overview**. If R2 is not active, complete the R2 subscription screen. Select **Create bucket**, enter **playspace-posters**, keep the standard storage class, and create it. Do not enable a public bucket URL or an R2 custom domain.

2

Add one-day cleanup

Open **playspace-posters** -> **Settings** -> **Object lifecycle rules** -> **Add rule**. Name it **Delete After One Day**. Leave the prefix empty so it applies to all poster objects. Enable **Delete uploaded objects after**, enter **1**, select **Days**, then save the rule.

3

Create the JavaScript Worker

Open **Workers & Pages** -> **Create** and start with **Hello World**. Name the Worker **playspace-poster-api** and deploy the starter once. Open **Edit code**, replace the starter source with the complete contents of the supplied **PlaySpace_Worker.js**, then select **Deploy**.

Expected at this stage

The Worker has a temporary **workers.dev** address. R2 is still not connected until the next page's binding step.

Quick dashboard checks

- R2 bucket name is playspace-posters.
- Public access for the bucket is disabled.
- Object lifecycle rule is enabled and set to 1 day.
- Worker source deploy completed without an error.

Cloudflare: [Create an R2 bucket and use it from Workers](#)
Cloudflare: [R2 object lifecycle rules](#)

Connect R2 and IdeaFest DNS

4

Bind the bucket to the Worker

Open **playspace-poster-api** -> **Settings** -> **Bindings** (some dashboard layouts show **Bindings** as a top tab). Select **Add binding** -> **R2 bucket**. Set the variable name to **POSTERS**, select **playspace-posters**, save, and deploy the binding change.

5

Verify storage on workers.dev

Open the Worker's temporary URL followed by **/health**. The response must be:
`{"ok":true,"storage":true}`
A 503 response or `storage:false` means the POSTERS binding is missing or points to the wrong bucket.

6

Attach poster.ideafest.id as a Custom Domain

Confirm **ideafest.id** is an active zone in the same Cloudflare account. Open **Worker** -> **Settings** -> **Domains & Routes** -> **Add** -> **Custom Domain**. Enter **poster.ideafest.id** and select **Add Custom Domain**. Cloudflare creates the DNS record and HTTPS certificate automatically. Wait until the hostname is active.

Routing note

Use a **Worker Custom Domain**, not a Route, because this Worker is the origin for every path on **poster.ideafest.id**. Do not manually point a CNAME at **workers.dev** first. If a DNS record already exists for **poster**, resolve that conflict before adding the Custom Domain.

Final verification and handoff

- Open <https://poster.ideafest.id/health> and confirm `{"ok":true,"storage":true}`.
- Send the developer the confirmed origin: <https://poster.ideafest.id>.
- Developer connects and rebuilds the local kiosk, then creates one test poster.
- Scan its QR using a separate phone and normal mobile data.
- Confirm the download page and PNG remain under **poster.ideafest.id**.

Completion message

Custom Domain: <https://poster.ideafest.id>
POSTERS binding: Active / Not active
Health check: Passed / Failed
Technical contact: _____

Cloudflare: R2 binding | Workers Custom Domains