

Con guration Switch SWGR2-2

BTS SIO - Option SISR

Étudiant : DENIEL Louis

Date : Mars 2026

Équipement : Switch Cisco - SWGR2-2

Con guration Complète

```
hostname SWGR2-2
!
!
no aaa new-model ip
subnet-zero
!
!
!
!
no le verify auto spanning-tree mode
pvst spanning-tree extend system-id
!
vlan internal allocation policy ascending
!
interface FastEthernet0/1 switchport
access vlan 10 switchport mode access
!
interface FastEthernet0/2 switchport
access vlan 10
!
interface FastEthernet0/3 switchport
access vlan 10
!
interface FastEthernet0/4 switchport
access vlan 20 !
interface FastEthernet0/5 switchport
access vlan 20
!
interface FastEthernet0/6 switchport
access vlan 20
```

```
!  
interface FastEthernet0/7 switchport  
access vlan 30  
!  
interface FastEthernet0/8 switchport  
access vlan 30  
!  
interface FastEthernet0/9 switchport  
access vlan 30  
!  
interface FastEthernet0/10 switchport  
access vlan 40  
!  
interface FastEthernet0/11 switchport  
access vlan 40  
!  
interface FastEthernet0/12 switchport  
access vlan 40  
!  
interface FastEthernet0/13  
!  
interface FastEthernet0/14  
!  
interface FastEthernet0/15  
!  
interface FastEthernet0/16  
!  
interface FastEthernet0/17  
!  
interface FastEthernet0/18  
!  
interface FastEthernet0/19  
!  
interface FastEthernet0/20  
!  
interface FastEthernet0/21  
!  
interface FastEthernet0/22  
!
```

```
interface FastEthernet0/23 switchport trunk
encapsulation dot1q switchport mode trunk
!
interface FastEthernet0/24 switchport trunk
encapsulation dot1q switchport mode trunk
!
interface GigabitEthernet0/1
!
interface GigabitEthernet0/2
!
interface Vlan1 no ip
address
shutdown
!
interface Vlan10 no ip
address
!
ip classless ip
http server
!
!
control-plane
!
!
line con 0 line
vty 0 4 no
login line vty 5
15 no login
!
!
end
```

Analyse de Configuration

Informations Générales

Paramètre	Valeur
Hostname	SWGR2-2
Spanning-Tree	PVST

HTTP Server	Activé
AAA	Désactivé

Table 1: Paramètres généraux du switch

VLANs Configurés

VLAN	Ports Access	Type
VLAN 10	Fa0/1 - Fa0/3	Access
VLAN 20	Fa0/4 - Fa0/6	Access
VLAN 30	Fa0/7 - Fa0/9	Access
VLAN 40	Fa0/10 - Fa0/12	Access

Table 2: Distribution des VLANs

Ports Trunk

Port	Configuration
FastEthernet0/23	Trunk 802.1Q
FastEthernet0/24	Trunk 802.1Q

Table 3: Ports trunk configurés

Interfaces Non Configurées

Ports FastEthernet0/13 à FastEthernet0/22 : Non attribués à des VLANs

Ports GigabitEthernet0/1 et 0/2 : Non configurés

Schéma de Répartition

VLAN 10 : 3 ports (Fa0/1-3)

VLAN 20 : 3 ports (Fa0/4-6)

VLAN 30 : 3 ports (Fa0/7-9)

VLAN 40 : 3 ports (Fa0/10-12)

Trunk : 2 ports (Fa0/23-24)

Disponibles : 12 ports (Fa0/13-22, Gi0/1-2)