



Message Implementation Guideline

Order status

C1

Issue date: 2019-07-30
Author: wdk/BRV/GEFEG

Please check with your supplier whether this specific version is supported by its organization.

Occurrence Element / Attribute

	order_status
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	Variant
0 .. 1	OrderDateFrom
0 .. 1	OrderDateTo
0 .. 1	OrderStatusIndicator
1 .. 1	ErrorHead
1 .. 1	xsd:sequence
1 .. 1	ErrorCode
1 .. 1	BuyerParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
0 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	OrderingParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 1	Consignee
1 .. 1	xsd:sequence
0 .. 1	PartyID
0 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
1 .. 2	Street
1 .. 1	City
0 .. 1	District
1 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	Geolocation
1 .. 1	xsd:sequence
1 .. 1	Latitude
1 .. 1	Longitude
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. unbounded	ReferencedOrder
1 .. 1	xsd:sequence
1 .. 1	Error
1 .. 1	xsd:sequence
1 .. 1	ErrorCode

Occurrence Element / Attribute

0 .. 1	└─ ErrorText
0 .. 1	└─ OrderDate
0 .. 1	└─ SupplierOrderNumber
1 .. 1	└─ xsd:sequence
1 .. 1	└─ DocumentID
0 .. 1	└─ OrderingMethod
0 .. 1	└─ OrderReference
1 .. 1	└─ xsd:sequence
1 .. 1	└─ DocumentID
0 .. 1	└─ PickUp
0 .. 1	└─ DeliveryOption
0 .. 1	└─ SellerParty
1 .. 1	└─ xsd:sequence
1 .. 1	└─ PartyID
1 .. 1	└─ AgencyCode
0 .. 1	└─ SupplierParty
1 .. 1	└─ xsd:sequence
1 .. 1	└─ PartyID
1 .. 1	└─ AgencyCode
0 .. 1	└─ Contract
1 .. 1	└─ xsd:sequence
1 .. 1	└─ DocumentID
0 .. unbounded	└─ OrderLine
1 .. 1	└─ xsd:sequence
1 .. 1	└─ LineID
0 .. 1	└─ CustomerLineItemNumber
0 .. 1	└─ AdditionalCustomerReferenceNumber
1 .. 1	└─ xsd:sequence
1 .. 1	└─ DocumentID
1 .. 1	└─ OrderedArticle
1 .. 1	└─ xsd:sequence
1 .. 1	└─ ArticleIdentification
1 .. 1	└─ xsd:sequence
0 .. 1	└─ BuyersArticleID
0 .. 1	└─ ManufacturersArticleID
0 .. 1	└─ EANUCCArticleID
0 .. 1	└─ ArticleDescription
1 .. 1	└─ xsd:sequence
1 .. 1	└─ ArticleDescriptionText
0 .. 1	└─ RequestedDeliveryDate
0 .. 1	└─ RequestedDeliveryTime
0 .. 1	└─ ArticleComment
0 .. unbounded	└─ ScheduleDetails
1 .. 1	└─ xsd:sequence
0 .. 1	└─ DeliveryDate
0 .. 1	└─ DeliveryTime
0 .. 1	└─ ConfirmedQuantity
1 .. 1	└─ xsd:sequence
1 .. 1	└─ QuantityValue
0 .. 1	└─ CancelledQuantity
1 .. 1	└─ xsd:sequence
1 .. 1	└─ QuantityValue
0 .. 1	└─ OpenQuantity
1 .. 1	└─ xsd:sequence
1 .. 1	└─ QuantityValue
0 .. unbounded	└─ ScheduledArticleDespatchDetails
1 .. 1	└─ xsd:sequence
1 .. 1	└─ DespatchDate
1 .. 1	└─ DespatchAdviceReference
1 .. 1	└─ xsd:sequence
1 .. 1	└─ DocumentID
0 .. 1	└─ LineID
1 .. 1	└─ DespatchedQuantity
1 .. 1	└─ xsd:sequence
1 .. 1	└─ QuantityValue
0 .. 1	└─ OrderedQuantity
1 .. 1	└─ xsd:sequence

Occurrence	Element / Attribute
1 .. 1	 QuantityValue

Element/Attribute	Annotation	User Comments
order_status		Identification numbers and text: The allowed characters are [a-z, A-Z,0-9 and the underscore '_']. The terms 'Mandatory', 'must be used', 'has to be used' and any min occurrence greater than '0' mean that an XML element must be sent with a value in it .
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Fixed C1 Length .. 17 Name Message version Descr. Identification of Message version Remark This is the identification of the message type within the framework of EDIwheel message types. Remark This field should only contain 'C1' as fix value.	
Variant	Occurrence 0 .. 1 Fixed 0 Length 1 Remark The variant of this release is "0"	
OrderDateFrom	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Order Date From Descr. The starting date (order creation date) from which all orders shall be included in an action, report or query. Remark The max. date range is 90 days. If no date or date range is defined, then the use of the supplier or customer order number or contract number or article identifier is mandatory. If one of the above is used as search criteria than this element could not be used.	
OrderDateTo	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Order Date To Descr. The end date (order creation date) up to which all orders shall be included in an action, report or query.	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
OrderStatusIndicator	Remark	The max. date range is 90 days. If no date or date range is defined, then the use of the supplier or customer order number or contract number or article identifier is mandatory. If one of the above is used as search criteria than this element could not be used.
	Occurrence	0 .. 1
	Length	.. 1
	Name	Order Status Indicator
	Descr.	Refines the categories of orders a status request is asking for and a Order Status message is informing about. This information should be identical in the Order Status Request message and in the Order Status message. Code 1 indicates that an answering Order Status message shall cover all open orders plus all cancelled orders. Code 2 indicates that an answering Order Status message shall cover all open orders, all cancelled orders and all delivered orders. If this element is not sent in the request then the request is about all open orders in the suppliers ERP only.
Applicable Codes		
	0	Open orders only
	1	Open orders and cancelled orders
	2	Open orders, cancelled orders and delivered orders
ErrorHead	Occurrence	1 .. 1
	Name	Error code information
	Descr.	Error code information
xsd:sequence	Occurrence	1 .. 1
ErrorCode	Occurrence	1 .. 1
	Length	.. 3
	Name	Error code
Applicable Codes		
	0	No errors occurred
	1	At least one item is incorrect. Details are distinctive in the error field on item level
	303	No connection to ERP system
	304	Request to ERP - System disconnected
	399	Miscellaneous - connection error
	405	Timeout during processing in ERP system
	499	Miscellaneous - processing error

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
Applicable Codes		
901	Document number invalid [identification number of document, blanket order reference, customer reference, additional customer reference number]	
913	Invalid consignee (ship-to) party ID number	
914	Missing buyer (sold-to) identification number	
915	Buyer (sold-to) party ID number invalid	
916	Adhoc version number incorrect (document ID or variant)	
917	Incorrect ad hoc message type	
920	Account not activated for this buyer (sold-to) party ID number	
921	Access permission password is expired	
924	Incorrect buyer (sold-to) agency code qualifier	
925	Incorrect consignee (ship-to) agency code qualifier	
926	Missing mapping for the customer assigned buyer (sold-to) party ID	
927	Missing mapping for the customer assigned consignee (ship-to) party ID	
932	Buyer (sold-to) definition error in supplier system (sales area, deletion indicator etc.)	
936	Wrong buyer - consignee combination (sold-to/ship-to combination)	
937	Consignee (ship-to) definition error in supplier system (sales area, deletion indicator etc.)	
946	Ad hoc version number missing	
947	Order selection date (from) invalid	
948	Order selection date (to) invalid	
949	Too large date range for an status request	
950	No authority to use this message type	
951	Wrong order status indicator	
952	Order status indicator not supported by the supplier	
953	Date range or ordering method cannot be used simultaneously with order reference as selection criteria	
954	Address definition invalid	
961	Supplier Party ID /address invalid	
962	Seller Party ID /address invalid	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
Applicable Codes		
	988 Search criteria is not unique	
	999 Miscellaneous	
BuyerParty	Occurrence 1 .. 1 Remark Contracting party, e.g. party who is doing / establishing the sales contract by a legal way. In other words it's the entity who's doing the business contract with the supplier and who takes the legal responsibility. Depending on the customers organisation it could be a central purchasing department (headquarter) or a main dealer.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Buyer ID Descr. Identification number of a buyer. Remark The buyer number could be assigned by three parties defined by agency code (91, 92, 9). It must consist of the characters [A..Z, 0..9, _] (letters, numbers, underscore).	By the party ID, called buyer party, is considered the number which identifies the purchasing party. In other words, who is demanding goods. Depending on the customer organisation, it might be the same as the ship-to (consignee) or the same as the invoice payer.
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the buyer's identification number. Descr. Code identifying the agency responsible for a code list.	
Applicable Codes		
	9 EAN (International Article Numbering association)	
	91 Assigned by seller or seller's agent	
	92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 0 .. 1 Length .. 40	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
District	Occurrence 0 .. 1 Length .. 40	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
OrderingParty	Occurrence 0 .. 1 Remark The initial ordering / stipulating party is the partner who is placing/creating the purchase order in the customer system. This element has to be used when the ordering party is different from the buyer (example shop versus head office). Note: This level is not supported by all manufacturers.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Ordering Party ID Remark The ordering party number could be assigned by three parties	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
AgencyCode	defined by agency code (91, 92, 9). It must consist of the characters [A..Z, 0..9, _] (letters, numbers, underscore). Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the ordering party's identification number. Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent 92 Assigned by buyer or buyer's agent	
Consignee	Occurrence 0 .. 1 Remark The delivery address in the header is valid for all items. Indicating a consignee [ship-to] on the item level, which differs from the consignee specified on the header level, is not possible. Remark If the delivery address is not identical with the buyer address, a consignee has to be sent. Exception: if a note in the supplier's system indicates that the goods have always to be delivered to another recorded address, then it is not necessary to send a separate consignee.	This code is used to identify the address where the goods are to be sent. For the supplier this address is where the goods will be shipped (ship-to address). The customer has to agree upfront with the supplier which are the concerned ship-to addresses for a given sold-to
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 0 .. 1 Length .. 17 Name Identification consignee/delivery address	
AgencyCode	Occurrence 0 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the consignee's identification number. Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent 92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
Address	Length .. 30	
xsd:sequence	Occurrence 0 .. 1	
Street	Occurrence 1 .. 1	
City	Occurrence 1 .. 1	
District	Length .. 30	
PostCode	Occurrence 0 .. 1	
SubCountry	Length .. 30	
CountryCode	Occurrence 1 .. 1	
Geolocation	Length .. 10	
xsd:sequence	Occurrence 1 .. 1	
Latitude	Occurrence 0 .. 1	
Longitude	Occurrence 1 .. 1	
InformationContact	Length .. 11	
xsd:sequence	Pattern (\\+ -)?(((0-8)[0-9])(\\.[0-9]{1,6})?)? 90)	
	Name Latitude as decimal degrees (between -90 and +90)	
	Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format.	
	Example -89.345543, 01.45, +25.23456	
	Occurrence 1 .. 1	
	Length .. 11	
	Pattern (\\+ -)?(((0[0-9]{2}1[0-7][0-9])(\\.[0-9]{1,6})?)? 180)	
	Name Longitude as decimal degrees (between -180 and +180)	
	Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format.	
	Example -145.956083, 092.123, +005.12345	
	Occurrence 0 .. 1	
	Remark One of the attributes of the contact has to be present.	
	Name Information contact	
	Occurrence 1 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
ReferencedOrder	Occurrence 0 .. unbounded	
xsd:sequence	Occurrence 1 .. 1	
Error	Occurrence 1 .. 1	
xsd:sequence	Occurrence 1 .. 1	
ErrorCode	Occurrence 1 .. 1 Length .. 3 Name Error code	
Applicable Codes		
0	No errors occurred	
1	At least one item is incorrect. Details are distinctive in the error field on item level	
303	No connection to ERP system	
304	Request to ERP - System disconnected	
399	Miscellaneous - connection error	
405	Timeout during processing in ERP system	
499	Miscellaneous - processing error	
901	Document number invalid [identification number of document, blanket order reference, customer reference, additional customer reference number]	
913	Invalid consignee (ship-to) party ID number	
914	Missing buyer (sold-to) identification number	
915	Buyer (sold-to) party ID number invalid	
916	Adhoc version number incorrect (document ID or variant)	
917	Incorrect ad hoc message type	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Applicable Codes	
	920 Account not activated for this buyer (sold-to) party ID number	
	921 Access permission password is expired	
	924 Incorrect buyer (sold-to) agency code qualifier	
	925 Incorrect consignee (ship-to) agency code qualifier	
	926 Missing mapping for the customer assigned buyer (sold-to) party ID	
	927 Missing mapping for the customer assigned consignee (ship-to) party ID	
	932 Buyer (sold-to) definition error in supplier system (sales area, deletion indicator etc.)	
	936 Wrong buyer - consignee combination (sold-to/ship-to combination)	
	937 Consignee (ship-to) definition error in supplier system (sales area, deletion indicator etc.)	
	946 Ad hoc version number missing	
	947 Order selection date (from) invalid	
	948 Order selection date (to) invalid	
	949 Too large date range for an status request	
	950 No authority to use this message type	
	951 Wrong order status indicator	
	952 Order status indicator not supported by the supplier	
	953 Date range or ordering method cannot be used simultaneously with order reference as selection criteria	
ErrorText	Occurrence 0 .. 1 Length .. 60 Name Error text Descr. Detailed explanations of an error, that has occurred.	
OrderDate	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Remark Some parties do not issue order numbers. They identify their orders by order date and part number. In this case, this stand alone order date can be used rather than order number (ID) and date.	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
SupplierOrderNumber	Occurrence 0 .. 1	
<i>xsd:sequence</i>	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1	
	Length .. 17	
	Name Document ID	
	Descr. Identification of the document	
OrderingMethod	Occurrence 0 .. 1	
	Length .. 2	
	Name Ordering method	
	Descr. The method by which an order has been created.	
	Applicable Codes	
	EI EDI	
	EM Electronic Mail	
	FX Fax	
	HO Adhoc	
	MA Paper	
	MO Mobile	
	OT Other	
	TE Telephone	
	VM VMI	
	WP Portal order by WWW	
OrderReference	Occurrence 0 .. 1	
	Name Customer assigned Order number	
<i>xsd:sequence</i>	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1	
	Length .. 35	
	Name Document ID	
	Descr. Identification of the document	
	Remark If both the supplier and customer numbers are used, than the primary search criteria is the "Suppliers order number". The document ID contains here the 'Customer assigned order number'	
PickUp	Occurrence 0 .. 1	
	Length .. 1	
	Name Pickup	
	Descr. Flag to specify if the Customer in the Inquiry or Order requires to pick-up the goods at supplier's location.	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
Applicable Codes		
	Y Yes	
DeliveryOption	Occurrence 0 .. 1 Length .. 3 Name Delivery option Descr. Examples: IA = Package, display, wooden IB = Package, display, cardboard IC = Package, display, plastic ID = Package, display, metal OA = Pallet, CHEP 40 cm x 60 cm OB = Pallet, CHEP 80 cm x 120 cm OC = Pallet, CHEP 100 cm x 120 cm OD = Pallet, AS 4068-1993 OE = Pallet, ISO T11 Link UN/EDIFACT Data Element 7065, and more precisely UN/ECE Recommendation 21, Annex V, alphabetic codes https://www.unece.org/fileadmin/DAM/cefact/recommendations/rec21/rec21_Rev9e_2012.xls	
SellerParty	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1	
	Length .. 17	
AgencyCode	Occurrence 1 .. 1	
	Descr. Code identifying the agency responsible for a code list.	
	Length .. 3	
	Name Code list responsible agency, coded	
	Remark Code identifying the agency responsible for a code list.	
Applicable Codes		
	9 EAN (International Article Numbering association)	
	91 Assigned by seller or seller's agent	
	92 Assigned by buyer or buyer's agent	
SupplierParty	Occurrence 0 .. 1	In North America supplier is preferred to identify the selling and supplying party. Seller is only included when the party actually differs from the supplier.
	Name Supplier identification	
	Descr. Identification of a supplier	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
AgencyCode	Length .. 17 Name Identification number supplier Descr. Identification number supplier	
	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list.	
	Applicable Codes	
	9 EAN (International Article Numbering association)	
	91 Assigned by seller or seller's agent	
	92 Assigned by buyer or buyer's agent	
	Contract Occurrence 0 .. 1 Name Contract number, reference to the sales agreement Remark To identify the sales agreement (ie, contract number) that needs to be used in a transaction.	
	- xsd:sequence DocumentID Occurrence 1 .. 1	
	Length .. 17 Name Document ID Descr. Identification of the document	
	OrderLine Occurrence 0 .. unbounded Name Line item information Remark It should be checked with each supplier what the supported maximum occurrence is.	
- xsd:sequence - LineID	Occurrence 1 .. 1	
	Occurrence 1 .. 1 Length .. 6 Name Line item number Descr. Supplier assigned identification number of a line item of a document.	
	Remark This supplier assigned line item number further specifies the Document ID of the supplier assigned Supplier Order Number. Always at least the Customer Line Item Number or the supplier assigned Line Item number must be indicated.	
	CustomerLineItemNumber Occurrence 0 .. 1 Length .. 6	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
AdditionalCustomerReferenceNumber xsd:sequence DocumentID OrderedArticle xsd:sequence ArticleIdentification xsd:sequence BuyersArticleID ManufacturersArticleID EANUCCArticleID	Name Customer Line Item Number Descr. Customer assigned Line Item Number Remark This is the customers purchase order line number used for reconciliation. This customer assigned line item number further specifies the Document ID of the customer assigned assigned Order Reference. Always at least the Customer Line Item Number or the supplier assigned Line Item number must be indicated.	
	Occurrence 0 .. 1	
	Name Additional Customer's reference information	
	Occurrence 1 .. 1	
	Occurrence 1 .. 1	
	Length .. 35	
	Descr. Customer's reference to the business transaction on item level.	
	Occurrence 1 .. 1	
	Remark Article information	
	Occurrence 1 .. 1	
	Occurrence 1 .. 1	
	Remark Article identification information	
	Remark The use of the manufacturer assigned ERP article number and of the buyer assigned article number requires bilateral agreements.	
	Occurrence 1 .. 1	
	Occurrence 0 .. 1	
	Length .. 17	
	Name Buyer article number	
	Descr. Identification of the article, assigned by the buyer	
	Occurrence 0 .. 1	
	Length .. 35	
	Name Manufacturer's article number	
	Descr. Identification of the article, assigned by the manufacturer.	
	Occurrence 0 .. 1	
	Length .. 14	
	Name EANUCC Article number	
	Remark The 13 digit GTIN (Global Trade Item Number, known as EAN Number) is used.	
		A sent EAN number has priority compared with a manufacturer assigned article number. If there is no EAN number, then a manufacturer assigned article number is mandatory.
		The use of any other number than the 13 digit GTIN (Global Trade Item Number, known as EAN Number) has to be agreed bilaterally.

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
ArticleDescription	Occurrence 0 .. 1	
<i>xsd:sequence</i>	Occurrence 1 .. 1	
ArticleDescriptionText	Occurrence 1 .. 1 Length .. 60 Name Article description	This is the product description provided by the supplier. It can be useful for the customer especially in the case he is asking for substitution products. It could be as well interesting for the customer to cross check with his own description.
RequestedDeliveryDate	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Requested delivery date Descr. The meaning of the requested delivery date can vary from supplier to supplier and from customer to customer. Sometimes the customer has a contractual agreement with the supplier to have planned delivery dates so the meaning of the requested delivery date can change. In any case, before implementing this message, contact your supplier to agree on the exact meaning of this field.	
RequestedDeliveryTime	Occurrence 0 .. 1 Name Delivery Time Descr. Hour of delivery at the place of deliver, Including time zone. Pattern \d{2}:\d{2}:\d{2}/(?:Z [-+](?:2[0-3][01][0-9]:[0-5][0-9])\$) Example : 18:00:00-06:30 or 18:00:00Z	
ArticleComment	Occurrence 0 .. 1 Length .. 60 Name Article comment Descr. The supplier can inform the customer about some specificities of this product or can send back useful information for the customer in this field. As it is an optional field, some suppliers might never send such information or only sometimes. Nevertheless the customers IT system should enable the display of this field.	
ScheduleDetails	Occurrence 0 .. unbounded Remark If both Delivery Date and Delivery Period are allowed then they shall be used mutually exclusive.	

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation	User Comments
xsd:sequence	Occurrence 1 .. 1	
DeliveryDate	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Date of delivery Descr. Forecasted date of delivery at the place of deliver. Remark If no date can be reflected by the ERP system, then the field will be set to 9999-12-31.	
DeliveryTime	Occurrence 0 .. 1 Name Delivery Time Descr. Hour of delivery at the place of deliver, Including time zone. Pattern \d{2}:\d{2}:\d{2}/(?:Z [-](?:2[0-3] [01][0-9]):[0-5][0-9])\$/ Example : 18:00:00-06:30 or 18:00:00Z	
ConfirmedQuantity	Occurrence 0 .. 1 Remark If this data is sent then neither Cancelled nor Open quantity is allowed to be sent. If this data is sent then Delivery date within Schedule details must be sent and Scheduled Article Despatch Details may be sent. The full quantity of the schedule line is confirmed for a give date. Partial deliveries could have been occurred already.	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1 TotalDigits 15 Name Confirmed quantity	
CancelledQuantity	Occurrence 0 .. 1 Remark If this data is sent then no other information of the Scheduled details is allowed to be sent. The indicated quantity will never be delivered.	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1 TotalDigits 15 Name Cancelled quantity	
OpenQuantity	Occurrence 0 .. 1 Remark If this data is sent then no other information of the Scheduled	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
	details is allowed to be sent. The quantity is not confirmed but it is not cancelled neither meaning the supplier does not know yet when will be delivered but the request is taken into account for the next replenishment process.	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1	
	TotalDigits 15	
	Name Open quantity	
ScheduledArticleDespatchDetails	Occurrence 0 .. unbounded	
xsd:sequence	Occurrence 1 .. 1	
DespatchDate	Occurrence 1 .. 1	
	Length 10	
	Pattern \d{4}-\d{2}-\d{2}	
	Example 2008-31-01	
	Remark Usually the date when goods left or are scheduled to leave the supplier's premises.	
DespatchAdviceReference	Occurrence 1 .. 1	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1	
	Length .. 35	
	Name Document ID	
	Descr. Identification of the document.	
	Remark This is the supplier's delivery note number.	
LineID	Occurrence 0 .. 1	
	Length .. 6	
	Name Line item number	
	Descr. Identification number of a line item of a document.	
	Remark This is the supplier's delivery note line item number.	
DespatchedQuantity	Occurrence 1 .. 1	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1	
	TotalDigits 15	
OrderedQuantity	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1	
	TotalDigits 15	

Bold = Element, Italic = Attribute, Grey = Group

Order status

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Name	Ordered quantity

Bold = Element, Italic = Attribute, Grey = Group

EDIWheel C1
Issue date: 2019-07-30

Print date: 05/09/2023
Page: 21 / 24

Changes	Message Item	Path
2021-06-16	Added RootTag note	order_status order_status
2021-10-11	Email from Clément Beaudonnat on 2021-06-16 Added below new codes to the code list: 900 - Number of allowed requests exceeded 954 - Incorrect supplier agency code qualifier 955 - Incorrect seller agency code qualifier 956 - Agreement Number is invalid 957 - Requested delivery time invalid 958 - Incorrect/invalid delivery option code 959 - No authority to use/invalid pickup option 960 - Incorrect/invalid consignee address 961 - Supplier party ID number/address invalid 962 - Seller party ID number/address invalid 988 - Search criteria is not unique	ErrorCode order_status/ErrorHead/ErrorCode
2021-10-12	Restricted code list by adding codes: 954, 955, 961, 962, 988 and removing codes: 970, 971	ErrorCode order_status/ErrorHead/ErrorCode
2021-06-10	Deleted next element InternalMailAddress Email from Alice Aguemon on 2021-06-10	EmailAddress order_status/BuyerParty/InformationContact/EmailAddress
2019-12-09	WebMeeting 2019-12-09 New remark: It is required to send either the partyID (with agency code) or the name and address.	Consignee order_status/Consignee
2020-03-18	WebMeeting 2020-03-18: Remark deleted: It is required to send either the partyID (with agency code) or the name and address.	Consignee order_status/Consignee
2021-06-10	Deleted next element InternalMailAddress Email from Alice Aguemon on 2021-06-10	EmailAddress order_status/Consignee/InformationContact/EmailAddress
2021-10-11	Email from Clément Beaudonnat on 2021-06-16 Added below new codes to the code list: 900 - Number of allowed requests exceeded 954 - Incorrect supplier agency code qualifier 955 - Incorrect seller agency code qualifier 956 - Agreement Number is invalid	ErrorCode order_status/ReferencedOrder/Error/ErrorCode

Changes	Message Item	Path
957 - Requested delivery time invalid 958 - Incorrect/invalid delivery option code 959 - No authority to use/invalid pickup option 960 - Incorrect/invalid consignee address 961 - Supplier party ID number/address invalid 962 - Seller party ID number/address invalid 988 - Search criteria is not unique		
2015-05-13 Codes deleted: A - Ad hoc orders C - Conventional orders (fax, letter, phone, e.g. by call center). E - EDI orders. I - All electronic orders except conventional orders. W - Web portal orders. Codes added: EI, EM, FX, HO, MA, MO, OT, TE, VM, WP 2015-05 Mail from Alice	OrderingMethod	order_status/ReferencedOrder/OrderingMethod
2015-06-09 Type changed from string..1 to string..2 2015-06-08 Mail from Alice	OrderingMethod	order_status/ReferencedOrder/OrderingMethod
2021-06 Changed the type from DeliveryTime to time Email from Clément Beaudonnat 2021-06-03	DeliveryTime	order_status/ReferencedOrder/OrderLine/OrderedArticle/ScheduleDetails/DeliveryTime
2021-11-24 Removed Remark in ModelSemantik note: Quantity must be larger than 0. No decimals are allowed. Email response from Alice Aguemon on 2021-11-24	QuantityValue	order_status/ReferencedOrder/OrderLine/OrderedArticle/ScheduleDetails/ConfirmedQuantity/QuantityValue
2021-11-24 Removed Remark in ModelSemantik note: Quantity must be larger than 0. No decimals are allowed. Email response from Alice Aguemon on 2021-11-24	QuantityValue	order_status/ReferencedOrder/OrderLine/OrderedArticle/ScheduleDetails/CancelledQuantity/QuantityValue
2021-11-24 Removed Remark in ModelSemantik note: Quantity must be larger than 0. No decimals are allowed. Email response from Alice Aguemon on 2021-11-24	QuantityValue	order_status/ReferencedOrder/OrderLine/OrderedArticle/ScheduleDetails/OpenQuantity/QuantityValue
2021-11-24 Removed Remark in ModelSemantik note: Quantity must be larger than 0. No decimals are allowed.	QuantityValue	order_status/ReferencedOrder/OrderLine/OrderedArticle/ScheduleDetails/ScheduledArticleDespatchDetails/DespatchedQuantity/QuantityValue

Changes	Message Item	Path
2021-11-24	Email response from Alice Aguemon on 2021-11-24 Removed Remark in ModelSemantik note: Quantity must be larger than 0. No decimals are allowed. Email response from Alice Aguemon on 2021-11-24	QuantityValue order_status/ReferencedOrder/OrderLine/OrderedArticle/OrderedQuantity/QuantityValue