



Message Implementation Guideline

Order status request

C1

Issue date: 2020-03-20
Author: wdk/BRV/GEFEG

Occurrence Element / Attribute

1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	Variant
0 .. 1	OrderDateFrom
0 .. 1	OrderDateTo
0 .. 1	OrderingMethod
0 .. 1	OrderStatusIndicator
1 .. 1	BuyerParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 1	OrderingParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 1	SellerParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 1	Consignee
1 .. 1	xsd:sequence
0 .. 1	PartyID
0 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
1 .. 2	Street
1 .. 1	City
0 .. 1	District
1 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	Geolocation
1 .. 1	xsd:sequence
1 .. 1	Latitude
1 .. 1	Longitude
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	InternalMailAddress
0 .. 1	SupplierParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. unbounded	ReferencedOrder
1 .. 1	xsd:sequence
0 .. 1	SupplierOrderNumber
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	OrderReference
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	Contract
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	OrderedArticle
1 .. 1	xsd:sequence
1 .. 1	ArticleIdentification
1 .. 1	xsd:sequence
0 .. 1	BuyersArticleID
0 .. 1	ManufacturersArticleID

Occurrence	Element / Attribute
0 .. 1	 EANUCCArticleID

Element/Attribute	Annotation	User Comments
	Remark Allowed combinations of search criteria are: 1. Order Date From only, 2. Both Order Date From and Order Date To 3. Order Identification numbers only (Supplier or Customer Order Number) 4. Contract Identification number only 5. Article Identification only	Identification numbers and text: The allowed characters are [a-z, A-Z,0-9 and the underscore '_']. The terms 'Mandatory', 'must be used', 'has to be used' and any min occurrence greater than '0' mean that an XML element must be sent with a value in it .
xsd:sequence DocumentID	Occurrence 1 .. 1 Occurrence 1 .. 1 Fixed C1 Length .. 17 Name Message version Descr. Identification of Message version Remark This is the identification of the message type within the framework of EDIwheel message types. Remark This field should only contain 'C1' as fix value.	
Variant	Occurrence 0 .. 1 Fixed 0 Length 1 Remark The variant of this release is "0"	
OrderDateFrom	Occurrence 0 .. 1 Length .. 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Order Date From Descr. The starting date (order creation date) from which all orders shall be included in an action, report or query. Remark The max. date range is 90 days. If no date or date range is defined, then the use of the supplier or customer order number or contract number or article identifier is mandatory. If one of the above is used as search criteria than this element could not be used.	
OrderDateTo	Occurrence 0 .. 1 Length .. 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Order Date To Descr. The end date (order creation date) up to which all orders shall be included in an action, report or query. Remark The max. date range is 90 days. If no date or date range is	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
OrderingMethod	defined, then the use of the supplier or customer order number or contract number or article identifier is mandatory. If one of the above is used as search criteria than this element could not be used.	In order to avoid issues with multiple selections there are some basic rules defined: - the search criteria 'document id' has priority over all other selection criteria. This means if the customer wants to search for a given document, the document number criteria will be taken and the other criteria will be ignored. - all other search criteria can be combined with each other. It is important to know that any combination of criteria will follow the 'AND' condition. Example: If a customer sends a request with a date range (01/12/2010 - 05/12/2010) and order status 'open', the reply will contain all orders created between the date range AND with the status open.
	Occurrence 0 .. 1 Length .. 2 Name Ordering method Descr. The method by which an order has been created. Remark If not sent then the ordering method is not a filter criteria. If sent it must have a value other then BLANK.	
OrderStatusIndicator	Applicable Codes EI EDI EM Electronic Mail FX Fax HO Adhoc MA Paper MO Mobile OT Other TE Telephone VM VMI WP Portal order by WWW	
	Occurrence 0 .. 1 Length .. 1 Name Order Status Indicator Descr. The current status of the orders to be retrieved Remark If not sent then the order status indicator is not a filter criteria. If sent it must have a value other then BLANK.	
BuyerParty	Applicable Codes 0 Open orders only 1 Open orders and cancelled orders 2 Open orders, cancelled orders and delivered orders	
	Occurrence 1 .. 1 Remark Contracting party, e.g. party who is doing / establishing the sales contract by a legal way. In other words it's the entity	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	who's doing the business contract with the supplier and who takes the legal responsibility. Depending on the customers organisation it could be a central purchasing department (headquarter) or a main dealer.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Buyer ID Descr. Identification number of a buyer.	By the party ID, called buyer party, is considered the number which identifies the purchasing party. In other words, who is demanding goods. Depending on the customer organisation, it might be the same as the ship-to (consignee) or the same as the invoice payer.
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the buyer's identification number. Descr. Code identifying the agency responsible for a code list.	
	Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent 92 Assigned by buyer or buyer's agent	
OrderingParty	Occurrence 0 .. 1 Remark The initial ordering / stipulating party is the partner who is placing/creating the purchase order in the customer system. This element has to be used when the ordering party is different from the buyer (example shop versus head office). Note: This level is not supported by all manufacturers.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Ordering Party ID	
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the ordering party's identification number.	
	Applicable Codes 9 EAN (International Article Numbering association)	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
Applicable Codes		
91	Assigned by seller or seller's agent	
92	Assigned by buyer or buyer's agent	
SellerParty	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1	
	Length .. 17	
AgencyCode	Occurrence 1 .. 1	
	Descr. Code identifying the agency responsible for a code list.	
	Length .. 3	
	Name Code list responsible agency, coded	
	Remark Code identifying the agency responsible for a code list.	
Applicable Codes		
9	EAN (International Article Numbering association)	
91	Assigned by seller or seller's agent	
92	Assigned by buyer or buyer's agent	
Consignee	Occurrence 0 .. 1	This code is used to identify the address where the goods are to be sent. For the supplier this address is where the goods will be shipped (ship-to address). The customer has to agree upfront with the supplier which are the concerned ship-to addresses for a given sold-to
	Remark The delivery address in the header is valid for all items. Indicating a consignee [ship-to] on the item level, which differs from the consignee specified on the header level, is not possible.	
	Remark If the delivery address is not identical with the buyer address, a consignee has to be sent. Exception: if a note in the supplier's system indicates that the goods have always to be delivered to another recorded address, then it is not necessary to send a separate consignee.	
	Remark The name, address and the information contact structure at consignee level are not intended to be used as search criteria.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 0 .. 1	
	Length .. 17	
	Name Identification consignee/delivery address	
AgencyCode	Occurrence 0 .. 1	
	Descr. Code identifying the agency responsible for a code list.	
	Length .. 3	
	Name Code list responsible agency, coded	
	Remark Code identifying the agency responsible for a code list.	
	Name Type of the consignee's identification number.	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
Applicable Codes		
	9 EAN (International Article Numbering association)	
	91 Assigned by seller or seller's agent	
	92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 30	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 1 .. 2 Length .. 30	
City	Occurrence 1 .. 1 Length .. 30	
District	Occurrence 0 .. 1 Length .. 30	
PostCode	Occurrence 1 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
Geolocation	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Latitude	Occurrence 1 .. 1 Length .. 10 Pattern (\+ -)?(((0-8)[0-9])(\.[0-9]{1,6})?)? 90) Name Latitude as decimal degrees (between -90 and +90) Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format. Example -89.345543, 01.45, +25.23456	
Longitude	Occurrence 1 .. 1 Length .. 11 Pattern (\+ -)?((0[0-9]{2})1[0-7][0-9])(\.[0-9]{1,6})? 180) Name Longitude as decimal degrees (between -180 and +180) Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format. Example -145.956083, 092.123, +005.12345	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present.	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
- xsd:sequence ContactID - Occurrence 1 .. 1 Name - Occurrence 0 .. 1 - Length .. 17 TelephoneNumber - Occurrence 0 .. 2 - Length .. 40 TelephoneExtension - Occurrence 0 .. 1 - Length .. 100 FaxNumber - Occurrence 0 .. 1 - Length .. 100 EmailAddress - Occurrence 0 .. 1 - Length .. 256 InternalMailAddress - Occurrence 0 .. 1 - Length .. 100 SupplierParty - Occurrence 0 .. 1 - Name Supplier identification - Descr. Identification of a supplier - xsd:sequence PartyID - Occurrence 1 .. 1 - Length .. 17 - Name Identification number supplier - Descr. Identification number supplier AgencyCode - Occurrence 1 .. 1 - Descr. Code identifying the agency responsible for a code list. - Length .. 3 - Name Code list responsible agency, coded - Remark Code identifying the agency responsible for a code list. ReferencedOrder - Occurrence 1 .. 1	Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent 92 Assigned by buyer or buyer's agent	In North America supplier is preferred to identify the selling and supplying party. Seller is only included when the party actually differs from the supplier. The 'document id' search criteria cannot be used in combination with the search criteria 'date (range)' and 'ordering method'. Such a combination would result in an error code 953 as a feed back.

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
SupplierOrderNumber	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1	
	Length .. 17	
	Name Document ID	
	Descr. Identification of the document	
OrderReference	Occurrence 0 .. 1	
	Name Customer assigned Order number	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1	
	Length .. 35	
	Name Document ID	
	Descr. Identification of the document	
	Remark If both the supplier and customer numbers are used, than the primary search criteria is the "Suppliers order number". The document ID contains here the 'Customer assigned order number'	
Contract	Occurrence 0 .. 1	
	Name Contract number, reference to the sales agreement	
	Remark To identify the sales agreement (ie, contract number) that needs to be used in a transaction.	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1	
	Length .. 17	
	Name Document ID	
	Descr. Identification of the document	
OrderedArticle	Occurrence 0 .. 1	
	Remark Article information	
xsd:sequence	Occurrence 1 .. 1	
ArticleIdentification	Occurrence 1 .. 1	
	Remark Article identification information	
xsd:sequence	Occurrence 1 .. 1	
BuyersArticleID	Occurrence 0 .. 1	
	Length .. 17	
	Name Buyer article number	
	Descr. Identification of the article, assigned by the buyer	
ManufacturersArticleID	Occurrence 0 .. 1	
	Length .. 35	
	Name Manufacturer's article number	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
EANUCCArticleID	Descr. Identification of the article, assigned by the manufacturer. Occurrence 0 .. 1 Length .. 14 Name EANUCC Article number	

Bold = Element, Italic = Attribute, Grey = Group

Changes	Message Item	Path
Old remark: Allowed combinations of search criteria are: 1. Order Date From only, 2. Both Order Date From and Order Date To 3. Order Identification numbers only New remark: Allowed combinations of search criteria are: 1. Order Date From only, 2. Both Order Date From and Order Date To 3. Order Identification numbers only (Supplier or Customer Order Number) 4. Contract Identification number only 5. Article Identification only	order_status_request	order_status_request