



Message Implementation Guideline

Order

C1

Issue date: 2019-07-30
Author: wdk/BRV/GEFEG

Please check with your supplier whether this specific version is supported by its organization.

Occurrence Element / Attribute

	order
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	Variant
0 .. 1	EarliestDeliveryDate
0 .. 1	TransportPriority
0 .. 1	Campaign
0 .. 1	PickUp
0 .. 1	DeliveryOption
0 .. 1	DeliveryRemarks
0 .. 1	BlanketOrderReference
1 .. 1	xsd:sequence
1 .. 1	DocumentID
1 .. 1	CustomerReference
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	SellerParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
0 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	SupplierParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
0 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
1 .. 1	BuyerParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence

Occurrence	Element / Attribute
0 .. 3	Street
0 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	OrderingParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 1	Consignee
1 .. 1	xsd:sequence
0 .. 1	PartyID
0 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
1 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	Geolocation
1 .. 1	xsd:sequence
1 .. 1	Latitude
1 .. 1	Longitude
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	Contract
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	PaymentTerms
1 .. 1	xsd:sequence
1 .. 1	PaymentMethod
1 .. unbounded	OrderLine
1 .. 1	xsd:sequence
1 .. 1	LineID
0 .. 1	PortalReference
0 .. 1	AdditionalCustomerReferenceNumber
1 .. 1	xsd:sequence
1 .. 1	DocumentID
1 .. 1	OrderedArticle
1 .. 1	xsd:sequence
1 .. 1	ArticleIdentification
1 .. 1	xsd:sequence
0 .. 1	BuyersArticleID
0 .. 1	ManufacturersArticleID
0 .. 1	EANUCCArticleID
0 .. 1	RequestedDeliveryDate
0 .. 1	RequestedDeliveryTime
1 .. 1	RequestedQuantity
1 .. 1	xsd:sequence



Occurrence	Element / Attribute
1 .. 1	 QuantityValue

Element/Attribute	Annotation	User Comments
order		Identification numbers and text: The allowed characters are [a-z, A-Z,0-9 and the underscore '_']. The terms 'Mandatory', 'must be used', 'has to be used' and any min occurrence greater than '0' mean that an XML element must be sent with a value in it .
xs:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Fixed C1 Length .. 17 Name Message version Descr. Identification of Message version Remark This field should only contain 'C1' as fix value.	
Variant	Occurrence 0 .. 1 Fixed 0 Length 1 Remark The variant of this release is "0"	
EarliestDeliveryDate	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Earliest delivery date Descr. Earliest delivery date at the place of delivery. Remark This header information provides optimization in the logistic.	
TransportPriority	Occurrence 0 .. 1 Length .. 4 Remark In order to express that the order is a normal order the element must not be used. Name Transport priority Remark This information is mainly used in the order message and is not supported by all suppliers. Remark The customer can inform the supplier how this order should be handled. If the element is not used it means the order will be handled by the supplier under the default way and the goods will be delivered within the default delivery scheme or according to the RequestDeliveryDates provided at line level. The default delivery schemes are supplier/customer/country specific and therefore not specified in this documentation.	Rush: If the customer wants to receive delivery faster than the agreed regular terms, then he can use this element to inform the supplier that the order must be treated differently from the usual case. As mentioned before, the delivery terms are agreed as a default at the supplier/ customer level so they can be specified differently on a case by case basis. The rush order simply means that the goods ordered in this order should be delivered faster as usual. Replenishment: It means that the customer either sends an order for which he does not expect an exact timing or sends an order for which the supplier will compute the contractual RequestedDeliveryDate. It should be used only on bilateral agreement between the customer and the

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Remark Before starting any integration, the customer and the supplier must agree on what is the normal delivery term. In order to express that the order is a normal order the element must not be used. The customer can inform the supplier how this order should be handled. If the element is not used it means the order will be handled by the supplier under the default way and the goods will be delivered within the default delivery scheme or according to the RequestDeliveryDates provided at line level. The default delivery schemes are supplier/customer/country specific and therefore not specified in this documentation. Before starting any integration, the customer and the supplier must agree on what is the normal delivery term. Applicable Codes REPL Replenishment The order has to be processed following the supplier's replenishment delivery scheme. Depending on the supplier it can mean that in the order response, - the delivery dates and quantities are not calculated at request time but later. In this case the order response returns 99991231, meaning the delivery dates cannot be committed.- the delivery dates and quantities are calculated based on the replenishment scheme of the supplier and provided requested dates. RUSH Rush Order SEAS Seasonal order Seasonal order means that there will never be a confirmed delivery date in the order confirmation message. The requested delivery date will be considered as a starting date by when the first shipments should take place. Nevertheless, the suppliers customer service will always contact the	supplier. Note some suppliers in some countries will confirm the dates for such kind of order so the rule should be if date is confirmed, than it means the supplier will deliver on those dates, if the date is 99991231, than no exact date is confirmed in the order confirmation message and it means as well that the suppliers customer service will contact the customer to agree on delivery dates and quantities. There are no general rules about the volume or about the way the supplier is processing this replenishment orders. Seasonal orders: This transport priority means that the customer is purchasing goods for a whole season (winter or summer). Knowing that these orders are containing big quantity of tyres and that the delivery of these goods has to be spread over the whole period, the exact delivery dates will not be confirmed in the order confirmation message. The actual procedures will remain meaning the customer service will contact regularly the customer to agree on which quantity should be delivered by when.

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
	Applicable Codes dealer to agree exactly what and when will be delivered.	
– Campaign	Occurrence 0 .. 1 Length .. 12 Name Campaign Descr. Identification of a Campaign/ a Promotion.	This information is mainly used in the order / order confirmation message and is optional. Not supported by all suppliers. This element is used to identify if the order is related to a sales campaign/promotion. The content of the element should be the campaign number given by the supplier. As for each functionality, the customer must check before implementing the automatic ordering with the supplier if a given functionality is supported or not by the supplier.
– Pickup	Occurrence 0 .. 1 Length .. 1 Name Pickup Descr. Flag to specify if the Customer in the Inquiry or Order requires to pick-up the goods at supplier's location.	
	Applicable Codes Y Yes	
– DeliveryOption	Occurrence 0 .. 1 Length .. 3 Name Delivery option Descr. Examples: IA = Package, display, wooden IB = Package, display, cardboard IC = Package, display, plastic ID = Package, display, metal OA = Pallet, CHEP 40 cm x 60 cm OB = Pallet, CHEP 80 cm x 120 cm OC = Pallet, CHEP 100 cm x 120 cm OD = Pallet, AS 4068-1993 OE = Pallet, ISO T11 Link UN/EDIFACT Data Element 7065, and more precisely UN/ ECE Recommendation 21, Annex V, alphabetic codes https://www.unece.org/fileadmin/DAM/cefact/recommendations/rec21/rec21_Rev9e_2012.xls	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
DeliveryRemarks	Occurrence 0 .. 1 Length .. 70 Name Delivery Remarks	Optional field. Not supported by all suppliers. This field could be used to give additional information about delivery purposes.
BlanketOrderReference	Occurrence 0 .. 1 Remark Equivalent EDIFACT code is BO Name Blanket order reference information	This value is used only in the order message. Not supported by all suppliers.
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Length .. 35 Name Reference to contract number Descr. Reference to the contract referring to the present order.	
CustomerReference	Occurrence 1 .. 1 Name Customer reference information	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Length .. 35 Name Document ID Descr. Identification of the document. Remark Only used in the order message. If a customer reference is sent within an inquiry the supplier will simply ignore it and return as received. This number is the customer purchase order number generated by the customer IT system. It should not be a manually created number. This number has to be unique for each customer (ordering party) and purchase order. So on supplier's side, a duplicate check may be possible in order to avoid to integrate the same order twice. This order number will be used in all subsequent flows (order confirmation, delivery, invoice, order status) for reconciliation and controlling purpose. This number is also present on the delivery and invoice and is as well sent back to the customer in the different EDI messages.	Only used in the order message. If a customer reference is sent within an inquiry the supplier will simply ignore it and return as received. This number is the customer purchase order number generated by the customer IT system. It should not be a manually created number. This number has to be unique if a customer wants the supplier to apply a control procedure that he does not process the same order twice. This order number will be used in all subsequent flows (order confirmation, delivery, invoice, order status) for reconciliation and controlling purpose. This number is also present on the delivery and invoice and is as well sent back to the customer in the different EDI messages.
SellerParty	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list.	
Applicable Codes		
9	EAN (International Article Numbering association)	
91	Assigned by seller or seller's agent	
92	Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 0 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 40	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
SupplierParty	Occurrence 0 .. 1 Name Supplier identification Descr. Identification of a supplier	In North America supplier is preferred to identify the selling and supplying party. Seller is only included when the party actually differs from the supplier.
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Identification number supplier Descr. Identification number supplier	
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list.	
Applicable Codes		
9 EAN (International Article Numbering association)		
91 Assigned by seller or seller's agent		
92 Assigned by buyer or buyer's agent		
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 0 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 40	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
CountryCode	Length .. 70 Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
BuyerParty	Occurrence 1 .. 1 Remark Contracting party, e.g. party who is doing / establishing the sales contract by a legal way. In other words it's the entity who's doing the business contract with the supplier and who takes the legal responsibility. Depending on the customers organisation it could be a central purchasing department (headquarter) or a main dealer.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Buyer ID Descr. Identification number of a buyer.	By the party ID, called buyer party, is considered the number which identifies the purchasing party. In other words, who is demanding goods. Depending on the customer organisation, it might be the same as the ship-to (consignee) or the same as the invoice payer.
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
	Remark Code identifying the agency responsible for a code list. Name Type of the buyer's identification number. Descr. Code identifying the agency responsible for a code list.	
	Applicable Codes	
	9 EAN (International Article Numbering association)	
	91 Assigned by seller or seller's agent	
	92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 0 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 40	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
OrderingParty	Occurrence 0 .. 1 Remark The initial ordering / stipulating party is the partner who is placing/creating the purchase order in the customer system. This element has to be used when the ordering party is different from the buyer (example shop versus head office). Note: This level is not supported by all manufacturers.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Ordering Party ID	
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the ordering party's identification number. Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent 92 Assigned by buyer or buyer's agent	
Consignee	Occurrence 0 .. 1 Remark The delivery address in the header is valid for all items. Indicating a consignee [ship-to] on the item level, which differs from the consignee specified on the header level, is not possible. Remark If the delivery address is not identical with the buyer address, a consignee has to be sent. Exception: if a note in the supplier's system indicates that the goods have always to be delivered to another recorded address, then it is not necessary to send a separate consignee.	This code is used to identify the address where the goods are to be sent. For the supplier this address is where the goods will be shipped (ship-to address). The customer has to agree upfront with the supplier which are the concerned ship-to addresses for a given sold-to.
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 0 .. 1 Length .. 17	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
AgencyCode	Name Identification consignee/delivery address Occurrence 0 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the consignee's identification number. Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent 92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 1 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 30	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
Geolocation	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Latitude	Occurrence 1 .. 1 Length .. 10 Pattern (\+ -)?(((0-8)[0-9])(\.[0-9]{1,6})?)? 90) Name Latitude as decimal degrees (between -90 and +90) Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format.	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
Longitude	Example -89.345543, 01.45, +25.23456 Occurrence 1 .. 1 Length .. 11 Pattern (\+ -)?((0[0-9]{2})1[0-7][0-9])(\.[0-9]{1,6})? 180) Name Longitude as decimal degrees (between -180 and +180) Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format.	
InformationContact	Example -145.956083, 092.123,+005.12345 Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
Contract	Occurrence 0 .. 1 Name Contract number, reference to the sales agreement Remark To identify the sales agreement (ie, contract number) that needs to be used in a transaction.	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Length .. 17 Name Document ID Descr. Identification of the document	
PaymentTerms	Occurrence 0 .. 1 Name Payment terms information	
xsd:sequence	Occurrence 1 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
PaymentMethod	Occurrence 1 .. 1 Length .. 10 Remark In order to express that the normal payment method (by Invoice) is used the element (i.e. the element group) must not be used. Name Payment method Descr. Identification of the method of payment.	This functionality is not supported by all suppliers. In some European markets, the customer might get a different discount depending on the payment method. For example paying cash at delivery, he could have a 2% extra discount, or paying by a Visa card. This option is supplier/customer dependent so before using this field, a preliminary bilateral agreement is required. If not used, the supplier will apply the usual agreed payment terms.
Applicable Codes		
	C Cash	
	K Credit Card	
OrderLine	Occurrence 1 .. unbounded Name Line item information Remark It should be checked with each supplier what the supported maximum occurrence is.	
xsd:sequence	Occurrence 1 .. 1	
LineID	Occurrence 1 .. 1 Length .. 6 Name Line identification number Descr. Identification of a line in a document	
PortalReference	Occurrence 0 .. 1 Length .. 14 Name Portal Reference Descr. Portal Reference Remark For statistic purposes. Not yet to be used.	
AdditionalCustomerReferenceNumber	Occurrence 0 .. 1 Name Additional Customer's reference information Remark Countermark	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Length .. 35 Name Document ID Descr. Customer's reference to the business transaction on item level.	If the customer wants to have more references (ex. 4 tyres for Mr. Smith) by sending this to the supplier, the supplier can print this information on the delivery document. The information in this field is not checked on the supplier side and is taken there as a kind of free text.

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
OrderedArticle	Occurrence 1 .. 1 Remark Article information	
xsd:sequence	Occurrence 1 .. 1	
ArticleIdentification	Occurrence 1 .. 1 Remark Normally the EAN is mandatory because it's used as primary key to identify the article on manufacturers side.	The customer MUST send either the EAN code or the supplier product code. The reason for this is that the supplier does not know the product code assigned by the customer. Nevertheless, if the customer wishes to send as well his product code, the supplier will store this number on the sales order, will print it on the delivery documents (on request) and will return it in all subsequent EDI messages (order confirmation, delivery, invoice). Not supported by some manufacturers. Before starting the electronic business, there has to be a bilateral agreement between the customer and supplier which codes will be used for article identification. The customer MUST send either the EAN code or the supplier product code. Michelin send the EAN and the Manufacturers Article ID. If he has the info, he also send the Customer Article ID for info.
xsd:sequence	Occurrence 1 .. 1	
BuyersArticleID	Occurrence 0 .. 1 Length .. 17 Name Buyer article number Descr. Identification of the article, assigned by the buyer	
ManufacturersArticleID	Occurrence 0 .. 1 Length .. 35 Name Manufacturer's article number Descr. Identification of the article, assigned by the manufacturer. Remark A sent EAN number has priority compared with a manufacturer assigned article number. If there is no EAN number, then a manufacturer assigned article number is mandatory. Remark A sent EAN number has priority compared with a manufacturer assigned article number.	
EANUCCArticleID	Occurrence 0 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
	Length .. 14 Name EANUCC Article number Remark The use of any other number than the 13 digit GTIN (Global Trade Item Number, known as EAN Number) has to be agreed bilaterally. Remark The 13 digit GTIN (Global Trade Item Number, known as EAN Number) is used.	
RequestedDeliveryDate	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Requested delivery date Descr. The meaning of the requested delivery date can vary from supplier to supplier and from customer to customer. Sometimes the customer has a contractual agreement with the supplier to have planned delivery dates so the meaning of the requested delivery date can change. In any case, before implementing this message, contact your supplier to agree on the exact meaning of this field.	
RequestedDeliveryTime	Occurrence 0 .. 1 Name Delivery Time Descr. Hour of delivery at the place of deliver, Including time zone. Pattern \d{2}:\d{2}:\d{2}/(?:Z [-+](?:2[0-3] [01][0-9]):[0-5][0-9])\$/ Example : 18:00:00-06:30 or 18:00:00Z	
RequestedQuantity	Occurrence 1 .. 1	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1 TotalDigits 15 Name Requested quantity	

Bold = Element, Italic = Attribute, Grey = Group