



Message Implementation Guideline

Order response

C1

Issue date: 2021-06-08
Author: wdk/BRV/GEFEG

Please check with your supplier whether this specific version is supported by its organization.

Occurrence Element / Attribute

	order_response
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	Variant
0 .. 1	EarliestDeliveryDate
0 .. 1	TransportPriority
0 .. 1	Campaign
0 .. 1	PickUp
0 .. 1	DeliveryOption
0 .. 1	DeliveryRemarks
1 .. 1	ErrorHead
1 .. 1	xsd:sequence
1 .. 1	ErrorCode
0 .. 1	BlanketOrderReference
1 .. 1	xsd:sequence
1 .. 1	DocumentID
1 .. 1	CustomerReference
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	SellerParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
0 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneNumberExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	SupplierParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
0 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneNumberExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
1 .. 1	BuyerParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode

Occurrence	Element / Attribute
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
0 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneNumberExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	OrderingParty
1 .. 1	xsd:sequence
1 .. 1	PartyID
1 .. 1	AgencyCode
0 .. 1	Consignee
1 .. 1	xsd:sequence
0 .. 1	PartyID
0 .. 1	AgencyCode
0 .. 4	Name
0 .. 1	Address
1 .. 1	xsd:sequence
0 .. 3	Street
1 .. 1	City
0 .. 1	District
0 .. 1	PostCode
0 .. 1	SubCountry
1 .. 1	CountryCode
0 .. 1	Geolocation
1 .. 1	xsd:sequence
1 .. 1	Latitude
1 .. 1	Longitude
0 .. 1	InformationContact
1 .. 1	xsd:sequence
0 .. 1	ContactID
0 .. 2	Name
0 .. 1	TelephoneNumber
0 .. 1	TelephoneNumberExtension
0 .. 1	FaxNumber
0 .. 1	EmailAddress
0 .. 1	Contract
1 .. 1	xsd:sequence
1 .. 1	DocumentID
0 .. 1	PaymentTerms
1 .. 1	xsd:sequence
1 .. 1	PaymentMethod
0 .. 1	CurrencyCode
0 .. 1	Charge
1 .. 1	xsd:sequence
1 .. 1	ChargeCategory
0 .. 1	ChargeAmount
1 .. 1	xsd:sequence
1 .. 1	AmountValue
0 .. 1	ChargePercent
1 .. unbounded	OrderLine
1 .. 1	xsd:sequence
1 .. 1	LineID
0 .. 1	SuppliersOrderLineID
0 .. 1	AdditionalCustomerReferenceNumber
1 .. 1	xsd:sequence
1 .. 1	DocumentID

Occurrence	Element / Attribute
1 .. 1	OrderedArticle
1 .. 1	xsd:sequence
1 .. 1	ArticleIdentification
1 .. 1	xsd:sequence
0 .. 1	BuyersArticleID
0 .. 1	ManufacturersArticleID
0 .. 1	EANUCCArticleID
1 .. 1	ArticleDescription
1 .. 1	xsd:sequence
1 .. 1	ArticleDescriptionText
0 .. 1	RequestedDeliveryDate
0 .. 1	RequestedDeliveryTime
0 .. 1	Availability
0 .. 1	ArticleComment
1 .. 1	OrderReference
1 .. 1	xsd:sequence
1 .. 1	DocumentID
1 .. 1	Error
1 .. 1	xsd:sequence
1 .. 1	ErrorCode
0 .. 1	ErrorText
1 .. unbounded	ScheduleDetails
1 .. 1	xsd:sequence
1 .. 1	DeliveryDate
0 .. 1	DeliveryTime
1 .. 1	ConfirmedQuantity
1 .. 1	xsd:sequence
1 .. 1	QuantityValue
0 .. 1	TransportMode
0 .. 1	PriceDetails
1 .. 1	xsd:sequence
1 .. 1	NetUnitPrice
1 .. 1	xsd:sequence
1 .. 1	PriceAmount
0 .. unbounded	Charge
1 .. 1	xsd:sequence
1 .. 1	ChargeCategory
0 .. 1	ChargeAmount
1 .. 1	xsd:sequence
1 .. 1	AmountValue
0 .. 1	ChargePercent
0 .. 1	KilledQuantity
1 .. 1	xsd:sequence
1 .. 1	QuantityValue
1 .. 1	OrderedQuantity
1 .. 1	xsd:sequence
1 .. 1	QuantityValue

Element/Attribute	Annotation	User Comments
order_response		Identification numbers and text: The allowed characters are [a-z, A-Z,0-9 and the underscore '_']. The terms 'Mandatory', 'must be used', 'has to be used' and any min occurrence greater than '0' mean that an XML element must be sent with a value in it .
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Fixed C1 Length .. 17 Name Message version Descr. Identification of Message version Remark This field should only contain 'C1' as fix value.	
Variant	Occurrence 0 .. 1 Fixed 0 Length 1 Remark The variant of this release is "0"	
EarliestDeliveryDate	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Earliest delivery date Descr. Earliest delivery date at the place of delivery. Remark This header information provides optimization in the logistic.	
TransportPriority	Occurrence 0 .. 1 Length .. 4 Remark In order to express that the order is a normal order the element must not be used. Name Transport priority Remark This information is mainly used in the order message and is not supported by all suppliers. Remark The customer can inform the supplier how this order should be handled. If the element is not used it means the order will be handled by the supplier under the default way and the goods will be delivered within the default delivery scheme or according to the RequestDeliveryDates provided at line level. The default delivery schemes are supplier/customer/country specific and therefore not specified in this documentation.	Rush: If the customer wants to receive delivery faster than the agreed regular terms, then he can use this element to inform the supplier that the order must be treated differently from the usual case. As mentioned before, the delivery terms are agreed as a default at the supplier/ customer level so they can be specified differently on a case by case basis. The rush order simply means that the goods ordered in this order should be delivered faster as usual. Replenishment: It means that the customer either sends an order for which he does not expect an exact timing or sends an order for which the supplier will compute the contractual RequestedDeliveryDate. It should be used only on bilateral agreement between the customer and the

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Before starting any integration, the customer and the supplier must agree on what is the normal delivery term.	supplier. Note some suppliers in some countries will confirm the dates for such kind of order so the rule should be if date is confirmed, than it means the supplier will deliver on those dates, if the date is 99991231, than no exact date is confirmed in the order confirmation message and it means as well that the suppliers customer service will contact the customer to agree on delivery dates and quantities. There are no general rules about the volume or about the way the supplier is processing this replenishment orders.
	Applicable Codes REPL Replenishment The order has to be processed following the supplier's replenishment delivery scheme. Depending on the supplier it can mean that in the order response, - the delivery dates and quantities are not calculated at request time but later. In this case the order response returns 99991231, meaning the delivery dates cannot be committed.- the delivery dates and quantities are calculated based on the replenishment scheme of the supplier and provided requested dates. RUSH Rush Order SEAS Seasonal order Seasonal order means that there will never be a confirmed delivery date in the order confirmation message. The requested delivery date will be considered as a starting date by when the first shipments should take place. Nevertheless, the suppliers customer service will always contact the	Seasonal orders: This transport priority means that the customer is purchasing goods for a whole season (winter or summer). Knowing that these orders are containing big quantity of tyres and that the delivery of these goods has to be spread over the whole period, the exact delivery dates will not be confirmed in the order confirmation message. The actual procedures will remain meaning the customer service will contact regularly the customer to agree on which quantity should be delivered by when.

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Applicable Codes dealer to agree exactly what and when will be delivered.	
– Campaign	Occurrence 0 .. 1 Length .. 12 Name Campaign Descr. Identification of a Campaign/ a Promotion.	This information is mainly used in the order / order confirmation message and is optional. Not supported by all suppliers. This element is used to identify if the order is related to a sales campaign/promotion. The content of the element should be the campaign number given by the supplier. As for each functionality, the customer must check before implementing the automatic ordering with the supplier if a given functionality is supported or not by the supplier.
– Pickup	Occurrence 0 .. 1 Length .. 1 Name Pickup Descr. Flag to specify if the Customer in the Inquiry or Order requires to pick-up the goods at supplier's location.	
	Applicable Codes Y Yes	
– DeliveryOption	Occurrence 0 .. 1 Length .. 3 Name Delivery option Descr. Examples: IA = Package, display, wooden IB = Package, display, cardboard IC = Package, display, plastic ID = Package, display, metal OA = Pallet, CHEP 40 cm x 60 cm OB = Pallet, CHEP 80 cm x 120 cm OC = Pallet, CHEP 100 cm x 120 cm OD = Pallet, AS 4068-1993 OE = Pallet, ISO T11 Link UN/EDIFACT Data Element 7065, and more precisely UN/ ECE Recommendation 21, Annex V, alphabetic codes https://www.unece.org/fileadmin/DAM/cefact/recommendations/rec21/rec21_Rev9e_2012.xls	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
DeliveryRemarks	Occurrence 0 .. 1 Length .. 70 Name Delivery Remarks	Optional field. Not supported by all suppliers. This field could be used to give additional information about delivery purposes.
ErrorHead	Occurrence 1 .. 1 Name Error code information	
xsd:sequence	Occurrence 1 .. 1	
ErrorCode	Occurrence 1 .. 1 Length .. 3 Name Error code Applicable Codes	
	0 No errors occurred 1 At least one item is incorrect. Details are distinctive in the error field on item level 301 No connection to ERP system (order) 303 No connection to ERP system 304 Request to ERP - System disconnected 399 Miscellaneous - connection error 403 Error during order processing in ERP 404 Order only processed partially 405 Timeout during processing in ERP system 499 Miscellaneous - processing error 901 Document number invalid [identification number of document, blanket order reference, customer reference, additional customer reference number] 902 Too many items (order lines, despatch note lines) 905 No items in message 906 Customer reference number already used - (valid only for orders where the reference MUST be unique) 907 Invalid consignee (ship-to) party ID number 908 No authority to select consignee (ship-to) 909 The mandatory customer reference number is missing in the order 910 Internal error in ad hoc system 912 Requested delivery date invalid 913 Invalid consignee (ship-to) party ID number 914 Missing buyer (sold-to) identification number 915 Buyer (sold-to) party ID number invalid	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
Applicable Codes		
916	Adhoc version number incorrect (document ID or variant)	
917	Incorrect ad hoc message type	
918	No authority to specify earliest requested (header level) or requested (item level) delivery date	
919	No authority for brand/sales organisation	
920	Account not activated for this buyer (sold-to) party ID number	
921	Access permission password is expired	
922	Incorrect/invalid blanket order (contract) number	
924	Incorrect buyer (sold-to) agency code qualifier	
925	Incorrect consignee (ship-to) agency code qualifier	
926	Missing mapping for the customer assigned buyer (sold-to) party ID	
927	Missing mapping for the customer assigned consignee (ship-to) party ID	
929	Incorrect promotion (campaign) code (wrong value)	
930	Incorrect payment method code	
932	Buyer (sold-to) definition error in supplier system (sales area, deletion indicator etc.)	
934	Customer not allowed to create backorders	
935	Order can not be created, at least one line is in error	
936	Wrong buyer - consignee combination (sold-to/ship-to combination)	
937	Consignee (ship-to) definition error in supplier system (sales area, deletion indicator etc.)	
938	All items in error, no sales order created	
939	Wrong or not allowed order type (transport priority)	
943	Error in ERP system during creation of sales order	
944	Promotion (campaign) code validity period expired	
946	Ad hoc version number missing	
950	No authority to use this message type	
954	Address definition invalid	
955	Attachment file(s) missing	
956	Attachment not readable	
958	Incorrect/invalid delivery option code	
959	No authority to use/invalid pickup option	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
BlanketOrderReference xsd:sequence DocumentID	Applicable Codes 960 Incorrect/invalid consignee address 961 Supplier Party ID /address invalid 962 Seller Party ID /address invalid 999 Miscellaneous	This value is used only in the order message. Not supported by all suppliers.
	Occurrence 0 .. 1	
	Remark Equivalent EDIFACT code is BO	
	Name Blanket order reference information	
	Occurrence 1 .. 1	
	Occurrence 1 .. 1	
	Length .. 35	
	Name Reference to contract number	
	Descr. Reference to the contract referring to the present order.	
	Occurrence 1 .. 1	
CustomerReference xsd:sequence DocumentID	Occurrence 1 .. 1 Name Customer reference information Remark User who is doing / establishing the sales contract by a legal way. In other words it's the user who's doing the business contract with the supplier and who takes the legal responsibility. Depending the customers organisation it could be a central purchasing department (headquarter) or a main dealer.	Only used in the order message. If a customer reference is sent within an inquiry the supplier will simply ignore it and return as received.
	Occurrence 1 .. 1	
	Occurrence 1 .. 1	
	Length .. 35	
	Name Document ID	
	Descr. Identification of the document	
	Occurrence 0 .. 1	
	Occurrence 1 .. 1	
	Occurrence 1 .. 1	
	Length .. 17	
SellerParty xsd:sequence PartyID AgencyCode	Occurrence 1 .. 1 Occurrence 1 .. 1 Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list.	
	Occurrence 1 .. 1	
	Length .. 3	
	Name Code list responsible agency, coded	
	Remark Code identifying the agency responsible for a code list.	
	Applicable Codes	
	9 EAN (International Article Numbering association)	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
Applicable Codes		
	91 Assigned by seller or seller's agent	
	92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 0 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 40	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
SupplierParty	Occurrence 0 .. 1 Name Supplier identification Descr. Identification of a supplier	In North America supplier is preferred to identify the selling and supplying party. Seller is only included when the party actually differs from the supplier.
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Identification number supplier Descr. Identification number supplier	
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list.	
Applicable Codes		
9 EAN (International Article Numbering association)		
91 Assigned by seller or seller's agent		
92 Assigned by buyer or buyer's agent		
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 0 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 40	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present.	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
- xsd:sequence ContactID - Name Information contact - Occurrence 1 .. 1 - Length .. 17 Name - Occurrence 0 .. 2 - Length .. 40 TelephoneNumber - Occurrence 0 .. 1 - Length .. 100 TelephoneExtension - Occurrence 0 .. 1 - Length .. 100 FaxNumber - Occurrence 0 .. 1 - Length .. 100 EmailAddress - Occurrence 0 .. 1 - Length .. 256 BuyerParty - Occurrence 1 .. 1 - Remark Contracting party, e.g. party who is doing / establishing the sales contract by a legal way. In other words it's the entity who's doing the business contract with the supplier and who takes the legal responsibility. Depending on the customers organisation it could be a central purchasing department (headquarter) or a main dealer. - xsd:sequence PartyID - Occurrence 1 .. 1 - Length .. 17 - Name Buyer ID - Descr. Identification number of a buyer. AgencyCode - Occurrence 1 .. 1 - Descr. Code identifying the agency responsible for a code list. - Length .. 3 - Name Code list responsible agency, coded - Remark Code identifying the agency responsible for a code list. - Name Type of the buyer's identification number. - Descr. Code identifying the agency responsible for a code list.	Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent	By the party ID, called buyer party, is considered the number which identifies the purchasing party. In other words, who is demanding goods. Depending on the customer organisation, it might be the same as the ship-to (consignee) or the same as the invoice payer.

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
Applicable Codes		
	92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 0 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 40	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
OrderingParty	Occurrence 0 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Remark The initial ordering / stipulating party is the partner who is placing/creating the purchase order in the customer system. This element has to be used when the ordering party is different from the buyer (example shop versus head office). Note: This level is not supported by all manufacturers.	
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 1 .. 1 Length .. 17 Name Ordering Party ID	
AgencyCode	Occurrence 1 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded Remark Code identifying the agency responsible for a code list. Name Type of the ordering party's identification number.	
	Applicable Codes	
	9 EAN (International Article Numbering association)	
	91 Assigned by seller or seller's agent	
	92 Assigned by buyer or buyer's agent	
Consignee	Occurrence 0 .. 1 Remark The delivery address in the header is valid for all items. Indicating a consignee [ship-to] on the item level, which differs from the consignee specified on the header level, is not possible. Remark If the delivery address is not identical with the buyer address, a consignee has to be sent. Exception: if a note in the supplier's system indicates that the goods have always to be delivered to another recorded address, then it is not necessary to send a separate consignee.	This code is used to identify the address where the goods are to be sent. For the supplier this address is where the goods will be shipped (ship-to address). The customer has to agree upfront with the supplier which are the concerned ship-to addresses for a given sold-to.
xsd:sequence	Occurrence 1 .. 1	
PartyID	Occurrence 0 .. 1 Length .. 17 Name Identification consignee/delivery address	
AgencyCode	Occurrence 0 .. 1 Descr. Code identifying the agency responsible for a code list. Length .. 3 Name Code list responsible agency, coded	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Remark Code identifying the agency responsible for a code list. Name Type of the consignee's identification number. Applicable Codes 9 EAN (International Article Numbering association) 91 Assigned by seller or seller's agent 92 Assigned by buyer or buyer's agent	
Name	Occurrence 0 .. 4 Length .. 40	
Address	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Street	Occurrence 0 .. 3 Length .. 40	
City	Occurrence 1 .. 1 Length .. 40	
District	Occurrence 0 .. 1 Length .. 30	
PostCode	Occurrence 0 .. 1 Length .. 10	
SubCountry	Occurrence 0 .. 1 Length .. 70	
CountryCode	Occurrence 1 .. 1 Length .. 3 Remark Use ISO 2 Alpha country code list	
Geolocation	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
Latitude	Occurrence 1 .. 1 Length .. 10 Pattern (\+ -)?(((0-8)[0-9])(\.[0-9]{1,6})?)? 90) Name Latitude as decimal degrees (between -90 and +90) Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format. Example -89.345543, 01.45, +25.23456	
Longitude	Occurrence 1 .. 1 Length .. 11 Pattern (\+ -)?((0[0-9]{2}) 1[0-7][0-9])(\.[0-9]{1,6})? 180) Name Longitude as decimal degrees (between -180 and +180)	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Remark The use of decimal coordinates for the Geolocation element is compliant with ISO 6709 and will be used for the format. Example -145.956083, 092.123,+005.12345	
InformationContact	Occurrence 0 .. 1 Remark One of the attributes of the contact has to be present. Name Information contact	
xsd:sequence	Occurrence 1 .. 1	
ContactID	Occurrence 0 .. 1 Length .. 17	
Name	Occurrence 0 .. 2 Length .. 40	
TelephoneNumber	Occurrence 0 .. 1 Length .. 100	
TelephoneExtension	Occurrence 0 .. 1 Length .. 100	
FaxNumber	Occurrence 0 .. 1 Length .. 100	
EmailAddress	Occurrence 0 .. 1 Length .. 256	
Contract	Occurrence 0 .. 1 Name Contract number, reference to the sales agreement Remark To identify the sales agreement (ie, contract number) that needs to be used in a transaction.	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Length .. 17 Name Document ID Descr. Identification of the document	
PaymentTerms	Occurrence 0 .. 1 Name Payment terms information	
xsd:sequence	Occurrence 1 .. 1	
PaymentMethod	Occurrence 1 .. 1 Length .. 10 Remark In order to express that the normal payment method (by Invoice) is used the element (i.e. the element group) must not be used.	This functionality is not supported by all suppliers. In some European markets, the customer might get a different discount depending on the payment method. For example paying cash at delivery, he could have a 2% extra discount, or paying by a Visa card. This option is supplier/customer dependent so before

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Name Payment method Descr. Identification of the method of payment.	using this field, a preliminary bilateral agreement is required.
	Applicable Codes C Cash K Credit Card	If not used, the supplier will apply the usual agreed payment terms.
- CurrencyCode	Occurrence 0 .. 1 Length .. 3 Remark The currency will be indicated only if the price information is provided.	
- Charge	Occurrence 0 .. 1	
- xsd:sequence	Occurrence 1 .. 1	
- ChargeCategory	Occurrence 1 .. 1 Applicable Codes AEV Environmental protection service AAB Returned goods charges Self-explanatory. AAT Rush delivery Charge for increased delivery speed. ABF Tooling The service of providing specific tooling. ABL Packaging surcharge Additional charge for packaging of items. ACS Fitting Fitting service. ADR Other services A code indicating that other non-specific services are in operation. ADZ Direct delivery Direct delivery service. CAU Sorting The provision of sorting services. DAD Driver assigned unloading The service of unloading by the driver. DL Delivery The service of providing delivery.	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
Applicable Codes		
FC	Freight charge Amount to be paid for moving goods, by whatever means, from one place to another, inclusive discounts, allowances, rebates, adjustment factors and additional cost relating to freight costs (UN/ECE Recommendation no 23).	
FH	Filling/handling The service of providing filling/handling.	
FI	Finance charge Description to be provided.	
HD	Handling Handling service.	
IN	Insurance Charge for insurance.	
PAD	Promotional allowance Description to be provided.	
PL	Palletizing The service of palletizing.	
QAA	Quantity surcharge Fee associated with providing goods outside "normal" quantity limits.	
QD	Quantity discount Description to be provided.	
RF	Refurbishing The service of refurbishing.	
SAD	Special packaging The service of special packaging.	
TD	Trade discount Description to be provided.	
V1	Heavy truck fee	
ZZZ	Mutually defined Self explanatory.	
ChargeAmount	Occurrence 0 .. 1	
<i>xsd:sequence</i>	Occurrence 1 .. 1	
AmountValue	Occurrence 1 .. 1	
	TotalDigits 10	
ChargePercent	Occurrence 0 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
OrderLine	TotalDigits 7 Occurrence 1 .. unbounded Name Line item information Remark It should be checked with each supplier what the supported maximum occurrence is.	
xsd:sequence	Occurrence 1 .. 1	
LineID	Occurrence 1 .. 1 Length .. 6 Name Line identification number Descr. Identification of a line in a document	This is the customer assigned purchase order line number.
SuppliersOrderLineID	Occurrence 0 .. 1 Length .. 6 Name Suppliers's Order Line Number Descr. Supplier assigned number of a line of a sales order Remark This field will not be provided by all suppliers.	
AdditionalCustomerReferenceNumber	Occurrence 0 .. 1 Name Additional Customer's reference information	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Length .. 35 Name Document ID Descr. Customer's reference to the business transaction on item level.	If the customer wants to have more references (ex. 4 tyres for Mr. Smith) by sending this to the supplier, the supplier can print this information on the delivery document. The information in this field is not checked on the supplier side and is taken there as a kind of free text.
OrderedArticle	Occurrence 1 .. 1 Remark Article information	
xsd:sequence	Occurrence 1 .. 1	
ArticleIdentification	Occurrence 1 .. 1 Remark Normally the EAN is mandatory because it's used as primary key to identify the article on manufacturers side.	The customer MUST send either the EAN code or the supplier product code. The reason for this is that the supplier does not know the product code assigned by the customer. Nevertheless, if the customer wishes to send as well his product code, the supplier will store this number on the sales order, will print it on the delivery documents (on request) and will return it in all subsequent EDI messages (order confirmation, delivery, invoice). Not supported by some manufacturers.

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
		Before starting the electronic business, there has to be a bilateral agreement between the customer and supplier which codes will be used for article identification. The customer MUST send either the EAN code or the supplier product code. Michelin send the EAN and the Manufacturers Article ID. If he has the info, he also send the Customer Article ID for info.
xsd:sequence	Occurrence 1 .. 1	
BuyersArticleID	Occurrence 0 .. 1 Length .. 17 Name Buyer article number Descr. Identification of the article, assigned by the buyer	
ManufacturersArticleID	Occurrence 0 .. 1 Length .. 35 Name Manufacturer's article number Descr. Identification of the article, assigned by the manufacturer. Remark A sent EAN number has priority compared with a manufacturer assigned article number. If there is no EAN number, then a manufacturer assigned article number is mandatory.	
EANUCCArticleID	Occurrence 0 .. 1 Length .. 14 Name EANUCC Article number Remark The 13 digit GTIN (Global Trade Item Number, known as EAN Number) is used.	
ArticleDescription	Occurrence 1 .. 1	
xsd:sequence	Occurrence 1 .. 1	
ArticleDescriptionText	Occurrence 1 .. 1 Length .. 60 Name Article description	This is the product description provided by the supplier. It can be useful for the customer especially in the case he is asking for substitution products. It could be as well interesting for the customer to cross check with his own description.
RequestedDeliveryDate	Occurrence 0 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Name Requested delivery date Descr. The meaning of the requested delivery date can vary from supplier to supplier and from customer to customer. Sometimes the customer has a contractual agreement with the supplier to have planned delivery dates so the meaning of the requested delivery date can change. In any case, before implementing this message, contact your supplier to agree on the exact meaning of this field.	
RequestedDeliveryTime	Occurrence 0 .. 1 Name Delivery Time Descr. Hour of delivery at the place of deliver, Including time zone. Pattern \d{2}:\d{2}:\d{2}/(?:Z [-+](?:2[0-3] [01][0-9]):[0-5][0-9])\$/ Example : 18:00:00-06:30 or 18:00:00Z	
Availability	Occurrence 0 .. 1 Length .. 1 Name Availability Applicable Codes 0 Error, no availability could be determined. 1 The article is immediately available in the requested quantity 2 The article is not available in the requested quantity for the requested delivery date, so temporarily delays or partial deliveries could occur. Here the announced actual quantity should be considered. 3 The article is currently not available.	
ArticleComment	Occurrence 0 .. 1 Length .. 60 Name Article comment Descr. The supplier can add additional information about the article.	
OrderReference	Occurrence 1 .. 1 Name Order reference information	
xsd:sequence	Occurrence 1 .. 1	
DocumentID	Occurrence 1 .. 1 Length .. 35 Name Document ID	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Descr. Identification of the document. Remark The allowed characters are [a-z, A-Z,0-9 and the underscore '_'].	
Error	Occurrence 1 .. 1 Name Error code information	
xsd:sequence	Occurrence 1 .. 1	
ErrorCode	Occurrence 1 .. 1 Length .. 3 Name Error code Remark Code 903 should only be used in old versions.	
Applicable Codes		
	0 No errors occurred	
	499 Miscellaneous - processing error	
	902 Too many items (order lines, despatch note lines)	
	903 Invalid article identification code	
	904 Quantity value invalid, must be greater than 0	
	911 Incorrect EAN number (not known on supplier side)	
	912 Requested delivery date invalid	
	918 No authority to specify earliest requested (header level) or requested (item level) delivery date	
	919 No authority for brand/sales organisation	
	928 Mandatory EAN code missing for this line	
	931 Material definition error in supplier system (sales view, plant view, prices etc)	
	933 This material can not be ordered via ad hoc EDI EDI (In this case a substituting article can be proposed if the substitution indicator has been flagged in the inquiry).	
	940 Incorrect supplier material number (not known on supplier side)	
	941 Wrong EAN/supplier material number combination	
	942 Maximum allowed quantity overpassed	
	945 Material status set to not sellable (material can not be purchased anymore) (In this case a substituting article can be proposed if the substitution indicator has been flagged in the inquiry).	
	970 Manufacturers order number invalid or not found	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
Applicable Codes		
	971 Customers order number invalid or not found	
	972 Requested delivery date out of authorised period horizon	
	973 Material is temporarily orderable only by phone. For more details contact the call centre (In this case a substituting article can be proposed if the substitution indicator has been flagged in the inquiry).	
	974 The ordered quantity is not equal to the content of the packaging, or does not correspond to the multiple of the packaging content.	
	975 Quantity value invalid. Must be an integer value.	
ErrorText	Occurrence 0 .. 1 Length .. 60 Name Error text Descr. Detailed explanations of an error, that has occurred.	The error text provided by the supplier has to be in English. It's recommended to translate the error code definition by the customers software providers in the country specific language.
ScheduleDetails	Occurrence 1 .. unbounded Remark If both Delivery Date and Delivery Period are allowed then they shall be used mutually exclusive.	In practice, a requested quantity for a requested date can be split in several partial deliveries: the supplier will send back a kind of 'delivery schedule proposal' called in all documents 'Schedule details'.
xsd:sequence	Occurrence 1 .. 1	
DeliveryDate	Occurrence 1 .. 1 Length 10 Pattern \d{4}-\d{2}-\d{2} Example 2008-31-01 Name Date of delivery Descr. Date of delivery at the place of delivery Remark If no date can be reflected by the ERP system, then the field will be set to 9999-12-31.	The date 9999-12-31 will be returned in case if no delivery date could be determined. This is the date on which the supplier is forecasting the arrival of the goods at the consignee / ship-to address. Note if the ship-to address is very far from the suppliers warehouse the exact timing could be different.
DeliveryTime	Occurrence 0 .. 1 Name Delivery Time Descr. Hour of delivery at the place of deliver, Including time zone. Pattern \d{2}:\d{2}:\d{2}/(?:Z [-+](?:2[0-3][01][0-9]:[0-5][0-9])\$/ Example : 18:00:00-06:30 or 18:00:00Z	
ConfirmedQuantity	Occurrence 1 .. 1	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
xsd:sequence QuantityValue	Occurrence 1 .. 1 Occurrence 1 .. 1 TotalDigits 15 Name Confirmed quantity	
TransportMode	Occurrence 0 .. 1 Descr. Coded method of transport used for the carriage of the goods. Name Note: Use UN/ECE Recommendation No 19. Mode of transport, coded Remark Coded method of transport used for the carriage of the goods. Note: Use UN/ECE Recommendation No 19. Applicable Codes 1 Maritime transport This code should be used whenever the transport vehicle completes any part of its journey by sea. 2 Rail transport 3 Road transport 4 Air transport 5 Mail (Actual mode of transport unknown) - This code is provided for practical reasons, despite the fact that mail is not a genuine mode of transport. In many countries, the value of merchandise exported by mail is considerable, but the exporter or importer concerned would be unable to state by which mode postal items had passed the national border. 6 Multimodal transport This code is used when goods are carried to their destination by at least two different modes on the basis of one transport contract. (Local pick-up and delivery of goods out in the performance of a unimodal transport contract shall not be considered as multimodal transport.) 7 Fixed transport installations This code applies to installations for continuous transport such as pipelines, ropeways and electric	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
	Applicable Codes	
	8 power lines. Inland water transport This code is used only where carriage is effected entirely by inland water transport.	
	9 Mode unknown This code can be used when the mode is not known or when information on it is not available at the time of issuing the document concerned.	
PriceDetails	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
NetUnitPrice	Occurrence 1 .. 1	
	Name Net unit price	
	Descr. The price per price unit where surcharges and reductions are included.	
xsd:sequence	Occurrence 1 .. 1	
PriceAmount	Occurrence 1 .. 1	
	TotalDigits 10	
Charge	Occurrence 0 .. unbounded	
xsd:sequence	Occurrence 1 .. 1	
ChargeCategory	Occurrence 1 .. 1	
	Applicable Codes	
	AEV Environmental protection service	
	AAB Returned goods charges Self-explanatory.	
	AAT Rush delivery	
	ABF Charge for increased delivery speed. Tooling	
	ABL The service of providing specific tooling. Packaging surcharge	
	ACS Additional charge for packaging of items. Fitting	
	ADR Fitting service. Other services	
	ADZ A code indicating that other non-specific services are in operation. Direct delivery	

Bold = Element, Italic = Attribute, Grey = Group

XML - INDUSTRIAL SOLUTION

Description



Element/Attribute	Annotation	User Comments
	Applicable Codes	
	CAU Direct delivery service. Sorting	
	DAD The provision of sorting services. Driver assigned unloading	
	DL The service of unloading by the driver. Delivery	
	FC The service of providing delivery. Freight charge	
	FH Amount to be paid for moving goods, by whatever means, from one place to another, inclusive discounts, allowances, rebates, adjustment factors and additional cost relating to freight costs (UN/ECE Recommendation no 23). Filling/handling	
	FI The service of providing filling/handling. Finance charge	
	HD Description to be provided. Handling	
	IN Handling service. Insurance	
	PAD Charge for insurance. Promotional allowance	
	PL Description to be provided. Palletizing	
	QAA The service of palletizing. Quantity surcharge	
	QD Fee associated with providing goods outside "normal" quantity limits. Quantity discount	
	RF Description to be provided. Refurbishing	
	SAD The service of refurbishing. Special packaging	
	TD The service of special packaging. Trade discount	
	V1 Description to be provided. Heavy truck fee	

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation	User Comments
Applicable Codes ZZZ Mutually defined Self explanatory.		
ChargeAmount	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
AmountValue	Occurrence 1 .. 1	
	TotalDigits 10	
ChargePercent	Occurrence 0 .. 1	
	TotalDigits 7	
KilledQuantity	Occurrence 0 .. 1	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1	
	TotalDigits 15	
	Name Killed Quantity	
	Descr. Killed Quantity is linked to Fill and/or Kill processes: Fill And Kill (FAK): a FAK order is an order to buy or sell a stock without any backorder. In case of partial availability, only the available quantity is ordered. The rest is killed at order confirmation (that is to say when the orderresponse is generated) and no trace of this killed quantity is kept in the back-end systems. Fill Or Kill (FOK): a FOK order is an order to buy or sell a stock that must be executed immediately in its entirety. Otherwise the entire order is killed (no partial fulfillment is allowed) and no trace of this killed order is kept in the back-end systems – Wikipedia –	
OrderedQuantity	Occurrence 1 .. 1	
xsd:sequence	Occurrence 1 .. 1	
QuantityValue	Occurrence 1 .. 1	
	TotalDigits 9	
	Name Ordered quantity	

Bold = Element, Italic = Attribute, Grey = Group