

 Sae-A Trading Co., Ltd.		One Sae-A, One Quality [Wear & Wash Test]		Doc. No. : EN54
				Version # : 1.0
				Date Created : Jun. 30. 2021
				Date Revised : Jun. 30. 2021
Prepared by	Sula Hwang	Department	HQ Sales/Washing Innovation/ QA/Sewing Factory	
Approved by	Connie Park	Date Validation	Until New Advise	
Objective	Predict and prevent possible risk during wearing and washing garments at customer's end. Experts from each department will review test result, and if there is any risk, callout internally and suggest preventive/corrective action. In order to understand quality and enforce capabilities of their own, Sae-a employees will wear and test garments by themselves.			
Note : If current SOP content differs from Sae-a Manual or data, this SOP takes precedence.				
Description of Activities				
No.	Section/ Responsible	Activities	Documentation of work	
1		Definition Thorough the test verify unexpected risk such as functionality/durability that is difficult to detect during normal visual inspection by performing customer's actual garment wearing as similar as possible. If there is possible risk consult with related departments and search for preventive/corrective action.		
2	HQ Sales/WI HQ Sales/WI Fabric Sourcing/HQ Sales/WI QA	Applicable Style If style is applicable for one or more than following conditions, conduct Wear & Wash test. 1) Special Washing : Lunar/ Comet / Indigo / Burnout / Mineral and etc. Special Dyeing : Tie Dye / Dip Dye / Sundry and etc. 2) Not included in 1) but HQ Sales/WI developed recipe with high level of complexity and considered as special washing & dyeing requiring to conduct Wear & Wash test. 3) Fabric Sourcing/ WI/HQ Sales consider high risk style due to pilling, rubbing colorfastness, color change and etc. 4) Decided during RAP Meeting or PPM that Wear & Wash Test is necessary.		
3	QA/Sewing Factory QA/Sewing Factory HQ Sales HQ Sales	Live model Selection <u>Sewing Factory</u> 1) Select live model with suitable body measurement. Physically active RnR employee preferred. 2) If additional test is necessary, same color/size should be tested for the same live model for accurate comparison & analysis. <u>HQ Sales</u> 1) Select live model with suitable body measurement. 2) If additional test is necessary, same color/size should be tested for the same live model for accurate comparison & analysis.		
4	QA/Sewing Factory QA/Sewing Factory HQ Sales HQ Sales	When <u>Sewing Factory</u> 1) FPP Samples made with bulk raw material or 1st output garments. 2) If FPP Samples does not cover all colors, remaining colors should be tested among 1st output garments. <u>HQ Sales</u> 1) Receive 1st output garments(1pc per color) from sewing factory. 2) HQ Sales team select color/size for testing and request to sewing factory to send sample.		

5	HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory	Sample Selection Method 1) At least 1pc per color should be tested. 2) Select size with available live model and make sure to test different sizes per color. 3) If fails, additional sample may be requested to sewing factory.	
6	HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory	Testing Method 1) Conduct Wear & Wash test 3 times. - Wear 8H/Day, conduct Wash/Dry 1 cycle. - Repeat Wear & Wash 2 more times. 2) Apply AATCC150 for Wash/Dry, but make sure to Wash/Dry 1 time per test. 3) Piled/brushed fabric or burnout washed garments have possibility of pile/fiber loss. For colored fabric conduct wearing test over the white innerwear, for white fabric black innerwear.	
7	HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory	Pass/Fail Decision <u>Wearing</u> 1) Fit : Live model must check if garment is uncomfortable or limiting movements. 2) Abrasion: Approver* must verify Fabric/Accessories/Artwork durability such as fall off and cracking. 3) Function: Live model must check function including wearing and taking off the garments. 4) Pilling : Approver must rate pilling caused by friction. Use pilling replica to come up with final result. 5) Skin irritation: Wearing live model must check if there is any inconvenience such as itching/scratching. 6) Rubbing Colorfastness : Approver must verify if there is any stain on the live model's skin or innerwear. <i>* Approver</i> <i>Sewing Factory-QA Manager & In-House Lab</i> <i>HQ Sales - Team Manager</i> <u>Washing</u> Follow below instruction for testing. *Sewing factory - In-House lab will conduct testing. **HQ Sales - Use washer/drier located at each floor and rate per category. 1) Shrinkage/Skew: Follow AATCC 150 method and standard for rating. Make sure to wash/dry 1 time per cycle. 2) Appearance: Any type of change after wash such as poor appearance and shape. 3) Colorchange/Bleeding: Verify if there is any color change/staining after wash.	

8	HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory HQ Sales/QA/Sewing Factory	Report Wear & Wash report must be filled out per test(Wash/Dry 1 cycle per test, 3 tests in total). If it is necessary to consult with related departments, share report/specimen(sample) for their comments. 1) After wearing 8H/Day rate according to given standards, fill out comments and add photos according to report format. Take close up photos at the issued part. When there are multiple issues, attach multiple photos. 2) Wash/Dry with 1)garment and rate according to given standards, fill out comments and add photos according to report format. May require multiple photos. 3) Conduct 1) & 2) 3 times repeatedly. 4) If there is any fail or difficult to make decision during 3 tests, consult with related departments such as QA/WI/TD/HQ Sales. 5) Test Report, specimen(sample) must be kept for 3months after last PO's ex-factory date.	Wear & Wash Test Report
---	---	--	--