Product Search
Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.
Please download the latest datasheet of GRM21BR71C475KE51# from the official website of Murata
Data https://pim.murata.com/en-us/pim/details/?partNum=GRM21BR71C475KE51#
Sheet

"#"at the end indicates the package specification code.

GRM21BR71C475KE51#

In Production

Chip Multilayer Ceramic Capacitors for Consumer Electronics & Industrial Equipment

GRM21BR71C475KE51#

"#" at the end indicates the package specification code.

GRM21BR71C475KE51L,GRM21BR71C475KE51K


Applications

Unsuitable Applications	Please be sure to read and comply with these "Precautions for use".
Specific Applications	Consumer equipment,Industrial Equipment,Automotive infotainment/comfort equipment,Medical equipment [GHTF A/B/C] except for implant equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued
without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Chip size code (mm/inch)	2012M/0805
Length	2mm ±0.15mm
Width	1.25mm ±0.15mm
Thickness	1.25mm ±0.15mm
External terminal size€	0.2～0.7mm

Specifications

Temperature characteristics (complied standard)	EIA
Temperature characteristics	X7R
Temperature range of temperature characteristics	-55～125℃
Operating Temperature	-55～125℃
Capacitance	4.7μF

Tolerance of capacitance	±10%
Rated Voltage DC	16Vdc

References

Packaging	Specifications	Standard Packing Quantity
L	φ180mm Reel W8P4* Embossed Tape	3000
K	φ330mm Reel W8P4* Embossed Tape	10000

Mass(Typ.)	
1 piece	19mg