


SQL Cheat Sheet: Basics

| Command | Syntax | Description | Example |
|----------|--|--|--|
| SELECT | SELECT column1, column2, ... FROM table_name; | SELECT statement is used to fetch data from a database. | SELECT city FROM placeofinterest; |
| WHERE | SELECT column1, column2, ...FROM table_name WHERE condition; | WHERE clause is used to extract only those records that fulfill a specified condition. | SELECT * FROM placeofinterest WHERE city = 'Rome' ; |
| COUNT | SELECT COUNT * FROM table_name ; | COUNT is a function that takes the name of a column as argument and counts the number of rows when the column is not NULL. | SELECT COUNT(country) FROM placeofinterest WHERE country='Canada'; |
| DISTINCT | SELECT DISTINCT columnname FROM table_name; | DISTINCT function is used to specify that the statement is a query which returns unique values in specified columns. | SELECT DISTINCT country FROM placeofinterest WHERE type='historical'; |
| LIMIT | SELECT * FROM table_name LIMIT number; | LIMIT is a clause to specify the maximum number of rows the result set must have. | SELECT * FROM placeofinterest WHERE airport="pearson" LIMIT 5; |
| INSERT | INSERT INTO table_name (column1,column2,column3...) VALUES(value1,value2,value3...); | INSERT is used to insert new rows in the table. | INSERT INTO placeofinterest (name,type,city,country,airport) VALUES('Niagara Waterfalls', 'Nature', 'Toronto', 'Canada', 'Pearson'); |
| UPDATE | UPDATE table_name SET [[column1]=[VALUES]] WHERE [condition]; | UPDATE used to update the rows in the table. | UPDATE placeofinterest SET name = 'Niagara Falls' WHERE name = "Niagara Waterfalls"; |
| DELETE | DELETE FROM table_name WHERE [condition]; | DELETE statement is used to remove rows from the table which are specified in the WHERE condition. | DELETE FROM placeofinterest WHERE city IN ('Rome', 'Vienna'); |

Author(s)

[Malika Singla](#)



Skills Network