barbac: fast DNA barcode clustering from reads to lineage trajectories

Loukas Theodosiou[1]*, Andrew D. Farr[2] and Paul B. Rainey[1,2]

[1] Department of Microbial Population Biology, Max Planck Institute for Evolutionary Biology, Plön, Germany. [2] Laboratory of Biophysics and Evolution, CBI, ESPCI Paris, Université PSL, CNRS, Paris, France. * Correspondence: theodosiou@evolbio.mpg.de

Abstract

Motivation: DNA barcode analysis requires accurate error correction and consistent lineage counts across time, including libraries containing indels.

Results: We present barbac, an R/C++ workflow with a local Shiny interface. Its abundance-aware Levenshtein engine achieved the highest exact-centroid F1 and read-assignment accuracy among six configurations on two replicated simulated designs and a deposited benchmark. The Hamming configuration was fastest. Paired comparisons supported LV's F1 advantage over Bartender and both Starcode configurations; a completed Shepherd sensitivity comparison also favoured LV. Single-end and overlapping paired-end workflows connect barcode extraction, clustering, statistics and lineage plots.

Availability and implementation: R/C++, GPL ≥2; https://github.com/loukesio/barbac. The submitted release and test-data archive identifier will be added before submission.

Contact: theodosiou@evolbio.mpg.de

Supplementary information: Benchmark methods, statistical comparisons, execution records and application analyses accompany this manuscript.

1 Introduction

Cell barcoding is an increasingly valuable technique for tracking cell lineages in experimental systems. By inserting short, unique DNA barcode sequences into individual cells, researchers can trace the relationships and dynamics of clones across multiple generations (Ba *et al.*, 2019; Blundell and Levy, 2014; Levy *et al.*, 2015; Theodosiou *et al.*, 2023; Geiler-Samerotte and Lang, 2023; Masuyama *et al.*, 2019; Woodworth *et al.*, 2017; VanHorn and Morris, 2021). When paired with time-series sampling, barcoding enables quantification of growth, mutation, and other eco-evolutionary characteristics of cell populations (Levy *et al.*, 2015; Fasanello *et al.*, 2020; Jasinska *et al.*, 2020). However, realising the potential of cell barcoding requires overcoming computational challenges in extracting and analysing barcode sequence data generated by high-throughput sequencing. Raw sequences contain errors and must be accurately clustered to progenitor barcodes before connecting into cell lineage trees (Johnson et al., 2023).

To generate barcode sequencing data, barcodes are first integrated into target genomes using CRISPR-mediated insertion or transposon mutagenesis via helper plasmids (Borchert *et al.*, 2022; Zhu *et al.*, 2019; Theodosiou *et al.*, 2023; Jasinska *et al.*, 2020; Levy *et al.*, 2015). Cells are then cultured over time, with population samples collected at specific intervals. Following DNA extraction and library preparation, high-throughput sequencing produces read data containing many copies of the barcode of each cell (Jasinska et al., 2020; Theodosiou et al., 2023; Vasquez et al., 2021). An ideal workflow would process these reads to identify barcode sequences, cluster similar sequences originating from a common progenitor, and connect barcodes into lineages across time in a time-sufficient manner.

Current computational approaches for lineage barcoding data typically address individual analytical steps rather than supporting end-to-end workflows. Considerable effort has been devoted to improving barcode error correction and clustering barcode families into lineages (Tavakolian et al., 2022). Nevertheless, important opportunities remain to advance lineage reconstruction over time and to increase the flexibility of clustering methods for diverse experimental contexts. Among existing tools, Bartender stands out by offering built-in functionality for longitudinal lineage tracking through the matching of barcode clusters across multiple time points (Zhao et al., 2018). Bartender

applies a statistical clustering strategy based primarily on Hamming distances, allowing it to effectively distinguish true barcodes from sequencing and PCR artifacts. However, its reliance on identifying the most abundant barcodes at early sampling points, coupled with the absence of correction mechanisms for insertion or deletion (indel) errors, may limit its accuracy in more complex experimental settings.

Alternatively, Starcode utilizes an exact all-pairs search within a defined Levenshtein distance to cluster barcodes rapidly, accommodating insertion-deletion errors effectively. Starcode uses an efficient search within a fixed distance threshold without an explicit error model, creating potential trade-offs in clustering precision (Johnson et al., 2023; Zorita et al., 2015). Addressing some of these limitations, the more recent Shepherd algorithm incorporates a k-mer indexing scheme alongside a Bayesian model of sequencing error rates. Shepherd achieves high clustering precision, substantially reducing spurious lineage counts, yet its rigorous filtering approach can inadvertently exclude barcodes exhibiting unexpected sequence variations, and it imposes a greater computational burden (Tavakolian et al., 2022; Johnson et al., 2023).

Beyond barcode-specific solutions, general-purpose clustering tools such as CD-HIT (Fu *et al.*, 2012) and DNA-Clust (Ghodsi *et al.*, 2011), along with specialized error-correction pipelines, have also been applied . However, barcode-centric methods like Bartender, Starcode, and Shepherd consistently outperform these alternatives in accuracy when denoising and clustering barcode data (Johnson et al., 2023). Importantly, Bartender remains the only tool among these with built-in functionality for directly tracking lineages across time points, whereas other methods require supplementary post hoc analysis.

To address these gaps, we present barbac, an R package and accompanying local Shiny interface for lineage barcoding analysis. barbac implements an end-to-end workflow that begins with raw FASTQ files, performs barcode extraction and error correction, and reconstructs lineage frequencies over time. Users can also start directly from extracted barcode counts. Its native C++ implementation supports Hamming and Levenshtein distances with abundance-aware centroid assignment. For time-series analysis, counts can be pooled across samples to define shared memberships, including lineages first observed at later timepoints. The clustering engine uses a configured error-rate approximation and deterministic ordering; it does not infer genealogical relationships among distinct barcodes. The R workflow and downloadable analysis records support reproducible use from both scripts and the local interface.

To demonstrate the utility of barbac, we compared two independently simulated barcode designs with substitutions and repeat-dependent indels, using an error model adapted from Johnson et al. (2023), and their deposited benchmark. We also processed published experimental barcode time series to illustrate extraction, clustering and lineage visualization.

2 System and methods

2.1 From sequencing reads to barcode counts

The public `barbac_map()` accepts a sample table containing R1 paths and optional R2 paths. FastQC assesses the input reads. R1-only samples map directly; overlapping paired reads are assembled with PEAR (Zhang et al., 2014) before mapping, and unassembled pairs do not enter downstream analysis. Minimap2 (Li, 2018) uses its short-read preset, with secondary alignments disabled. Samtools (Danecek et al., 2021) removes secondary and supplementary alignments and produces sorted, indexed BAM files. Primary mapped and unmapped counts, command logs and command-level elapsed times are saved. MultiQC summarizes QC reports when available. This wrapper ends at BAM and QC outputs (Figure 1).

`barbac_extract()` extracts barcodes from primary mapped reads using reference coordinates or a supplied flank pattern. Variable-length flank extraction retains observed insertions and deletions instead of forcing all barcodes to a nominal length. The resulting CSV records each distinct sequence, its count and length. Length, abundance and entropy diagnostics are available through `barbac_extract_stats()`. Study-specific quality filters and UMI

deduplication must be specified separately. Neither FASTQ quality scores nor mapping tools are required when `barbac_cluster()` receives an existing barcode-count table.




Figure 1. The Barbac workflow. R1-only reads map directly; overlapping paired reads merge with PEAR. Extracted barcodes or independent count tables enter the same native clustering engine. Shared memberships support sample counts, statistics and lineage-frequency plots.

2.2 Barcode designs, error generation and reference data

The principal comparison comprises random N20 barcodes, an anchored design `NNNNNAANNNNNAANNNNNTTNNNNN`, and the deposited Johnson et al. (2023) simulation (referred to here as Milo). Both new designs contain 20 variable positions; the anchored construct is 26 nt long. We generated 60 independent libraries per design, each with 10,000 intended identities and one million expected reads. Within each seed, designs share variable identities and parent abundances. Abundances follow a scaled exponential mixture: 9,989 ordinary identities with mean 1, ten intermediate identities with mean 10 and one abundant identity with mean 1,000, normalized before Poisson read sampling.

Johnson et al. (2023) measured repeat-associated indel frequencies in barcode sequencing experiments and incorporated these rates into a simulation with 0.4% substitutions per base. We use the archived homopolymer-rate table without inflation and apply the same substitution probability, 0.004. Indel events are allocated recursively, updating repeat coordinates after each event. A repeat longer than the measured support of 13 bases stops further indel recursion for the affected reads; their counts, origin labels and subsequent substitutions remain intact. This boundary affected 249 of 119,992,068 reads across 16 of 120 libraries. The model represents a specified barcode error process; it does not claim to calibrate every instrument or protocol, and it does not explicitly model all dinucleotide, PCR-family or synthesis effects.

The fixed Milo input contains 100,000 listed true identities, 1,544,850 distinct observed sequences and 24,996,128 reads. It was used during development. Its reference count table and origin labels differ at four parents by six reads in total absolute difference, while identities and overall totals reconcile. We retain the deposited centroid truth and score read assignments against the origin labels. Independent inference uses the newly generated libraries; Milo results are descriptive. All generated evaluation seeds were frozen before the final campaign and were not used to select subsequent Barbac changes.

2.3 Competing methods and metrics

We evaluated barbac LV and Hamming, Shepherd, Starcode sphere and message passing, and Bartender, each with distance limit three. Both Barbac modes use support ordering, merge ratio 20, configured error proxy 0.005 and disabled design scoring. LV enables the existing Poisson indel option; Hamming retains its limited rare-indel rescue. Starcode message passing uses ratio 5. Bartender uses seed length 5, step 1, cutoff 1, z = 5 and forward direction. Native clustering and external tools use one thread for this benchmark. Complete commands, versions and source fingerprints are supplied with Table 1.

The original frozen Shepherd configuration used Bayes-factor threshold +4 and automatic substitution-rate estimation. Ten of 120 new simulated inputs failed in that estimator. A separately registered, post hoc sensitivity configuration uses Shepherd's documented threshold −4 and the known generating substitution rate 0.004 on every new library; Milo retains automatic estimation. Both changes were applied consistently, without an accuracy-based configuration search. Table 1 presents this completed comparison and reuses all other method results. Original Shepherd outcomes and the two unavailable original contrasts remain archived. Shepherd primarily uses Hamming distances and separately corrects single insertions and deletions; it is not a general Levenshtein engine.

For exact-centroid scoring, TP counts output strings present in the true set, FN counts missing true strings, and FP counts extra output strings. F1 is `2TP/(2TP + FN + FP)`. All designed identities remain in the denominator, including zero-read identities. Read-assignment accuracy is the fraction of input reads assigned to their labelled true parent; incorrect and unassigned reads both reduce this metric. Accuracy summaries average library-level scores, with sample standard deviation shown for F1. This F1 is distinct from a purity/completeness harmonic mean. Input counts, membership uniqueness and output totals were reconciled before scoring.

2.4 Paired inference and timing scope

The original primary family contains eight LV-versus-external comparisons: four external configurations in each of two designs. We calculated paired-t one-sided lower confidence bounds at alpha = 0.05/8 and paired bootstrap bounds at the same level using 100,000 whole-library resamples. Six original contrasts with Bartender and Starcode were complete. The two additional Shepherd sensitivity contrasts retain the same conservative alpha but remain post hoc. No population-level test is inferred from the single Milo dataset.

Clustering workflow time includes a fresh worker, tool/package startup, required input conversion and canonical centroid/member exports. Shared staging, scoring and hashing are excluded. Original runs were serial. Twenty-eight calls affected by computer sleep were repeated once under a registered repair, with identical clustering outputs required; these replacements were retained unconditionally. The 121 completed Shepherd calls were measured in a later session, with lightweight diagnostic file reads overlapping early calls. Their runtime comparison is descriptive. The complete raw-read application timing described below measures a separate workflow and must not be compared directly with Table 1 times.

3 Algorithm and implementation

3.1 Abundance-aware centroid assignment

`barbac_cluster()` (named `super_cluster2()` in release 0.2.1 and in the benchmark receipts) collapses exact duplicate sequences, processes sequences in abundance order and returns centroids, complete memberships and conserved counts. For equal counts, the optional support ordering sums the counts of one-edit neighbours that are no more abundant than the candidate, with sequence order as the final deterministic tie rule. It uses observed counts rather than truth labels and makes results independent of input row order.

The v14 native engine searches existing eligible centroids within the requested distance and selects an assignment using a count-aware approximation based on parent abundance, edit distance and the configured error proxy. A distance-dependent count-ratio guard protects plausible separate identities. Exact candidate partitions, bit-parallel distance kernels and conservative abundance/score bounds avoid comparisons that cannot change the selected parent. This is greedy centroid assignment, not graph connected-component clustering. Search acceleration and merge acceptance are separate operations; recognizing an indel does not alone justify merging its sequence into another identity. The search selects the highest-scoring eligible centroid; a guard-blocked candidate does not suppress a lower-scoring acceptable parent.

For parent count n_p, child count n_c, distance d and comparison length L (the larger sequence length), the ranking score is

$$S = \log(1 + n_p) + d \log(e/a) + \max(0, L - d) \log(1 - e) - 0.15 \log(1 + n_c),$$

with $a = 5$ for LV and $a = 3$ for Hamming, and configured error proxy e. For LV distances 1, 2 and 3, the ratio guard applies when child counts reach 10, 5 and 2, respectively, requiring parent-to-child ratios of 20, 60 and 100 under the reported settings. Hamming retains ratio 20 and child-count floor 10. These are configured heuristics, not learned assay-specific parameters.

A local refinement stage can promote absorbed distance-two-or-more sequences whose counts exceed the expected exact-edit error burden, then reassign members to better-supported local representatives. LV uses its conservative local error expectation; Hamming refinement uses the binomial Bayes criterion described for Shepherd (Tavakolian et al., 2022). Subsequent cleanup and the Hamming mode's limited rare-indel rescue are retained in the versioned native implementation.

The opt-in LV Poisson exception permits a repeated-base single insertion or deletion to pass an otherwise blocking ratio guard when its count is compatible with an expected-error approximation. It uses the configured error proxy as a deletion-rate upper-bound proxy and one quarter of that rate for a specific inserted base, multiplied by equivalent gap positions; the upper-tail threshold is 0.01. It neither learns the simulation's repeat-specific rates nor provides a platform-calibrated posterior. It remains an explicit option because genuine nearby length variants can satisfy the same criterion. The package default is `indel_model="none"`; Table 1 evaluates the stated enabled configuration.

3.2 Reproducible analysis and local interface

Counts can be pooled over all timepoints within each independent population to define one membership map, then assigned back to their samples. This retrospective pooling includes later observations when defining shared identities. It should not be interpreted as reconstruction of a genealogical tree or prospective prediction. `cluster_stats()` summarizes clusters and abundance, while `barbac_ts_area()` plots lineage frequencies with configurable zero filling, abundance filtering and 32 built-in LTC palettes. Static and interactive outputs use the same prepared counts.

Barbac Studio supplies local barcode-count and raw-read uploads, including R1-only input, and calls the same native engine. A labelled publication LV preset selects the Table 1 settings. Downloads include extracted counts, centroids, memberships, sample counts, statistics, settings, source/build identifiers, an R result and a self-contained HTML report. Large populations retain every output count; Studio defers figures above 5,000 lineages per population to direct R plotting. Native clustering time is recorded separately from the broader analysis time. Synthetic examples and local video walkthroughs allow users to inspect the workflow without submitting data to a public service.

The 0.2.2 release retains the verified v14 native clustering implementation, adds command-level workflow timings and introduces the preferred public function names used here; the original names remain supported. Lazy loading of BAM-related namespaces reduces startup work for standalone count clustering. Release verification passed 547 package assertions in 47 cases and 65 Studio assertions in ten cases, including known indel recovery, R1 and paired processing, complete memberships, sample-level count reconciliation, native plot parity and report export.

4 Results

4.1 Accuracy across the three benchmarks

Barbac LV has the highest exact-centroid F1, lowest FP and highest read-assignment accuracy in all three comparisons (Table 1). Mean F1 is 99.28038% on random libraries and 99.23726% on anchored libraries, with 99.72246% on Milo. Corresponding read-assignment accuracies are 99.997083%, 99.994257% and 99.999476%.

For the random and anchored designs, LV improves mean F1 over Bartender by 0.149749 and 0.565086 percentage points, respectively. Its gains over Starcode sphere are 0.044684 and 0.042949 points, and over message passing 0.584555 and 0.790526 points. All six original contrasts have positive multiplicity-adjusted paired-t and bootstrap lower bounds. Against the completed Shepherd sensitivity configuration, LV improves F1 by 0.016172 and 0.014868 points; the corresponding t lower bounds are 0.011819 and 0.009718 points, and bootstrap lower bounds 0.012066 and 0.009941 points. These two comparisons are post hoc (Supplementary Methods, Table S1).

The results also distinguish precision from recall. Starcode message passing recovers more true centroid strings in both new designs, with fewer FN, but introduces substantially more FP. On Milo, Hamming has two fewer FN than LV; LV has four fewer FP and the higher F1. A descriptive development audit found that many missed identities had zero reads or no exact error-free observation, while most observed-but-merged identities had only one or two reads. These cases illustrate the limited evidence available for recovering rare nearby identities.

Table 1. Accuracy and runtime of barcode clustering across three benchmarks.

Panels A and B: 10,000 true barcodes and approximately 1 million reads per library. Panel C: 100,000 true barcodes and 24,996,128 reads.

Method	FN ↓	FP ↓	F1 (%) ↑	Read accuracy (%) ↑	Runtime[b] (s) ↓
A Random N20: substitutions + indels (60 libraries)					
barbac Hamming	124.92	18.30	99.28004 ± 0.0758	99.997077	**1.40**
barbac LV + Poisson	124.90	**18.25**	**99.28038 ± 0.0752**	**99.997083**	1.76
Shepherd[a]	126.53	19.83	99.26421 ± 0.0766	99.996495	4.67
Starcode sphere	129.72	22.32	99.23569 ± 0.0797	99.982520	3.29
Starcode MP	**118.18**	142.98	98.69582 ± 0.1112	99.983934	3.22
Bartender	125.17	48.03	99.13063 ± 0.0921	99.930972	1.89
B Anchored N20 + AA/TT: substitutions + indels (60 libraries)					
barbac Hamming	127.70	24.90	99.23302 ± 0.0736	99.993137	**1.52**
barbac LV + Poisson	127.67	**24.08**	**99.23726 ± 0.0741**	**99.994257**	2.05
Shepherd[a]	129.65	25.05	99.22239 ± 0.0796	99.993818	13.45
Starcode sphere	132.63	27.65	99.19431 ± 0.0829	99.986583	3.77
Starcode MP	**119.95**	191.83	98.44674 ± 0.1384	99.979174	3.67
Bartender	127.73	137.97	98.67218 ± 0.0786	99.906649	2.31
C Milo / Johnson published simulation (one fixed reference)					
barbac Hamming	**469**	87	99.72147	99.999088	**17.50**
barbac LV + Poisson	471	**83**	**99.72246**	**99.999476**	33.65
Shepherd[a]	470	85	99.72196	99.999132	165.23
Starcode sphere	771	353	99.43682	99.847880	170.68
Starcode MP	532	560	99.45408	99.981789	193.39
Bartender	496	795	99.35546	99.935342	41.77

Panels A and B: FN, FP and read accuracy are means; F1 is mean ± standard deviation; runtime is median. Panel C reports one observation. Bold and pale orange shading identify the best observed value for each metric within each panel.

FN, false negatives: true identities absent from inferred centroids. FP, false positives: inferred identities absent from truth. Exact-centroid F1 = 200TP/(2TP + FN + FP), including zero-read true identities. Read accuracy is the percentage of all reads assigned to their true barcode; incorrect and unassigned reads both count as errors.

[a] Shepherd uses distance 3, Bayes-factor threshold −4, and the generating substitution rate 0.004 in panels A/B; panel C uses automatic rate estimation. This is the completed post hoc sensitivity configuration; all other methods retain their original settings and results.

[b] All workflows use one thread. Runtime includes fresh-worker/tool startup, required input conversion and centroid/member export; common staging and scoring are excluded. Shepherd was measured in a later session, so its timing comparisons are descriptive.

The accompanying Table 1 methods provide simulation details, complete settings, paired statistical comparisons and measurement provenance.

4.2 Runtime of clustering and the complete raw-read workflow

Barbac Hamming has the lowest measured workflow time in all three benchmark summaries: 1.40 s for random libraries, 1.52 s for anchored libraries and 17.50 s for Milo. LV takes 1.76 s, 2.05 s and 33.65 s, respectively, faster than every external configuration in each summary. The closest competitor by runtime is Bartender at 1.89 s, 2.31 s and 41.77 s. These rankings describe the recorded workflows, including startup and required exports, rather than isolated distance kernel speed.

For a complete R1 application, we processed 10,754,210 reads from three successive Jasińska et al. (2020) samples on an Apple M1 with 16 GiB RAM. The raw-read workflow mapped 8,591,566 reads and extracted 8,578,419 barcode reads, comprising 437,009 distinct sequences. It produced 144,537 inferred lineages with complete sample-count reconciliation. The outer R-process time was 1,997.98 s (33 min 18 s). FASTQ-to-BAM processing with QC took 203.78 s, extraction 45.64 s and native LV clustering 343.51 s. Saving every lineage to PDF and PNG took 1,398.07 s and dominated the total. Downloads, installation and input checksum verification were excluded; combining technical-run inputs was included. This single run occurred during ordinary desktop use with no other analysis jobs and no system sleep interruption. Complete stage and command receipts are provided.




Figure 2. Complete lineage-frequency plot for three E. coli samples (generations 12, 24 and 36), with all 144,537 inferred lineages retained and frequencies normalized to all extracted barcode reads in each sample. Colours distinguish bands rather than biological categories. The saved benchmark data are unchanged; the manuscript shortens the axis label for legibility.

4.3 Experimental time-series applications

The raw-read application demonstrates the generic R1 workflow on E. coli barcode sequencing from Jasińska et al. (2020). All four technical runs from each selected sample are included, with observed counts pooled across three chronological timepoints and mapped back to a shared lineage table. This example operates on raw reads and does not reproduce the separate study analysis's Q10 filter.

A separate archived reanalysis of the Chen et al. (2023) hBFA1 YPD time series processed 16,511,755 read pairs into 16,051,344 extracted, UMI-deduplicated molecules across eight samples. LV had median Spearman agreement of 0.999968 with published counts over 2,314 paired-barcode identifiers. Starcode showed slightly higher reference

agreement, while Barbac Hamming had the lowest recorded clustering workflow time. Complete results and their earlier timing scope are retained in Supplementary Table S2. Published-count agreement measures reproducibility against a differently processed reference; it is not known-truth accuracy and is separate from the three simulated benchmark rankings.

5 Discussion

Barbac combines accurate barcode correction with a fast, inspectable route from raw sequencing reads or barcode counts to lineage trajectories. Across the three specified benchmarks, LV leads on exact-centroid F1 and read-assignment accuracy, while Hamming provides the shortest measured clustering workflow. The replicated simulations support LV's advantage over Bartender and both Starcode configurations; the completed Shepherd sensitivity comparison supports the same direction under its explicitly reported configuration.

The anchored and random designs address barcode libraries with substitutions and repeat-associated indels. They represent a biological mechanism described in published barcode experiments, retaining the archived empirical indel rates. Their error model remains a defined simulation rather than a universal sequencing model. A larger or differently distributed library may have different search costs, and a nominal Levenshtein distance alone does not determine whether a weak sequence is a true identity or an error. The method's count and error assumptions therefore matter alongside its distance search.

Recall remains constrained by sampling and closely related low-count identities. A sequence-only count table cannot always distinguish a genuine rare barcode from an error of an abundant neighbour. Retaining standalone count input is useful for users who already have extracted sequences; it does not require FASTQ qualities to be available. Independent known-neighbour controls remain appropriate when choosing optional merge settings. Future work can address this ambiguity without changing the frozen comparisons reported here.

The practical contribution extends beyond clustering: R1 and overlapping paired input, indel-preserving extraction, shared time-series memberships, explicit runtime records and a local interface reduce the steps needed to inspect and reproduce an analysis. Source, settings, data provenance and complete outputs make the reported strengths testable on additional barcode experiments.

Data and software availability

Source code and installation instructions are available at https://github.com/loukesio/barbac, with documentation. Benchmark protocols, simulation code, frozen seeds, per-run scores, validation and table renderers are included in the repository. The deposited Johnson source data and analysis are available at Zenodo record 7411747. Experimental run accessions, checksums and study references are listed in the Chen and Jasińska application manifests. The submitted software/test-data archive identifier must be inserted before journal submission.

Acknowledgements

We thank Carsten Fortmann-Grote for comments on the manuscript and code, and Thijs Jansen for discussions on software development.

AI assistance (OpenAI Codex) was used during software development, benchmark orchestration, documentation and manuscript preparation. The authors are responsible for reviewing the code, analyses and scientific conclusions.

Funding

[Author completion required: funding sources and grant identifiers, or the applicable no-specific-funding statement.]

Competing interests

[Author completion required.]

References

Li,H. (2018) Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics*, **34**, 3094–3100. doi:10.1093/bioinformatics/bty191.

Ba,A.N.N. *et al.* (2019) High-resolution lineage tracking reveals traveling wave of adaptation in laboratory yeast. *Nature*, **575**, 494–499.

Blundell,J.R. and Levy,S.F. (2014) Beyond genome sequencing: Lineage tracking with barcodes to study the dynamics of evolution, infection, and cancer. *Genomics*, **104**, 417–430.

Borchert,A.J. *et al.* (2022) Experimental and analytical approaches for improving the resolution of randomly barcoded transposon insertion sequencing (RB-TnSeq) studies. *ACS Synth Biol*, **11**.

Chen,V. *et al.* (2023) Evolution of haploid and diploid populations reveals common, strong, and variable pleiotropic effects in non-home environments. *eLife*, **12**, e92899.

Danecek,P. *et al.* (2021) Twelve years of SAMtools and BCFtools. *GigaScience*, **10**, giab008. doi:10.1093/gigascience/giab008.

Fasanello,V.J. *et al.* (2020) High-throughput analysis of adaptation using barcoded strains of Saccharomyces cerevisiae. *PeerJ*, **8**.

Fu,L. *et al.* (2012) CD-HIT: accelerated for clustering the next-generation sequencing data. *Bioinformatics*, **28**, 3150–3152.

Geiler-Samerotte,K. and Lang,G.I. (2023) Best Practices in Microbial Experimental Evolution. *J Mol Evol*.

Ghodsi,M. *et al.* (2011) DNACLUST: accurate and efficient clustering of phylogenetic marker genes. *BMC Bioinformatics*, **12**, 271.

Jasinska,W. *et al.* (2020) Chromosomal barcoding of E. coli populations reveals lineage diversity dynamics at high resolution. *Nat Ecol Evol*, **4**, 437–452.

Johnson,M.S. *et al.* (2023) Best Practices in Designing, Sequencing, and Identifying Random DNA Barcodes. *J Mol Evol*, **91**, 263–280.

Levy,S.F. *et al.* (2015) Quantitative evolutionary dynamics using high-resolution lineage tracking. *Nature*, **519**, 181–6.

Masuyama,N. *et al.* (2019) DNA barcodes evolve for high-resolution cell lineage tracing. *Curr Opin Chem Biol*, **52**.

R Core Team (2024) R: A language and environment for statistical computing.

Tavakolian,N. *et al.* (2022) Shepherd: accurate clustering for correcting DNA barcode errors. *Bioinformatics*, **38**, 3710–3716.

Theodosiou,L. *et al.* (2023) Barcoding Populations of Pseudomonas fluorescens SBW25. *J Mol Evol*, **91**, 254–262.

VanHorn,S. and Morris,S.A. (2021) Next-Generation Lineage Tracing and Fate Mapping to Interrogate Development. *Dev Cell*, **56**.

Vasquez,K.S. *et al.* (2021) Quantifying rapid bacterial evolution and transmission within the mouse intestine. *Cell Host & Microbe*, **29**, 1454-1468.e4.

Wickham,H. (2009) ggplot2: Elegant Graphics for Data Analysis New York.

Woodworth,M.B. *et al.* (2017) Building a lineage from single cells: genetic techniques for cell lineage tracking. *Nat Rev Genet*, **18**.

Zhang,J. *et al.* (2014) PEAR: a fast and accurate Illumina Paired-End reAd mergeR. *Bioinformatics*, **30**, 614–620. doi:10.1093/bioinformatics/btt593.

Zhao,L. *et al.* (2018) Bartender: a fast and accurate clustering algorithm to count barcode reads. *Bioinformatics*, **34**, 739–747.

Zhu,S. *et al.* (2019) Guide RNAs with embedded barcodes boost CRISPR-pooled screens. *Genome Biol*, **20**.

Zorita,E. *et al.* (2015) Starcode: sequence clustering based on all-pairs search. *Bioinformatics*, **31**, 1913–1919.