





# Chapter I

This is a Demonstration 中國皇帝

# A Section Title I 中國皇帝

14<sup>00</sup>

[illegible]

## A Section Title 2 中國皇帝

[illegible]

A Section Title 3 中國皇帝

[illegible]

## MKTS Regions 中國皇帝

To indicate the start of an MKTS-MD Region, place a triple at-sign @@@ at the start of a line, immediately followed by a command name such as `keep-lines` or `single-column`. The end of a region is indicated by a triple at-sign without a command name. Nested regions are possible; for example,

you can put a `@@@keep-lines` region inside a `@@@single-column` region as done here:

Here are some formulas: `u-cjk/4e36` 、 ●

`u-cjk/4e37` ヽ ● 、 /

`u-cjk/4e38` 丸 ⑨ 九 、

`u-cjk/4e39` 丹 ⑩ 冂 ㊦ 、 一

`u-cjk/4e3a` 为 ⑪ 、 ㊦ 力 、

`u-cjk/4e3b` 主 ㊦ 、 王

`u-cjk/4e3b` 主 ㊦ ㄣ 土

`u-cjk/4e3c` 井 ㊦ 井 、

`u-cjk-xb/250b7` 𪚩 ㊦ ㊦ 告 巨 皿

`u-cjk-xb/250b8` 𪚪 ㊦ 楊 皿

At this point, a line consisting of a triple at-sign `@@@` indicates the end of the `keep-lines` region; since the `single-column` region is still active, however, this paragraph runs across the entire width of the documents text area.

xxxx





## Chapter 3

# Regions

### Keep-Lines Regions

-----  
A-before A-within  
A-within  
A-within  
A-after  
% $\Delta\Delta\Delta$ end

-----  
B-before  
B-within  
B-within  
B-within

B-after

-----  
C-before

C-within  
C-within  
C-within

C-after

-----  
D-before

D-within  
D-within  
D-within

D-after